

Product name: Rechargeable Lithium ion Cell 5068A8 3.7V 18.5Wh Version: 3.0/EN

Revision date: 04/01/2016 Issue date: 11/03/2016

1.	Identification		
	(a) Product identifier		
	Product name	Rechargeable Lithium ion Cell 5068A8 3.7V 18.5Wh	
	(b) Other means of identit	fication	
	Product description	Model: 5068A8 Nominal Voltage:3.7V Typical Capacity:5000mAh Watt-hour:18.5Wh	
	(c) Recommended use of the chemical and restrictions on use		
	Recommended use Uses advised against	LITHIUM ION BATTERIES No information available.	
	(d) Details of the supplier	of the safety data sheet	
	Supplier Name Supplier Address Supplier Email	Dongguan AISIPU Energy Technology CO.,LTD. Aisipu Industrial Park, Jinying Road, Chenwu Village, Houjie Town, Dongguan City, Guangdong Province 523942, P.R. China shikf@aisipu.com.cn	
	Supplier Phone Number	+86-769-38941888	
	(e) Emergency telephone +86-769-38941888	number	

+86-769-38941888

2. Hazard(s) identification

(a) Classification

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200) This product is an article which is a sealed battery and as such does not require an MSDS per the OSHA hazard communication standard unless ruptured. The hazards indicated are for a ruptured battery.

Skin corrosion/irritation	Category 1 Sub-category B
Serious eye damage/eye irritation	Category 1
Specific target organ toxicity (repeated exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 1

(b) GHS Label elements, including precautionary statements



Product name: Rechargeable Lithium ion Cell 5068A8 3.7V 18.5Wh Version: 3.0/EN

Revision date: 04/01/2016 Issue date: 11/03/2016

		Eme	rgency Ove	rview	
Signal word		Danger			
Hazard Stateme					
		and eye damage			
May cause resp	ratory irrit	ation. May cause dro	owsiness or	dizziness	
(!)			CE C		
the article as so	ld. Intende		t should no	t result in ex	information is given for exposure to posure to the chemical substance.
Appearance	Silver	Physical State	Solid	Odor	No information available

Precautionary Statements - Prevention

Do not breathe dust/fume/gas/mist/vapors/spray Wash face, hands and any exposed skin thoroughly after handling Wear protective gloves/protective clothing/eye protection/face protection Use only outdoors or in a well-ventilated area Do not eat, drink or smoke when using this product

Precautionary Statements - Response

Immediately call a POISON CENTER or doctor/physician Specific treatment (see supplemental first aid instructions on this label) Get medical advice/attention if you feel unwell

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician

Skin

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower Wash contaminated clothing before reuse



Product name: Rechargeable Lithium ion Cell 5068A8 3.7V 18.5Wh Version: 3.0/EN

Revision date: 04/01/2016 Issue date: 11/03/2016

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing Immediately call a POISON CENTER or doctor/physician Call a POISON CENTER or doctor/physician if you feel unwell

Ingestion

IF SWALLOWED: Rinse mouth. DO NOT induce vomiting

Precautionary Statements - Storage

Store locked up Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

(c) Hazards not otherwise classified (HNOC)

Not applicable

(d) Unknown Toxicity

33% of the mixture consists of ingredient(s) of unknown toxicity

(e) Other information

May be harmful if swallowed May be harmful in contact with skin Very toxic to aquatic life with long lasting effects

(f) Interactions with Other Chemicals

No information available.

3. Composition/information on ingredients

Chemical name	CAS No.	Weight-%	Trade Secret
Lithium Cobalt Oxide (CoLiO2)	12190-79-3	15 - 40	*
Copper	7440-50-8	10 - 30	*
Graphite	7782-42-5	10 - 30	*
Ethylene carbonate	96-49-1	10 - 30	*
Phosphate(1-), hexafluoro-, lithium	21324-40-3	7 - 13	*
Aluminum foil	7429-90-5	3 - 7	*

*The exact percentage (concentration) of composition has been withheld as a trade secret



Product name: Rechargeable Lithium ion Cell 5068A8 3.7V 18.5Wh Version: 3.0/EN

Revision date: 04/01/2016 Issue date: 11/03/2016

4. First-aid measures	
(a)First aid measure	S
(b)General Advice	First aid is upon rupture of sealed battery.
Eye contact:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Seek immediate medical attention/advice.
Skin contact:	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Seek immediate medical attention/advice.
Inhalation:	Remove to fresh air. If breathing has stopped, give artificial respiration. Get medical attention immediately. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If breathing is difficult, (trained personnel should) give oxygen. Delayed pulmonary edema may occur. Get medical attention immediately if symptoms occur.
Ingestion:	Do NOT induce vomiting. Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately.
Self-protection of the first aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid contact with skin, eyes or clothing. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use personal protective equipment as required. Wear personal protective clothing (see section 8).
(c)Most important sy	mptoms and effects, both acute and delayed
Most Important Symptoms and	Burning sensation.

Effects

(d) Indication of any immediate medical attention and special treatment needed

Notes to Physician Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Do not give chemical antidotes. Asphyxia from glottal edema may occur. Marked decrease in blood pressure may occur with moist rales, frothy sputum, and high pulse pressure.

5. Fire-fighting measures

(a) Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

(b) Unsuitable extinguishing media

CAUTION: Use of water spray when fighting fire may be inefficient.

(c) Specific Hazards Arising from the Chemical

The product causes burns of eyes, skin and mucous membranes. Thermal decomposition can lead to



Product name: Rechargeable Lithium ion Cell 5068A8 3.7V 18.5Wh **Version:** 3.0/EN

Revision date: 04/01/2016 Issue date: 11/03/2016

release of irritating gases and vapors.

(d) Hazardous Combustion Products

Carbon oxides.

(e) Hazardous Combustion Products

Sensitivity to No. Mechanical Impact

Sensitivity to Static No. Discharge

(f) Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. Accidental release measures

(a)Personal precautions, protective equipment and emergency procedures

PersonalAttention!Corrosive material. Avoid contact with skin, eyes or clothing. EnsurePrecautionsadequate ventilation. Use personal protective equipment as required. Evacuate
personnel to safe areas. Keep people away from and upwind of spill/leak.

Other Information Refer to protective measures listed in Sections 7 and 8.

(b)Environmental Precautions

Environmental Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Should not be released into the environment. Do not allow to enter into soil/subsoil. Prevent product from entering drains.

(c)Methods and material for containment and cleaning up

```
Methods for Prevent further leakage or spillage if safe to do so.
Containment
```

Methods for Pick up and transfer to properly labeled containers.

cleaning up

7. Handling and storage

(a) Precautions for safe handling

Handling In case of rupture. Handle in accordance with good industrial hygiene and safety practice.Use personal protection equipment. Avoid contact with skin, eyes or clothing.



Product name: Rechargeable Lithium ion Cell 5068A8 3.7V 18.5Wh Version: 3.0/EN

Revision date: 04/01/2016 Issue date: 11/03/2016

(b) Conditions for safe storage, including any incompatibilities

Storage Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from moisture. Store locked up. Keep out of the reach of children. Store away from other materials.

Incompatible Acids. Bases. Oxidizing agent. Products

8. Exposure controls/personal protection

(a)Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Lithium Cobalt Oxide (CoLiO2) 12190-79-3	TWA: 0.02 mg/m ³	-	
Copper 7440-50-8	TWA: 0.2 mg/m ³ fume TWA: 1 mg/m ³ Cu dust and mist	TWA: 0.1 mg/m ³ fume TWA: 1 mg/m ³ dust and mist (vacated) TWA: 0.1 mg/m ³ Cu dust, fume, mist	IDLH: 100 mg/m ³ dust, fume and mist TWA: 1 mg/m ³ dust and mist TWA: 0.1 mg/m ³ fume
Graphite 7782-42-5	TWA: 2 mg/m ³ respirable fraction all forms except graphite fibers	TWA: 15 mg/m ³ total dust synthetic TWA: 5 mg/m ³ respirable fraction synthetic (vacated) TWA: 2.5 mg/m ³ respirable dust natural (vacated) TWA: 10 mg/m ³ total dust synthetic (vacated) TWA: 5 mg/m ³ respirable fraction synthetic TWA: 15 mppcf natural	IDLH: 1250 mg/m ³ TWA: 2.5 mg/m ³ respirable dust
Phosphate(1-), hexafluoro-, lithium 21324-40-3	TWA: 2.5 mg/m ³ F	TWA: 2.5 mg/m ³ F TWA: 2.5 mg/m ³ dust (vacated) TWA: 2.5 mg/m ³	
Aluminum foil 7429-90-5	TWA: 1 mg/m ³ respirable fraction	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 15 mg/m ³ Total dust (vacated) TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 5 mg/m ³ Al Aluminum	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust



Product name: Rechargeable Lithium ion Cell 5068A8 3.7V 18.5Wh **Version:** 3.0/EN

Revision date: 04/01/2016 Issue date: 11/03/2016

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits Immediately Dangerous to Life or Health

Other Exposure	Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965
Guidelines	F.2d 962(11th Cir., 1992) See section 15 for national exposure control parameters

(b) Appropriate engineering controls

Engineering	Showers
Measures	Eyewash stations
	Ventilation systems

(c) Individual protection measures, such as personal protective equipment

Eye/Face Protection Skin and body Protection	Face protection shield. Wear protective gloves and protective clothing. Long sleeved clothing. Chemical resistant apron. Impervious gloves.
Respiratory Protection	No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.
Hygiene Measures	Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. For environmental protection, remove and wash all contaminated protective equipment before re-use.

(a)Physical and Chemical Prope	erties	
Physical State	Solid	
Appearance	Milk-white	e
Odor	No inform	nation available
Color	No inform	nation available
Odor Threshold	No inform	nation available
(b)Property	(c)Values	(d)Remarks Method
рН	No data available	None known
Melting / freezing point	No data available	None known
Boiling point / boiling range	No data available	None known
Flash Point	No data available	None known
Evaporation Rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		
Upper flammability limit	No data available	



Product name: Rechargeable Lithium ion Cell 5068A8 3.7V 18.5Wh Version: 3.0/EN

Revision date: 04/01/2016 Issue date: 11/03/2016

Lower flammability limit	No data available
Vapor pressure	No data available
	No data available
Vapor density	NO Uala avaliable
Specific Gravity	No data available
Water Solubility	Insoluble in water
Solubility in other solvents	No data available
Partition coefficient: n-octanol/water	No data available
Autoignition temperature	No data available
Decomposition temperature	No data available
Kinematic viscosity	No data available
Dynamic viscosity	No data available
Explosive properties	No data available
Oxidizing Properties	No data available

(e)Other Information

Softening Point
VOC Content (%)
Particle Size
Particle Size Distribution

No data available No data available No data available None known None known None known None known

None known None known None known

10. Stability and reactivity

(a) Reactivity

No data available.

(b) Chemical stability

Stable under recommended storage conditions.

(c) Possibility of hazardous reactions

None under normal processing.

(d) Hazardous Polymerization

Hazardous polymerization does not occur.

(e) Conditions to avoid

Exposure to air or moisture over prolonged periods.

(f) Incompatible materials

Acids. Bases. Oxidizing agent.

(g) Hazardous decomposition products

Carbon oxides.

11. Toxicological information

(a) Information on the likely routes of exposure

Product	Product does not present an acute toxicity hazard based on known or supplied
Information	information.



Product name: Rechargeable Lithium ion Cell 5068A8 3.7V 18.5Wh Version: 3.0/EN

Revision date: 04/01/2016 Issue date: 11/03/2016

In case of rupture:.

- Inhalation Specific test data for the substance or mixture is not available. Corrosive by inhalation. (based on components). Inhalation of corrosive fumes/gases may cause coughing, choking, headache, dizziness, and weakness for several hours. Pulmonary edema may occur with tightness in the chest, shortness of breath, bluish skin, decreased blood pressure, and increased heart rate. Inhaled corrosive substances can lead to a toxic edema of the lungs. Pulmonary edema can be fatal. May cause irritation of respiratory tract.
- Eye Contact Specific test data for the substance or mixture is not available. Causes burns. (based on components). Corrosive to the eyes and may cause severe damage including blindness. Causes serious eye damage. May cause irreversible damage to eyes.
- Skin contact Specific test data for the substance or mixture is not available. Corrosive. (based on components). Causes burns
- Ingestion Specific test data for the substance or mixture is not available. Causes burns. (based on components). Ingestion causes burns of the upper digestive and respiratory tracts. May cause severe burning pain in the mouth and stomach with vomiting and diarrhea of dark blood. Blood pressure may decrease. Brownish or yellowish stains may be seen around the mouth. Swelling of the throat may cause shortness of breath and choking. May cause lung damage if swallowed. May be fatal if swallowed and enters airways. Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Graphite	> 10000 mg/kg (Rat)	-	-
7782-42-5			

(b) Information on toxicological effects

Symptoms Erythema (skin redness). Burning. May cause blindness. Coughing and/ or wheezing.

(c)Delayed and immediate effects as well as chronic effects from short and long-term exposure

- Sensitization No information available.
- Mutagenic Effects No information available.
- Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.



Product name: Rechargeable Lithium ion Cell 5068A8 3.7V 18.5Wh Version: 3.0/EN

Revision date: 04/01/2016 Issue date: 11/03/2016

Chemical Name	ACGIH	IARC	NTP	OSHA
Lithium Cobalt Oxi				Y
(CoLiO2) 12190-79-3	A3	Group 2B		X
ACGIH (American Conference of Governmental Industrial Hygienists) A3 - Animal Carcinogen IARC (International Agency for Research on Cancer) Group 2B - Possibly Carcinogenic to Humans OSHA (Occupational Safety and Health Administration of the US Department of Labor) X - Present				
Reproductive Toxicity	No information available			
STOT-single exposure	No information available			
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure. Based on classification criteria from the 2012 OSHA Hazard Communication Standard			
	(29 CFR 1910.1200), organ toxicity from chror	•		o cause systemic targe
Chronic Toxicity	Chronic exposure to corrosive fumes/gases may cause erosion of the teeth followed by jaw necrosis. Bronchial irritation with chronic cough and frequent attacks of pneumonia are common. Gastrointestinal disturbances may also be seen. Contains a known or suspected carcinogen. Avoid repeated exposure. Prolonged exposure may cause chronic effects. May cause adverse liver effects.			
Target Organ Effects	Respiratory system. Eye (CVS).	es. Skin. Gastrointesti	nal tract (GI). (Central Vascular Systen
	Kidney. Liver. Lungs.			
Aspiration Hazard	No information available			

(d) Numerical measures of toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)

3,350.00 mg/kg

ATEmix (dermal)

2,010.00 mg/kg (ATE)

12. Ecological information

(a) Ecotoxicity



Product name: Rechargeable Lithium ion Cell 5068A8 3.7V 18.5Wh Version: 3.0/EN

Revision date: 04/01/2016 Issue date: 11/03/2016

Very toxic to aquatic life with long lasting effects.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to	Daphnia Magna
			Microorgani	(Water
			sms	Flea)
Copper	96h EC50: 0.031 -	96h LC50: 0.0068 - 0.0156 mg/L		48h EC50: = 0.03
7440-50-8	0.054 mg/L	(Pimephales promelas)		mg/L
	(Pseudokirchneriella	96hLC50:=0.112mg/L		
	subcapitata)	(Poecilia reticulata)		
	72h EC50:	96h LC50:=0.3mg/L		
	0.0426 - 0.0535 mg/L	(Cyprinus carpio)		
	(Pseudokirchneriella	96h LC50:= 0.8 mg/L		
	subcapitata)	(Cyprinus carpio)		
		96h LC50: =1.25 mg/L		
		(Lepomis macrochirus)		
		96h LC50: =0.052 mg/L		
		(Oncorhynchus mykiss)		
		96h LC50: =0.2 mg/L		
		(Pimephales promelas)		
		96h LC50: < 0.3 mg/L		
		(Pimephales promelas)		

(b) Persistence and Degradability

No information available.

(c) Bioaccumulation

No information available.

(d) Other adverse effects

No information available.

13. Disposal considerations

Safe handling and methods of disposal

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Local regulations may be more stringent than regional or national requirements.

Product disposal recommendation: Observe local, state and federal laws and regulations.

Packaging disposal recommendation: Be aware discarded batteries may cause fire, tape the battery terminals to insulate them. Don't disassembly the battery. Completely discharge containers (no tear drops, no powder rest, scraped carefully). Containers may be recycled or re-used. Observe local, state and federal laws and regulations.

The potential effects on the environment and human health of the substances used in batteries and accumulators; the desirability of not disposing of waste batteries and accumulators as unsorted municipal waste and of participating in their separate collection so as to facilitate treatment and recycling.



Product name: Rechargeable Lithium ion Cell 5068A8 3.7V 18.5Wh Version: 3.0/EN

Revision date: 04/01/2016 Issue date: 11/03/2016

14. Transport information

According to PACKING INSTRUCTION 965 ~ 967 of IATA DGR 57th Edition for transportation, the special provision 188 of IMDG (inc Amdt 35-10). The batteries should be securely packed and protected against short-circuits. Examine whether the package of the containers are integrate and tighten closed before transport. Take in a cargo of them without falling, dropping, and breakage. Prevent collapse of cargo piles. Don't put the goods together with oxidizer and chief food chemicals. The transport vehicle and ship must be cleaned and sterilized otherwise it is not allowed to assemble articles. During transport, the vehicle should prevent exposure, rain and high temperature. For stopovers, the vehicle should be away from fire and heat sources. When transported by sea, the assemble place should keep away from bedroom and kitchen, and isolated from the engine room, power and fire source. Under the condition of Road Transportation, the driver should drive in accordance with regulated route, don't stop over in the residential area and congested area. Forbid to use wooden, cement for bulk transport.

(a) UN number	3480&3481
(b) UN Proper shipping name	LITHIUM ION BATTERIES (including lithium ion polymer
	batteries) or;LITHIUM ION BATTERIES CONTAINED IN
	EQUIPMENT or LITHIUM ION BATTERIES PACKED WITH
	EQUIPMENT (including lithium ion polymer batteries)
(c) Transport hazard class(es)	9
(d) Packing group (if applicable)	ll
(e) Marine pollutant (Yes/No)	No
(f) Transport in bulk (according to	No information available.
Annex II of MARPOL 73/78 and the IBC	
Code)	
(g) Special precautions	No information available.

15. Regulatory information

OSHA hazard communication standard (29 CFR 1910.1200)

<u>Hazardous</u>

V Non-hazardous

16. Other information, including date of preparation or last revision

(a) Preparation and revision information

Prepared By Shenzhen Beihang Testing Co., Ltd.

Room B201, The Complex Building of Virtual University Park, No.2, Yuexing 3rd Road, South Zone of Technology Park, Yuehai Street, Nanshan District, Shenzhen, Guangdong, China. 04/01/2016

Date of this revision 04/01/2

(b) Abbreviations and acronyms

TSCA:	Toxic Substances Control Act, The American chemical inventory.
DSL	Domestic Substances List
EINECS:	European Inventory of Existing Commercial chemical Substances



Product name: Rechargeable Lithium ion Cell 5068A8 3.7V 18.5Wh Version: 3.0/EN

Revision date: 04/01/2016 Issue date: 11/03/2016

ENCS	Japanese Existing and New Chemical Substances
ECL:	Existing Chemicals List, the Korean chemical inventory.
IECSC:	Inventory of existing chemical substances in China.

(c) Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

--End of Safety Data Sheet--