SYNERGY SCIENTECH CORP. -- Advanced Hybrid Batteries

MATERIAL SAFETY DATA SHEET

Manufacturer's CAGE: SYNERGY

Part No. Indicator: A

Part Number/Trade Name: AHB Series- Lithium ion Polymer batteries.

Model name: AHB392128PS-02

Voltage: 3.7V

Nominal Capacity: 195mAh; Minimum Capacity: 185mAh Lithium metal content: 0.0585g

Wh: 0.7Wh Weight: 4.6g

1. General Information

Company's Name: SYNERGY SCIENTECH CORP.

Company's Street: 7F, No. 9, Park Ave. II, Hsinchu Science Park, Hsinchu, Taiwan 30077 R.O.C.

Company's City: HSIN-CHU, TAIWAN Company's Emerge PhD #: 886-3-564-3700

Company's Info Ph #: 886-3-564-3700

Record No. For Safety Entry: 001 Tot Safety Entries This Sty #: 001

Status: SMJ

Date MSDS Prepared: January 1, 2015 (8th Edition)

Safety Data Review Date: January 1, 2015 MSDS Preparer's Name: Dr. Kevin Wang

Preparer's Company: SAME MSDS Serial Number: LIASN

2. Ingredients/Identity Information

Material Name. (e.g. Sn alloy)	Substance Name (e.g. Copper (Cu))	CAS No.	Percentage (%)
active material	LiCoO2	12190-79-3	32.62
Binder-PVDF	Poly(vinyliden difluoride)	24937-79-9	1.04
conditive material	Carbon	1333-86-4	0.78
conditive material	Carbon	1333-86-4	0.26
foil	Aluminium	7429-90-5	4.61
active material	Carbon	1333-86-4	15.92
Binder-PVDF	Poly(vinyliden difluoride)	24937-79-9	1.3
conditive material	Carbon	1333-86-4	0.09
additive	Oxalic acid	144-62-7	0.05
foil	Copper	7440-50-8	7.87

electrolyte-solvent	Ethylene carbonate	96-49-1	5.06
electrolyte-solvent	Diethyl carbonate	105-58-8	3.72
electrolyte-solvent	Ethyl methyl carbonate	623-53-0	3.83
electrolyte-additive	Lithium hexafluorophosphate	21324-40-3	1.82
separator	polyethylene	9002-88-4	3.62
tape-film	polyimide	75-55-8	0.1
tape-adhesive	Acrylic	9011-14-7	0.03
tape-film	polyester	25038-59-9	0.14
tape-adhesive	Acrylic	9011-14-7	0.03
Al bag	Nylon	32131-17-2	3.85
Al bag	Aluminium	7429-90-5	9.75
Al bag	Polypropylene	9003-07-0	2.57
tab lead	Nickel	7440-02-0	0.38
tab lead	polypropylene	9003-07-0	0.05
tab lead	Aluminium	7429-90-5	0.24
tab lead	polypropylene	9003-07-0	0.05
tab	Nickel	7440-02-0	0.22

3. Hazards Identification

Route Of Entry - Inhalation: YES Route Of Entry - Skin: YES

Route Of Entry - Ingestion: YES

Health Haz Acute And Chronic: UNDER NORM CNDTNS OF USE, THESE CHEMICALS ARE CONTAINED IN SEALED CAN. RISK OF EXPOS OCCURS ONLY IF BATTERY IS

MECHANICALLY ABUSED. ACUTE: INHAL: CONTENTS OF OPENED BATTERY CAN CAUSE

CONTENTS OF OPENED BATTERY CAN CAUSE IRRIT.

Carcinogenicity - NTP: NO Carcinogenicity - IARC: NO Carcinogenicity - OSHA: NO

4. First Aid Measures

Explanation Carcinogenicity: NOT RELEVANT.

Signs/Symptoms Of Overexp: SEE HEALTH HAZARDS.

Med Cond Aggravated By Exp: NONE SPECIFIED BY MANUFACTURER.

WASH WITH SOAP AND WATER. EYES: IMMEDIATELY FLUSH THOROUGHLY WITH COPIOUS

AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. SEEK MEDICAL ATTENTION.

INGESTION: CALL MD IMMEDIATELY (FP N).

5. Fire Fighting Measures

Extinguishing Media: IN CASE OF FIRE, USE CARBON DIOXIDE OR DRY CHEMICAL EXTINGUISHERS. Special Fire Fighting Proc: WEAR NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT (FP N). Unusual Fire And Expl Hazrds: NONE SPECIFIED BY MANUFACTURER. 6. Accidental Release Measures Wear appropriate personal protective equipment. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. 7. Handling and Storage _____ Wear suitable chemical resistant gloves, safety glasses and filtered cartridge respirator. Goggles, full face protection and other protective clothing is required if potential exists for direct exposure to liquid battery electrolyte. In case Material is released or spilled: Carefully recover spillages with appropriate ladle and transfer to a suitably labeled, sealable container for safe disposal. Wash the spillage area neutorize with calclumhydroxide. Wear suitable personal protection during removal of spillages. Be stored in clearly labeled, tightly closed exclusive containers in a cool, dry area. 8. Exposure Controls/Personal Protection Ventilation: Use local exhaust. Protective Gloves: Wear rubber or plastic gloves. Eye/Face Protection: Wear safety glasses, goggles or full face protections. Respiratory Protection: Wear filtered cartridge respirator or a respirator of greater protection. 9. Physical and Chemical Properties Product Type: Solid Appearance: Prismatic Odor: Odorless 10. Stability and Reactivity Stability: YES Cond To Avoid (Stability): NONE SPECIFIED BY MANUFACTURER.

Materials To Avoid: NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomp Products: NONE SPECIFIED BY MANUFACTURER.

Hazardous Poly Occur: NO

Conditions To Avoid (Poly): NOT RELEVANT.

11. Toxicological Information

In case electrolyte is spilled and explored with air, the HF could be released.

May include hydrogen fluoride and carbon oxides gas.

May cause skin and eye irritation when contacted.

12. Ecological Information

13. Disposal Consideration

13. Disposal Consideration

Disposal should be in accordance with local, state or national legislation.

UN No: UN3480 / UN3481

The battery models listed have aggregate equivalent lithium content below the 0.0585g and the Watt hour is not more than 100Wh. And shipment contains no item listed under IATA DGR Packing instruction PI-965 to PI-967 Section II and meets all requirements under UN Manual of Tests and Criteria Part III, subsection 38.3

14. Transport Information

	UN 38.3 Lithium Battery	Test results	Remarks
NO	Test item	OK	Test 1 to 5 must be conducted in
T1	Altitude simulation	OK	sequence on the same cell or
T2	Thermal test	OK	battery
T3	Vibration	OK	
T4	Shock	OK	
T5	External short circuit	OK	
T6	Impact	OK	
T7	Overcharge	OK	Only battery do need this test item
T8	Forced discharge	OK	For cell only

The product is not classified as dangerous under the current edition of the 2014 IATA dangerous goods regulations. The products are safe for air transportation and not regulated by IATA DGR. Also they comply with the PI-965 to PI-967 Section II accordingly.

15. Regulatory Information	

See ACGIH exposure limits information as noted in Section 3.

US: This MSDS meets/exceeds OSHA requirements

International: this MSDS conforms to European Union (UN), the International Standards Organization (ISO) and the International Labor Organization (ILO) and as documental in ANSI (American National Standards Institute) Standard Z400.1-1993.

16. Other Information

Reference:

Chemical substances information: Japan Advanced Information center of Safety and Health International Chemical Safety Cards (ICSCs): International Occupational Safety and Health Information Centre (CIS)

2002 TLVs and BELs: American Conference of Governmental Industrial Hygienists (ACGIH) Dangerous Goods Regulations-55th Edition Effective 1 January 2014: International Air Transport Association (IATA)

IMDG Code-2008 Edition: International Maritime Organization (IMO)

The European Agreement concerning the International Carriage of Dangerous Goods by Road-2009:

The United Nations Economic Commission for Europe (UNECE)

MSDS of raw materials prepared by the manufactures