



新普科技股份有限公司  
新世電子(常熟)有限公司  
新普科技(重慶)有限公司  
華普電子(常熟)有限公司  
Simplo Technology Co., Ltd.  
Simplo Technology(Changshu)Inc.  
Simplo Technology(Chongqing)Inc.  
Huapu Technology(Changshu)Inc.

# MATERIAL SAFETY DATA SHEET

Issued/Revised date : March 29 2016

Document No. : AS-1600302003

## 1. Product and Company Identification

Product Identification : Li-  
Polymer Battery Pack /1S2P  
Model Name : T101HA  
Customer P/N : 0B200-  
02120100 Simplo P/N :  
906T/QA148HA Rating : 32 Wh

Manufacturer :

Simplo Technology Co., Ltd.

No.471, Sec.2, Pa Teh Rd., Hu Kou 303, Hsin Chu Hsien, Taiwan

Tel : +886-3-5695920 Fax : +886-3-5695931

Simplo Technology (CHANGSHU) INC.

No.2 DongNan Avenue, ChangShu, JiangSu Province , China

Tel : +86-0512-52302255 Fax : +86-0512-52302277

Simplo Technology (CHONGQING) INC

NO.2 Zongbao Avenue, Shapingba District, Chongqing, China

Tel : 023-61718899 Fax : 023-61710488

Huapu Technology(Changshu) Inc.

No.2 DongNan Avenue, ChangShu, JiangSu Province , China

Tel : +86-0512-52302255 Fax : +86-0512-52302277

## 2. Hazards Identification

Primary routes of entry : Skin contact, Skin absorption; Eye contact, Inhalation and ingestion: No

Symptoms of exposure : Skin contact, No effect under routine handling and use.

Skin absorption : No effect under routine handling and use.

Eye contact : No effect under routine handling and use.

Inhalation : No effect under routine handling and use.

Reported as carcinogen : Not applicable

According to the OSHA Hazard Communication Standard (29 CFR 1910.1200), this product is nonhazardous.

## 3. Composition / Identification on Ingredients

Substance : Lithium Ion Battery

CAS number : Reference 3-3

UN Class : Even classified as lithium batteries, they are exempted from dangerous goods. UN-Recommendations on the Transport of Dangerous Goods Model Regulations.

\* Lithium ion cells and batteries may be offered for transport if they meet the following :

\* For cells, the Watt-hour rating should not be more than 20 Wh;

\* For batteries, the Watt-hour rating should not be more than 100 Wh. The Watt-hour rating must be marked on the outside of the battery case .

\* Each cell or battery of the type proved to meet the requirements of each test in the UN manual of tests and criteria, Part III, subsection 38.3.

\* General requirements and additional requirements, Please see Section II or IB of Packing Instruction 965, 966, 967 accordingly or UN 3480 , UN3481.



新普科技股份有限公司  
 新世電子(常熟)有限公司  
 新普科技(重慶)有限公司  
 華普電子(常熟)有限公司  
 Simplo Technology Co., Ltd.  
 Simplo Technology(Changshu)Inc.  
 Simplo Technology(Chongqing)Inc.  
 Huapu Technology(Changshu)Inc.

Composition :

- 3-1. Cases: Plastic Not dangerous
- 3-2. Printed Circuit Board Assembly Not dangerous
- 3-3. Lithium Ion Cell :

Hazardous Ingredients	%	CAS Number
Graphite	7-25	7782-42-5
Lithium cobalt	15-40	12190-79-3
Lithium Nickel Cobalt Manganese Oxide	5-40	182442-95-1
Lithium Hexafluorophosphate	0-5	21324-40-3
Acetylene Black	0-2	1333-86-4
Diethyl Carbonate	0-15	105-58-8
Dimethyl Carbonate	0-15	616-38-6
Ethyl Methyl Carbonate	0-15	623-53-0
Propylene Carbonate	0-15	108-32-7
Ethylene Carbonate	0-15	96-49-1

#### 4. First Aid Measures

Inhalation : Make the victim blow his/her nose, gargle. Seek medical attention if necessary.

Skin contact : Remove contaminated clothes and shoes immediately. Wash extraneous matter or contact region with soap and plenty of water immediately.

Eye contact : Do not rub one's eyes. Immediately flush eyes with water continuously for at least 15 minutes. Seek medical attention immediately.

Ingestion : Make the victim vomit. When it is impossible or the feeling is not well after vomiting, seek medical attention.

#### 5. Fire Fighting Measures

Extinguishing Media : Use suitable extinguishing media.

Firefighting Equipment : Use NIOSH/MSHA approved full-face self-contained breathing apparatus (SCBA) with full protective gear.

#### 6. Accidental Release Measures

On Land : Place material into suitable containers and call local fire/police department. In

Water : If possible, Remove from water and call local fire/police department.

#### 7. Handling and Storage

Handling :

Do not expose the battery to excessive physical shock or vibration. Short-circuiting should be avoided. However, accidental short-circuiting for a few seconds will not seriously affect the battery. Prolonged short circuits will cause the battery to rapidly lose energy, could generate enough heat to burn skin. Sources of short circuits include jumbled batteries in bulk containers, coins, metal jewelry, metal covered tables, or metal belts used for assembly of batteries in devices. To minimize risk of short-circuiting, the protective case supplied with the battery should be used to cover the terminals when transporting or storing the battery. Do not disassemble or deform the battery. Should an individual cell within a battery become ruptured, do not allow contact with water.

Storage :



新普科技股份有限公司  
 新世電子(常熟)有限公司  
 新普科技(重慶)有限公司  
 華普電子(常熟)有限公司  
 Simplo Technology Co., Ltd.  
 Simplo Technology(Changshu)Inc.  
 Simplo Technology(Chongqing)Inc.  
 Huapu Technology(Changshu)Inc.

The lithium ion battery should be between 25% and 75% of full charge when stored for a long period of time. Store in a cool, dry, well ventilated area. And temperature above 100 Celsius degree can result in loss of battery performance, leakage, or rust. Do not expose the battery to open flames..

**8. Exposure Controls / Personal Protection**

Engineering Controls : Keep away from heat and open flame. Store in a cool dry place  
Personal Protection :

Respirator : Not required during normal operations. SCBA required in the event of a fire.  
Eye/Face Protection : Not required beyond safety practices of employer.

Gloves : Not required for handling of battery.

Foot Protection : Steel toed shoes recommended for large container handling.

**9. Physical and Chemical Properties**

State	Solid
Odor	N/A
PH	N/A
Vapor pressure	N/A
Vapor density	N/A
Boiling point	N/A
Solubility in water	Insoluble
Specific gravity	N/A
Density	N/A

**10. Stability and Reactivity**

Reactivity : None

Incompatibilities : None during normal operation. Avoid exposure to heat, open flame, and corrosives.

Conditions to Avoid : Avoid exposure to heat and open flame. Do not puncture, crush or incinerate.

**11. Toxicological Information**

This product does not elicit toxicological properties during routine handling and use.

**12. Ecological Information**

Lithium ion battery pack can be disposable in accordance with appropriate federal, state and local regulations.

**13. Disposal Consideration**

Recommended methods for safe and environmentally preferred disposal: Product(waste from residues)

Do not throw out a used battery cell. Recycle it through the recycling company. Contaminated packaging

Neither a container nor packing is contaminated during normal use. When internal materials leaked from a battery cell contaminates, dispose as industrial wastes subject to special control.

**14. Transport Information**

With regard to transport, the following regulations are cited and considered:





新普科技股份有限公司  
新世電子(常熟)有限公司  
新普科技(重慶)有限公司  
華普電子(常熟)有限公司  
Simplo Technology Co., Ltd.  
Simplo Technology(Changshu)Inc.  
Simplo Technology(Chongqing)Inc.  
Huapu Technology(Changshu)Inc.

Chemical substances information: Japan Advanced Information center of Safety and Health

International Chemical Safety Cards (ICSCs):

International Occupational Safety and Health Information Centre (CIS)

1999 TLVs and BEIs: American Conference of Governmental Industrial Hygienists (ACGIH) Wastes Disposal and Public Cleaning Law [Japan]

Law for Promotion of Effective Utilization of resources [Japan]