

According to HCS-2012 APPENDIX D TO §1910.1200

Version: 2.0/EN Product name: Polymer Li-ion Battery Revision date: 2018.01.01 Issue date: 2018.02.01

(a) Product identifier	
Product name:	Polymer Li-ion Battery
(b) Other means of ident	ification
Product description:	Model: JXY 402030
	Nominal Voltage: 3.7V
	Typical Capacity: 200mAh
	Watt-hour: 0.7Wh
(c) Recommended use of	the chemical and restrictions on use
Recommended use:	Polymer Li-ion Battery
Restriction on use:	No information available.
(d) Details of the supplier	r of the product
Company name	Shenzhen Tongshunhui Video Technology Co., LTD
Address:	2 Floor, J Building, No. 8, School Of Science And Technology Industrial City East,
	Xuexiang Community, Bantian, Longgang , Shenzhen.
E-mail:	sztsh@tongshunhui.com
Telephone:	+86-13715063139

2. Hazard(s) identification

(a) Classification

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200) This product is an article which is a sealed battery and as such does not require an MSDS per the OSHA hazard communication standard unless ruptured. The hazards indicated are for a ruptured battery.

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 1
Specific target organ toxicity (repeated exposure) Category	Category 1

(b) GHS Label elements, including precautionary statements

Safety Data Sheet According to HCS-2012 APPENDIX D TO §1910.1200



Version: 2.0/EN Product name: Polymer Li-ion Battery

Revision date: 2018.01.01 Issue date: 2018.02.01

Emergency C	Overview
Signal word Danger	
Hazard Statements	
Causes skin irritation	
Causes serious eye damage	
This product is an article which contains a chemical subs	
article as sold. Intended use of the product should not r	result in exposure to the chemical substance. This is
battery. In case of rupture: the above hazards exist.	- Cha
Appearance Silver Physical State So	lid Odor Odorless
Appearance Silver Physical State So	Oddi Oddi ess
Precautionary Statements - Prevention	
Wash face, hands and any exposed skin thoroughly after ha	Indling
Wear protective gloves/protective clothing/eye protection/	
Do not breathe dust/fume/gas/mist/vapors/spray	Tace protection
Do not eat, drink or smoke when using this product	
Precautionary Statements - Response	
Specific treatment (see supplemental first aid instructions o	on this label)
Get medical advice/attention if you feel unwell	
0 2008	× .×
Eyes	
IF IN EYES: Rinse cautiously with water for several minutes.	Remove contact lenses, if present and easy to do.
Continue rinsing. Immediately call a POISON CENTER or doc	ctor/physician
Skin	
IF ON SKIN: Wash with plenty of soap and water	
If skin irritation occurs: Get medical advice/attention	
Take off contaminated clothing and wash before reuse	
Precautionary Statements - Storage	
No information available.	
Precautionary Statements - Disposal	
Dispose of contents/container to an approved waste dispos	al plant
(c) Hazards not otherwise classified (HNOC)	
	Page 2 of 10
No.: NCT18004881S1-1	



According to HCS-2012 APPENDIX D TO §1910.1200

Version: 2.0/EN

Product name: Polymer Li-ion Battery

Revision date: 2018.01.01 Issue date: 2018.02.01

No information available.

(d) Unknown Toxicity

10% of the mixture consists of ingredient(s) of unknown toxicity.

(e) Other information

No information available.

(f) Interactions with Other Chemicals

No information available.

3. Composition/information on ingredients

Chemical name	CAS No.	Concentration%
Lithium Cobalt Oxide (CoLiO2)	12190-79-3	40
Graphite	7782-42-5	22
Copper	7440-50-8	9
Aluminium	7429-90-5	6
Polypropylene	9003-07-0	3
Polyethylene	9002-88-4	6
Phosphate(1-), hexafluoro-, lithium	21324-40-3	12
Nickel	7440-02-0	2

4. First-aid measures

(a) Description of f	irst aid measures 2008
General Advice	First aid is upon rupture of sealed battery.
Eye contact:	Show this safety data sheet to the doctor in attendance. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists. Do not rub affected area.
Skin contact:	Remove contaminated clothes and rinse the skin with plenty of water. Get medical advice / attention if you feel unwell.
Inhalation:	Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, (trained personnel should) give oxygen. Get medical advice / attention if you feel unwell.
Ingestion:	Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Get medical aid.
Self-protection of the first aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.
(b) Most important	symptoms/effects, acute and delayed

(b) Most important symptoms/effects, acute and delayed



According to HCS-2012 APPENDIX D TO §1910.1200

Version: 2.0/EN

Product name: Polymer Li-ion Battery

Revision date: 2018.01.01 Issue date: 2018.02.01

Contact with internal components may cause allergic skin sensitization (rash) and irritate eyes, skin, nose, throat, respiratory system. Cobalt and Cobalt compounds are considered to be possible human carcinogen(s).

(c) Immediate medical attention and special treatment

No information available.

5. Fire-fighting measures

(a) Extinguishing media

Suitable extinguishing media: Unsuitable extinguishing media: Use foam, dry powder or dry sand, CO_2 as appropriate.

No information available.

(b) Special hazards arising from the chemical

Under fire conditions, batteries may burst and release hazardous decomposition products when exposed to a fire situation. This could result in the release of flammable or corrosive materials. Hazardous combustion products: CO, CO₂, Metal oxides, Irritating fumes

(c) Special protective equipment and precautions for fire-fighters

Firefighters must wear fire resistant protective equipment and appropriate breathing apparatus. The staff must equip with filtermask (full mask) or isolated breathing apparatus. The staff must wear the clothes which can defense the fire and the toxic gas. Put out the fire in the upwind direction. Remove the container to the open space as soon as possible. Spray water on the containers in the fireplace to keep them cool until finish extinguishment.

6. Accidental release measures

(a) Personal precautions, protective equipment and emergency procedures

If the battery material is released, remove personnel from area until fumes dissipate. Provide maximum ventilation to clear out hazardous gases. The preferred response is to leave the area, dispose the case after the batteries cool and vapors dissipate. Provide maximum ventilation. Avoid skin and eye contact or inhalation of vapors.

(b) Environmental Precautions

Prevent material from contaminating soil and from entering sewers or waterways.

(c) Methods and materials for containment and cleaning up

If the battery casing is dismantled, small amounts of electrolyte may leak. Collect all released material in a plastic lined container. Dispose off according to the local law and rules. Avoid leached substances to get into the earth, canalization or waters.

7. Handling and storage

(a) Precautions for safe handling



According to HCS-2012 APPENDIX D TO §1910.1200

Version: 2.0/EN Product name: Polymer Li-ion Battery

Revision date: 2018.01.01 Issue date: 2018.02.01

Always follow the warning information on the batteries and in the manuals of devices. Only use the recommended battery types. Keep batteries away from children. For devices to be used by children, the battery casing should be protected against unauthorized access. Unpacked batteries shall not lie about in bulk. In case of battery change always replace all batteries by new ones of identical type and brand. Do not swallow batteries. Do not throw batteries into fire. Avoid deep discharge. Do not short-circuit batteries Use recommended charging time and current.

(b) Conditions for safe storage, including any incompatibilities

If the battery is subject to storage for such a long term as more than 3 months, it is recommended to recharge the battery periodically. And recommended at $-5^{\circ}C^{\circ}+45^{\circ}C^{\circ}$ for 1 month storage, at $-5^{\circ}C^{\circ}+35^{\circ}C^{\circ}$ for 3 months storage. Do not storage the battery haphazardly in a box or drawer where they may short-circuit each other or be short-circuited by other metal objects. Keep out of reach of children.

8. Exposure controls/personal protection

(a)Control parameters **Exposure Guidelines OSHA PEL Chemical Name** ACGIH TLV NIOSH IDLH Lithium Cobalt Oxide (CoLiO2) TWA: 0.02 mg/m3 12190-79-3 Graphite 2 mg/m3 TWA 15 mppcf (Z-3) 2.5 mg/m3 TWA 7782-42-5 (Respirable fraction) IDLH: 100 mg/m3 dust, TWA: 0.1 mg/m3 fume TWA: 0.2 mg/m3 fume fume and mist TWA: 1 mg/m3 dust and mist Copper TWA: 1 TWA: 1 mg/m3 dust 7440-50-8 (vacated) TWA: 0.1 mg/m3 Cu mg/m3 Cu dust and mist and mist dust, fume, mist TWA: 0.1 mg/m3 fume TWA: 15 mg/m3 total dust TWA: 5 mg/m3 respirable fraction TWA: 10 mg/m3 total (vacated) TWA: 15 mg/m3 total Aluminum TWA: 1 mg/m3 dust dust 7429-90-5 respirable fraction TWA: 5 mg/m3 (vacated) TWA: 5 mg/m3 respirable dust respirable fraction (vacated) TWA: 5 mg/m3 Al Aluminum Phosphate(1-), TWA: 2.5 mg/m3 F hexafluoro-, lithium TWA: 2.5 mg/m3 F TWA: 2.5 mg/m3 dust 21324-40-3 (vacated) TWA: 2.5 mg/m3

According to HCS-2012 APPENDIX D TO §1910.1200

NCT Technology

Version: 2.0/EN Product name: Polymer Li-ion Battery Revision date: 2018.01.01 Issue date: 2018.02.01

ACGIH TLV: American Conference of Governmental Industrial Hygienists -Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits Immediately Dangerous to Life or Health

Other Exposure Guidelines: Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962(11th Cir., 1992) See section 15 for national exposure control parameters

(b) Appropriate engineering controls

Engineering Measures: 1.Showers 2.Eyewash stations 3.Ventilation systems

(c) Individual protection measures, such as personal protective equipment

Eye/Face Protection:	Not necessary under normal conditions, wear safety glasses if handling an open or
	leaking battery.
Skin and body Protection:	Not necessary under normal conditions, Wear protective gloves and protective
	clothing such as long sleeved clothing, impervious gloves, chemical resistant apron,
	and antistatic boots if handling an open or leaking battery.
Respiratory Protection:	Not necessary under normal conditions. If exposure limits are exceeded or irritation
	is experienced, ventilation and evacuation may be required.
Hygiene Measures:	Handle in accordance with good industrial hygiene and safety practice. Avoid contact
ž	with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat,
	drink, or smoke in work area. Maintain good housekeeping.

9. Physical and chemical properties

(a) Appearance	Silver Solid
(b) Odor	Odorless
(c) Odor threshold	No data available.
(d) pH	No data available.
(e) Melting point/freezing point	No data available.
(f) Initial boiling point and boiling range	No data available.
(g) Flash point	No data available.
(h) Evaporation rate	No data available.
(i) Flammability	No data available.
(j) Upper/lower flammability or explosive limits	No data available.
(k) Vapor pressure	No data available.
(l) Vapor density	No data available.
(m) Relative density	No data available.
(n) Solubility(ies)	Insoluble in water.
(o) Partition coefficient: n-octanol/water	No data available.
(p) Auto-ignition temperature	No data available.
(q) Decomposition temperature	No data available.
(r) Viscosity	No data available.



According to HCS-2012 APPENDIX D TO §1910.1200

Version: 2.0/EN

Product name: Polymer Li-ion Battery

Revision date: 2018.01.01 Issue date: 2018.02.01

10. Stability and reactivity

(a) Reactivity

Stable under recommended storage and handling conditions.

(b) Chemical stability

Stable under normal conditions.

(c) Possibility of hazardous reactions

When heated above 150°C the risk of rupture occurs. Due to special safety construction, rupture implies controlled release of pressure without ignition.

(d) Conditions to avoid

Do not subject the battery to mechanical shock. Keep away from open flames, high temperature.

(e) Incompatible materials

Strong oxidizer, strong acid.

(f) Hazardous decomposition products

Under fire conditions, the electrode materials can form carcinogenic nickel and cobalt oxides.

11. Toxicological information

Inhalation: Ingestion:

Skin contact:

Eve contact:

(a) Information on the likely routes of exposure

Inhalation of a large number of vapors or fumes released due to heat may cause respiratory. Ingestion of battery contents may cause mouth, throat and intestinal burns and damage.

Contact with battery electrolyte may cause burns and skin irritation.

Contact with battery electrolyte may cause burns. Eye damage is possible.

Under normal conditions (during charge and discharge) release of ingredients does not occur. If accidental release occurs see information in section 4. Swallowing of a battery can be harmful. Call the local Poison Control Centre for advice and follow-up.

(b) Information on toxicological characteristics

Acute toxicity:	No data available.
Skin corrosion/irritation:	The liquid in the battery irritates.
Serious eye damage/irritation:	The liquid in the battery irritates.
Respiratory sensitization:	The liquid in the battery may cause sensitization to some person.
Skin sensitization:	The liquid in the battery may cause sensitization to some person.
Carcinogenicity:	Cobalt and Cobalt compounds are considered to be possible human
	carcinogen(s).
Germ Cell Mutagenicity:	No data available.
Reproductive Toxicity:	No data available.
STOT-Single Exposure:	No data available.
STOT-Repeated Exposure:	No data available.
Aspiration Hazard:	No data available.

According to HCS-2012 APPENDIX D TO §1910.1200



Version: 2.0/EN Product name: Polymer Li-ion Battery

Revision date: 2018.01.01 Issue date: 2018.02.01

(c) Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization: Mutagenic Effects: Carcinogenicity: Reproductive Toxicity: Chronic Toxicity: Target Organ Effects: Aspiration Hazard:

No data available. No data available.

12. Ecological information

(a) Ecotoxicity

Water hazard class 1(Self-assessment): slightly hazardous for water.

(b) Persistence and Degradability

No information available.

(c) Bioaccumulative potential

No information available.

(d) Mobility in soil

No information available.

(e) Other adverse effects

No information available.

13. Disposal considerations

Safe handling and methods of disposal

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Local regulations may be more stringent than regional or national requirements.

Product disposal recommendation: Observe local, state and federal laws and regulations.

Packaging disposal recommendation: Be aware discarded batteries may cause fire, tape the battery terminals to insulate them. Don't disassembly the battery. Completely discharge containers (no tear drops, no powder rest, scraped carefully). Containers may be recycled or re-used. Observe local, state and federal laws and regulations.

The potential effects on the environment and human health of the substances used in batteries and accumulators; the desirability of not disposing of waste batteries and accumulators as unsorted municipal waste and of participating in their separate collection so as to facilitate treatment and recycling.

14. Transport information



According to HCS-2012 APPENDIX D TO §1910.1200

Version: 2.0/EN Product name: Polymer Li-ion Battery

Revision date: 2018.01.01 Issue date: 2018.02.01

According to Section II/Section IB of PACKING INSTRUCTION 965, or Section II of PACKING INSTRUCTION 966 \sim 967 of the 2018 IATA Dangerous Goods regulations 59th Edition and the special provision 188 of IMDG (inc Amdt 38-16). The batteries should be securely packed and protected against short-circuits. Examine whether the package of the containers are integrate and tighten closed before transport. Take in a cargo of them without falling, dropping, and breakage. Prevent collapse of cargo piles. Don't put the goods together with oxidizer and chief food chemicals. The transport vehicle and ship must be cleaned and sterilized otherwise it is not allowed to assemble articles. During transport, the vehicle should prevent exposure, rain and high temperature. For stopovers, the vehicle should be away from fire and heat sources. When transported by sea, the assemble place should keep away from bedroom and kitchen, and isolated from the engine room, power and fire source. Under the condition of Road Transportation, the driver should drive in accordance with regulated route, don't stop over in the residential area and congested area. Forbid to use wooden, cement for bulk transport.

(a) UN number

(b) UN Proper shipping name

(c) Transport Hazard class(es)

(e) Marine pollutant (Yes/No)

(d) Packing group (if applicable)

(f) Transport in bulk (according to Annex II

of MARPOL 73/78 and the IBC Code)

3480 or 3481

LITHIUM ION BATTERIES (including lithium ion polymer batteries) or; LITHIUM ION BATTERIES CONTAINED IN EQUIPMENT or LITHIUM ION BATTERIES PACKED WITH EQUIPMENT (including lithium ion polymer batteries)

Class 9 (PI965 Section IB) or N/A (PI965~967 Section II)

II

No

No information available.

No information available.

15. Regulatory information

(g) Special precautions

With regard to transport, the following regulations are cited and considered:

- The International Civil Aviation Organization (ICAO) Technical Instructions.
- The International Air transport Association (IATA) Dangerous Goods Regulations.
- The International Maritime Dangerous Goods (IMDG) Code.
- The Office of Hazardous Materials Safety within the US Department of Transportation (DOT)
- Research and Special Programs Administration (RSPA)

16. Other information, including date of preparation or last revision

(a) Preparation and revision information

Date of previous revision: 2015.04.29	Date of this revision: 2018.01.01
Revision summary: The Second New SDS	

(b) Abbreviations and acronyms

TSCA:	Toxic Substances Control Act, The American chemical inventory.
DSL	Domestic Substances List
EINECS:	European Inventory of Existing Commercial chemical Substances

According to HCS-2012 APPENDIX D TO §1910.1200

Version: 2.0/EN Product name: Polymer Li-ion Battery

ENCS	Japanese Existing and New Chemical Substances
ECL:	Existing Chemicals List, the Korean chemical inventory.
IECSC:	Inventory of existing chemical substances in China.

(c) Disclaimer

Because all of our batteries are defined as "articles", they are exempted from the requirements of the Hazard Communication Standard. The information in this SDS is provided all the relevant data fully and truly. However, the information is provided without any warranty on their absolute extensiveness and accuracy. This SDS was prepared to provide safety preventive measures for the users who have got professional training. The personal user who obtained this SDS should make independent judgment for the applicability of this SDS under special conditions. In these special cases, we do not assume responsibility for the damage.





Revision date: 2018.01.01

Issue date: 2018.02.01