Issuing Date 16-Feb-2016

SAFETY DATA SHEET

Revision Date 16-Feb-2016

Revision Number 3

(U)

The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier	
Product Name	Lithium-Ion Rechargeable Battery Cell UR18650AY
Other means of identification	
Synonyms	None
Recommended use of the chemical	and restrictions on use
Recommended Use	LITHIUM ION BATTERIES
Uses advised against	No information available
Details of the supplier of the safety	data sheet
Supplier Name	Getac Technology Corp.
Supplier Address	5F., Building A, No.209, Sec.1, Nangang Rd., Nangang Dist., 5F., Building A, No.209, Sec.1, Nangang Rd., Nangang Dist., Taipei Taiwan 11568 TW
Supplier Phone Number	Phone:+886-2-27857888 Fax:+886-2-27865656
Supplier Email	jeffrey.cheng@getac.com
Emergency telephone number	
Company Emergency Phone Number	886-920656361

2. HAZARDS IDENTIFICATION

Classification

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200). This product is an article which is a sealed battery and as such does not require an MSDS per the OSHA hazard communication standard unless ruptured. The hazards indicated are for a ruptured battery.

Skin corrosion/irritation	Category 2



Serious eye damage/eye irritation	Category 2
Skin sensitization	Category 1
Carcinogenicity	Category 1A
Specific target organ toxicity (repeated exposure)	Category 1

GHS Label elements, including precautionary statements

Signal word	Dange	Emergency Overview	
Hazard Statements			
Causes skin irritation			
Causes serious eye irritat			
May cause an allergic ski	n reaction		
May cause cancer Causes damage to organ	s through prolonged	or repeated exposure	
			is given for exposure to the article as sold. e. This is a battery. In case of rupture: the
	ation available	Physical state Solid	Odor No information availab

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required Wash face, hands and any exposed skin thoroughly after handling Contaminated work clothing should not be allowed out of the workplace Wear protective gloves Do not breathe dust/fume/gas/mist/vapors/spray Do not eat, drink or smoke when using this product Wear eye/face protection

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention Specific treatment (see supplemental first aid instructions on this label)

Eves

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

Skin

IF ON SKIN: Wash with plenty of soap and water Take off contaminated clothing and wash before reuse If skin irritation or rash occurs: Get medical advice/attention

Precautionary Statements - Storage

Store locked up



Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Unknown Toxicity

20 % of the mixture consists of ingredient(s) of unknown toxicity

Other information

May be harmful if swallowed Very toxic to aquatic life with long lasting effects Repeated or prolonged skin contact may cause allergic reactions with susceptible persons

Interactions with Other Chemicals

No information available.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%	Trade Secret
Cobalt lithium manganese nickel oxide	182442-95-1	15 - 40	*
Graphite	7782-42-5	10 - 30	*
ron	7439-89-6	10 - 30	*
Copper	7440-50-8	3 - 7	*
Aluminum	7429-90-5	3 - 7	*
Phosphate(1-), hexafluoro-, lithium	21324-40-3	1 - 5	*
Propylene carbonate	108-32-7	1 - 5	*
Nickel	7440-02-0	0.1 - 1	*

*The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

First aid measures

General Advice	First aid is upon rupture of sealed battery.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Remove contact lenses, if present and easy to do. Continue rinsing. Do not rub affected area. Get medical attention if irritation develops and persists.
Skin contact	Wash off immediately with soap and plenty of water for at least 15 minutes. May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a physician.
Inhalation	Remove to fresh air. Get medical attention immediately if symptoms occur.
Ingestion	Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Call a physician.
Self-protection of the first aider	Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. Wear personal protective clothing (see section 8).

Most important symptoms and effects, both acute and delayed



Most Important Symptoms and Effects	Itching. Coughing and/ or wheezing.				
Indication of any immediate medic	al attention and special treatment needed				
Notes to Physician May cause sensitization in susceptible persons. Treat symptomatically.					
	5. FIRE-FIGHTING MEASURES				
Suitable Extinguishing Media Use extinguishing measures that are Unsuitable extinguishing media CAUTION: Use of water spray when	appropriate to local circumstances and the surrounding environment. fighting fire may be inefficient.				
	Specific hazards arising from the chemical Product is or contains a sensitizer. May cause sensitization by skin contact.				
Explosion Data Sensitivity to Mechanical Impact	None.				
Sensitivity to Static Discharge	None.				
Protective equipment and precautions for firefighters As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.					
6. ACCIDENTAL RELEASE MEASURES					
Personal precautions, protective equipment and emergency procedures					
Personal precautions	Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas.				
Other Information	Refer to protective measures listed in Sections 7 and 8.				

Environmental precautions

Environmental precautions Prevent further leakage or spillage if safe to do so.

Methods and material for containment and cleaning up

Methods for containmentPrevent further leakage or spillage if safe to do so.

Methods for cleaning up Pick up and transfer to properly labeled containers.



7. HANDLING AND STORAGE

Precautions for safe handling

HandlingIn case of rupture: Handle in accordance with good industrial hygiene and safety practice.
Avoid contact with skin, eyes or clothing. Use personal protection equipment.Conditions for safe storage, including any incompatibilitiesStorageKeep containers tightly closed in a dry, cool and well-ventilated place. Store locked up.
Keep out of the reach of children.Incompatible ProductsStrong acids. Strong oxidizing agents. Strong bases.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Cobalt lithium manganese nickel oxide 182442-95-1	TWA: 0.02 mg/m ³ Co TWA: 0.02 mg/m ³ Mn TWA: 0.1 mg/m ³ Mn	(vacated) Ceiling: 5 mg/m ³ Ceiling: 5 mg/m ³ Mn	IDLH: 500 mg/m ³ Mn IDLH: 10 mg/m ³ Ni TWA: 1 mg/m ³ Mn TWA: 0.015 mg/m ³ except Nickel carbonyl Ni STEL: 3 mg/m ³ Mn
Graphite 7782-42-5	TWA: 2 mg/m ³ respirable fraction all forms except graphite fibers	TWA: 15 mg/m ³ total dust synthetic TWA: 5 mg/m ³ respirable fraction synthetic (vacated) TWA: 2.5 mg/m ³ respirable dust natural (vacated) TWA: 10 mg/m ³ total dust synthetic (vacated) TWA: 5 mg/m ³ respirable fraction synthetic TWA: 15 mppcf natural	IDLH: 1250 mg/m ³ TWA: 2.5 mg/m ³ respirable dust
Copper 7440-50-8	TWA: 0.2 mg/m³ fume TWA: 1 mg/m³ Cu dust and mist	TWA: 0.1 mg/m³ fume TWA: 1 mg/m³ dust and mist (vacated) TWA: 0.1 mg/m³ Cu dust, fume, mist	IDLH: 100 mg/m ³ dust, fume and mist TWA: 1 mg/m ³ dust and mist TWA: 0.1 mg/m ³ fume
Aluminum 7429-90-5	TWA: 1 mg/m ³ respirable fraction	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 15 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 5 mg/m ³ Al Aluminum	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
Phosphate(1-), hexafluoro-, lithium 21324-40-3	TWA: 2.5 mg/m ³ F	TWA: 2.5 mg/m ³ F TWA: 2.5 mg/m ³ dust (vacated) TWA: 2.5 mg/m ³	
Nickel 7440-02-0 ACGIH TI V: American Conference of Gov	TWA: 1.5 mg/m ³	TWA: 1 mg/m ³ (vacated) TWA: 1 mg/m ³	IDLH: 10 mg/m ³ TWA: 0.015 mg/m ³

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits NIOSH IDLH Immediately Dangerous to Life or Health

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992)



Appropriate engineering controls

Engineering Measures	Showers Eyewash stations Ventilation systems
Individual protection measures, such	ch as personal protective equipment
Eye/face protection	Wear safety glasses with side shields (or goggles).
Skin and body protection	Wear protective gloves and protective clothing. Long sleeved clothing. Impervious gloves.
Respiratory protection	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.
Hygiene Measures	Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Physical state Solid Appearance No information available Color No information available

Property_	Values	Remarks Metho
pH	No data available	None known
Melting / freezing point	No data available	None known
Boiling point / boiling range	No data available	None known
Flash Point	No data available	None known
Evaporation Rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		
Upper flammability limit	No data available	
Lower flammability limit	No data available	
Vapor pressure	No data available	None known
Vapor density	No data available	None known
Specific Gravity	No data available	None known
Water Solubility	No data available	None known
Solubility in other solvents	No data available	None known
Partition coefficient: n-octanol/w	vater No data available	None known
Autoignition temperature	No data available	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known
Explosive properties	No data available	
Oxidizing properties	No data available	
Other Information		
Softening Point	No data available	
VOC Content (%)	No data available	

No data available



No information available No information available

rks_Method D

Particle Size

Particle Size Distribution

10. STABILITY AND REACTIVITY

Reactivity

No data available.

<u>Chemical stability</u> Stable under recommended storage conditions. <u>Possibility of Hazardous Reactions</u> None under normal processing. <u>Conditions to avoid</u> None known based on information supplied. <u>Incompatible materials</u> Strong acids. Strong oxidizing agents. Strong bases. <u>Hazardous Decomposition Products</u> None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information	Product does not present an acute toxicity hazard based on known or supplied information. In case of rupture:.
Inhalation	Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract.
Eye contact	Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components). May cause redness, itching, and pain.
Skin contact	Specific test data for the substance or mixture is not available. Causes skin irritation. (based on components). Prolonged contact may cause redness and irritation.
Ingestion	Specific test data for the substance or mixture is not available. Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Iron 7439-89-6	= 984 mg/kg (Rat)	-	-
Propylene carbonate 108-32-7	= 29000 mg/kg (Rat)	> 20 mL/kg (Rabbit)	-
Nickel 7440-02-0	> 9000 mg/kg (Rat)	-	-

Information on toxicological effects

 Symptoms
 Erythema (skin redness). May cause redness and tearing of the eyes. Itching. Rashes. Hives.

 Delayed and immediate effects as well as chronic effects from short and long-term exposure

 Sensitization
 May cause sensitization by skin contact.



Mutagenic Effects

No information available.

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA	
Cobalt lithium manganese nickel oxide 182442-95-1	A3	Group 1 Group 2B	Known	Х	
Nickel 7440-02-0		Group 1 Group 2B	Reasonably Anticipated	Х	
A3 - Animal Carcinogen IARC (International Age Group 1 - Carcinogenic t Group 2B - Possibly Carc NTP (National Toxicolo Known - Known Carcinog Reasonably Anticipated	cinogenic to Humans gy Program)	e a Human Carcinogen	t of Labor)		
Reproductive toxicity	No information	No information available.			
STOT - single exposure	No information	No information available.			
STOT - repeated exposure Causes damage to organs through prolonged or repeated exposure. B classification criteria from the 2012 OSHA Hazard Communication Sta 1910.1200), this product has been determined to cause systemic targe chronic or repeated exposure. (STOT RE).		Standard (29 CFR			
Chronic Toxicity Contains a known or suspected carcinogen. Avoid repeated exposure. Prolonge may cause chronic effects.		re. Prolonged exposure			
Target Organ Effects	Respiratory s	system. Eyes. Skin. Gast	trointestinal tract (GI).		
Aspiration Hazard No information available.					

Numerical measures of toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 3,894.00 mg/kg ATEmix (dermal) 12,000.00 mg/kg (ATE)

12. ECOLOGICAL INFORMATION

<u>Ecotoxicity</u> Very toxic to aquatic life with long lasting effects.

Chemical name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Iron 7439-89-6		96h LC50: = 13.6 mg/L (Morone saxatilis)		
Copper 7440-50-8	96h EC50: 0.031 - 0.054 mg/L (Pseudokirchneriella subcapitata) 72h EC50: 0.0426 - 0.0535 mg/L (Pseudokirchneriella subcapitata)	96h LC50: $0.0068 - 0.0156$ mg/L (Pimephales promelas) 96h LC50: $= 1.25$ mg/L (Lepomis macrochirus) 96h LC50: $= 0.052$ mg/L (Oncorhynchus mykiss) 96h LC50: $= 0.2$ mg/L (Pimephales promelas) 96h LC50: < 0.3 mg/L (Pimephales promelas) 96h LC50: $= 0.112$ mg/L (Poecilia reticulata) 96h LC50: $= 0.3$ mg/L (Cyprinus carpio) 96h LC50: $= 0.8$ mg/L (Cyprinus carpio)		48h EC50: = 0.03 mg/L
Propylene carbonate 108-32-7	72h EC50: > 500 mg/L (Desmodesmus subspicatus)	96h LC50: > 1000 mg/L (Cyprinus carpio) 96h LC50: = 5300 mg/L (Leuciscus idus)	EC50 > 10000 mg/L 17 h	48h EC50: > 500 mg/L
Nickel 7440-02-0	72h EC50: = 0.18 mg/L (Pseudokirchneriella subcapitata) 96h EC50: 0.174 - 0.311 mg/L (Pseudokirchneriella subcapitata)	96h LC50: > 100 mg/L (Brachydanio rerio) 96h LC50: = 1.3 mg/L (Cyprinus carpio) 96h LC50: = 10.4 mg/L (Cyprinus carpio)		48h EC50: > 100 mg/L 48h EC50: = 1 mg/L

Persistence and Degradability No information available.

Bioaccumulation

Chemical name	Log Pow
Propylene carbonate	0.48
108-32-7	

Other adverse effects No information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal methods	This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.
Contaminated Packaging	Dispose of contents/containers in accordance with local regulations.

California Hazardous Waste Codes 141

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical name	California Hazardous Waste
Cobalt lithium manganese nickel oxide 182442-95-1	Toxic
Copper 7440-50-8	Тохіс
Aluminum 7429-90-5	Ignitable powder
Nickel 7440-02-0	Toxic powder Ignitable powder

14. TRANSPORT INFORMATION

Note:	The transportation of primary lithium cells and batteries is regulated by the International Civil Aviation Organization, International Air Transport Association, International Maritime Dangerous Goods Code and the US Department of Transportation. The batteries must meet the following criteria for shipment: 1. Air shipments must meet the requirements listed in Special Provision A45 of the International Air Transport Association Dangerous Goods Regulations. 2. Meet the requirements for the US Department of Transportation Iisted in 49 CFR 173.185. 3. The transport of primary lithium batteries is prohibited aboard passenger aircraft. Refer to the Federal Register December 15, 2004 (Hazardous Materials; Prohibited on the Transportation of Primary Lithium Batteries and Cells Aboard Passenger Aircraft; Final Rule) Lithium batteries contained in equipment" may not be classified as "Dangerous Goods" when shipped in accordance with "special provision A45 of IATA-DGR" or "special provision 188 of IMO-IMDG Code"
DOT Proper Shipping Name Hazard Class Emergency Response Guide Number	NOT REGULATED NON-REGULATED N/A 147
TDG	Not regulated
MEX	Not regulated
ICAO	Not regulated
ΙΑΤΑ	Not regulated



Proper Shipping Name Hazard Class	NON REGULATED N/A
IMDG/IMO Hazard Class EmS-No.	Not regulated N/A F-A, S-I
RID	Not regulated
ADR	Not regulated
<u>ADN</u>	Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA Complies DSL All components are listed either on the DSL or NDSL.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory **DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

<u>SARA 313</u>

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	CAS No	Weight-%	SARA 313 - Threshold Values %
Cobalt lithium manganese nickel oxide - 182442-95-1	182442-95-1	15 - 40	1.0 0.1
Copper - 7440-50-8	7440-50-8	3 - 7	1.0
Aluminum - 7429-90-5	7429-90-5	3 - 7	1.0
Nickel - 7440-02-0	7440-02-0	0.1 - 1	0.1
SARA 311/312 Hazard Categories Acute Health Hazard	No		
Chronic Health Hazard Fire Hazard	No No		
Sudden release of pressure hazard Reactive Hazard	No No		

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Cobalt lithium manganese nickel oxide 182442-95-1		Х		
Copper 7440-50-8		Х	X	
Nickel 7440-02-0		X	X	

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name Hazardous Substances RQs Extremely Hazardous Substances RQ RQ	Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances	RQ
--	---------------	--------------------------	--------------------------------	----



		RQs	
Copper	5000 lb		RQ 5000 lb final RQ
7440-50-8			RQ 2270 kg final RQ
Nickel	100 lb		RQ 100 lb final RQ
7440-02-0			RQ 45.4 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical name	California Proposition 65	
Cobalt lithium manganese nickel oxide - 182442-95-1	Carcinogen	
Nickel - 7440-02-0	Carcinogen	

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Cobalt lithium manganese nickel oxide 182442-95-1			Х	Х	Х
Graphite 7782-42-5	Х	X	Х		
Dimethyl carbonate 616-38-6	Х	Х	Х		
Copper 7440-50-8	Х	Х	Х	Х	Х
Aluminum 7429-90-5	Х	Х	Х	Х	
Nickel 7440-02-0	Х	Х	Х	Х	Х

International Regulations

Mexico

National occupational exposure limits

Component	Carcinogen Status	Exposure Limits
Cobalt lithium manganese nickel oxide 182442-95-1 (15 - 40)		Mexico: TWA 0.2 mg/m ³
Graphite 7782-42-5 (10 - 30)		Mexico: TWA= 2 mg/m ³
Copper 7440-50-8(3 - 7)		Mexico: TWA= 1 mg/m ³ Mexico: TWA= 0.2 mg/m ³ Mexico: STEL= 2 mg/m ³
Aluminum 7429-90-5 (3 - 7)		Mexico: TWA= 10 mg/m ³
Nickel 7440-02-0 (0.1 - 1)		Mexico: TWA 1 mg/m ³

Mexico - Occupational Exposure Limits - Carcinogens

Canada WHMIS Hazard Class Non-controlled

16. OTHER INFORMATION

NFPA HMIS	Health Hazards 1 Health Hazards 0	Flammability 0 Flammability 0	Instability 0 Physical Hazard 0	Physical and Chemical Hazards - Personal Protection X
Prepared By	Product Stewardship			



	23 British American Blvd. Latham, NY 12110	
	1-800-572-6501	
Issuing Date	16-Feb-2016	
Revision Date	16-Feb-2016	
Revision Note	No information available	

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet

