

Version WM SDS Number: 400000005374 Revision Date: 05/24/2017

SECTION 1. IDENTIFICATION

Product name : PURELL® Food Processing HEALTHY SOAP™ 0.5% PCMX

Antimicrobial E2 Foam Handwash

Manufacturer or supplier's details

Company name of supplier : GOJO Industries, Inc.

Address : One GOJO Plaza, Suite 500

Akron, Ohio 44311

Telephone : 1 (330) 255-6000

Emergency telephone

number

: 1-800-424-9300 CHEMTREC

Recommended use of the chemical and restrictions on use

Recommended use : Antibacterial Soap

Restrictions on use : This is a personal care or cosmetic product that is safe for

consumers and other users under normal and reasonably foreseeable use. Cosmetics and consumer products, specifically defined by regulations around the world, are exempt from the requirement of an SDS for the consumer. While this material is not considered hazardous, this SDS contains valuable information critical to the safe handling and proper use of the product for industrial workplace conditions as well as unusual and unintended exposures such as large spills. This SDS should be retained and available for employees and other users of this product. For specific intended-use guidance, please refer to the information

provided on the package or instruction sheet.

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 3

Serious eye damage : Category 1

GHS label elements

Hazard pictograms





Signal word : Danger



Version WM SDS Number: 400000005374 Revision Date: 05/24/2017

Hazard statements : H226 Flammable liquid and vapour.

H318 Causes serious eye damage.

Precautionary statements : **Prevention**:

P210 Keep away from heat/sparks/open flames/hot surfaces. -

No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting/

equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P280 Wear eye protection/ face protection.

Response:

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON

CENTER or doctor/ physician.

P370 + P378 In case of fire: Use dry sand, dry chemical or

alcohol-resistant foam to extinguish.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous components

Chemical name	CAS-No.	Concentration (%)
Ethyl Alcohol	64-17-5	>= 5 - < 10
Lauric Acid	143-07-7	>= 5 - < 10
Ethanolamine	141-43-5	>= 1 - < 5
Lactic Acid	79-33-4	>= 1 - < 5
Chloroxylenol	88-04-0	>= 0.1 - < 1

SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical

advice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

If inhaled : If inhaled, remove to fresh air.

If symptoms persist, call a physician.

In case of skin contact : Wash with water and soap as a precaution.

Get medical attention immediately if irritation develops and

persists.



Version WM SDS Number: 400000005374 Revision Date: 05/24/2017

In case of eye contact : In case of contact, immediately flush eyes with plenty of water

for at least 15 minutes.

If easy to do, remove contact lens, if worn.

Seek medical advice.

If swallowed : If swallowed, DO NOT induce vomiting.

Rinse mouth with water. Obtain medical attention.

Most important symptoms

and effects, both acute and

delayed

: Causes serious eye damage.

Protection of first-aiders : First Aid responders should pay attention to self-protection

and use the recommended protective clothing

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not use a solid water stream as it may scatter and spread

fire.

Cool closed containers exposed to fire with water spray.

Flash back possible over considerable distance.

May form explosive mixtures in air.

Exposure to decomposition products may be a hazard to

health.

Carbon oxides

Nitrogen oxides (NOx)

Hazardous combustion

products

: Carbon oxides

Nitrogen oxides (NOx)

Specific extinguishing

methods

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment. Use water spray to cool unopened containers.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment

for firefighters

: In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES



Version WM SDS Number: 400000005374 Revision Date: 05/24/2017

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition.

Evacuate personnel to safe areas.

Keep people away from and upwind of spill/leak.

Material can create slippery conditions.

Environmental precautions : Discharge into the environment must be avoided.

Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

: Non-sparking tools should be used. Soak up with inert absorbent material.

Suppress (knock down) gases/vapours/mists with a water

spray jet.

Keep in suitable, closed containers for disposal.

Clean contaminated floors and objects thoroughly while

observing environmental regulations.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : For personal protection see section 8.

Keep away from heat.

Use with local exhaust ventilation.

Avoid contact with eyes.

Conditions for safe storage : Take measures to prevent the build up of electrostatic charge.

Keep in properly labelled containers.

Keep containers tightly closed in a dry, cool and well-

ventilated place.

Store in accordance with the particular national regulations.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Ethyl Alcohol	64-17-5	TWA	1,000 ppm 1,900 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,900 mg/m3	OSHA Z-1
		STEL	1,000 ppm	ACGIH
Ethanolamine	141-43-5	TWA	3 ppm	ACGIH
		STEL	6 ppm	ACGIH
		TWA	3 ppm 8 mg/m3	NIOSH REL
		ST	6 ppm	NIOSH REL



Version WM SDS Number: 400000005374 Revision Date: 05/24/2017

	15 mg/m3	
TWA	3 ppm 6 mg/m3	OSHA Z-1
STEL	6 ppm 15 mg/m3	OSHA P0
TWA	3 ppm 8 mg/m3	OSHA P0

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally

required.

Hand protection

Remarks : No special protective equipment required.

Eye protection : Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : No special measures necessary provided product is used

correctly.

Protective measures : Choose body protection in relation to its type, to the

concentration and amount of dangerous substances, and to

the specific work-place.

Ensure that eye flushing systems and safety showers are

located close to the working place.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice.

Avoid contact with eyes.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : clear, colourless, light yellow

Odour : like soap

Odour Threshold : No data available

pH : 7.8 - 9.7, (20 °C)

Melting point/freezing point : No data available

Flash point : 45.60 °C

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Upper explosion limit : No data available

Lower explosion limit : No data available



Version WM SDS Number: 400000005374 Revision Date: 05/24/2017

Vapour pressure : No data available

Relative vapour density : No data available

Density : 0.9998 g/cm3

Solubility(ies)

Water solubility : soluble

Partition coefficient: n-

octanol/water

: Not applicable

Auto-ignition temperature : No data available

Thermal decomposition : The substance or mixture is not classified self-reactive.

Viscosity

Viscosity, kinematic : 10 - 20 mm2/s (20 °C)

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Oxidizing agents

Hazardous decomposition

products

: No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation Eye contact

Skin contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg



Version WM SDS Number: 400000005374 Revision Date: 05/24/2017

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : > 200 mg/l

Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

Components:

Ethyl Alcohol:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 124.7 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Lauric Acid:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 0.162 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: Based on data from similar materials

Ethanolamine:

Acute oral toxicity : LD50 (Rat): 1,515 mg/kg

Acute inhalation toxicity : Acute toxicity estimate : 11 mg/l

Test atmosphere: vapour Method: Expert judgement

Remarks: Based on harmonised classification in EU regulati

on 1272/2008, Annex VI

Acute dermal toxicity : LD50 (Rabbit): 1,025 mg/kg

Lactic Acid:

Acute oral toxicity : LD50 (Rat, female): 3,543 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 7.94 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Chloroxylenol:



Version WM SDS Number: 40000005374 Revision Date: 05/24/2017

Acute oral toxicity : Acute toxicity estimate : 500 mg/kg

Method: Expert judgement

Remarks: Based on harmonised classification in EU regulati

on 1272/2008, Annex VI

Acute inhalation toxicity : LC50 (Rat): > 6.29 mg/l

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Product:

Assessment: Not irritating when applied to human skin.

Result: No skin irritation

Components:

Ethyl Alcohol:

Species: Rabbit

Method: OECD Test Guideline 404

Result: No skin irritation

Lauric Acid:

Species: Rabbit

Method: OECD Test Guideline 404

Result: No skin irritation

Ethanolamine: Species: Rabbit

Result: Corrosive after 3 minutes to 1 hour of exposure

Lactic Acid: Species: Rabbit

Result: Skin irritation

Chloroxylenol:

Result: Skin irritation

Remarks: Based on harmonised classification in EU regulati on 1272/2008, Annex VI

Serious eye damage/eye irritation

Causes serious eye damage.

Components:

Ethyl Alcohol:

Species: Rabbit

Result: Irritation to eyes, reversing within 21 days

Method: OECD Test Guideline 405

Lauric Acid: Species: Rabbit

Result: Irreversible effects on the eye



Version WM SDS Number: 400000005374 Revision Date: 05/24/2017

Method: OECD Test Guideline 405

Ethanolamine: Species: Rabbit

Result: Irreversible effects on the eye

Lactic Acid:

Species: Chicken eye

Result: Irreversible effects on the eye

Chloroxylenol:

Result: Irreversible effects on the eye

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information. Respiratory sensitisation: Not classified based on available information.

Product:

Result: Does not cause skin sensitisation.

Remarks: Patch test on human volunteers did not demonstrate sensitisation properties.

Components:

Ethyl Alcohol:

Test Type: Local lymph node assay (LLNA)

Exposure routes: Skin contact

Species: Mouse Result: negative

Lauric Acid:

Test Type: Maximisation Test (GPMT)

Exposure routes: Skin contact

Species: Guinea pig Result: negative

Ethanolamine:

Test Type: Maximisation Test (GPMT)

Exposure routes: Skin contact

Species: Guinea pig Result: negative

Lactic Acid:

Test Type: Buehler Test Exposure routes: Skin contact

Species: Guinea pig Result: negative

Chloroxylenol:

Assessment: Probability or evidence of skin sensitisation in humans

Remarks: Based on harmonised classification in EU regulati on 1272/2008, Annex VI

Germ cell mutagenicity

Not classified based on available information.

Components:



Version WM SDS Number: 400000005374 Revision Date: 05/24/2017

Ethyl Alcohol:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test

Result: negative

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)

Test species: Mouse

Application Route: Ingestion

Result: negative

Lauric Acid:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Remarks: Based on data from similar materials

Ethanolamine:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Test species: Mouse

Application Route: Ingestion Method: OECD Test Guideline 474

Result: negative

Lactic Acid:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro

Metabolic activation: with and without metabolic activation

Result: negative

Remarks: Based on data from similar materials

Test Type: Bacterial reverse mutation assay (AMES)
Metabolic activation: with and without metabolic activation

Result: negative

Chloroxylenol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Carcinogenicity

Not classified based on available information.

Components:

Lactic Acid: Species: Rat

Application Route: Ingestion Exposure time: 2 Years Result: negative

Remarks: Based on data from similar materials

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed



Version WM SDS Number: 400000005374 Revision Date: 05/24/2017

human carcinogen by IARC.

OSHA No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by OSHA.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

Reproductive toxicity

Not classified based on available information.

Components:

Ethyl Alcohol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Mouse

Application Route: Ingestion Method: OECD Test Guideline 416

Result: negative

Lauric Acid:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the re

production/developmental toxicity screening test

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 422

Result: negative

Remarks: Based on data from similar materials

Effects on foetal development

: Test Type: Combined repeated dose toxicity study with the re

production/developmental toxicity screening test

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 422

Result: negative

Remarks: Based on data from similar materials

Ethanolamine:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: Ingestion

Result: negative

Effects on foetal development

Test Type: Embryo-foetal development

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 414

Result: negative

STOT - single exposure

Not classified based on available information.

Components:



Version WM SDS Number: 400000005374 Revision Date: 05/24/2017

Ethanolamine:

Assessment: May cause respiratory irritation.

Lactic Acid:

Assessment: May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

Components:

Ethanolamine:

Exposure routes: inhalation (dust/mist/fume)

Assessment: No significant health effects observed in animals at concentrations of 0.2 mg/l/6h/d

or less.

Repeated dose toxicity

Components:

Ethyl Alcohol:

Species: Rat

NOAEL: 2,400 mg/kg Application Route: Ingestion

Exposure time: 2 y

Lauric Acid:

Species: Rat

NOAEL: 10,000 mg/kg Application Route: Ingestion

Exposure time: 18 w

Ethanolamine:

Species: Rat

NOAEL: 150 mg/m3

Application Route: inhalation (dust/mist/fume)

Exposure time: 28 d

Lactic Acid:

Species: Rat

NOAEL: >= 886 mg/kg

Application Route: Skin contact

Exposure time: 13 w

Chloroxylenol:

Species: Rabbit LOAEL: 180 mg/kg

Application Route: Skin contact

Exposure time: 90 d

Aspiration toxicity

Not classified based on available information.



Version WM SDS Number: 400000005374 Revision Date: 05/24/2017

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components: Ethyl Alcohol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 1,000 mg/l

Exposure time: 96 h

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): > 1,000 mg/l

Exposure time: 48 h

Toxicity to algae : EC50 (Chlorella vulgaris (Fresh water algae)): 275 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to daphnia and other

aquatic invertebrates (Chronic toxicity)

: NOEC (Daphnia magna (Water flea)): 9.6 mg/l

Exposure time: 9 d

Toxicity to bacteria : EC50 (Photobacterium phosphoreum): 32.1 mg/l

Exposure time: 0.25 h

Lauric Acid:

Toxicity to fish : LC50 (Oryzias latipes (Japanese medaka)): 5 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): 3.6 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae : EC50 (Selenastrum capricornutum (green algae)): > 7.6 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: No toxicity at the limit of solubility

NOEC (Selenastrum capricornutum (green algae)): > 7.6 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: No toxicity at the limit of solubility

Toxicity to fish (Chronic

toxicity)

: NOEC (Danio rerio (zebra fish)): 2 mg/l

Exposure time: 28 d

Remarks: Based on data from similar materials

Toxicity to daphnia and other

aquatic invertebrates (Chronic toxicity)

: NOEC (Daphnia magna (Water flea)): 0.47 mg/l

Exposure time: 21 d

Method: OECD Test Guideline 211

Toxicity to bacteria : EC10 (Pseudomonas putida): > 1,000 mg/l

Exposure time: 30 min

Method: OECD Test Guideline 209



SDS Number: 40000005374 Version WM Revision Date: 05/24/2017

Ethanolamine:

Toxicity to fish : LC50 (Cyprinus carpio (Carp)): 349 mg/l

Exposure time: 96 h

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): 65 mg/l

Exposure time: 48 h

Toxicity to algae : ErC50 (Selenastrum capricornutum (green algae)): 2.8 mg/l

Exposure time: 72 h

NOEC (Scenedesmus capricornutum (fresh water algae)): 1

mg/l

Exposure time: 72 h

Toxicity to fish (Chronic

toxicity)

: NOEC (Oryzias latipes (Orange-red killifish)): 1.24 mg/l

Exposure time: 41 d

Toxicity to daphnia and other

aquatic invertebrates (Chronic toxicity)

: NOEC (Daphnia magna (Water flea)): 0.85 mg/l

Exposure time: 21 d

: EC50 (Pseudomonas putida): 110 mg/l Toxicity to bacteria

Exposure time: 17 h

Lactic Acid:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 130 mg/l

Exposure time: 96 h

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): 250 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae : EC50 (Selenastrum capricornutum (fresh water algae)): 3.5 g/l

Exposure time: 72 h

Method: OECD Test Guideline 201

NOEC (Selenastrum capricornutum (fresh water algae)): 1.9

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to bacteria EC50: > 100 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209

Chloroxylenol:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 0.76 mg/l

Exposure time: 96 h

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): 7.7 mg/l

Exposure time: 48 h

M-Factor (Acute aquatic

toxicity)

: 1



Version WM SDS Number: 400000005374 Revision Date: 05/24/2017

Persistence and degradability

Components:

Ethyl Alcohol:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 84 % Exposure time: 20 d

Lauric Acid:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 86 % Exposure time: 30 d

Method: OECD Test Guideline 301D

Ethanolamine:

Biodegradability : Result: Readily biodegradable.

Biodegradation: > 90 % Exposure time: 21 d

Lactic Acid:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 67 % Exposure time: 20 d

Bioaccumulative potential

Components:

Ethyl Alcohol:

Partition coefficient: n-

octanol/water

: log Pow: -0.35

Lauric Acid:

Bioaccumulation : Species: Fish

Bioconcentration factor (BCF): 234 - 288 Remarks: Based on data from similar materials

Partition coefficient: n-

octanol/water

: Pow: 4.6

Ethanolamine:

Partition coefficient: n-

octanol/water

: log Pow: -1.91

Lactic Acid:

Partition coefficient: n-

: log Pow: -0.6

octanol/water

Chloroxylenol:

Partition coefficient: n-

: log Pow: 3.27

octanol/water

Mobility in soil

No data available



Version WM SDS Number: 400000005374 Revision Date: 05/24/2017

Other adverse effects

No data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of

Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a

Class I or Class II ODS as defined by the U.S. Clean Air Act

Section 602 (40 CFR 82, Subpt. A, App.A + B).

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Dispose of as unused product.

Empty containers should be taken to an approved waste

handling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION

This Section not required under 29 CFR 1910.1200

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Fire Hazard

Acute Health Hazard

SARA 302 : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.



Version WM SDS Number: 400000005374 Revision Date: 05/24/2017

Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 12 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489):

 64-17-5
 8.81 %

 Ethanolamine
 141-43-5
 3.833 %

 Dipropylene Glycol
 25265-71-8
 3 %

This product does not contain any VOC exemptions listed under the U.S. Clean Air Act Section 450.

Clean Water Act

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

US State Regulations

5 - 10 %
4 = 0/
1 - 5 %
0 - 0.1 %
70 - 90 %
5 - 10 %
5 - 10 %
1 - 5 %
8 1 - 5 %
0.1 - 1 %
0 - 0.1 %
70 - 90 %
5 - 10 %
5 - 10 %
1 - 5 %

California Prop 65

Dipropylene Glycol

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

25265-71-8

1 - 5 %



Version WM SDS Number: 400000005374 Revision Date: 05/24/2017

The components of this product are reported in the following inventories:

TSCA : On TSCA Inventory

AICS : On the inventory, or in compliance with the inventory

DSL : All components of this product are on the Canadian DSL.

ENCS : On the inventory, or in compliance with the inventory

ISHL : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

NZIoC : On the inventory, or in compliance with the inventory


Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

NFPA:



Special hazard.

HMIS III:

HEALTH	3
FLAMMABILITY	2
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme, * = Chronic

Revision Date : 05/24/2017

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.