

Safety Data Sheet

Regulation (EU) 2015/830 (REACH Annex II)

Applicant: BMZ USA Inc

Address: 2656 Lishelle PI

Virginia beach, VA 23452

Sample

Description: Li-ion Battery Pack

Model No.: 107500

Tel.: (86) 755 88286998



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name: : 107500 battery pack

Brand :

Model No.: : 107500 79.2V 3.0Ah 237Wh

REACH registration No.: : Not applicable

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : No information available

1.2.2. Uses advised against

Restrictions on use : No information available

1.3. Details of the supplier of the safety data sheetSupplier : BMZ USA Inc
Address : 2656 Lishelle PI

Virginia beach, VA 23452

1.4. Emergency telephone number

Emergency number : +86-0755-89775803

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Adverse physicochemical, human health and environmental effects

To our knowledge, this product does not present any particular risk, provided it is handled in accordance with good occupational hygiene and safety practice.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP] Extra labelling to displayExtra classification(s) to display

No labelling applicable

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Metal Oxide (proprietary)	-	20 - 50	Not classified
Carbon	(CAS-No.) 7440-44-0 (EC-No.) 231-153-3	10 - 30	Not classified
Electrolyte (proprietary)	-	10 - 20	Not classified
Aluminum	(CAS-No.) 7429-90-5 (EC-No.) 231-072-3 (EC Index-No.) 013-002-00-1	2 - 10	Flam. Sol. 1, H228 Water-react. 2, H261
Соррег	(CAS-No.) 7440-50-8 (EC-No.) 231-159-6	2 - 10	Not classified

TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch

TÜV SÜD Group

Building 12&13, Zhiheng Wisdomland Business Park,

Nantou Checkpoint road 2,

Shenzhen 518052. P. R. China

Page: 2 of 12

Tel.: (86) 755 88286998



1,1-Difluoroethylene polymer	(CAS-No.) 24937-79-9 (EC-No.) 607-458-6	< 5	Not classified
Stainless steel, Nickel and inert materials	-	Remainder	Not classified
Equivalent Lithium content: 0.90g, Electric Power Capacity: 10.8Wh			

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures First-aid measures general

First-aid measures after inhalation

: If you feel unwell, seek medical advice (show the label where possible).

: Not expected to present a significant hazard under anticipated conditions of normal use. If contents of an opened battery are inhaled, remove source of

contamination or move victim to fresh air. Obtain medical advice.

First-aid measures after skin contact : Not expected to present a significant skin hazard under anticipated conditions of

normal use. If skin contact with contents of an open battery occurs, as guickly as possible remove contaminated clothing, shoes and leather goods. Immediately flush with lukewarm, gently flowing water for at least 30 minutes. If irritation or pain

persists, seek medical attention

Not an expected route of exposure. If eye contact with contents of an open battery First-aid measures after eye contact

occurs, immediately flush the contaminated eye(s) with lukewarm, gently flowing water for at least 30 minutes while holding the eyelids open. Neutral saline solution may be used as soon as it is available. If necessary, continue flushing during

transport to emergency care facility

First-aid measures after ingestion If ingestion of contents of an open battery occurs, never give anything by mouth if

victim is rapidly losing consciousness, or is unconscious or convulsing. Have victim rinse mouth thoroughly with water. DO NOT INDUCE VOMITING. Have victim drink 60 to 240 mL (2-8 oz.) of water. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Have victim rinse mouth with water

again. Quickly transport victim to an emergency care facility.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects

Contact electrolyte may cause an allergic skin reaction. Causes skin irritation. Causes serious eye irritation. Harmful if inhalation or swallowed. Ingestion of large amounts may cause gastrointestinal irritation

4.3. Indication of any immediate medical attention and special treatment needed Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Use extinguishing agent suitable for surrounding fire.

: No information available. Unsuitable extinguishing media

5.2. Special hazards arising from the substance or mixture

: If cells are opened, hydrogen fluorid and carbon monoxide may be released Fire hazard

5.3. Advice for firefighters

Precautionary measures fire : Eliminate every possible source of ignition. Keep container tightly closed and away

from heat, sparks and flame.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained

breathing apparatus. Complete protective clothing.

Other information : Ensure adequate ventilation, especially in confined areas. Evacuate personnel to

a safe area. Move containers from fire area if it can be done without personal risk. Keep upwind. Cool tanks/drums with water spray/remove them into safety.

Eliminate every possible source of ignition.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid breathing (dust, vapor, mist, gas). Avoid contact with skin and eyes.

TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch TÜV SÜD Group

Building 12&13, Zhiheng Wisdomland Business Park,

Nantou Checkpoint road 2, Shenzhen 518052. P. R. China

Page: 3 of 12

Tel.: (86) 755 88286998



6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further

information refer to section 8: "Exposure controls/personal protection".

Emergency procedures : Stop leak if safe to do so. Do not touch spilled material. Keep away from

combustible material. Prevent from entering sewers, basements and workpits, or

any place where its accumulation can be dangerous.

6.2. Environmental precautions

Avoid release to the environment. Do not flush into surface water or sewer system. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Mechanically recover the product. Cover spill with non combustible material, e.g.;

sand, earth, vermiculite. Shovel or sweep up and put in a closed container for

disposal.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 7.8 & 13.

SECTION 7: Handling and storage 7.1. Precautions for safe handling

Precautions for safe handling

: Ensure good ventilation of the work station. Wear personal protective equipment. Protect from moisture. Handle in accordance with good industrial hygiene and safety practice.

Ensure adequate ventilation, especially in confined areas. Take precautionary measures against static discharge. Use explosion-proof equipment Avoid

breathing dust/fume/gas/mist/vapours/spray

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after

handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Store in a well-ventilated place. Keep cool. Store in dry protected location to prevent any moisture contact. Keep away from clothing and other combustible

materials. Remove all sources of ignition.

7.3. Specific end use(s)

Coffee maker -Descaler

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Aluminum (7429-90-5)		
Austria	MAK (mg/m³)	10 mg/m³ (inhalable fraction)
Austria	MAK Short time value (mg/m³)	20 mg/m³ (inhalable fraction)
Belgium	Limit value (mg/m³)	1 mg/m³
Bulgaria	OEL TWA (mg/m³)	10 mg/m³ (metal dust) 1.5 mg/m³ (respirable fraction)
Croatia	GVI (granična vrijednost izloženosti) (mg/m³)	10 mg/m³ (total dust) 4 mg/m³ (respirable dust)
Croatia	Croatia - BLV	200 mg/l Parameter: Aluminum - Medium: urine - Sampling time: at the end of the shift
Czech Republic	Expoziční limity (PEL) (mg/m³)	10 mg/m³ (dust)
Denmark	Grænseværdie (langvarig) (mg/m³)	5 mg/m³ (dust, fume and powder, total) 2 mg/m³ (dust and powder, respirable)
Estonia	OEL TWA (mg/m³)	10 mg/m³ (total dust) 4 mg/m³ (respirable dust)

TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch TÜV SÜD Group

Building 12&13, Zhiheng Wisdomland Business Park,

Nantou Checkpoint road 2, Shenzhen 518052. P. R. China

Page: 4 of 12

Tel.: (86) 755 88286998



Aluminum (7429-90-	5)		
France	VME (mg/m³)	10 mg/m³ (metal) 5 mg/m³ (dust)	
Greece	OEL TWA (mg/m³)	10 mg/m³ (inhalable fraction) 5 mg/m³ (respirable fraction)	
Hungary	AK-érték	6 mg/m³ (respirable dust)	
Ireland	OEL (8 hours ref) (mg/m³)	1 mg/m³ (respirable fraction)	
Ireland	OEL (15 min ref) (mg/m3)	3 mg/m³ (calculated-respirable dust)	
Latvia	OEL TWA (mg/m³)	2 mg/m³	
Lithuania	IPRV (mg/m³)	5 mg/m³ (inhalable fraction) 2 mg/m³ (respirable fraction) 1 mg/m³	
Poland	NDS (mg/m³)	2.5 mg/m³ (inhalable fraction) 1.2 mg/m³ (respirable fraction)	
Portugal	OEL TWA (mg/m³)	10 mg/m³ (metal dust)	
Romania	OEL TWA (mg/m³)	3 mg/m³ (dust) 1 mg/m³ (fume)	
Romania	OEL STEL (mg/m³)	10 mg/m³ (dust) 3 mg/m³ (fume)	
Romania	Romania - BLV	200 μg/l Parameter: Aluminum - Medium: urine - Sampling time: end of shift	
Slovakia	NPHV (priemerná) (mg/m³)	1.5 mg/m³ (metal) 6 mg/m³ (total aerosol)	
Slovakia	Slovakia - BLV	60 μg/g creatinine Parameter: Aluminum - Medium: urine - Sampling time: not critical	
Spain	VLA-ED (mg/m³)	10 mg/m³ (dust)	
Sweden	nivågränsvärde (NVG) (mg/m³)	5 mg/m³ (total dust) 2 mg/m³ (respirable dust)	
United Kingdom	WEL TWA (mg/m³)	10 mg/m³ (inhalable dust) 4 mg/m³ (respirable dust)	
United Kingdom	WEL STEL (mg/m³)	30 mg/m³ (calculated-inhalable dust) 12 mg/m³ (calculated-respirable dust)	
Russian Federation	OEL TWA (mg/m³)	2 mg/m³ (aerosol)	
Norway	Grenseverdier (AN) (mg/m³)	5 mg/m³ (pyrotechnical-powder)	
Norway	Grenseverdier (Korttidsverdi) (mg/m3)	10 mg/m³ (pyrotechnical-powder)	
Switzerland	MAK (mg/m³)	3 mg/m³ (respirable dust)	
Switzerland	Switzerland - BLV	60 μg/g creatinine Parameter: Aluminum - Medium urine - Sampling time: no restrictions	
Australia	TWA (mg/m³)	10 mg/m³ (dust) 5 mg/m³ (welding fume)	
Canada (Quebec)	VEMP (mg/m³)	10 mg/m³	
USA - ACGIH	ACGIH TWA (mg/m³)	1 mg/m³ (respirable particulate matter)	
USA - NIOSH	NIOSH REL (TWA) (mg/m³)	10 mg/m³ (total dust) 5 mg/m³ (respirable dust)	
USA - OSHA	OSHA PEL (TWA) (mg/m³)	15 mg/m³ (total dust) 5 mg/m³ (respirable fraction)	

Tel.: (86) 755 88286998 Fax: (86) 755 88285299



Austria	MAK (mg/m³)	1 mg/m³ (inhalable fraction) 0.1 mg/m³ (respirable fraction, smoke)	
Austria	MAK Short time value (mg/m³)	4 mg/m³ (inhalable fraction) 0.4 mg/m³ (respirable fraction, smoke)	
Belgium	Limit value (mg/m³)	0.2 mg/m³ (fume) 1 mg/m³ (dust and mist)	
Bulgaria	OEL TWA (mg/m³)	0.1 mg/m³ (metal vapor)	
Croatia	GVI (granična vrijednost izloženosti) (mg/m³)	0.2 mg/m³ (fume) 1 mg/m³ (dust)	
Croatia	KGVI (kratkotrajna granična vrijednost izloženosti) (mg/m³)	2 mg/m³ (dust and fume)	
Czech Republic	Expoziční limity (PEL) (mg/m³)	1 mg/m³ (dust) 0.1 mg/m³ (fume)	
Denmark	Grænseværdie (langvarig) (mg/m³)	1 mg/m³ (dust and powder) 0.1 mg/m³ (fume)	
Estonia	OEL TWA (mg/m³)	1 mg/m³ (total dust) 0.2 mg/m³ (respirable dust)	
Finland	HTP-arvo (8h) (mg/m³)	0.02 mg/m³ (respirable dust)	
France	VME (mg/m³)	0.2 mg/m³ (fume) 1 mg/m³ (dust)	
France	VLE (mg/m³)	2 mg/m³ (dust)	
Greece	OEL TWA (mg/m³)	0.2 mg/m³ (fume) 1 mg/m³ (dust)	
Greece	OEL STEL (mg/m³)	2 mg/m³ (dust)	
Hungary	AK-érték	1 mg/m³ 0.1 mg/m³ (fume)	
Hungary	CK-érték	4 mg/m³ 0.4 mg/m³ (fume)	
Ireland	OEL (8 hours ref) (mg/m³)	0.2 mg/m³ (fume) 1 mg/m³ (dusts and mists)	
Ireland	OEL (15 min ref) (mg/m3)	0.6 mg/m³ (calculated-fume) 2 mg/m³ (dusts and mists)	
Latvia	OEL TWA (mg/m³)	0.5 mg/m³	
Lithuania	IPRV (mg/m³)	1 mg/m³ (inhalable fraction) 0.2 mg/m³ (respirable fraction)	
Netherlands	Grenswaarde TGG 8H (mg/m³)	0.1 mg/m³ (inhalable fraction)	
Poland	NDS (mg/m³)	0.2 mg/m³	
Portugal	OEL TWA (mg/m³)	0.2 mg/m³ (fume) 1 mg/m³ (dust and mist)	
Romania	OEL TWA (mg/m³)	0.5 mg/m³ (powder)	
Romania	OEL STEL (mg/m³)	0.2 mg/m³ (fume) 1.5 mg/m³ (dust)	
Slovakia	NPHV (priemerná) (mg/m³)	1 mg/m³ (dust) 0.1 mg/m³ (fume)	
Slovakia	NPHV (Hraničná) (mg/m³)	2 mg/m³ (dust) 0.2 mg/m³ (fume)	

TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch TÜV SÜD Group
Building 12&13, Zhiheng Wisdomland Business Park,
Nantou Checkpoint road 2,
Shenzhen 518052, P. R. China

Tel.: (86) 755 88286998 Fax: (86) 755 88285299



Copper (7440-50-8)			
Slovenia	OEL TWA (mg/m³)	1 mg/m³ (inhalable fraction) 0.1 mg/m³ (respirable fraction, fume)	
Slovenia	OEL STEL (mg/m³)	4 mg/m³ (inhalable fraction) 0.4 mg/m³ (respirable fraction, fume)	
Spain	VLA-ED (mg/m³)	0.2 mg/m³ (fume) 1 mg/m³ (dust and mist)	
Sweden	nivågränsvärde (NVG) (mg/m³)	1 mg/m³ (total dust) 0.2 mg/m³ (respirable dust)	
United Kingdom	WEL TWA (mg/m³)	1 mg/m³ (dust and mists) 0.2 mg/m³ (fume)	
United Kingdom	WEL STEL (mg/m³)	0.6 mg/m³ (calculated-fume) 2 mg/m³ (dust and mist)	
Russian Federation	OEL TWA (mg/m³)	0.5 mg/m³ (aerosol)	
Norway	Grenseverdier (AN) (mg/m³)	0.1 mg/m³ (fume) 1 mg/m³ (dust)	
Norway	Grenseverdier (Korttidsverdi) (mg/m3)	0.3 mg/m³ (value calculated-fume) 2 mg/m³ (value calculated-dust)	
Switzerland	MAK (mg/m³)	0.1 mg/m³ (inhalable dust)	
Switzerland	KZGW (mg/m³)	0.2 mg/m³ (inhalable dust)	
Australia	TWA (mg/m³)	1 mg/m³ (dust and mist) 0.2 mg/m³ (fume)	
Canada (Quebec)	VEMP (mg/m³)	0.2 mg/m³ (fume) 1 mg/m³ (dust and mist)	
USA - ACGIH	ACGIH TWA (mg/m³)	0.2 mg/m³ (fume)	
USA - IDLH	US IDLH (mg/m³)	100 mg/m³ (dust, fume and mist)	
USA - NIOSH	NIOSH REL (TWA) (mg/m³)	1 mg/m³ (dust and mist) 0.1 mg/m³ (fume)	
USA - OSHA	OSHA PEL (TWA) (mg/m³)	0.1 mg/m³ (fume) 1 mg/m³ (dust and mist)	

Carbon (7440-4	14-0)	
Austria	MAK (mg/m³)	5 mg/m³ (alveolar dust with <1% Quartz, respirable fraction)
Austria	MAK Short time value (mg/m³)	10 mg/m³ (alveolar dust with <1% Quartz, respirable fraction)
Poland	NDS (mg/m³)	4 mg/m³ (natural-inhalable fraction) 1 mg/m³ (natural-respirable fraction) 6 mg/m³ (synthetic-inhalable fraction)

8.2. Exposure controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Hand protection:	
Protective gloves	
Eye protection:	

TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch TÜV SÜD Group
Building 12&13, Zhiheng Wisdomland Business Park,
Nantou Checkpoint road 2,
Shenzhen 518052, P. R. China

Tel.: (86) 755 88286998



Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Solid

Colour : No data available
Odour : No data available
Odour threshold : No data available
pH : No data available
Relative evaporation rate (butylacetate=1) : No data available
Melting point : No data available
Boiling point : No data available

Flash point : No data available
Auto-ignition temperature : No data available
Decomposition temperature : No data available
Flammability (solid, gas) : Non flammable.

Vapour pressure : No data available Relative vapour density at 20 °C : No data available

Relative density : No data available
Solubility : insoluble in water.
Log Pow : No data available
Viscosity, kinematic : No data available

Viscosity, dynamic : No data available
Explosive properties : No data available
Oxidising properties : No data available
Explosive limits : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

None during normal operating conditions. If cells are opened, hydrogen fluorid and carbon monoxide may be released

TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch

TÜV SÜD Group

Building 12&13, Zhiheng Wisdomland Business Park,

Nantou Checkpoint road 2,

Shenzhen 518052. P. R. China

Tel.: (86) 755 88286998



SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Carbon (7440-44-0)	
LD50 oral rat	> 10000 mg/kg
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term

adverse effects in the environment.

Acute aquatic toxicity : Not classified Chronic aquatic toxicity : Not classified

Copper (7440-50-8)	
LC50 fish 1	0.0068 - 0.0156 mg/l (Exposure time: 96 h - Species: Pimephales promelas)
LC50 fish 2	< 0.3 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 1	0.03 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
EC50 72h algae (1)	0.0426 - 0.0535 mg/l (Species: Pseudokirchneriella subcapitata [static])
EC50 96h algae (1)	0.031 - 0.054 mg/l (Species: Pseudokirchneriella subcapitata [static])

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting

instructions.

Product/Packaging disposal : Dispose of contents/container in accordance with licensed collector's sorting

recommendations instructions.

TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch TÜV SÜD Group

Building 12&13, Zhiheng Wisdomland Business Park,

Nantou Checkpoint road 2, Shenzhen 518052, P. R. China

Page: 9 of 12

Tel.: (86) 755 88286998



SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
3481	3481	3481	3481	3481
14.2. UN proper ship	ping name			
LITHIUM ION	LITHIUM ION	LITHIUM ION	LITHIUM ION	LITHIUM ION
BATTERIES	BATTERIES	BATTERIES	BATTERIES	BATTERIES
CONTAINED IN	CONTAINED IN	CONTAINED IN	CONTAINED IN	CONTAINED IN
EQUIPMENT	EQUIPMENT	EQUIPMENT	EQUIPMENT	EQUIPMENT
Transport document des	scription		'	
UN 3481 LITHIUM ION	UN 3481 LITHIUM ION	UN 3481 LITHIUM ION	UN 3481 LITHIUM ION	UN 3481 LITHIUM ION
BATTERIES	BATTERIES	BATTERIES	BATTERIES	BATTERIES
CONTAINED IN	CONTAINED IN	CONTAINED IN	CONTAINED IN	CONTAINED IN
EQUIPMENT, 9A, (E)	EQUIPMENT, 9	EQUIPMENT, 9	EQUIPMENT, 9A	EQUIPMENT, 9A
14.3. Transport haza	ard class(es)			
9A	9	9	9A	9A
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Dangerous for the	Dangerous for the	Dangerous for the	Dangerous for the	Dangerous for the
environment : No	environment : No	environment : No	environment : No	environment : No
	Marine pollutant : No			
No supplementary information available				

14.6. Special precautions for user

- Overland transport

Classification code (ADR) : M4

Special provisions (ADR) : 188, 230, 310, 360, 348, 376, 377, 636

Limited quantities (ADR) : 0
Excepted quantities (ADR) : E

Packing instructions (ADR) : P903, P908, P909, P910, LP903, LP904

Transport category (ADR) : 2
Tunnel restriction code (ADR) : E
EAC code : 4W

- Transport by sea

Special provisions (IMDG) : 188, 230, 348, 360, 376, 377

Limited quantities (IMDG) : 0
Excepted quantities (IMDG) : E0

Packing instructions (IMDG) : P903, P908, P909, LP903, LP904

EmS-No. (Fire): F-AEmS-No. (Spillage): S-IStowage category (IMDG): AStowage and handling (IMDG): SW19

Properties and observations (IMDG) : Electrical batteries containing lithium ion encased in a rigid metallic body. Lithium ion

batteries may also be shipped in, or packed with, equipment. Electrical lithium batteries may cause fire due to an explosive rupture of the body caused by improper

construction or reaction with contaminants.

Shenzhen 518052, P. R. China

Tel.: (86) 755 88286998



- Air transport

PCA Excepted quantities (IATA) : E0 PCA Limited quantities (IATA) : Forbidden PCA limited quantity max net quantity : Forbidden

(IATA)

PCA packing instructions (IATA) : 967 PCA max net quantity (IATA) : 5kg CAO packing instructions (IATA) : 967 CAO max net quantity (IATA) : 35kg

Special provisions (IATA) : A48, A99, A154, A164, A181, A185, A88, A206

ERG code (IATA)

- Inland waterway transport

Classification code (ADN) : M4

Special provisions (ADN) : 188, 230, 310, 348, 360, 376, 377, 636

Limited quantities (ADN) : 0 Excepted quantities (ADN) : E0 : PP Equipment required (ADN) Number of blue cones/lights (ADN) : 0

- Rail transport

: M4 Classification code (RID)

Special provisions (RID) : 188, 230, 310, 348, 360, 376, 377, 636

0 Limited quantities (RID) E0 Excepted quantities (RID)

P903, 908, 909, P910, LP903, LP904 Packing instructions (RID)

Transport category (RID) 2 CE2 Colis express (express parcels) (RID)

Hazard identification number (RID) 90

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no substance on the REACH candidate list

Directive 2012/18/EU (SEVESO III)

15.1.2. National regulations

Germany

Reference to AwSV : Water hazard class (WGK) 3, severe hazard to water (Classification according to

AwSV. Annex 1)

12th Ordinance Implementing the Federal

Immission Control Act - 12.BlmSchV

: Is not subject of the 12. BlmSchV (Hazardous Incident Ordinance)

Netherlands

SZW-lijst van kankerverwekkende stoffen : None of the components are listed SZW-lijst van mutagene stoffen : None of the components are listed NIET-limitatieve lijst van voor de voortplanting : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting

giftige stoffen - Vruchtbaarheid

giftige stoffen - Borstvoeding

: None of the components are listed

TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch

TÜV SÜD Group

Building 12&13, Zhiheng Wisdomland Business Park,

Nantou Checkpoint road 2, Shenzhen 518052. P. R. China

Page: 11 of 12

Tel.: (86) 755 88286998 Fax: (86) 755 88285299



NIET-limitatieve lijst van voor de voortplanting : None of the components are listed giftige stoffen – Ontwikkeling

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Full text of H- and EUH-statements:	
Flam. Sol. 1	Flammable solids, Category 1
Water-react. 2	Substances and Mixtures which, in contact with water, emit flammable gases, Category 2
H228	Flammable solid.
H261	In contact with water releases flammable gases.

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product



Tel.: (86) 755 88286998