# PROBRANDS

# SAFETY DATA SHEET

#### 1. Identification

Product identifier Dymon® Natural Force® Foaming Degreaser

Other means of identification

Part Number 36120

**Recommended use** Industrial Use Only **Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name ITW Pro Brands
Address 4647 Hugh Howell Rd
Tucker, GA 30084

United States

**Telephone** 1-800-241-8334 / 770-243-8800

Website www.lpslabs.com

E-mail lpssds@itwprobrands.com

Emergency phone number Chemtrec 1-800-424-9300

2. Hazard(s) identification

Physical hazards Flammable aerosols Category 1

Gases under pressure Liquefied gas Serious eye damage/eye irritation Category 2A

Sensitization, skin

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements

Health hazards



Signal word Danger

Hazard statement Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May cause an

allergic skin reaction. Causes serious eye irritation.

**Precautionary statement** 

**Prevention** Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open

flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing gas. Wash thoroughly after handling. Contaminated work clothing must not be allowed

Category 1

out of the workplace. Wear eye protection/face protection. Wear protective gloves.

Response If on skin: Wash with plenty of water. If in eyes: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Wash

contaminated clothing before reuse.

Storage Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding

50°C/122°F.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

#### 3. Composition/information on ingredients

**Mixtures** 

Material name: Dymon® Natural Force® Foaming Degreaser
36120 Version #: 02 Revision date: 10-18-2018 Issue date: 10-09-2018

Chemical name	Common name and synonyms	CAS number	%
Methyl Ester of Soybean Oil		67784-80-9	5 - 10
Alcohols, C9-11, Ethoxylated		68439-46-3	1 - 5
Distillates Petroleum Hydrotreated Light		64742-47-8	1 - 5
d-limonene		5989-27-5	1 - 5
Orange, sweet, ext		8028-48-6	1 - 5
Petroleum Gases, Liquefied, Sweetened		68476-86-8	1 - 5
Sodium carbonate		497-19-8	1 - 5
1-dodecyl, sulfate, sodium salt		151-21-3	0.1 - 1
Alcohols, C12-13, Ethoxylated		66455-14-9	0.1 - 1
Cocamidopropyl Betaine		61789-40-0	0.1 - 1
Disodium Cocoampho Diproprionate		68604-71-7	0.1 - 1
Lauramine Oxide		1643-20-5	0.1 - 1
Sodium Nitrite		7632-00-0	0.1 - 1

#### 4. First-aid measures

Inhalation Skin contact

Eye contact

Ingestion

Move to fresh air. Call a physician if symptoms develop or persist.

Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Not likely, due to the form of the product. In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth.

Most important symptoms/effects, acute and delayed

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause an allergic skin reaction. Dermatitis. Rash.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

#### 5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing media Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire fighting equipment/instructions

In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also consider initial evacuation for 800 meters (1/2 mile) in all directions. ALWAYS stay away from tanks engulfed in flame. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Cool containers exposed to flames with water until well after the fire is out. In the event of fire and/or explosion do not breathe fumes.

General fire hazards

Extremely flammable aerosol. Contents under pressure. Pressurized container may explode when

exposed to heat or flame.

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing gas. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

# Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways.

Large Spills: Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Scoop up used absorbent into drums or other appropriate container. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

#### **Environmental precautions**

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

### 7. Handling and storage

#### Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Close valve after each use and when empty. Protect cylinders from physical damage; do not drag, roll, slide, or drop. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Purge air from system before introducing gas. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Avoid breathing gas. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

# Conditions for safe storage, including any incompatibilities

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Keep away from heat, sparks and open flame. This material can accumulate static charge which may cause spark and become an ignition source. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in tightly closed container. Store in a well-ventilated place. Stored containers should be periodically checked for general condition and leakage. Store away from incompatible materials (see Section 10 of the SDS).

### 8. Exposure controls/personal protection

#### Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

U.S OSHA			
Components	Туре	Value	Form
Distillates Petroleum Hydrotreated Light (CAS 64742-47-8)	PEL	5 mg/m3	Oil mist
ACGIH Components	Typo	Value	Form
Components	Туре	value	1 01111
Distillates Petroleum	TWA	5 mg/m3	Oil mist

# **Biological limit values**

No biological exposure limits noted for the ingredient(s).

# Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

#### Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

**Hand protection** Wear appropriate chemical resistant gloves.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

**Respiratory protection** In case of insufficient ventilation, wear suitable respiratory equipment.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

#### 9. Physical and chemical properties

**Appearance** 

Physical state Gas.
Form Aerosol.
Color White.
Odor Citrus.

Odor threshold Not available.

**pH** 10.7

Melting point/freezing point Not available.

Initial boiling point and boiling 212 °F (100 °C)

range

Flash point 135.0 °F (57.2 °C) Pensky-Martens Closed Cup

Evaporation rate Not available.
Flammability (solid, gas) Not available.
Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit - upper

Not available.

(%)

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure Not available.

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Completely soluble.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

Other information

Density 8.23

**Explosive properties** Not explosive. **Oxidizing properties** Not oxidizing.

Percent volatile 10 %

SDS US

Specific gravity 0.986 @ 70°F

VOC 9.51 % per US State and Federal Consumer Product Regulations

#### 10. Stability and reactivity

**Reactivity**The product is stable and non-reactive under normal conditions of use, storage and transport.

**Chemical stability** Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid

temperatures exceeding the flash point. Contact with incompatible materials.

**Incompatible materials** Strong oxidizing agents.

**Hazardous decomposition** 

products

Carbon oxides.

#### 11. Toxicological information

#### Information on likely routes of exposure

InhalationProlonged inhalation may be harmful.Skin contactMay cause an allergic skin reaction.Eye contactCauses serious eye irritation.

**Ingestion** Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

vision. May cause an allergic skin reaction. Dermatitis. Rash.

## Information on toxicological effects

**Acute toxicity** Not expected to be acutely toxic.

Components Species Test Results

Alcohols, C12-13, Ethoxylated (CAS 66455-14-9)

Acute Dermal

LD50 Rat > 2000 mg/kg, 24 Hours

Oral

LD50 Rat

Alcohols, C9-11, Ethoxylated (CAS 68439-46-3)

Acute Dermal

LD50 Rabbit 2000 mg/kg, 24 Hours

Oral

LD50 Rat 3500 mg/kg

Distillates Petroleum Hydrotreated Light (CAS 64742-47-8)

**Acute** 

Dermal

LD50 Rabbit > 2000 mg/kg

Inhalation

Vapor

LC50 Rat > 4.5 mg/l, 4 Hours

> 0.1 mg/l, 8 Hours

7600 mg/kg

Oral

LD50 Rat > 5000 mg/kg

d-limonene (CAS 5989-27-5)

Acute Oral

LD50 Rat > 2000 mg/kg

Material name: Dymon® Natural Force® Foaming Degreaser

**Species** Components **Test Results** 

Orange, sweet, ext (CAS 8028-48-6)

Acute Dermal

LD50 Rabbit > 5000 mg/kg, 24 Hours

Oral

LD50 Rat > 5000 mg/kg

Sodium carbonate (CAS 497-19-8)

Acute **Dermal** 

LD50 Rabbit > 2000 mg/kg

Inhalation

LC50 Rat 2.3 mg/l, 2 Hours

Oral

LD50 Rat 2800 mg/kg

Sodium Nitrite (CAS 7632-00-0)

**Acute** Inhalation

LC50 Rat 5.5 mg/l, 4 Hours

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause an allergic skin reaction.

No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

d-limonene (CAS 5989-27-5) 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

Not classified.

repeated exposure

**Aspiration hazard** Not likely, due to the form of the product. **Chronic effects** Prolonged inhalation may be harmful.

12. Ecological information

The product is not classified as environmentally hazardous. However, this does not exclude the **Ecotoxicity** 

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

**Test Results** Components **Species** 

1-dodecyl, sulfate, sodium salt (CAS 151-21-3)

Aquatic

Crustacea EC50 Water flea (Daphnia obtusa) 9.2 - 10.4 mg/l, 48 hours Fish LC50 Carp, hawk fish (Cirrhinus mrigala) 1.36 mg/l, 96 hours

Components Species Test Results

Alcohols, C12-13, Ethoxylated (CAS 66455-14-9)

Aquatic

Crustacea EC50 Water flea (Daphnia magna) 0.39 - 0.56 mg/l, 48 hours
Fish LC50 Fathead minnow (Pimephales promelas) 0.72 - 2.7 mg/l, 96 hours

Alcohols, C9-11, Ethoxylated (CAS 68439-46-3)

Aquatic

Crustacea EC50 Water flea (Daphnia magna) 2.9 - 8.5 mg/l, 48 hours
Fish LC50 Fathead minnow (Pimephales promelas) 6 - 12 mg/l, 96 hours

Distillates Petroleum Hydrotreated Light (CAS 64742-47-8)

Aquatic

Fish LC50 Rainbow trout, donaldson trout 2.9 mg/l, 96 hours

(Oncorhynchus mykiss)

d-limonene (CAS 5989-27-5)

Aquatic

Crustacea EC50 Water flea (Daphnia pulex) 69.6 mg/l, 48 hours

Fish LC50 Fathead minnow (Pimephales promelas) 0.619 - 0.796 mg/l, 96 hours

Sodium carbonate (CAS 497-19-8)

Aquatic

Crustacea EC50 Water flea (Ceriodaphnia dubia) 156.6 - 298.9 mg/l, 48 hours

Fish LC50 Bluegill (Lepomis macrochirus) 300 mg/l, 96 hours

Sodium Nitrite (CAS 7632-00-0)

Aquatic

Crustacea EC50 Greasyback shrimp (Metapenaeus 16.14 - 26.61 mg/l, 48 hours

ensis)

Fish LC50 Rainbow trout, donaldson trout 0.15 - 0.25 mg/l, 96 hours

(Oncorhynchus mykiss)

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

1-dodecyl, sulfate, sodium salt 1.6 d-limonene 4.232

Mobility in soilNo data available.Other adverse effectsNone known.

13. Disposal considerations

**Disposal instructions**Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents

under pressure. Do not puncture, incinerate or crush. Incinerate the material under controlled conditions in an approved incinerator. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose of contents/container in accordance with local/regional/national/international

regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

D003: Waste Reactive material

D001: Waste Flammable material with a flash point <140 F

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal. Do not re-use empty containers.

14. Transport information

DOT

UN number UN1950

UN proper shipping name Aerosols, flammable, (each not exceeding 1 L capacity), MARINE POLLUTANT

Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

Packing group Not available.

**Environmental hazards** 

Marine pollutant Yes

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisionsN82Packaging exceptions306Packaging non bulkNonePackaging bulkNone

IATA

UN number UN1950

UN proper shipping name Aerosols, flammable

Transport hazard class(es)

Class 2.1 Subsidiary risk -

Packing group Not available.

**Environmental hazards** No. **ERG Code** 10L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only Allowed with restrictions.

**IMDG** 

UN number UN1950

UN proper shipping name Aerosols, flammable, MARINE POLLUTANT

Not applicable.

Transport hazard class(es)

Class 2.1 Subsidiary risk -

Packing group Not available.

**Environmental hazards** 

Marine pollutant Yes
EmS F-D. S-U

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

DOT



#### IATA; IMDG



#### Marine pollutant



**General information** 

IMDG Regulated Marine Pollutant. DOT Regulated Marine Pollutant. Ensure compliance with applicable regulations.

#### 15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Sodium Nitrite (CAS 7632-00-0)

1.0 % One-Time Export Notification only.

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

Sodium Nitrite (CAS 7632-00-0)

Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

#### SARA 302 Extremely hazardous substance

Not listed.

Classified hazard

Flammable (gases, aerosols, liquids, or solids)

categories

Gas under pressure

Serious eye damage or eye irritation Respiratory or skin sensitization

#### SARA 313 (TRI reporting)

Not regulated.

#### Other federal regulations

## Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

#### **US** state regulations

#### US. New Jersey Worker and Community Right-to-Know Act

Sodium Nitrite (CAS 7632-00-0)

#### California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 2016 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

# US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Petroleum Gases, Liquefied, Sweetened (CAS 68476-86-8)

#### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

 Issue date
 10-09-2018

 Revision date
 10-18-2018

Version # 02

**Disclaimer** ITW Pro Brands cannot anticipate all conditions under which this information and its product, or

the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the

sheet was written based on the best knowledge and experience currently available.

**Revision information** Composition / Information on Ingredients: Ingredients

Physical & Chemical Properties: Multiple Properties

GHS: Classification

Material name: Dymon® Natural Force® Foaming Degreaser

SDS US

Yes