

Safety Data Sheets (SDSs)

Client	Changzhou Anyida Power Technology Co.,Ltd			
Add. of Client	No.60, Tianshan Road, Xinbei District, Changzhou, JiangSu			
Description	Lithium Manganese Dioxide Button Battery			
Model /Type	CR2450			
Trade Name	N/A			
Manufacturer	Changzhou Anyida Power Technology Co.,Ltd			
Add. of Manufacturer	No.60, Tianshan Road, Xinbei District, Changzhou, JiangSu			
Nominal Voltage	3.0V, 600mAh			
Weight of Lithium in grams	0.18g			
Date of Receipt	2021-04-07			
	ZILIA WERCS			
Laboratory	Dongguan ZRLK Testing Technology Co., Ltd.			
Address	Building D, No.2, Jinyuyuan Mansion, No.18, Industrial West Road, Songshan Lake High-tech Industrial Development Zone, Dongguan, Guangdong, China			
Approved Signatory	Maggie.Gao Ailis.Ma Lahm Peng Lahm Peng			
Inspected by	Ailis.Ma Ailis Ma			
Censored by	Lahm Peng Lahm Peng			



1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product Identifier

Product name: Lithium Manganese Dioxide Button Battery

Model: CR2450

Other means of identification

Synonyms:none

Recommended use of the chemical and restrictions on use

Recommended Use:Used in portabl electronic equipments;

Uses advidsed against:

a) Do not dismantle, open or shred batteries.

b) Do not expose batteries to heat or fire. Avoid storage in direct sunlight.

c) Do not short-circuit battery. Do not store batteries haphazardly in a box or drawer where they may short-

circuit each other or be short-circuited by other metal objects.

d) Do not remove a battery from its original packaging until required for use.

e) Do not subject batteries to mechanical shock.

f) In the event of a cell leaking, do not allow the liquid to come in contact with the skin or eyes. If contact has been made, wash the affected area with copious amounts of water and seek medical advice.

g) Observe the plus (+) and minus (-) marks on the cell, battery and equipment and ensure correct use.

h) Do not use any cell or battery which is not designed for use with the equipment.

i) Do not mix cells of different manufacture, capacity, size or type within a device.

j) Battery usage by children should be supervised.

k) Seek medical advice immediately if a cell or a battery has been swallowed.

1) Always purchase the battery recommended by the device manufacturer for the equipment.

m) Keep cells and batteries clean and dry.

n) After extended periods of storage, it may be necessary to charge and discharge the cells or batteries several times to obtain maximum performance.

o) Use only the cell or battery in the application for which it was intended.

p) When possible, remove the battery from the equipment when not in use.

q) Dispose of properly.

Details of the supplier of the safety data sheet:

Supplier Name: Changzhou Anyida Power Technology Co.,Ltd

Address: No.60, Tianshan Road, Xinbei District, Changzhou, JiangSu

Telephone number of the supplier: 0086-0519-83270474

Postcode: 213000

E-mail address: marketing@suyucell.cn

Emergency telephone number

Company Emergency Phone Number: 0086-0519-83270474

2. HAZARDS IDENTIFICATION



Classification

Acute toxicity - Dermal	Category 3
Serious eye damage/eye irritation	Category 2A
Carcinogenicity	Category 2
Specific target organ toxicity (repeated exposure)	Category 1

GHS Label elements, including precautionary statements

Danger

Hazard statements

Toxic in contact with skin Causes serious eye irritation

Suspected of causing cancer

Causes damage to organs through prolonged or repeated exposure



Precautionary statements-Prevention

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Wear protective gloves/protective clothing/eye protection/face protection Wash face, hands and any exposed skin thoroughly after handling Do not breathe dust/fume/gas/mist/vapors/spray Do not eat, drink or smoke when using this product

Precautionary Statements - Response

If exposed or concerned: Get medical advice/attention Specific treatment (see supplemental first aid instructions on this label)

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

Skin

IF ON SKIN: Wash with plenty of water and soap



Call a POISON CENTER or doctor if you feel unwell Take off immediately all contaminated clothing and wash it before reuse

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other information

harmful if swallowed. Very toxic to aquatic life with long lasting effects.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical characterization: Mixtures

Description:

Product: Consisting of the following components.

Common Chemical Name	Concentration	CAS
	(%)	Number
Lithium	2.5	7439-93-2
Propylene Carbonate	4	108-32-7
Manganese Dioxide	40	1313-13-9
Stainless steel	50.5	12597-68-1
Perchloric acid, lithium salt	1	7791-03-9
Graphite	2	7782-42-5

Note: CAS number is Chemical Abstract Service Registry Number.

N/A=Not apply.

4. FIRST-AID MEASURES

First aid measures

Eye Contact Rinse thoroughly with plenty of water, also under the eyelids. If symptoms persist, call a physician.

Skin Contact Remove contaminated clothing and shoes. Wash skin with soap and water. In the case of skin irritation or allergic reactions see a physician.

Inhalation Move to fresh air. If symptoms persist, call a physician.

Ingestion Do NOT induce vomiting. Drink plenty of water. If symptoms persist, call a physician.

Most important symptoms and effects, both acute and delayed

Swallowing Do not induce vomiting. Get medical attention.



Most Important Symptoms/Effects No information available.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

CO2, dry chemical powder, water spray.

Unsuitable Extinguishing Media:No information available.

Specific Hazards Arising from the Chemical

Formation of toxic gases is possible during heating or in case of fire.

In case of fire, the following can be released:

Carbon monoxide(CO)

Carbon dioxide

Other irritating and toxic gases.

Hazardous Combustion Products

Carbon oxides.

Explosion Data

Sensitivity to Mechanical Impact No

Sensitivity to Static Discharge No

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. For example: Wear self-contained respiratory protective device. Wear suitable protective clothing and eye/face protection.

Special hazards arising from the substance or mixture:

Battery may burst and release hazardus decomposition products when exposed to a fire situation. Lithium ion batteries contain flammable electrolyte that may vent, ignite and produce sparks when subjected to high temperature(>150°C), When damaged or abused(e.g. mechanical damage or electrical overcharging); may burn rapidly with flare-burning effect; may ignite other batteries in clothes proximity.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Avoid contact with eyes.

Refer to section 8 for personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition.

Evacuate personnel to safe areas.

Environmental precautions

Environmental Precautions Refer to protective measures listed in Sections 7 and 8.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Methods and material for containment and cleaning up



Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Cleaning up Use personal protective equipment. Dam up. Cover liquid spill with sand, earth or other Non combustible absorbent material. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes and clothing. Wear personal protective equipment.

Wash thoroughly after handling. Use this material with adequate ventilation. The product is not explosive.

Conditions for safe storage, including any incompatibilities

If the 3V Lithium Manganese Dioxide Button Cell is subject to storage for such a long term as more than 3 months, it is recommended to recharge the 3V Lithium Manganese Dioxide Button Cell periodically. 3 months: -10°C~+40°C, 45 to 85%RH

And recommended at 0°C~+35°C for long period storage.

Do not storage 3V Lithium Manganese Dioxide Button Cell haphazardly in a box or drawer where they may short-circuit each other or be short-circuited by other metal objects.

Keep out of reach of children.

Do not expose 3V Lithium Manganese Dioxide Button Cell to heat or fire. Avoid storage in direct sunlight. Do not store together with oxidizing and acidic materials.

Keep ignition sources away- Do not smoke.

Store in cool, dry and well-ventilated place.

Incompatible Products None known.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Control parameters

None

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962(11th Cir., 1992).

Appropriate engineering controls

Engineering Measures Showers

Evewash stations

Ventilation systems

Use adequate general or local exhaust ventilation to keep airborne concentrations below the permissible exposure limits. Ensure adequate ventilation.

Individual protection measures, such as personal protective equipment

Eye/Face Protection:



Body protection:



Protective work clothing.

Skin protection:



Material of gloves:

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material:

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Respiratory Protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

	Form: button				
Physical	Color: silver				
State	Odour: Odourless				
	Odor Threshold: No information available				
Change in co	ondition:				
pH, with ind	lication of the concentration	Not determined.			
Melting poir	nt/freezing point	Not determined.			
Initial boilin	g point and Boiling range:	Not determined.			
Flash Point		Not determined.			
Evaporation rate		Not determined.			
Flammability (solid, gas)		Not determined.			
Upper/lower flammability or explosive limits		Not determined.			
Vapor Press	ure:	Not determined.			
Vapor Density:		Not determined.			
relative density:		Not determined.			
Solubility in Water:		Not determined.			
Solubility in other solvents		Not determined.			
n-octanol/water partition coefficient		Not determined.			



Auto-ignition temperature	Product is not self-igniting.
Decomposition temperature	Not determined.
Odout threshold	Not determined.
Evaporation rate	Not determined.
Viscosity	Not determined.
Other Information	:
Voltage	3.0V
Electric capacity	210mAh
Lithium content	0.063g

10. STABILITY AND REACTIVITY

<u>Reactivity</u>: Stable under recommended storage and handling conditions (see section 7, Handling and storage). <u>Chemical stability</u>: Stable under normal conditions of use, storage and transport.

Thermal decomposition/conditions to be avoided: No decomposition if used according to specifications.

Possibility of Hazardous Reactions: None under normal processing.

Hazardous Polymerization: Hazardous polymerization does not occur.

Conditions to avoid: Strong heating, fire, Incompatible materials.

Incompatible materials: Strong oxidizing agents. Strong acids.Base metals.

Hazardous Decomposition Products: Carbon oxides, Other irritating and toxic gases.

11. TOXICOLOGICAL INFORMATION

Acute toxiciy: No data available.

LD/LC50 values relevant for classification:

Not available.

Skin corrosion/irritation: No irritant effect.

Serious eye damage/irritation: Cause serious eye irritation.

Respiratory or skin sensitization: No sensitizing effects known.

Specific target organ system toxicity: No information available.

CMR effects(carcinogenity, mutagenicity and toxicity for reproduction): No information available.

12. Ecological Information

Toxicity:

Acquatic toxicity:

No further relevant information available.

Persistence and degradability: No further relevant information available.

Bioaccumulative potential: No further relevant information available.

Mobility in soil: No further relevant information available.



Results of PBT and vPvB assessment PBT: Not applicable. vPvB: Not applicable. **Other adverse effects:** No information available.

13. DISPOSAL CONSIDERATIONS

[•] Waste treatment methods

Recommendation: Must not be disposed together with household garbage.

Do not allow product to reach sewage system

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

14. TRANSPORT INFORMATION

Land transport

ADR/RID class: Not regulated. UN-Number: UN3090 or UN3091.

Maritime transport

IMDG Class: Class 9. UN Number: UN3090 or UN3091. Marine pollutant: No <u>Air transport</u>

ICAO/IATA Class: Class 9

UN/ID Number: UN3090 or UN3091

Environmental hazards: Not applicable.

Special precautions for user: Not applicable.

Transport/Additional information: Not restricted goods according to the above specifications.

The 3V Lithium Manganese Dioxide Button Cell had been tested according to the requirements of the UN manual of tests and Criteria, Part III, subsection 38.3;

The lithium ion batteries according to Section II of PACKING INSTRUCTION 968, or Section II of PACKING INSTRUCTION $969 \sim 970$ of the Dangerous Goods regulations 59^{th} Edition may be transported. The packaging shall be adequate to avoid mechanical damage during transport, handling and stacking. The materials and pack design shall be chosen so as to prevent the development of unintentional electrical conduction, corrosion of the terminals and ingress of moisture.

Meets requirements of Special Provision 188 of IMDG(38-16) to be transported as non-dangerous goods Meets the requirements of 49CFR173.185 to be transported as non-dangerous goods for road, rail, air, and vessel (Effective August 6, 2014 per HM224F)

The package must be handled with care and that a flammability hazard exists if the package is damaged;

15. REGULATORY INFORMATION



Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation:

Authorisations: No information available.

Restrictions on use: No information available.

Regulatory information

CAS No.	EU	US	Japan	Canada	Austrlia	Korea	China
	(EINECS)	(TSCA)	(ENCS)	(DSL/	(AICS)	(ECL)	(IECSC)
				NDSL)			
7439-93-2	Listed	Listed	Listed	DSL	Listed	Listed	Listed
108-32-7	Listed	Listed	Listed	DSL	Listed	Listed	Listed
1313-13-9	Listed	Listed	Listed	DSL	Listed	Listed	Listed
12597-68-1	Listed	Listed	Listed	DSL	Listed	Listed	Listed
7791-03-9	Listed	Listed	Listed	DSL	Listed	Listed	Listed
7782-42-5	Listed	Listed	Listed	DSL	Listed	Listed	Listed

Chemical safety assessment A Chemical Safety Assessment has not been carried out.

16. OTHER INFORMATION

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases:

R20/22: Harmful by inhalation and if swallowed.

R36: Irritating to eyes.

H302: Harmful if swallowed.

H332: Harmful if inhaled.



Version 1.5	Revision Date: 02/17/2015		SDS Number: 169-00006	Date of last issue: 02/10/2015 Date of first issue: 09/26/2014	
SECTIO	ON 1. IDENTIFICATION				
Pro	Product name		PURELL® Advanced Green Certified Instant Hand Sanitizer Foam		
Ма	anufacturer or supplier's	deta	ails		
	mpany name of supplier	:		Inc.	
Ad	Address		One GOJO Plaza, Suite 500 Akron OH 44311		
Te	lephone	:	1 (330) 255-6000		
En	nergency telephone	:	1-800-424-9300	CHEMTREC	
Re	commended use of the c	chen	nical and restriction	ons on use	
Re	commended use	:	Human hygiene b	biocidal products	
Re	Restrictions on use		consumers and o foreseeable use. specifically define exempt from the While this materia contains valuable proper use of the as well as unusua spills. This SDS s employees and o intended-use guid	I care or cosmetic product that is safe for ther users under normal and reasonably Cosmetics and consumer products, ed by regulations around the world, are requirement of an SDS for the consumer. al is not considered hazardous, this SDS information critical to the safe handling and product for industrial workplace conditions al and unintended exposures such as large should be retained and available for ther users of this product. For specific dance, please refer to the information package or instruction sheet.	

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification Flammable liquids	: Category 3
Eye irritation	: Category 2A
GHS Label element Hazard pictograms	
Signal Word	: Warning



Version 1.5	Revision Date: 02/17/2015	MSDS Number: 16169-00006	Date of last issue: 02/10/2015 Date of first issue: 09/26/2014
Hazard Statements		: H226 Flammabl H319 Causes se	e liquid and vapor. erious eye irritation.
Preca	utionary Statements	No smoking. P233 Keep cont P241 Use explo equipment. P242 Use only r P243 Take prec P264 Wash skin P280 Wear prot Response: P303 + P361 + I all contaminated P305 + P351 + I for several minu to do. Continue P337 + P313 If attention. Storage: P403 + P235 St Disposal:	y from heat/sparks/open flames/hot surfaces ainer tightly closed. sion-proof electrical/ ventilating/ lighting/ non-sparking tools. autionary measures against static discharge. thoroughly after handling. ective gloves/ eye protection/ face protection. P353 IF ON SKIN (or hair): Take off immediately I clothing. Rinse skin with water/shower. P338 IF IN EYES: Rinse cautiously with water tes. Remove contact lenses, if present and easy rinsing. eye irritation persists: Get medical advice/ ore in a well-ventilated place. Keep cool. f contents/ container to an approved waste

Other hazards

Vapors may form explosive mixture with air.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous ingredients

Chemical Name	CAS-No.	Concentration (%)
Ethanol	64-17-5	>= 50 - < 70
Propan-2-ol	67-63-0	>= 1 - < 5

SECTION 4. FIRST AID MEASURES

General advice	 In the case of accident or if you feel unwell, seek medical advice immediately. When symptoms persist or in all cases of doubt seek medic advice. 	al
If inhaled	: If inhaled, remove to fresh air. Get medical attention if symptoms occur.	
In case of skin contact	: Wash with water and soap as a precaution. Get medical attention if symptoms occur.	



Version 1.5	Revision Date: 02/17/2015	MSDS Number: 16169-00006	Date of last issue: 02/10/2015 Date of first issue: 09/26/2014	
In case of eye contact		 In case of contact, immediately flush eyes with plenty of wa for at least 15 minutes. If easy to do, remove contact lens, if worn. Get medical attention. 		
If swallowed		Get medical a	DO NOT induce vomiting. ttention if symptoms occur. horoughly with water.	
Most important symptoms and effects, both acute and delayed		: Causes seriou	us eye irritation.	
Protection of first-aiders		and use the re	onders should pay attention to self-protection, ecommended personal protective equipment ential for exposure exists.	
Notes to physician		: Treat symptor	natically and supportively.	

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Water spray Alcohol-resistant foam Dry chemical Carbon dioxide (CO2)
Unsuitable extinguishing media	:	High volume water jet
Specific hazards during fire fighting	:	Do not use a solid water stream as it may scatter and spread fire. Flash back possible over considerable distance. Vapors may form explosive mixtures with air. Exposure to combustion products may be a hazard to health.
Hazardous combustion prod- ucts	:	Carbon oxides Silicon oxides
Specific extinguishing methods	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.
Special protective equipment for fire-fighters	:	In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES



Versio 1.5	on	Revision Date: 02/17/2015		DS Number: 169-00006	Date of last issue: 02/10/2015 Date of first issue: 09/26/2014		
Personal precautions, protective equipment and emergency procedures		:	 Remove all sources of ignition. Use personal protective equipment. Follow safe handling advice and personal protective equipment recommendations. 				
Environmental precautions		:	 Discharge into the environment must be avoided. Prevent further leakage or spillage if safe to do so. Prevent spreading over a wide area (e.g. by containment or oil barriers). Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained. 				
Methods and materials for containment and cleaning up		:	Suppress (knock jet. For large spills, pro- containment to kee can be pumped, so container. Clean up remaining absorbent. Local or national of disposal of this m employed in the co determine which of Sections 13 and 1	s should be used. absorbent material. down) gases/vapors/mists with a water spray rovide diking or other appropriate ep material from spreading. If diked material tore recovered material in appropriate ng materials from spill with suitable regulations may apply to releases and aterial, as well as those materials and items leanup of releases. You will need to egulations are applicable. 5 of this SDS provide information regarding tional requirements.			

SECTION 7. HANDLING AND STORAGE

Technical measures	: See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
Local/Total ventilation	: Use with local exhaust ventilation. Use only in an area equipped with explosion proof exhaust ventilation.
Advice on safe handling	 Do not breathe vapors or spray mist. Do not swallow. Do not get in eyes. Avoid prolonged or repeated contact with skin. Handle in accordance with good industrial hygiene and safety practice. Non-sparking tools should be used. Keep container tightly closed. Keep away from heat and sources of ignition. Take precautionary measures against static discharges. Take care to prevent spills, waste and minimize release to the environment.
Conditions for safe storage	: Keep in properly labeled containers.



Version 1.5	Revision Date: 02/17/2015	MSDS Number: 16169-00006	Date of last issue: 02/10/2015 Date of first issue: 09/26/2014
Mate	rials to avoid	Store in accord Keep away from Do not store wit Strong oxidizing Organic peroxic Flammable soli Pyrophoric liqui Pyrophoric solic Self-heating sul	well-ventilated place. ance with the particular national regulations. n heat and sources of ignition. th the following product types: g agents des ds ds ds ds ds ds ds ds ds ds ds ds ds

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Ethanol	64-17-5	TWA	1,000 ppm 1,900 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,900 mg/m3	OSHA Z-1
		STEL	1,000 ppm	ACGIH
Propan-2-ol	67-63-0	TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH
		TWA	400 ppm 980 mg/m3	NIOSH REL
		ST	500 ppm 1,225 mg/m3	NIOSH REL
		TWA	400 ppm 980 mg/m3	OSHA Z-1

Ingredients with workplace control parameters

Biological occupational exposure limits

Ingredients	CAS-No.	Control parameters	Biological specimen	Sam- pling time	Permissible concentratio n	Basis
Propan-2-ol	67-63-0	Acetone	Urine	End of shift at end of work- week	40 mg/l	ACGIH BEI
Engineering measures	: Min	imize workpla	ce exposure	concentrat	ions.	

Engineering measures

Minimize workplace exposure concentrations. Use only in an area equipped with explosion proof exhaust ventilation. Use with local exhaust ventilation.



Version	Revision Date:	MSDS Number:	Date of last issue: 02/10/2015
1.5	02/17/2015	16169-00006	Date of first issue: 09/26/2014

Personal protective equipment

Respiratory protection	:	General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.
Hand protection Material		Impervious gloves
Material		Flame retardant gloves
Material	•	rano rotardan giovos
Remarks	:	Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.
Eye protection	:	Wear the following personal protective equipment: Safety goggles
Skin and body protection	:	Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential. Wear the following personal protective equipment: Flame retardant antistatic protective clothing. Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).
Hygiene measures	:	Ensure that eye flushing systems and safety showers are located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	liquid
Color	:	clear



Ver 1.5	sion	Revision Date: 02/17/2015		DS Number: 69-00006	Date of last issue: 02/10/2015 Date of first issue: 09/26/2014
	Odor		:	alcohol-like	
	Odor T	hreshold	:	No data available	9
	рН		:	6 - 9	
	Melting	point/freezing point	:	No data available	9
	Initial b range	oiling point and boiling	:	No data available	9
	Flash p	point	:	26.00 °C	
	Evapo	ration rate	:	No data available	9
	Flamm	ability (solid, gas)	:	Not applicable	
	Upper	explosion limit	:	No data available	9
	Lower	explosion limit	:	No data available	9
	Vapor	pressure	:	No data available	9
	Relativ	e vapor density	:	No data available	9
	Density	ý	:	0.880 g/cm3	
	Solubil Wat	ity(ies) er solubility	:	soluble	
	Partitic octano	n coefficient: n- I/water	:	Not applicable	
	Autoig	nition temperature	:	No data available	9
	Decom	position temperature	:	The substance o	r mixture is not classified self-reactive.
	Viscos Visc	ity osity, kinematic	:	10 - 20 mm2/s (2	20 °C)
	Explos	ive properties	:	Not explosive	
	Oxidizi	ng properties	:	The substance o	r mixture is not classified as oxidizing.

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Not classified as a reactivity hazard.	
Chemical stability	: Stable under normal conditions.	
Possibility of hazardous reac-	: Flammable liquid and vapor.	



Version 1.5	Revision Date: 02/17/2015	MSDS Number: 16169-00006	Date of last issue: 02/10/2015 Date of first issue: 09/26/2014		
tions		Vapors may form explosive mixture with air. Can react with strong oxidizing agents.			
Conditions to avoid		: Heat, flames and sparks.			
Incom	patible materials	: Oxidizing agents			
Hazaı produ	dous decomposition	: No hazardous	decomposition products are known.		

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes Inhalation Skin contact Ingestion Eye contact	s of exposure
Acute toxicity	
Not classified based on availa	able information.
Product:	
Acute oral toxicity	: Acute toxicity estimate: > 5,000 mg/kg Method: Calculation method
Ingredients:	
Ethanol: Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity	: LC50 (Rat): 124.7 mg/l Exposure time: 4 h Test atmosphere: vapor
Propan-2-ol:	
Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity	: LC50 (Rat): 72.6 mg/l Exposure time: 4 h Test atmosphere: vapor
Acute dermal toxicity	: LD50 (Rat): > 5,000 mg/kg
Skin corrosion/irritation	

Skin corrosion/irritation

Not classified based on available information.

Product:

Result: No skin irritation

Ingredients:

Ethanol: Species: Rabbit Method: OECD Test Guideline 404



Version	Revision Date:	MSDS Number:	Date of last issue: 02/10/2015
1.5	02/17/2015	16169-00006	Date of first issue: 09/26/2014

Result: No skin irritation

Propan-2-ol:

Species: Rabbit Result: No skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Ingredients:

Ethanol: Species: Rabbit Result: Irritation to eyes, reversing within 21 days Method: OECD Test Guideline 405

Propan-2-ol:

Species: Rabbit Result: Irritation to eyes, reversing within 21 days

Respiratory or skin sensitization

Skin sensitization: Not classified based on available information. Respiratory sensitization: Not classified based on available information.

Product:

Assessment: Does not cause skin sensitization.

Ingredients:

Ethanol:

Test Type: Local lymph node assay (LLNA) Routes of exposure: Skin contact Species: Mouse Result: negative

Propan-2-ol:

Test Type: Buehler Test Routes of exposure: Skin contact Species: Guinea pig Method: OECD Test Guideline 406 Result: negative

Germ cell mutagenicity

Not classified based on available information.

Ingredients:

Ethanol: Genotoxicity in vitro	: Test Type: In vitro mammalian cell gene mutation test Result: negative	
Genotoxicity in vivo	: Test Type: Rodent dominant lethal test (germ cell) (in vivo Species: Mouse Application Route: Ingestion)



rsion 5	Revision Date: 02/17/2015	MSDS Number: 16169-00006	Date of last issue: 02/10/2015 Date of first issue: 09/26/2014	
		Result: negat	ive	
	an-2-ol: toxicity in vitro	: Test Type: Ba Result: negat	acterial reverse mutation assay (AMES) ive	
Geno	toxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Mouse Application Route: Intraperitoneal injection Result: negative		
Carci	nogenicity			
Not cl	assified based on availa	ble information.		
Speci Applic Expos Metho	an-2-ol: es: Rat cation Route: inhalation (sure time: 104 weeks od: OECD Test Guideline t: negative			
IARC	:		this product present at levels greater than or identified as probable, possible or confirmed en by IARC.	
OSH	A	No ingredient of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.		
NTP		No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.		
-	oductive toxicity assified based on availa	ble information.		
Ethar	dients: nol: is on fertility	Species: Mou Application R	oute: Ingestion D Test Guideline 416	
	an-2-ol: s on fertility	Species: Rat	vo-generation reproduction toxicity study oute: Ingestion ive	



Version	Revision Date:	MSDS Number:
1.5	02/17/2015	16169-00006

Date of last issue: 02/10/2015 Date of first issue: 09/26/2014

Species: Rat Application Route: Ingestion Result: negative

STOT-single exposure

Not classified based on available information.

Ingredients:

Propan-2-ol: Assessment: May cause drowsiness or dizziness.

STOT-repeated exposure

Not classified based on available information.

Repeated dose toxicity

Ingredients:

Ethanol: Species: Rat NOAEL: 2,400 mg/kg Application Route: Ingestion Exposure time: 2 y

Propan-2-ol:

Species: Rat NOAEL: 5000 ppm Application Route: inhalation (vapor) Exposure time: 104 w Method: OECD Test Guideline 413

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity	
Ingredients: Ethanol: Toxicity to fish	: LC50 (Pimephales promelas (fathead minnow)): > 1,000 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): > 1,000 mg/l Exposure time: 48 h
Toxicity to algae	: EC50 (Chlorella vulgaris (Fresh water algae)): 275 mg/l Exposure time: 72 h Method: OECD Test Guideline 201
Toxicity to daphnia and other aquatic invertebrates	: NOEC (Daphnia magna (Water flea)): 9.6 mg/l Exposure time: 9 d



ersion 5	Revision Date: 02/17/2015		DS Number: 169-00006	Date of last issue: 02/10/2015 Date of first issue: 09/26/2014	
(Chro	nic toxicity)				
Toxici	ty to bacteria	:	EC50 (Photoba Exposure time:	cterium phosphoreum): 32.1 mg/l 0.25 h	
	an-2-ol: ity to fish	:	LC50 (Pimepha Exposure time:	ales promelas (fathead minnow)): 10,000 mg/l 96 h	
	ty to daphnia and other ic invertebrates	:	EC50 (Daphnia Exposure time:	magna (Water flea)): > 10,000 mg/l 24 h	
Toxici	ty to algae	:	ErC50 (Scenec mg/l Exposure time:	esmus quadricauda (Green algae)): > 1,800 8 d	
Toxici	ty to bacteria	:	EC50 (Pseudor Exposure time:	nonas putida): > 1,050 mg/l 16 h	
Persis	stence and degradabili	ity			
	dients:				
Ethan Biode	nol: gradability	:	Result: Readily Biodegradation Exposure time:	: 84 %	
	a n-2-ol: gradability	:	: Result: rapidly degradable		
Bioac	cumulative potential				
Ingree	dients:				
	nol: on coefficient: n- ol/water	:	log Pow: -0.35		
Partiti	an-2-ol: on coefficient: n- ol/water	:	log Pow: 0.05		
	ity in soil Ita available				
Other	adverse effects				

SECTION 13. DISPOSAL CONSIDERATIONS

- **Disposal methods**
- Waste from residues

: Dispose of in accordance with local regulations.



ersion 5	Revision Date: 02/17/2015	MSDS Number: 16169-00006	Date of last issue: 02/10/2015 Date of first issue: 09/26/2014
Conta	aminated packaging	handling site fo	inused product. ers should be taken to an approved waste r recycling or disposal. use a cutting torch on, the empty drum.
ECTION	14. TRANSPORT INF	ORMATION	
Interr	national Regulation		
Prope	umber er shipping name ng group	: UN 1987 : ALCOHOLS, N (Ethanol, Propa : 3 : III : 3	
IATA UN/IE Prope		: UN 1987 : Alcohols, n.o.s.	
Label Packi aircra Packi	ng group s ng instruction (cargo	(Ethanol, Propa : 3 : III : Flammable Liqu : 366 : 355	
IMDG UN ni	i-Code umber er shipping name	: UN 1987 : ALCOHOLS, N (Ethanol, Propa	
Label EmS	ng group s	: 3 : III : 3 : F-E, S-D : no	an-∠-on

Domestic regulation

49 CFR UN/ID/NA number Proper shipping name	: UN 1987 : ALCOHOLS, N.O.S.
Class	: 3
Packing group	: III



Version	Revision Date:	MSDS Number:	Date of last issue: 02/10/2015
1.5	02/17/2015	16169-00006	Date of first issue: 09/26/2014
Labels ERG (Marine		: FLAMMABLE LI : 127 : no	QUID

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312	Hazards :	Fire Hazard Acute Health Hazard				
SARA 302	:	No chemicals in this materian requirements of SARA Title		reporting		
SARA 313	:	The following components a established by SARA Title I		ng levels		
		Propan-2-ol	67-63-0	3.4086 %		
US State Regu	lations					
Pennsylvania	Right To Know					
	Ethanol		64-17-5	50 - 70 %		
	Water		7732-18-5	30 - 50 %		
	Propan-2-ol		67-63-0	1 - 5 %		
New Jersey Ri	ight To Know					
•	Ethanol		64-17-5	50 - 70 %		
	Water		7732-18-5	30 - 50 %		
	Propan-2-ol		67-63-0	1 - 5 %		
	Dimethyl Siloxar		102783-01-7	1 - 5 %		
	Dimethyl(propyl(
	oxide))hydroxy)s	siloxy-terminated				
California Pro	p 65	This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.				
The ingredien AICS	•	•	The ingredients of this product are reported in the following inventories:AICS: All ingredients listed or exempt.			

Inventories




Version	Revision Date:	MSDS Number:	Date of last issue: 02/10/2015
1.5	02/17/2015	16169-00006	Date of first issue: 09/26/2014

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), NECSI (Taiwan), TSCA (USA)

SECTION 16. OTHER INFORMATION





Full text of other abbreviations

ACGIH ACGIH BEI NIOSH REL OSHA Z-1	:	USA. ACGIH Threshold Limit Values (TLV) ACGIH - Biological Exposure Indices (BEI) USA. NIOSH Recommended Exposure Limits USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim- its for Air Contaminants
ACGIH / TWA		8-hour, time-weighted average
ACGIH / STEL		Short-term exposure limit
NIOSH REL / TWA		Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA Z-1 / TWA	:	8-hour time weighted average
Sources of key data used to compile the Material Safety Data Sheet	:	Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, http://echa.europa.eu/
Revision Date	:	02/17/2015

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, in-



Version Revision Date: MSDS Number: 02/17/2015 1.5 16169-00006

Date of last issue: 02/10/2015 Date of first issue: 09/26/2014

cluding an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8