

SAFETY DATA SHEET

Sample name : Rechargeable Li-ion Battery

Model No. : SUPER LIFEJACKET JOLT

Consignor : Shenzhen Powercome Electronics Co., Ltd.

Address : Building 10, Shi'ao Second Industrial Zone,
No.8,Langqin Road,Shi'ao, Dalang Village,
Longhua Area, Shenzhen, Guangdong, China

1. IDENTIFICATION

Product identifier

Product Name Rechargeable Li-ion Battery
 Model: SUPER LIFEJACKET JOLT
 Nominal Voltage: 14.8V
 Typical Capacity: 2400mAh
 Watt-hour: 35.52Wh

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use LITHIUM ION BATTERIES

Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Name Shenzhen Powercome Electronics Co., Ltd.

Supplier Address Building 10, Shi'ao Second Industrial Zone, No.8, Langqin Road, Shi'ao, Dalang Village, Longhua Area, Shenzhen, Guangdong, China

Supplier Phone Number Phone: +86-13418779030

Emergency telephone number Phone: +86-13418779030

2. HAZARDS IDENTIFICATION

This product is defined as an 'article' under the OSHA Hazard Communication standard 1910.1200(c). Articles are exempt from OSHA Safety Data Sheet (SDS) requirements.

This product should not present a health or safety hazard during recommended normal use. Misuse of this product may affect the product performance and / or present a potential health or safety hazard.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Weight-%
Lithium Cobalt Oxide (CoLiO ₂)	12190-79-3	29.23
Graphite	7782-42-5	22.87
Copper	7440-50-8	8.51
Aluminum foil	7429-90-5	15.16
Phosphate(1-), hexafluoro-,	21324-40-3	3.44

lithium		
Carbon black	1333-86-4	1.00
Polypropylene	9003-07-0	4.13
Nickel	7440-02-0	6.08
Polyethylene	9002-88-4	3.58
Poly[[imino(1-oxo-1,12-dodecane-1,12-diyl)], (nylon 12 chips)	24937-16-4	6.00

4. FIRST AID MEASURES

First aid measures

General Advice

First aid is upon rupture of sealed battery.

Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists. Do not rub affected area.

Skin Contact

Wash off immediately with soap and plenty of water for at least 15 minutes. Get medical attention if irritation develops and persists.

Inhalation

Remove to fresh air. Get medical attention immediately if symptoms occur.

Ingestion

Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Do not induce vomiting. Call a physician.

Self-protection of the first aider

Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. Wear personal protective clothing (see section 8).

Most important symptoms and effects, both acute and delayed

Most Important Symptoms and Effects

Coughing and/or wheezing. Itching.

Indication of any immediate medical attention and special treatment needed

Notes to Physician

Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media

CAUTION: Use of water spray when fighting fire may be inefficient.

Specific Hazards Arising from the Chemical

No information available.

Hazardous Combustion Products

Carbon oxides.

Explosion Data**Sensitivity to Mechanical Impact** No.**Sensitivity to Static Discharge** No.**Protective equipment and precautions for firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas.

Other Information Refer to protective measures listed in Sections 7 and 8.

Environmental Precautions

Environmental Precautions Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so.

Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Pick up and transfer to properly labeled containers.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling In case of rupture. Use personal protection equipment. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Do not breathe dust / fume / gas / mist / vapors / spray.

Conditions for safe storage, including any incompatibilities

Storage Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up.

Incompatible Products Strong acids. Strong oxidizing agents. Strong bases.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters**Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Lithium Cobalt Oxide (CoLiO ₂)	TWA: 0.02 mg/m ³	--	--

12190-79-3			
Graphite 7782-42-5	TWA: 2 mg/m ³ respirable fraction all forms except graphite fibers	TWA: 15 mg/m ³ total dust synthetic TWA: 5 mg/m ³ respirable fraction synthetic (vacated) TWA: 2.5 mg/m ³ respirable dust natural (vacated) TWA: 10 mg/m ³ total dust synthetic (vacated) TWA: 5 mg/m ³ respirable fraction synthetic TWA: 15 mppcf natural	IDLH: 1250 mg/m ³ TWA: 2.5 mg/m ³ respirable dust
Copper 7440-50-8	TWA: 0.2 mg/m ³ fume TWA: 1 mg/m ³ Cu dust and mist	TWA: 0.1 mg/m ³ fume TWA: 1 mg/m ³ dust and mist (vacated) TWA: 0.1 mg/m ³ Cu dust, fume, mist	IDLH: 100 mg/m ³ dust, fume and mist TWA: 1 mg/m ³ dust and mist TWA: 0.1 mg/m ³ fume
Aluminum 7429-90-5	TWA: 1 mg/m ³ respirable fraction	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 15 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 5 mg/m ³ Al Aluminum	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
Aluminum 7429-90-5	TWA: 1 mg/m ³ respirable fraction	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 15 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 5 mg/m ³ Al Aluminum	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value
 OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits Immediately
 Dangerous to Life or Health

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIOv.

OSHA, 965 F.2d 962 (11th Cir., 1992) See section 15 for national exposure control parameters

Appropriate engineering controls

Engineering Measures Showers
 Eyewash stations
 Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/Face Protection If splashes are likely to occur: Wear safety glasses with side shields (or goggles). None required for consumer use.

Skin and Body Protection Wear protective gloves and protective clothing. Long sleeved clothing. Impervious gloves.

Respiratory Protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Wash hands before breaks and immediately after handling the product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Physical	Solid containing liquid, Solid		
Appearance	Blue	Odor	None
Color	No information available	Odor Threshold	No information available

Property	Values	Remarks	Method
pH	No data available	None known	
Melting / freezing point	No data available	None known	
Boiling point / boiling range	No data available	None known	
Flash Point	No data available	None known	
Evaporation Rate	No data available	None known	
Flammability (solid, gas)	No data available	None known	
Flammability Limit in Air	No data available	None known	
Upper flammability limit	No data available	None known	
Lower flammability limit	No data available	None known	
Vapor pressure	No data available	None known	
Vapor density	No data available	None known	
Specific Gravity	No data available	None known	
Water Solubility	Insoluble in water	None known	
Solubility in other solvents	No data available	None known	
Partition coefficient: n-octanol/water	No data available	None known	

Autoignition temperature	No data available	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known
Explosive properties	No data available	
Oxidizing Properties	No data available	
Other Information		
Softening Point	No data available	
VOC Content (%)	No data available	
Particle Size	No data available	
Particle Size Distribution		

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

None known based on information supplied.

Incompatible materials

Strong acids. Strong oxidizing agents. Strong bases.

Hazardous Decomposition Products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information	Product does not present an acute toxicity hazard based on known or supplied information. In case of rupture.
Inhalation	Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract.
Eye Contact	Specific test data for the substance or mixture is not available. Expected to be an irritant based on components. Irritating to eyes. May cause redness, itching, and pain. May cause temporary eye irritation.
Skin Contact	Specific test data for the substance or mixture is not available. Expected to be an irritant based on components. Irritating to skin. Prolonged contact

may cause redness and irritation.

Ingestion

Specific test data for the substance or mixture is not available.

Ingestion may cause irritation to mucous membranes.

Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Graphite 7782-42-5	> 10000 mg/kg (Rat)	-	-

Information on toxicological effects**Symptoms**

Erythema (skin redness). May cause redness and tearing of the eyes.

Delayed and immediate effects as well as chronic effects from short and long-term exposure**Sensitization**

No information available.

Mutagenic Effects

No information available.

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Lithium Cobalt Oxide (CoLiO ₂) 12190-79-3	A3	Group 2B		X

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive Toxicity

Contains a known or suspected reproductive toxin.

STOT - single exposure

No information available.

STOT - repeated exposure

Causes damage to organs through prolonged or repeated exposure. Based on classification criteria from the OSHA Hazard Communication Standard, this product has been determined to cause systemic target organ toxicity from chronic or repeated exposure. (STOT RE).

Chronic Toxicity

Contains a known or suspected carcinogen. Contains a known or suspected reproductive toxin. Possible risk of irreversible effects. Avoid repeated exposure. Prolonged exposure may cause chronic effects. May cause adverse liver effects.

Target Organ Effects

Respiratory system. Eyes. Skin. Reproductive System. Central Vascular System (CVS). Kidney. Liver. Bone marrow. Endocrine system. Lungs. Spleen.

Aspiration Hazard

No information available.

Numerical measures of toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)

23,232.00 mg/kg

ATEmix

(dermal)

16,077.00 mg/kg

(ATE)

ATEmix (inhalation-dust/mist)

142.00 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

Very toxic to aquatic life with long lasting effects.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Copper 7440-50-8	96h EC50: 0.031 - 0.054 mg/L (Pseudokirchneriella subcapitata) 72h EC50: 0.0426 - 0.0535 mg/L (Pseudokirchneriella subcapitata)	96h LC50: 0.0068 - 0.0156 mg/L (Pimephales promelas) 96h LC50:= 0.112 mg/L (Poecilia reticulata) 96h LC50: = 0.3 mg/L (Cyprinus carpio) 96h LC50: = 0.8 mg/L (Cyprinus carpio) 96h LC50: = 1.25 mg/L (Lepomis macrochirus) 96h LC50: = 0.052 mg/L (Oncorhynchus mykiss) 96h LC50: = 0.2 mg/L (Pimephales promelas) 96h LC50: < 0.3 mg/L (Pimephales promelas)		48h EC50: = 0.03 mg/L

Persistence and Degradability

No information available.

Bioaccumulation

No information available.

Other adverse effects

No information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal methods Should not be released into the environment.

Contaminated Packaging Dispose of contents/containers in accordance with local regulations.

California Hazardous Waste Codes 141

This product contains one or more substances that are listed with the State of California as a hazardous waste

Chemical Name	California Hazardous Waste
Lithium Cobalt Oxide (CoLiO ₂)	Toxic
Copper	Toxic
Aluminum foil	Ignitable powder
Aluminum	Ignitable powder

14. TRANSPORT INFORMATION

Note:

According to PACKING INSTRUCTION 965 ~ 967 of IATA DGR 60th Edition for transportation, the special provision 188 of IMDG (inc Amdt 38-16). The batteries should be securely packed and protected against short-circuits. Examine whether the package of the containers are integrate and tighten closed before transport. Take in a cargo of them without falling, dropping, and breakage. Prevent collapse of cargo piles. Don't put the goods together with oxidizer and chief food chemicals. The transport vehicle and ship must be cleaned and sterilized otherwise it is not allowed to assemble articles. During transport, the vehicle should prevent exposure, rain and high temperature. For stopovers, the vehicle should be away from fire and heat sources. When transported by sea, the assemble place should keep away from bedroom and kitchen, and isolated from the engine room, power and fire source. Under the condition of Road Transportation, the driver should drive in accordance with regulated route, don't stop over in the residential area and congested area. Forbid to use wooden, cement for bulk transport.

UN number

3480 & 3481

UN Proper shipping name

LITHIUM ION BATTERIES (including lithium ion polymer batteries) or; LITHIUM ION BATTERIES CONTAINED IN EQUIPMENT or LITHIUM ION BATTERIES PACKED WITH EQUIPMENT (including lithium ion polymer batteries)

Transport hazard class(es)

9

Packing group (if applicable)

II or IB

Marine pollutant (Yes/No)

Not regulated

Transport in bulk (according to

No information available.

**Annex II of MARPOL 73/78 and
the IBC Code)**

Special precautions

No information available.

Transport fashion

By air, by sea, by railway, by road.

15. REGULATORY INFORMATION

OSHA hazard communication standard

_____ Hazardous

_____ **V** _____ Non-hazardous

16. OTHER INFORMATION

Preparation and revision information

Prepared By

Shenzhen Powercome Electronics Co., Ltd.
Building 10, Shi'ao Second Industrial Zone, No.8, Langqin Road, Shi'ao,
Dalang Village, Longhua Area, Shenzhen, Guangdong, China

Date of this revision

2019-09-07

Abbreviations and acronyms

TSCA:	Toxic Substances Control Act, The American chemical inventory.
DSL	Domestic Substances List
EINECS:	European Inventory of Existing Commercial chemical Substances
ECL	Existing Chemicals List, the Korean chemical inventory.
IECSC	Inventory of existing chemical substances in China.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet