

Date of Issue: 15.01.2010 Date of Review: 27.06.2019

Version 7.0 Replace Version 6.0

Section 1: Identification of the Substance or Preparation and company

1.1 Trade name:

1.2 Producer/supplier: Einhell Germany AG; Wiesenweg 22; 94405 Landau / Isar

Tel: + 49 9951 959 20-66 (Information, emergency call) Fax: + 49 9951 942 410 843

E-Mail: Sicherheitsdatenblatt@Einhell.com

Application: Rechargeable Lithium Ion battery pack

Section 2: Hazards Identification

- 2.1 Classification of the substance or mixture according Regulation (EC) No. 1272/2008 (CLP): The product does not have to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.
- 2.2 Labelling (Regulation (EC) No. 1272/2008)

Hazard pictograms: ---

Signal word: none

Hazard description: Not applicable.

Precautionary statements: P102: Keep out of reach of children.

2.3 Information concerning particular hazards for human and environment:

In the event of exposure to internal contents by opened or injured battery: contact with internal contents causes burns to skin, eyes and mucous membranes. May cause sensitisation by skin contact.

Section 3: Composition/information on ingredients

3.1 Chemical characterization (preparation): Battery pack with Lithium metal oxide.

3.2	Composition	Name of Component	CAS-No.	%
	Cath a da.	Lithium-Cobalt Oxide (active material)	12190-79-3	<30%
	Cathode:	Polyvinyldiene Fluoride (binder)	24937-79-9	<10%
		Graphite (conductive material)	7782-42-5	
	Anode:	Carbon (active material)	1333-86-4	<30%
		Polyvinyldiene Fluoride (binder)	24937-79-9	<10%
	Electrolyte:	Organic Solvent	21324-40-3	<20%
	Electroryte.	Lithium Salt	554-13-2	<2%

The battery should not be opened, heated above 120° C or burned since the exposition with the ingredients could be harmful under certain conditions. The product contains neither metallic lithium nor lithium alloy.

Section 4: First Aid Measures

4.1 General information: The batteries are hermetically closed. A risk of exposure can only occur when the

cells are mechanically abused. The following first aid measures therefore only refer to the handling in the case of release of the ingredients and not on the use of the

battery under normal conditions.



Date of Issue: 15.01.2010 Date of Review: 27.06.2019

Version 7.0 Replace Version 6.0

4.2	Skin contact:	Immediately remove contaminated clothing. Wash skin with water and soap and rinse thoroughly. Consult a doctor if skin irritation persists.
4.3	Eye contact:	Rinse the open eye thoroughly with running water for at least 15 minutes. Rest eyes for 30 minutes. If redness, burning, blurred vision or swelling persists, transport to the nearest medical facility for additional treatment.
4.4	Ingestion:	Do not induce vomiting. Supply fresh air. Call for medical help immediately.
4.5	Inhalation:	Supply fresh air; consult doctor in case of complaints. In case of unconsciousness place patient stably in side position for transportation.

Section 5: Fire Fighting Measures

5.1	Suitable extinguishing media:	Fire extinguisher class D, CO ₂ , powder or water s	pray.
5.1	Suitable extinguishing media:	Fire extinguisher class D, CO ₂ , powder or wate	ır S

5.2 Unsuitable extinguishing media Water with full jet.

5.3 Special exposure hazards arising from the substance or preparation itself, its combustion products or from resulting gases:

Hydrogen fluoride (HF). In case of fire, toxic pyrolysis products can be released. Bursting batteries can be forcibly projected from a fire.

5.4 Special protective equipment for firefighters: Fire fighting measures, rescue works and clearance works with impact of the smouldering fire fumes or fire gases should

only be carried out with suitable respiratory protective

equipment.

Section 6: Accidental Release Measures

6.1	Person-related safety precautions:	Use personal protective clothing. Avoid skin contact. Keep away

from ignition sources.

6.2 Measures for environmental **Do not allow to enter sewers / surface or ground water.**

protection:

6.3 Measures for cleaning/absorption: Absorb with liquid-binding material (sand, diatomite, acid binders,

universal binders, sawdust). Dispose contaminated material as waste

according to item 13.

Section 7: Handling and Storage

7.1	Handling:	Follow Manufactures recommendations regarding maximum recommended currents and
		operating temperature range. Use for charge and discharge only the recommended
		equipment. Do not allow conductive material to touch the battery terminals. A dangerous
		short-circuit may occur and cause battery failure and fire. Do not open or disassemble
		hatteries. Do not throw hatteries into fire

No special measures necessary if handled and stored appropriately.

7.2 Storage: Store in well ventilated cool areas. Avoid overheating, e.g. through incident solar

radiation. Protect from air humidity and water. Do not short-circuit. Storage temperature

below 60° C.

7.3 Storage Keep away from flammable, oxidizing or acidic materials.

conditions:



Date of Issue: 15.01.2010 Date of Review: 27.06.2019

Version 7.0 Replace Version 6.0

Section 8: Exposure Controls and Personal Protection

8.1 Additional information about design of technical facilities: No further data; see item 7.

8.2 Ingredients with limit values that require monitoring at the workplace:

WEL: not applicable

8.3 Personal protective equipment:

Respiratory protection: Not required if used according to specifications. In case of fire fumes

use respiratory protection with A2B2-filters or self-contained

respiratory protective device.

Protection of hands: In the event of leakage: Wear protective gloves (chemical resistant), e.g.

nitrile rubber or butyl rubber. The protective gloves to be used must comply with the specifications of EC directive 89/656/EEC and the resultant standard EN 374. Penetration time of glove material: the exact break trough time has to be found out by the manufacturer of the

protective gloves and has to be observed.

Eye protection: Tightly sealed goggles.

Others: ---

General protective and hygienic

measures:

Keep away from foodstuffs, beverages and feed. Use skin protective cream. Do not eat, drink, smoke or take snuff while working. Wash

hands before eating, drinking, smoking and using the toilet.

Section 9: Physical and Chemical Properties

Compact battery pack with plastic shell. The product neither contains metallic lithium nor lithium alloys.

Section 10: Stability and Reactivity

10.1 Conditions to be avoided: At temperatures over 70° C risk of bursting and withdrawal

of electrolyte liquid exists. When cell is exposed to an external short-cicuit, it will cause heat generation and ignition. Do not allow conductive material to touch the

battery terminals.

10.2 Dangerous reactions: Reactions of the electrolyte and the electrodes with water

and humidity possible.

10.3 Dangerous decomposition products: None if handled and stored appropriately. In case of fire

toxic fumes can be released.

Section 11: Toxicological Information

Acute toxicity: No risk if handled reasonable. In case of damages or improper use irritant or

sensitizing ingredients may get released.

Section 12: Ecological Information

12.1 General notes: Ecological dates are not available. Do not allow product or ingredients to reach

ground water, water course or sewage system. No negative ecologic effects are

expected, if the product is used and disposed regularly.



Date of Issue: 15.01.2010 Date of Review: 27.06.2019

Version 7.0 Replace Version 6.0

Section 13: Disposal Considerations

Product: According to official regulations. Batteries have to be collected separately from

other wastes. Avoid short-circuits during collecting or string. If damages occur,

batteries have to be packed solitary in a plastic bag.

Admit to an approved disposal system. Use only approved containers for the

collection. EWC: 16 06 05 (other batteries an accumulators).

Section 14: Transport Information

Entry in AWB:

The batteries fulfils the requirements to part III, sub-section 38.3 of the UN Manual of Tests and Criteria.

Applies to Lithium-Ion Battery Pack contained in equipment:

	Class 9	UN 3481
14.1	Transport by road (ADR/RID/GGVSEB):	The product complies with the requirements of special provision 188 of the ADR / RID and is exempt from compliance with the other provisions of ADR / RID.
		Handle with care. Danger of ignition if the shipping item is damaged. If the package is damaged: Check and repack if necessary.
		Labeling of packages obligatory if the volume limits of SV 188 are exceeded.
14.2	Transport by ship (IMDG-Code):	The product complies with the requirements of special provision 188 of the IMDG Code and is exempted from the application of the remaining provisions of the IMDG Code, subject to compliance with the described quantity limits.
		Labeling of packages obligatory if the volume limits of SV 188 are exceeded.
14.3	Air transport (ICAO/IATA):	Limit per package: PAX A/C = 5 kg; CAO = 5 kg
		Labeling of packages obligatory if more than 2 batteries per package resp. more than 2 packages are shipped.
	Proper Shipping Name:	LITHIUM ION BATTERIES CONTAINED IN EQUIPMENT or LITHIUM ION BATTERIES PACKED WITH EQUIPMENT



LITHIUM ION BATTERIES in compliance with Section II of PI 966





Date of Issue: 15.01.2010 Date of Review: 27.06.2019

Version 7.0 Replace Version 6.0

Applies to Lithium-Ion Battery - single packed und shipped:

UN 3480 Classe 9

The product complies with the requirements of special provision 188 of the 14.1 Transport by road ADR / RID and is exempt from compliance with the other provisions of ADR / (ADR/RID/GGVSEB):

Handle with care. Danger of ignition if the shipping item is damaged. If the

package is damaged: Check and repack if necessary.

Labeling of packages obligatory if the volume limits of SV 188 are exceeded.

The product complies with the requirements of special provision 188 of the 14.2 Transport by ship IMDG Code and is exempted from the application of the remaining provisions (IMDG-Code): of the IMDG Code, subject to compliance with the described quantity limits.

Labeling of packages obligatory if the volume limits of SV 188 are exceeded.

14.3 Air transport (ICAO/IATA):

> **LITHIUM ION BATTERIES** Proper Shipping Name:

not more than 1 package: max. 2 batteries per package Section II

PAX: forbidden

CAO: max. 1 package, max. 2 batteries





Entry in AWB: LITHIUM ION BATTERIES in compliance with Section II of PI 965

if more than 2 batteries or more than one package Section IB

PAX: forbidden

CAO: max. net weight per package: 10 kg









Date of Issue: 15.01.2010 Date of Review: 27.06.2019

Version 7.0 Replace Version 6.0

Section 15: Regulatory Information

15.1 Safety, health and environmental regulation / legislation specific for the substance or mixture:

2002/96/EC – Directive 2002/96/EC of the European Parliament and of the Council "waste electrical and electronic equipment (WEEE)"

2002/95/EC – Directive 2002/95/EC of the European Parliament and of the Council "Restriction of Hazardous Substances (ROHS)"

2006/66/EC - Directive 2006/66/EC of the European Parliament and of the Council of 6 September 2006 on batteries and accumulators and waste batteries and accumulators repealing 91/157/EEC

Classification according to German Betriebssicherheitsverordnung (BetrSichV): ---Further regulations, restrictions and prohibitions:

Substances of very high concern, according REACH, Article 57: None.

15.2 Chemical Safety Assessment: Not applicable

Section 16: Other Information

Data do not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities. The information describes exclusively the safety requirements for the product and is based on the present level of our knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. The delivery specifications are contained in the corresponding product sheet.

A vertical bar (I) in the left margin indicates an amendment from the previous version.