

MSDS

MATERIAL SAFETY DATA SHEET

Goods Name

: Lithium ion Battery Pack

Model Name

: YN-18650-3.7V-2400MAH

Applicant

: Guangzhou Yunnen NEW Energy Co., LTD

Report Number : KS2101S0418B04

Issue Date

: January 18, 2021

Written by:

Approved by:

KSIGN(Guangdong

Co., Ltd.

Page 1 of 10



Report No.: KS2101S0418B04

* The MSDS is prepared based on the information provided by client. The contents and formats of this MSDS are revised as per client's request.

1. IDENTIFICATION

Product identifier

Product Name Lithium ion Battery Pack (Model: YN-18650-3.7V-2400MAH)

Other means of identification

Product description Rating: 3.7Vd.c., 2400mAh, 8.88Wh

Weight: appr. 76.6g

Dimensions: Max.: 18.5×36.6×66.3 (mm)

Trademark

Recommended use of the chemical and restrictions on use

LITHIUM ION BATTERIES Recommended Use

Restrictions on use No information available

Details of the supplier of the Material safety data sheet

Initial supplier identifier Guangzhou Yunnen NEW Energy Co., LTD

Address No.401, Block 2 No.22, Dongxing Road, Chadong Village, Dalong Street, Panyu

District, Guangzhou

Telephone +86-20-39021990

Website http://www.yuneng.com/

E-mail 122129599@qq.com

Emergency telephone number

Company Emergency Phone

Number

+86-20-39021990

2. HAZARDS IDENTIFICATION

Classification LITHIUM ION BATTERIES

Acute toxicity - Dermal	Category 4	
Skin corrosion/irritation	Category 1 Sub-category B	
Serious eye damage/eye irritation	Category 1	
Skin sensitization	Category 1	
Carcinogenicity	Category 1B	
Specific target organ toxicity (repeated exposure)	Category 1	

KSB TRF No. MSDS R2 KSIGN(Guangdong) Testing Co., Ltd. West Side of 1/F., Building C, Zone A, Fuyuan New Factory, Jiujiu Industrial Park, Minzhu, Shatou, Shajing, Bao'an District, Shenzhen, Page 2 of 10



Report No.: KS2101S0418B04

GHS Label elements, including precautionary statements

Signal Word: Danger

Hazard Label







Hazard statements

This is a battery. In case of rupture:. Harmful in contact with skin Causes severe skin burns and eye damage May cause an allergic skin reaction

May cause cancer

Causes damage to organs through prolonged or repeated exposure

Classification according to GHS

Substances and mixtures which, in contact with water, emit flammable gases (2, 3) Specific target organ toxicity, repeated exposure (1) (respiratory system)

H261 in contact with water releases flammable gas

H372 causes damage to organs through prolonged or repeated exposure (respiratory system)

CAS# 7440-50-8

Classification according to GHS

Sensitisation, skin(1, 1A, 1B)

Specific target organ toxicity, single exposure (1)(digestive system)

Specific target organ toxicity, single exposure; Respiratory tract irritation(3)

H317 May cause an allergic skin reaction

H370 causes damage to organs (digestive system)

H335 May cause respiratory irritation

Precautionary Statements - Prevention CAS#7429-90-5

P223 Do not allow contact with water.

P231+ P232 Handle and store contents under inert gas, protect from moisture.

P280 wear protective gloves, protective clothing, eye protection and face protection.

P260 Do not breathe dust.

P264 wash skin and clothing thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

CAS# 7440-50-8

P260 Do not breathe dust, fume.

P272 contaminated work clothing should not be allowed out of the workplace.

P280 wear protective gloves, eye protection, face protection.

P264 wash skin and clothing thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 use only outdoors or in a well-ventilated area.

Precautionary Statements - Response CAS#7429-90-5

P302+ P335+ P334IFON SKIN: Brush off loose particles from skin and immerse in cool water.

P370+ P378 in case of fire: use the appropriate media put out the fire.

P314 Get medical advice if you feel unwell.

KSIGN(Guangdong) Testing Co., Ltd.

KSB TRF No. MSDS R2



Report No.: KS2101S0418B04

CAS# 7440-50-8

P302+ P352 IF ON SKIN: wash with plenty water.

P333 +P313 if skin irritation or rash occurs: Get medical advice.

P321 specific treatment (see additional emergency instructions).

P362+ P364 Take off contaminated clothing and wash it before reuse

P308+ P311 IF exposed or concerned: call a POISON CENTER.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 call a POISON CENTER if you feel unwell.

Immediately call a POISON CENTER or doctor

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

Skin

Call a POISON CENTER or doctor if you feel unwell Take off contaminated clothing and wash it before reuse IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower] If skin irritation or rash occurs: Get medical advice/attention

IF INHALED: Remove person to fresh air and keep comfortable for breathing Immediately call a POISON CENTER or doctor

Ingestion

IF SWALLOWED: Rinse mouth. DO NOT induce vomiting

Precautionary Statements - Storage

Wash contaminated clothing before reuse

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other information

May be harmful if swallowed Very toxic to aquatic life Very toxic to aquatic life with long lasting effects

KSIGN(Guangdong) Testing Co., Ltd.

KSB TRF No. MSDS R2



Report No.: KS2101S0418B04

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance

Not applicable.

Mixture

Chemical name	CAS No.	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
Lithium Cobalt Oxide (CoLiO2)	12190-79-3	15 - 40		- 30
Copper	7440-50-8	11 - 31		- Marie Co
Graphite	7782-42-5	10 - 27	-	V
Ethylene carbonate	96-49-1	10 - 31	-	\$5c -
Phosphate(1-), hexafluoro-, lithium	21324-40-3	5 - 16	-	<u> </u>
Aluminum foil	7429-90-5	3 - 10	-/32	<u>-</u>

4. FIRST AID MEASURES

Description of first aid measures

General advice First aid is upon rupture of sealed battery. Show this Material safety data sheet to the doctor in attendance. Immediate medical attention is required. IF exposed or

concerned: Get medical advice/attention.

Inhalation Remove to fresh air. If breathing has stopped, give artificial respiration. Get

medical attention immediately. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If breathing is difficult, (trained personnel should) give oxygen. Delayed pulmonary

edema may occur.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15

> minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical

advice/attention.

Wash off immediately with soap and plenty of water while removing all Skin contact

contaminated clothes and shoes. Get immediate medical advice/attention. May

cause an allergic skin reaction.

Ingestion Do NOT induce vomiting. Clean mouth with water and drink afterwards plenty of

water. Never give anything by mouth to an unconscious person. Get immediate

medical advice/attention.

Self-protection of the first aider Ensure that medical personnel are aware of the material(s) involved, take

precautions to protect themselves and prevent spread of contamination. Wear personal protective clothing (see section 8). Avoid contact with skin, eyes or clothing. Avoid direct contact with skin. Use barrier to give mouth-to-mouth

KSIGN(Guangdong) Testing Co., Ltd.

KSB TRF No. MSDS R2



Report No.: KS2101S0418B04

resuscitation.

Most important symptoms and effects, both acute and delayed

Symptoms Burning sensation. Itching. Rashes. Hives.

Indication of any immediate medical attention and special treatment needed

Product is a corrosive material. Use of gastric lavage or emesis is Note to physicians

> contraindicated. Possible perforation of stomach or esophagus should be investigated. Do not give chemical antidotes. Asphyxia from glottal edema may occur. Marked decrease in blood pressure may occur with moist rales, frothy sputum, and high pulse pressure. May cause sensitization in susceptible persons.

Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media Use extinguishing measures that are appropriate to local circumstances and the

surrounding environment.

Large Fire CAUTION: Use of water spray when fighting fire may be inefficient.

Unsuitable extinguishing media Do not scatter spilled material with high pressure water streams.

Specific hazards arising from the The product causes burns of eyes, skin and mucous membranes. Thermal

chemical

decomposition can lead to release of irritating gases and vapors. Product is or contains a sensitizer. May cause sensitization by skin contact.

Hazardous Combustion

Products

Carbon oxides.

Explosion Data

Sensitivity to Mechanical

Impact

Sensitivity to Static

Discharge

None. None.

Special protective equipment for Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment. fire-fighters

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use

personal protective equipment as required. Attention! Corrosive material. Evacuate

personnel to safe areas. Keep people away from and upwind of spill/leak.

Other Information Refer to protective measures listed in Sections 7 and 8.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Pick up and transfer to properly labeled containers.

KSIGN(Guangdong) Testing Co., Ltd.

KSB TRF No. MSDS R2



Report No.: KS2101S0418B04

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling

In case of rupture: Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Handle product only in closed system or provide appropriate exhaust ventilation. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Protect from moisture. Keep out of the reach of children. Store away from other materials.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls

Use local exhaust ventilation or other engineering controls to control sources of

dust, mist, fumes and vapor.

Keep away from heat and open flame. Store in a cool, dry place.

Respiratory Protection: Not necessary under normal conditions.

Skin and body Protection: Not necessary under normal conditions, Wear suitable

protective clothing and gloves if handling an open or leaking battery.

Hand protection: Wear suitable gloves if handling an open or leaking battery. Eye Protection: Not necessary under normal conditions, Wear safety glasses if

handling an open or leaking battery.

Other Protective Equipment

Personal Protective Equipment

Have a safety shower and eye wash fountain readily available in the immediate

work area.

Hygiene Measures

Do not eat, drink, or smoke in work area. Maintain good housekeeping.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Solid Blue **Appearance**

Odor No information available No information available Color **Odor Threshold** No information available

Property Values Remarks Method No data available None known No data available Melting / freezing point None known Boiling point / boiling range No data available None known Flash Point No data available None known **Evaporation Rate** No data available None known No data available Flammability (solid, gas) None known Flammability Limit in Air None known **Upper flammability limit** No data available No data available Lower flammability limit Vapor pressure No data available None known Vapor density No data available None known Relative density No data available None known **Water Solubility** Insoluble in water

KSIGN(Guangdong) Testing Co., Ltd.

KSB TRF No. MSDS R2



Report No.: KS2101S0418B04

Solubility(ies) Partition coefficient:

n-octanol/water

Autoignition temperature **Decomposition temperature** Kinematic viscosity **Dynamic viscosity**

No data available

N/A

None known

No data available No data available No data available No data available

None known None known None known None known

Other Information

Explosive properties No information available. Oxidizing properties No information available. **Softening Point** No information available Molecular Weight No information available **VOC Content (%)** No information available **Liquid Density** No information available **Bulk Density** No information available **Particle Size** No information available **Particle Size Distribution** No information available

10. STABILITY AND REACTIVITY

Reactivity No information available.

Chemical stability Stable under normal conditions.

Possibility of Hazardous

Reactions

None under normal processing.

Hazardous Polymerization Hazardous polymerization does not occur.

Conditions to avoid Exposure to air or moisture over prolonged periods.

Incompatible materials Acids. Bases. Oxidizing agent.

Hazardous Decomposition

Products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Risk of irritation occurs only if the cell is mechanically, thermally or electrically Irritation abused to the point of compromising the enclosure. If this occurs, irritation to the

skin, eyes and respiratory tract may occur.

Sensitization Not Available **Neurological Effects** Not Available **Teratogenicity** Not Available **Reproductive Toxicity** Not Available Mutagenicity (Genetic Effects) Not Available **Toxicologically Synergistic**

Materials

Not Available

KSB TRF No. MSDS R2 KSIGN(Guangdong) Testing Co., Ltd. West Side of 1/F., Building C, Zone A, Fuyuan New Factory, Jiujiu Industrial Park, Minzhu, Shatou, Shajing, Bao'an District, Shenzhen, Guangdong, China

Page 8 of 10



Report No.: KS2101S0418B04

12. ECOLOGICAL INFORMATION

Ecological Toxicity Not Available

Mobility in soil Not Available

Persistence and Degradability Not Available

Bioaccumulation potential Not Available

Other Adverse Effects Not Available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste from residues/unused

products

Dispose of in accordance with local regulations. Dispose of waste in accordance

with environmental legislation.

Contaminated packaging Do not reuse empty containers.

14. TRANSPORT INFORMATION

UN Number -DOT, IMDG, IATA

UN 3480 & UN 3481

Transport information

Lithium ion Battery Pack (Sample Model: YN-18650-3.7V-2400MAH) is tested and has passed in accordance with UN manual of Tests and Criteria, Part III,

subsection 38.3.

The goods shall be complied with the requirements of Section II~IB of Packing Instruction 965 or of Section II of Packing Instruction 966 & 967 of 62nd DGR

Manual of IATA or IMDG CODE (Amdt. 39-18).

Separate Lithium-ion batteries when shipping to prevent short-circuiting. They should be packed in strong packaging for support during transport, ensure that the goods will not falling, dropping, and breakage, prevent collapse of cargo piles and wet by rain.

Lithium batteries shipped as "Lithium batteries", "Lithium batteries packed with equipment", or "Lithium batteries contained in equipment" may not be classified as "Dangerous Goods" when shipped in accordance with "special provision A45 of IATA-DGR" or "special provision 188 of IMO-IMDG Code".

Proper Shipping Name

Lithium ion Batteries (Including lithium ion polymer batteries) or;

Lithium ion Batteries packed with equipment (Including lithium ion polymer

batteries) or:

Lithium ion Batteries contained in equipment (Including lithium ion polymer

batteries)

TDG

Not regulated

DOT

Hazard Class Emergency Response Guide 147

Number

MEX

Not regulated

KSIGN(Guangdong) Testing Co., Ltd.

KSB TRF No. MSDS R2



Report No.: KS2101S0418B04

Not regulated ICAO

IATA

Hazard Class 9

IMDG/IMO

Hazard Class EmS-No. F-A, S-I

RID Not regulated

ADR Not regulated

ADN Not regulated

15. REGULATORY INFORMATION

Law information

《Dangerous Goods Regulations》

《Recommendation on the Transport of Dangerous Goods Model Regulations》

《International Maritime Dangerous Goods》

《Technical Instructions for the Safe Transport of Dangerous Goods》

《Classification and code of dangerous Goods》

《Occupational Safety and Health Act》(OSHA)

《Toxic Substance Control Act》(TSCA)

《Consumer Product Safety Act》(CPSA)

《Federal Environmental Pollution Control Act》(FEPCA)

《The Oil Pollution Act》(OPA)

《Superfund Amendments and Reauthorization Act Title III (302/311/312/313)》(SARA)

《Resource Conservation and Recovery Act》(RCRA)

《Safety Drinking Water Act》(CWA)

《California Proposition 65》

《Code of Federal Regulations》(CFR)

In according with all Federal, State and local laws.

16. OTHER INFORMATION

NFPA Health hazards 1 Flammability 0 Instability 0 Physical and **Chemical Properties**

HMIS Health hazards 0 Flammability 0 Physical hazards 0 **Personal Protection**

Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Material Safety Data Sheet

KSIGN(Guangdong) Testing Co., Ltd.

KSB TRF No. MSDS R2