

SAFETY DATA SHEET

Issuing Date No data available

Revision Date 09-Oct-2019

Revision Number 1

NGHS / English



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is ©2014 UL LLC. All rights reserved.

1. IDENTIFICATION

Product identifier

Product Name AHB421133PA-03 Li-ion Rechargeable battery by SYNergy

Other means of identification

Product Code(s) 1545514

Recommended use of the chemical and restrictions on use

Recommended Use LITHIUM ION BATTERIES

Restrictions on use No information available

Details of the supplier of the safety data sheet

Supplier Identification Synergy

Address 7F, No9, Park Avenue II,
Science-based Industrial Park
HsinChu
N/A
30075
TW

Telephone Phone:886-3-5643700
Fax:886-3-5646767

E-mail stellah0917@gmail.com

Emergency telephone number

Company Emergency Phone Number 886-911254622

2. HAZARDS IDENTIFICATION

Classification

Acute toxicity - Dermal	Category 3
Acute toxicity - Inhalation (Gases)	Category 4
Skin corrosion/irritation	Category 2



Serious eye damage/eye irritation	Category 2A
Skin sensitization	Category 1
Carcinogenicity	Category 1B
Specific target organ toxicity (repeated exposure)	Category 1

This is a battery. In case of rupture: the above hazards exist.

Appearance Solid

Physical state Solid

Odor No information available

GHS Label elements, including precautionary statements

Danger

Hazard statements

Toxic in contact with skin

Harmful if inhaled

Causes skin irritation

Causes serious eye irritation

May cause an allergic skin reaction

May cause cancer

Causes damage to organs through prolonged or repeated exposure



Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Wear protective gloves/protective clothing/eye protection/face protection

Use only outdoors or in a well-ventilated area

Wash face, hands and any exposed skin thoroughly after handling

Contaminated work clothing must not be allowed out of the workplace

Do not breathe dust/fume/gas/mist/vapors/spray

Do not eat, drink or smoke when using this product

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

Specific treatment (see supplemental first aid instructions on this label)

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

Skin

IF ON SKIN: Wash with plenty of water and soap

Call a POISON CENTER or doctor if you feel unwell

Take off immediately all contaminated clothing and wash it before reuse

If skin irritation or rash occurs: Get medical advice/attention

Wash contaminated clothing before reuse

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other information

May be harmful if swallowed. Very toxic to aquatic life with long lasting effects.

Unknown acute toxicity 90.01 % of the mixture consists of ingredient(s) of unknown toxicity
62.55 % of the mixture consists of ingredient(s) of unknown acute oral toxicity
88.19 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity
90.01 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)
90.01 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)
90.01 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance

Not applicable.

Mixture

Chemical name	CAS No.	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
Lithium Cobalt Oxide (CoLiO ₂)	12190-79-3	32.62	-	-
Carbon black	1333-86-4	16.96	-	-
Aluminum	7429-90-5	14.6	-	-
Copper	7440-50-8	7.87	-	-
Phosphate(1-), hexafluoro-, lithium	21324-40-3	1.82	-	-
Nickel	7440-02-0	0.6	-	-
Propylene imine	75-55-8	0.1	-	-

4. FIRST AID MEASURES

Description of first aid measures

General advice

First aid is upon rupture of sealed battery. Show this safety data sheet to the doctor in attendance. Immediate medical attention is required. IF exposed or concerned: Get medical advice/attention.

Inhalation

Remove to fresh air. Get medical attention immediately if symptoms occur. If breathing has stopped, give artificial respiration. Get medical attention immediately. If symptoms persist, call a physician.

Eye contact

Get immediate medical advice/attention. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Remove contact lenses, if present and easy to do. Continue rinsing. Do not rub affected area.

Skin contact

Get immediate medical advice/attention. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. May cause an allergic skin reaction.

Ingestion

Do NOT induce vomiting. Clean mouth with water and drink afterwards plenty of water.



Never give anything by mouth to an unconscious person. Get immediate medical advice/attention.

Self-protection of the first aider Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Avoid contact with skin, eyes or clothing. Avoid breathing dust/fume/gas/mist/vapors/spray. Use personal protective equipment as required. See section 8 for more information.

Most important symptoms and effects, both acute and delayed

Symptoms Itching. Rashes. Hives. Burning sensation. Coughing and/ or wheezing. Difficulty in breathing.

Indication of any immediate medical attention and special treatment needed

Note to physicians May cause sensitization in susceptible persons. Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Large Fire CAUTION: Use of water spray when fighting fire may be inefficient.

Unsuitable extinguishing media Do not scatter spilled material with high pressure water streams.

Specific hazards arising from the chemical Product is or contains a sensitizer. May cause sensitization by skin contact.

Hazardous Combustion Products Carbon oxides.

Explosion Data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge None.

Special protective equipment for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Avoid generation of dust. Do not breathe dust.

Other Information Refer to protective measures listed in Sections 7 and 8.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Pick up and transfer to properly labeled containers.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling

In case of rupture. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Take off contaminated clothing and wash before reuse. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid generation of dust.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Keep out of the reach of children.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Limits

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH	
Lithium Cobalt Oxide (CoLiO2) 12190-79-3	TWA: 0.02 mg/m³	-		
Carbon black 1333-86-4	TWA: 3 mg/m³ inhalable particulate matter	TWA: 3.5 mg/m³ (vacated) TWA: 3.5 mg/m³	IDLH: 1750 mg/m³ TWA: 3.5 mg/m³ TWA: 0.1 mg/m³ Carbon black in presence of Polycyclic aromatic hydrocarbons PAH	
Aluminum 7429-90-5	TWA: 1 mg/m³ respirable particulate matter	TWA: 15 mg/m³ total dust TWA: 5 mg/m³ respirable fraction (vacated) TWA: 15 mg/m³ total dust (vacated) TWA: 5 mg/m³ respirable fraction	TWA: 10 mg/m³ total dust TWA: 5 mg/m³ respirable dust	
Copper 7440-50-8	TWA: 0.2 mg/m³ fume	TWA: 0.1 mg/m³ fume TWA: 1 mg/m³ dust and mist (vacated) TWA: 0.1 mg/m³ Cu dust, fume, mist	IDLH: 100 mg/m³ dust, fume and mist TWA: 1 mg/m³ dust and mist TWA: 0.1 mg/m³ fume	
Phosphate(1-), hexafluoro-, lithium 21324-40-3	TWA: 2.5 mg/m³ F	TWA: 2.5 mg/m³ F (vacated) TWA: 2.5 mg/m³	IDLH: 250 mg/m³ F	
Nickel 7440-02-0	TWA: 1.5 mg/m³	TWA: 1 mg/m³ (vacated) TWA: 1 mg/m³	IDLH: 10 mg/m³ TWA: 0.015 mg/m³	
Propylene imine 75-55-8	STEL: 0.4 ppm TWA: 0.2 ppm S*	TWA: 2 ppm TWA: 5 mg/m³ (vacated) TWA: 2 ppm (vacated) TWA: 5 mg/m³ (vacated) S* S*	IDLH: 100 ppm TWA: 2 ppm TWA: 5 mg/m³	
Chemical name	Alberta	British Columbia	Ontario TWA/EV	Quebec
Lithium Cobalt Oxide (CoLiO2)	TWA: 0.02 mg/m³	TWA: 0.02 mg/m³	TWA: 0.02 mg/m³	TWA: 0.02 mg/m³

12190-79-3				
Carbon black 1333-86-4	TWA: 3.5 mg/m ³	TWA: 3 mg/m ³	TWA: 3 mg/m ³	TWA: 3.5 mg/m ³
Aluminum 7429-90-5	TWA: 10 mg/m ³	TWA: 1.0 mg/m ³	TWA: 1 mg/m ³	TWA: 10 mg/m ³
Copper 7440-50-8	TWA: 0.2 mg/m ³ TWA: 1 mg/m ³	TWA: 1 mg/m ³ TWA: 0.2 mg/m ³	TWA: 0.2 mg/m ³ TWA: 1 mg/m ³	TWA: 0.2 mg/m ³ TWA: 1 mg/m ³
Phosphate(1-), hexafluoro-, lithium 21324-40-3	TWA: 2.5 mg/m ³	TWA: 2.5 mg/m ³	TWA: 2.5 mg/m ³	TWA: 2.5 mg/m ³
Nickel 7440-02-0	TWA: 1.5 mg/m ³	TWA: 0.05 mg/m ³	TWA: 1 mg/m ³	TWA: 1 mg/m ³
Propylene imine 75-55-8	TWA: 2 ppm TWA: 4.7 mg/m ³ Skin	TWA: 2 ppm	TWA: 0.2 ppm STEL: 0.4 ppm Skin	TWA: 2 ppm TWA: 4.7 mg/m ³ Skin

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992). See section 15 for national exposure control parameters.

Appropriate engineering controls

Engineering controls

Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles).

Hand protection

Wear suitable gloves. Impervious gloves.

Skin and body protection

Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron.

Respiratory protection

No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

General hygiene considerations

Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Avoid breathing dust/fume/gas/mist/vapors/spray.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	Solid
Appearance	Solid
Odor	No information available
Color	No information available
Odor Threshold	No information available

Property	Values	Remarks	Method
pH	No data available	None known	
Melting / freezing point	No data available	None known	
Boiling point / boiling range	No data available	None known	
Flash Point	No data available	None known	



Evaporation Rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		None known
Upper flammability limit	No data available	
Lower flammability limit	No data available	
Vapor pressure	No data available	None known
Vapor density	No data available	None known
Relative density	No data available	None known
Water Solubility	Insoluble in water	
Solubility(ies)	No data available	None known
Partition coefficient: n-octanol/water	0	
Autoignition temperature	No data available	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known

Other Information

Explosive properties	No information available
Oxidizing properties	No information available
Softening Point	No information available
Molecular Weight	No information available
VOC Content (%)	No information available
Liquid Density	No information available
Bulk Density	No information available
Particle Size	No information available
Particle Size Distribution	No information available

10. STABILITY AND REACTIVITY

Reactivity	No information available.
Chemical stability	Stable under normal conditions.
Possibility of Hazardous Reactions	None under normal processing.
Hazardous Polymerization	Hazardous polymerization does not occur.
Conditions to avoid	Excessive heat.
Incompatible materials	Strong acids. Strong bases. Strong oxidizing agents.
Hazardous Decomposition Products	Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information	Product does not present an acute toxicity hazard based on known or supplied information In case of rupture:
Inhalation	Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract. Harmful by inhalation. (based on components).
Eye contact	Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components). Irritating to eyes.

Skin contact Specific test data for the substance or mixture is not available. May cause sensitization by skin contact. Causes skin irritation. (based on components). Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. Toxic in contact with skin.

Ingestion Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. May be harmful if swallowed.

Information on toxicological effects

Symptoms Itching. Rashes. Hives. Redness. May cause redness and tearing of the eyes. Coughing and/ or wheezing.

Numerical measures of toxicity

Acute Toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral)	3,797.50 mg/kg
ATEmix (dermal)	453.10 mg/kg
ATEmix (inhalation-gas)	9,991.00 ppm
ATEmix (inhalation-dust/mist)	5.01 mg/L
ATEmix (inhalation-vapor)	50.05 mg/L

Unknown acute toxicity 90.01 % of the mixture consists of ingredient(s) of unknown toxicity

62.55 % of the mixture consists of ingredient(s) of unknown acute oral toxicity

88.19 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity

90.01 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)

90.01 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)

90.01 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Lithium Cobalt Oxide (CoLiO ₂)	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rat)	> 5.05 mg/L (Rat) 4 h
Carbon black	> 15400 mg/kg (Rat)	> 3 g/kg (Rabbit)	-
Nickel	> 9000 mg/kg (Rat)	-	> 10.2 mg/L (Rat) 1 h
Propylene imine	= 19 mg/kg (Rat)	-	-

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. Irritating to skin.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

Respiratory or skin sensitization May cause sensitization by skin contact.

Germ cell mutagenicity No information available.

Carcinogenicity Contains a known or suspected carcinogen. Classification based on data available for ingredients. May cause cancer.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Lithium Cobalt Oxide (CoLiO ₂) 12190-79-3	A3	Group 2B	Reasonably Anticipated	X
Carbon black 1333-86-4	A3	Group 2B	-	X

Nickel 7440-02-0	-	Group 2B	Reasonably Anticipated	X
Propylene imine 75-55-8	A3	Group 2B	Reasonably Anticipated	X

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

NTP (National Toxicology Program)

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity	No information available.
STOT - single exposure	No information available.
STOT - repeated exposure	Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard	No information available.

12. ECOLOGICAL INFORMATION

Ecotoxicity Very toxic to aquatic life with long lasting effects.

Chemical name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Carbon black	-	-	-	24h EC50: > 5600 mg/L
Copper	72h EC50: 0.0426 - 0.0535 mg/L (Pseudokirchneriella subcapitata) 96h EC50: 0.031 - 0.054 mg/L (Pseudokirchneriella subcapitata)	96h LC50: = 0.052 mg/L (Oncorhynchus mykiss) 96h LC50: = 0.3 mg/L (Cyprinus carpio) 96h LC50: 0.0068 - 0.0156 mg/L (Pimephales promelas) 96h LC50: = 0.2 mg/L (Pimephales promelas) 96h LC50: = 0.8 mg/L (Cyprinus carpio) 96h LC50: = 0.112 mg/L (Poecilia reticulata) 96h LC50: = 1.25 mg/L (Lepomis macrochirus) 96h LC50: < 0.3 mg/L (Pimephales promelas)	-	48h EC50: = 0.03 mg/L
Nickel	96h EC50: 0.174 - 0.311 mg/L (Pseudokirchneriella subcapitata) 72h EC50: = 0.18 mg/L (Pseudokirchneriella subcapitata)	96h LC50: = 1.3 mg/L (Cyprinus carpio) 96h LC50: = 10.4 mg/L (Cyprinus carpio) 96h LC50: > 100 mg/L (Brachydanio rerio)	-	48h EC50: = 1 mg/L 48h EC50: > 100 mg/L

Persistence and Degradability	No information available.
Bioaccumulation	There is no data for this product.

Mobility No information available.

Other adverse effects No information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste from residues/unused products Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Do not reuse empty containers.

Chemical name	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
Propylene imine 75-55-8		P067		

California Waste Codes 141

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical name	California Hazardous Waste
Lithium Cobalt Oxide (CoLiO ₂) 12190-79-3	Toxic
Aluminum 7429-90-5	Ignitable powder
Copper 7440-50-8	Toxic
Nickel 7440-02-0	Toxic powder Ignitable powder

14. TRANSPORT INFORMATION

Note: The transportation of primary lithium cells and batteries is regulated by the International Civil Aviation Organization, International Air Transport Association, International Maritime Dangerous Goods Code and the US Department of Transportation. The batteries must meet the following criteria for shipment: 1. Air shipments must meet the requirements listed in Special Provision A45 of the International Air Transport Association Dangerous Goods Regulations. 2. Meet the requirements for the US Department of Transportation listed in 49 CFR 173.185. 3. The transport of primary lithium batteries is prohibited aboard passenger aircraft. Refer to the Federal Register December 15, 2004 (Hazardous Materials; Prohibited on the Transportation of Primary Lithium Batteries and Cells Aboard Passenger Aircraft; Final Rule) Lithium batteries shipped as "Lithium batteries", "Lithium batteries packed with equipment", or "Lithium batteries contained in equipment" may not be classified as "Dangerous Goods" when shipped in accordance with "special provision A45 of IATA-DGR" or "special provision 188 of IMO-IMDG Code"

DOT NOT REGULATED
Proper Shipping Name NON-REGULATED
Hazard Class N/A
Emergency Response Guide Number 147



<u>TDG</u>	Not regulated
<u>MEX</u>	Not regulated
<u>ICAO</u>	Not regulated
<u>IATA</u>	Not regulated
Proper Shipping Name	NON REGULATED
Hazard Class	N/A
<u>IMDG/IMO</u>	Not regulated
Hazard Class	N/A
EmS-No.	F-A, S-I
<u>RID</u>	Not regulated
<u>ADR</u>	Not regulated
<u>ADN</u>	Not regulated

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

International Inventories

TSCA	Contact supplier for inventory compliance status.
DSL/NDSL	Contact supplier for inventory compliance status.
EINECS/ELINCS	Contact supplier for inventory compliance status.
ENCS	Contact supplier for inventory compliance status.
KECL	Contact supplier for inventory compliance status.
PICCS	Contact supplier for inventory compliance status.
AICS	Contact supplier for inventory compliance status.

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
 DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
 EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
 ENCS - Japan Existing and New Chemical Substances
 KECL - Korean Existing and Evaluated Chemical Substances
 PICCS - Philippines Inventory of Chemicals and Chemical Substances
 AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	CAS No.	Weight-%	SARA 313 - Threshold
---------------	---------	----------	----------------------



			Values %
Lithium Cobalt Oxide (CoLiO ₂) - 12190-79-3	12190-79-3	32.62	0.1
Aluminum - 7429-90-5	7429-90-5	14.6	1.0
Copper - 7440-50-8	7440-50-8	7.87	1.0
Nickel - 7440-02-0	7440-02-0	0.6	0.1
Propylene imine - 75-55-8	75-55-8	0.1	0.1

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications. Under the amended regulations at 40 CFR 370, EPCRA 311/312 Tier II reporting for the 2017 calendar year will need to be consistent with updated hazard classifications.

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Copper 7440-50-8		X	X	
Nickel 7440-02-0		X	X	

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Copper 7440-50-8	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Nickel 7440-02-0	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
Propylene imine 75-55-8	1 lb	1 lb	RQ 1 lb final RQ RQ 0.454 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical name	California Proposition 65
Carbon black - 1333-86-4	Carcinogen
Nickel - 7440-02-0	carcinogen, 10/1/1989 (metallic)
Propylene imine - 75-55-8	carcinogen, 1/1/1988
1,3-Propane sultone - 1120-71-4	carcinogen, 1/1/1988

U.S. State Right-to-Know Regulations

This product may contain substances regulated by state right-to-know regulations.

Chemical name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Lithium Cobalt Oxide (CoLiO ₂) 12190-79-3	X		X	X	X
Carbon black 1333-86-4	X	X	X		X
Aluminum	X	X	X	X	



7429-90-5					
Copper 7440-50-8	X	X	X	X	X
Phosphate(1-), hexafluoro-, lithium 21324-40-3	X				
Nickel 7440-02-0	X	X	X	X	X
Propylene imine 75-55-8	X	X	X	X	X

16. OTHER INFORMATION

NFPA	Health hazards 1	Flammability 0	Instability 0	Physical and Chemical Properties -
HMIS	Health hazards 0	Flammability 0	Physical hazards 0	Personal Protection X

Prepared By Product Stewardship
23 British American Blvd.
Latham, NY 12110
1-800-572-6501

Revision Date 09-Oct-2019

Revision Note No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet