Cel>(pert Safety Data Sheet [29 CFR 1910.1200]

Safety Data Sheet

May be used to comply with OSHA's Hazard communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

US Department of Labor

Occupational Safety and Health Administration (Non-Mandatory Form) Form Approved OMB No.1218-0072

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME : Lithium Ion Rechargeable Battery Pack CUSTOMER : ASUS CUSTOMER P/N : 0B200-04370000 CPT P/N : 920100417 MODEL NAME : C31N2210 DESCRIPTION : 3S1P, CosMX 11.55V/4440mAh/52Wh

MANUFACTURER : Celxpert(KunShan)Energy Co., Ltd ADDRESS : NO.1111, Hanpu Road, Yushan Town, Kunshan City, Jiangsu Province, P.R. China TELEPHONE : +86-512-57775999#2532 FAX : +86-512-5777-3839

SECTION 2: HAZARDS IDENTIFICATION

PROTENTIAL HEALTH EFFECTS

PRIMARY ROUTES OF ENTRY Skin contact, Skin absorption, Eye contact, Inhalation, and Ingestion : NO

SYMPTOMS OF EXPOSURE

Skin contact

No effect under routine handling and use.

Skin absorption

No effect under routine handling and use.

Eye contact

No effect under routine handling and use.

Inhalation

No effect under routine handling and use.

SECTION 3: INGREDIENT

| Battery Cell | | |
|----------------------------------|-------|------------|
| HAZARDOUS INGREDIENTS | % | CAS NUMBER |
| Cobalt compound | 4-50 | 1307-96-6 |
| Styrene-Butadiene-Rubber | <1 | 27288-99-9 |
| Aluminum Foil | 2-10 | 7429-90-5 |
| Polyvinylidene Fluoride (PVDF) | <5 | 24937-79-9 |
| Copper Foil | 2-10 | 7440-50-8 |
| Carbon | 10-30 | 7440-44-0 |
| Electrolyte (Ethylene carbonate) | 10-20 | 96-49-1 |
| Lithium hexafluorophosphate | <5 | 21324-40-3 |
| Aluminium | <6 | 7459-90-5 |
| Nickel | <2 | 7440-02-0 |
| Polypropylene | <1 | 9003-07-0 |

| Circuit Module | | |
|-----------------------|-------|------------|
| HAZARDOUS INGREDIENTS | % | CAS NUMBER |
| Lead | 0.001 | 7439-92-1 |
| Mercury | 0 | 7439-97-6 |
| Chromium | 0 | 7440-47-3 |
| Cadmium | 0 | 7440-43-9 |
| Plastic case and Si2O | 0 | N/A |

Plastic Parts and Paints

| HAZARDOUS INGREDIENTS | % | CAS NUMBER |
|--------------------------|--------|------------|
| Lead | < 0.1 | 7439-92-1 |
| Nickle | < 0.01 | 7440-02-0 |
| CFCs | 0 | 75-69-4 |
| Polyclorinated Biphenyls | 0 | 1336-36-3 |

SECTION 4: FIRST AID MEASURES

INHALATION, EYE CONTACT, and SKIN CONTACT : Not a health hazard.

INGESTION

If swallowed, obtain medical attention immediately.

If exposure to internal materials within cell(pack) due to damaged outer casing, the Following actions are recommended.

INHALATION

Leave area immediately and seek medical attention.

EYE CONTACT

Rinse eyes with water for 15 minutes and seek medical attention.

SKIN CONTACT

Wash area thoroughly with soap and water and seek medical attention.

INGESTION

Drink milk/water and induce vomiting; seek medical attention.

SECTION 5: FIRE FIGHTING MEASURES

5.1 GENERAL HAZARD

Cell is not flammable but internal organic material will burn if the cell is incinerated. Combustion products include, but are not limited to hydrogen fluoride, carbon monoxide and carbon dioxide.

5.2 EXTINGUSHING MEDIA

Use extinguishing media suitable for the materials that are burning.

5.3 SPECIAL FIREFIGHTING INSTRUCTIONS

If possible, remove cell(s) from fire fighting area. If heated above 125°C, cell(s) can explode/vent.

5.4 FIREFIGHTING EQUIPMENT

Use NIOSH/MSHA approved full-face self-contained breathing apparatus (SCBA) with full protective gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 ON LAND

Place material into suitable containers and call local fire/police department.

6.2 IN WATER

If possible, remove from water and call local fire/police department.

SECTION 7: HANDLING AND STORAGE

7.1 HANDLING

No special protective clothing required for handling individual cells.

7.2 STORAGE

Store in a cool, dry place.

SECTION 8: EXPOSURE CONTROLS//PERSONAL PROTENTION

8.1 ENGINEERING CONTROLS

Keep away from heat and open flame. Store in a cool dry place.

8.2 PERSONAL PROTECTION

Respirator: Not required during normal operations. SCBA required in the event of a fire.

Eye/face protection: Not required beyond safety practices of employer.

Gloves: Not required for handling of cells.

Foot protection: Steel toed shoes recommended for large container handling.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

| Physical State : Solid | Boiling point : N/A |
|------------------------|---------------------------------|
| Odor : N/A | Solubility in water : Insoluble |
| PH : N/A | Specific gravity : N/A |
| Vapor pressure : N/A | Density : N/A |
| Vapor density : N/A | Flash Point:N/A |

SECTION 10: STABILITY AND REACTIVITY

10.1 REACTIVITY

None

10.2 INCOMPATIBILITIES

None during normal operation. Avoid exposure to heat, open flame, and corrosives.

10.3 HAZARDOUS DECOMPOSITION PRODUCTS

None during normal operating conditions. If cells are opened, hydrogen fluoride and carbon monoxide may be released.

10.4 CONDITIONS TO AVOID

Avoid exposure to heat and open flame. Do not puncture, crush or incinerate.

SECTION 11: TOXICOLOGICAL INFORMATION

This product does not elicit toxicological properties during routine handling and use.

Sensitization: NO Teratogenicity: NO Reproductive toxicity: NO Acute toxicity: NO

This product does not contain any kinds of the following substances and halogen-type flame retardants including Chlorine and Bromide type harmful flame retardants which are listed in Appendix of TCO documents and relevant international ECO requirements:

Polybromated Biphenyls (PBB) Polybromated Diphenylethers (PBDE) Polychlorinated Biphenyls (PCBs) Polychlorinated Terphenyls(PCTs) Polychlorinated Paphthalene(PCN) Chlorinated Paraffins(C10-C13) Chlorofluorocarbons(CFCs) Polyvinyl Chloride(PVC) Carbon Tetrachloride

None of the following substances will be exposed, leaked, or emitted during transportation, storage or any operation and any temperature condition:

Chlorinated Fluorohydrocarbon (FCKW)

Acrylonitride Styrol Phenol Benzol Mercury of greater than 0.0001 wt% for alkaline battery Mercury of greater than 0.0005 wt% for other battery Lithium content of greater than 0.5g/battery cell Cadmium, lead, and other harmful heavy metal

And will comply with the regulation of 49 CFR (DOT regulation), International Air Transport Association (IATA), and Deuche Forschungsgemeinschaft (DFG) regarding concentrations of emitted substances.

This product does not contain mercury and cadmium.

Mercury content: N/A

Cadmium content: N/A

If the cells are opened through misuse or damage, discard immediately. Internal components of cell are irritants and sensitizers.

SECTION 12: ECOLOGICAL INFORMATION

Some materials within the cell are bio-accumulative. Under normal conditions, these materials are contained and pose no risk to persons or the surrounding environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Disposal should be in accordance with local, state or national legislation.

SECTION 14: TRANSPORT INFORMATION

- The International Civil Aviation Organization (ICAO) Technical Instructions.
- The International Air Transport Association (IATA) Dangerous Goods Regulations (64th Edition, 2023). Packing instruction 965 Section IA、 IB for Lithium Ion battery. (When shipping batteries "packed with" or "contained in" equipment, use packing instruction 966 or 967 as appropriate).

- The International Maritime Dangerous Goods (IMDG) Code , 2020 Edition (Incorporating Amendment 40-20) with special provision 188 & 230.

- The UN Recommendations on the Transport of Dangerous Goods, Manual of Tests and Criteria 38.3 Lithium batteries, ST-SG-AC10-11-Rev7(UN3480).

SECTION 15: REGULATORY INFORMATION

OSHA hazard communication standard (29 CFR 1910.1200)

_Hazardous __V_ Non-hazardous

SECTION 16: OTHER INFORMATION

Package if damaged: do not load or transport. Celxpert contact window: Shannon Huang For more information,call: +886-3-4899054