SAFETY DATA SHEET

Issuing Date 08-Feb-2019

Revision Date 08-Feb-2019

Revision Number 2

NGHS / English



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

1. IDENTIFICATION

Product identifier	
Product Name	Rechargeable Li-Polymer Battery Pack AP18JHQ
Other means of identification	
Product Code(s)	1500523
Recommended use of the chemical	and restrictions on use
Recommended Use	LITHIUM ION BATTERIES
Restrictions on use	No information available
Details of the supplier of the safety	data sheet
Supplier Identification	Getac Technology Corp.
Address	5F, Building A, No. 209, Sec 1, Nangang Rd. Nangang Dist. Taipei Taiwan 11568 TW
Telephone	Phone:+886-2-27857888
E-mail	getacppbu@gmail.com
Emergency telephone number	
Company Emergency Phone Number	+886-919985359

2. HAZARDS IDENTIFICATION

Classification

Acute toxicity - Oral	Category 4
Acute toxicity - Dermal	Category 3
Skin corrosion/irritation	Category 1 Sub-category B
Serious eye damage/eye irritation	Category 1
Skin sensitization	Category 1



Carcinogenicity	Category 1B
Specific target organ toxicity (repeated exposure)	Category 1

This is a battery. In case of rupture: the above hazards exist.

Appearance No information available

Physical state Solid

Odor No information available

GHS Label elements, including precautionary statements

Danger

Hazard statements

Harmful if swallowed Toxic in contact with skin Causes severe skin burns and eye damage May cause an allergic skin reaction May cause cancer Causes damage to organs through prolonged or repeated exposure



Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood Wear protective gloves/protective clothing/eye protection/face protection Wash face, hands and any exposed skin thoroughly after handling Do not eat, drink or smoke when using this product Contaminated work clothing must not be allowed out of the workplace

Do not breathe dust/fume/gas/mist/vapors/spray

Precautionary Statements - Response

Specific treatment (see supplemental first aid instructions on this label)

Immediately call a POISON CENTER or doctor

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing Immediately call a POISON CENTER or doctor

Skin

Call a POISON CENTER or doctor if you feel unwell

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower

Wash contaminated clothing before reuse

If skin irritation or rash occurs: Get medical advice/attention

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing

Immediately call a POISON CENTER or doctor

Ingestion

IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell Rinse mouth Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up



Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other information

Very toxic to aquatic life with long lasting effects.

Unknown acute toxicity

99.4 % of the mixture consists of ingredient(s) of unknown toxicity 83.8 % of the mixture consists of ingredient(s) of unknown acute oral toxicity

86.3 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity

99.4 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)

99.4 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)

99.4 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance

Not applicable.

Mixture

Chemical name	CAS No.	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
Lithium Cobalt Oxide (CoLiO2)	12190-79-3	42.6	-	-
Graphite	7782-42-5	27.7	-	-
Phosphate(1-), hexafluoro-, lithium	21324-40-3	13.1	-	-
Copper	7440-50-8	9.1	-	-
Aluminum foil	7429-90-5	4.4	-	-
Nickel	7440-02-0	0.3	-	-

4. FIRST AID MEASURES

First aid measures

General advice	First aid is upon rupture of sealed battery. Show this safety data sheet to the doctor in attendance. Immediate medical attention is required. IF exposed or concerned: Get medical advice/attention.
Inhalation	Remove to fresh air. If breathing has stopped, give artificial respiration. Get medical attention immediately. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If breathing is difficult, (trained personnel should) give oxygen. Delayed pulmonary edema may occur. Get immediate medical advice/attention.
Eye contact	Get immediate medical advice/attention. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing.
Skin contact	Get immediate medical advice/attention. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. May cause an allergic skin reaction.



Ingestion	Do NOT induce vomiting. Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Get immediate medical advice/attention.	
Self-protection of the first aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Wear personal protective clothing (see section 8). Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Avoid contact with skin, eyes or clothing.	
Most important symptoms and effe	cts, both acute and delayed	
Symptoms	Burning sensation. Itching. Rashes. Hives.	
Indication of any immediate medica	I attention and special treatment needed	
Note to physicians	Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Do not give chemical antidotes. Asphyxia from glottal edema may occur. Marked decrease in blood pressure may occur with moist rales, frothy sputum, and high pulse pressure. May cause sensitization in susceptible persons. Treat symptomatically.	

5. FIRE-FIGHTING MEASURES				
Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.			
Large Fire	CAUTION: Use of water spray when fighting fire may be inefficient.			
Unsuitable extinguishing media	Do not scatter spilled material with high pressure water streams.			
Specific hazards arising from the chemical	The product causes burns of eyes, skin and mucous membranes. Thermal decomposition can lead to release of irritating gases and vapors. Product is or contains a sensitizer. May cause sensitization by skin contact.			
Hazardous Combustion Products	Carbon oxides.			
Explosion Data Sensitivity to Mechanical Impac Sensitivity to Static Discharge	ct None. None.			
Special protective equipment for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.			

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions	Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Attention! Corrosive material. Keep people away from and upwind of spill/leak.			
Other Information	Refer to protective measures listed in Sections 7 and 8.			
Methods and material for containment and cleaning up_				

Methods for containment Prev

Methods for cleaning up

Prevent further leakage or spillage if safe to do so.

cleaning up Pick up and transfer to properly labeled containers.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling In case of rupture: Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Take off contaminated clothing and wash before reuse. In case of insufficient ventilation, wear suitable respiratory equipment. Handle product only in closed system or provide appropriate exhaust ventilation. Do not eat, drink or smoke when using this product.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Keep out of the reach of children. Store locked up. Protect from moisture. Store away from other materials.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Limits

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Lithium Cobalt Oxide (CoLiO2) 12190-79-3	TWA: 0.02 mg/m ³	-	
Graphite 7782-42-5	TWA: 2 mg/m ³ respirable particulate matter all forms except graphite fibers	TWA: 15 mg/m ³ total dust synthetic TWA: 5 mg/m ³ respirable fraction synthetic (vacated) TWA: 2.5 mg/m ³ respirable dust natural (vacated) TWA: 10 mg/m ³ total dust synthetic (vacated) TWA: 5 mg/m ³ respirable fraction synthetic TWA: 15 mppcf natural	IDLH: 1250 mg/m ³ TWA: 2.5 mg/m ³ respirable dust
Phosphate(1-), hexafluoro-, lithium 21324-40-3	TWA: 2.5 mg/m ³ F	TWA: 2.5 mg/m ³ F (vacated) TWA: 2.5 mg/m ³	IDLH: 250 mg/m ³ F
Copper 7440-50-8	TWA: 0.2 mg/m³ fume	TWA: 0.1 mg/m ³ fume TWA: 1 mg/m ³ dust and mist (vacated) TWA: 0.1 mg/m ³ Cu dust, fume, mist	IDLH: 100 mg/m ³ dust, fume and mist TWA: 1 mg/m ³ dust and mist TWA: 0.1 mg/m ³ fume
Aluminum foil 7429-90-5	TWA: 1 mg/m ³ respirable particulate matter	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 15 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m³ total dust TWA: 5 mg/m³ respirable dust



Nickel 7440-02-0		TWA: 1.5 m	ıg/m ³	TWA: 1 mg/m ³ (vacated) TWA: 1 mg/m ³		IDLH: 10 mg/m ³ TWA: 0.015 mg/m ³	
Chemical name		Alberta	British C	olumbia	Ontario TWAEV		Quebec
Lithium Cobalt Oxide (CoLiO2) 12190-79-3	Tν	VA: 0.02 mg/m ³	TWA: 0.02 mg/m ³		TWA: 0.02 mg/m ³		TWA: 0.02 mg/m ³
Graphite 7782-42-5]	FWA: 2 mg/m³	TWA: 2	: mg/m³	TWA: 2 mg/m	3	TWA: 2 mg/m ³
Phosphate(1-), hexafluoro-, lithium 21324-40-3	T	WA: 2.5 mg/m ³	TWA: 2.5 mg/m ³		TWA: 2.5 mg/n	n ³	TWA: 2.5 mg/m ³
Copper 7440-50-8		WA: 0.2 mg/m³ ГWA: 1 mg/m³		mg/m³ 2 mg/m³	TWA: 0.2 mg/n TWA: 1 mg/m		TWA: 0.2 mg/m ³ TWA: 1 mg/m ³
Aluminum foil 7429-90-5	TWA:	10 mg/m ³ TWA: 5 mg/m ³	TWA: 1.	0 mg/m ³	TWA: 1 mg/m	3	TWA: 10 mg/m ³ TWA: 5 mg/m ³
Nickel 7440-02-0	T	WA: 1.5 mg/m ³	TWA: 0.0)5 mg/m ³	TWA: 1 mg/m	3	TWA: 1 mg/m ³

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering controls	Showers
	Eyewash stations
	Ventilation systems.

Individual protection measures, such as personal protective equipment Eye/face protection Face protection shield. Hand protection Wear suitable gloves. Impervious gloves. Skin and body protection Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron. No protective equipment is needed under normal use conditions. If exposure limits are **Respiratory protection** exceeded or irritation is experienced, ventilation and evacuation may be required. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with **General hygiene considerations** skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Contaminated work clothing should not be allowed out of the workplace.

Physical and Chemical Properties Physical state Appearance Odor Color Odor Threshold	Solid No information available No information available No information available No information available	
<u>Property</u>	<u>Values</u>	<u>Remarks Method</u>
pH	No data available	None known
Melting / freezing point	No data available	None known

Boiling point / boiling range	No data available	None known
Flash Point	No data available	None known
Evaporation Rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		None known
Upper flammability limit	No data available	
Lower flammability limit	No data available	
Vapor pressure	No data available	None known
Vapor density	No data available	None known
Relative density	No data available	None known
Water Solubility	Insoluble in water	
Solubility(ies)	No data available	None known
Partition coefficient: n-octanol/wat	ter0	
Autoignition temperature	No data available	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known
Other Information		
Explosive properties	No information available	
Oxidizing properties	No information available	
Softening Point	No information available	
Molecular Weight	No information available	
VOC Content (%)	No information available	
Liquid Density	No information available	
Bulk Density	No information available	
Particle Size	No information available	
Particle Size Distribution	No information available	

10. STABILITY AND REACTIVITY

Reactivity	No information available.
Chemical stability	Stable under normal conditions.
Possibility of Hazardous Reactions	None under normal processing.
Hazardous Polymerization	Hazardous polymerization does not occur.
Conditions to avoid	Exposure to air or moisture over prolonged periods.
Incompatible materials	Acids. Bases. Oxidizing agent.

Hazardous Decomposition Products Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information	Product does not present an acute toxicity hazard based on known or supplied information In case of rupture:
Inhalation	Specific test data for the substance or mixture is not available. Corrosive by inhalation. (based on components). Inhalation of corrosive fumes/gases may cause coughing, choking, headache, dizziness, and weakness for several hours. Pulmonary edema may occur with tightness in the chest, shortness of breath, bluish skin, decreased blood pressure, and

	increased heart rate. Inhaled corrosive substances can lead to a toxic edema of the lungs. Pulmonary edema can be fatal.
Eye contact	Specific test data for the substance or mixture is not available. Causes burns. (based on components). Corrosive to the eyes and may cause severe damage including blindness. Causes serious eye damage. May cause irreversible damage to eyes.
Skin contact	Specific test data for the substance or mixture is not available. Corrosive. (based on components). Causes burns. May cause sensitization by skin contact. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. Toxic in contact with skin.
Ingestion	Specific test data for the substance or mixture is not available. Causes burns. (based on components). Ingestion causes burns of the upper digestive and respiratory tracts. May cause severe burning pain in the mouth and stomach with vomiting and diarrhea of dark blood. Blood pressure may decrease. Brownish or yellowish stains may be seen around the mouth. Swelling of the throat may cause shortness of breath and choking. May cause lung damage if swallowed. May be fatal if swallowed and enters airways.

Information on toxicological effects

Symptoms Redness. Burning. May cause blindness. Coughing and/ or wheezing. Itching. Rashes. Hives.

Numerical measures of toxicity

Acute Toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral)	611.00 mg/kg
ATEmix (dermal)	313.70 mg/kg

Unknown acute toxicity

99.4 % of the mixture consists of ingredient(s) of unknown toxicity

83.8 % of the mixture consists of ingredient(s) of unknown acute oral toxicity

86.3 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity

99.4 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)

99.4 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)

99.4 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Nickel	> 9000 mg/kg (Rat)	-	> 10.2 mg/L (Rat)1 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	Classification based on data available for ingredients. Causes burns.
Serious eye damage/eye irritation	Classification based on data available for ingredients. Risk of serious damage to eyes. Causes burns.
Respiratory or skin sensitization	May cause sensitization by skin contact.
Germ cell mutagenicity	No information available.
Carcinogenicity	Contains a known or suspected carcinogen. Classification based on data available for ingredients. May cause cancer.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Lithium Cobalt Oxide	A3	Group 2B	Reasonably Anticipated	Х
(CoLiO2)				
12190-79-3				
Nickel	-	Group 2B	Reasonably Anticipated	Х
7440-02-0				
Legend				

ACGIH (American Conference of Governmental Industrial Hygienists) A3 - Animal Carcinogen IARC (International Agency for Research on Cancer) Group 2B - Possibly Carcinogenic to Humans NTP (National Toxicology Program) Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen OSHA (Occupational Safety and Health Administration of the US Department of Labor) X - Present **Reproductive toxicity** No information available. No information available. STOT - single exposure **STOT - repeated exposure** Causes damage to organs through prolonged or repeated exposure. No information available. Aspiration hazard

12. ECOLOGICAL INFORMATION

Ecotoxicity

Very toxic to aquatic life with long lasting effects.

Chemical name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Copper	96h EC50: 0.031 - 0.054 mg/L (Pseudokirchneriella subcapitata) 72h EC50: 0.0426 - 0.0535 mg/L (Pseudokirchneriella subcapitata)	96h LC50: 0.0068 - 0.0156 mg/L (Pimephales promelas) 96h LC50: < 0.3 mg/L (Pimephales promelas) 96h LC50: = 0.2 mg/L (Pimephales promelas) 96h LC50: = 0.3 mg/L (Cyprinus carpio) 96h LC50: = 0.052 mg/L (Oncorhynchus mykiss) 96h LC50: = 1.25 mg/L (Lepomis macrochirus) 96h LC50: = 0.112 mg/L (Poecilia reticulata) 96h LC50: = 0.8 mg/L (Cyprinus carpio)	-	48h EC50: = 0.03 mg/L
Nickel	72h EC50: = 0.18 mg/L (Pseudokirchneriella subcapitata) 96h EC50: 0.174 - 0.311 mg/L (Pseudokirchneriella subcapitata)	96h LC50: = 1.3 mg/L (Cyprinus carpio) 96h LC50: = 10.4 mg/L (Cyprinus carpio) 96h LC50: > 100 mg/L (Brachydanio rerio)	-	48h EC50: > 100 mg/L 48h EC50: = 1 mg/L

Persistence and Degradability

No information available.

Bioaccumulation	There is no data for this product.
Mobility	No information available.
Other adverse effects	No information available.
	13. DISPOSAL CONSIDERATIONS
Waste treatment methods	
Waste from residues/unused products	Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.
Contaminated packaging	Do not reuse empty containers.
California Waste Codes	141

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical name	California Hazardous Waste
Lithium Cobalt Oxide (CoLiO2)	Toxic
12190-79-3	
Copper	Toxic
7440-50-8	
Aluminum foil	Ignitable powder
7429-90-5	
Nickel	Toxic powder
7440-02-0	Ignitable powder

14. TRANSPORT INFORMATION

Note: DOT Proper Shipping Name Hazard Class Emergency Response Guide Number	The transportation of primary lithium cells and batteries is regulated by the International Civil Aviation Organization, International Air Transport Association, International Maritime Dangerous Goods Code and the US Department of Transportation. The batteries must meet the following criteria for shipment: 1. Air shipments must meet the requirements listed in Special Provision A45 of the International Air Transport Association Dangerous Goods Regulations. 2. Meet the requirements for the US Department of Transportation listed in 49 CFR 173.185. 3. The transport of primary lithium batteries is prohibited aboard passenger aircraft. Refer to the Federal Register December 15, 2004 (Hazardous Materials; Prohibited on the Transportation of Primary Lithium Batteries and Cells Aboard Passenger Aircraft; Final Rule) Lithium batteries shipped as "Lithium batteries", "Lithium batteries packed with equipment", or "Lithium batteries contained in equipment" may not be classified as "Dangerous Goods" when shipped in accordance with "special provision A45 of IATA-DGR" or "special provision 188 of IMO-IMDG Code"
TDG	Not regulated
<u>MEX</u>	Not regulated

ICAO	Not regulated
IATA Proper Shipping Name Hazard Class	Not regulated NON REGULATED N/A
IMDG/IMO Hazard Class EmS-No.	Not regulated N/A F-A, S-I
<u>RID</u>	Not regulated
ADR	Not regulated
ADN	Not regulated

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Regulations

Ozone-depleting substances (ODS) Not applicable

Persistent Organic Pollutants Not applicable

Export Notification requirements Not applicable

International Inventories

TSCA	Contact supplier for inventory compliance status.
DSL/NDSL	Contact supplier for inventory compliance status.
EINECS/ELINCS	Contact supplier for inventory compliance status.
ENCS	Contact supplier for inventory compliance status.
KECL	Contact supplier for inventory compliance status.
PICCS	Contact supplier for inventory compliance status.
AICS	Contact supplier for inventory compliance status.

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

<u>SARA 313</u>

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	CAS No.	Weight-%	SARA 313 - Threshold Values %
Lithium Cobalt Oxide (CoLiO2) - 12190-79-3	12190-79-3	42.6	0.1
Copper - 7440-50-8	7440-50-8	9.1	1.0
Aluminum foil - 7429-90-5	7429-90-5	4.4	1.0



Nickel - 7440-02-0 7440-02-0	0.3	0.1

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications. Under the amended regulations at 40 CFR 370, EPCRA 311/312 Tier II reporting for the 2017 calendar year will need to be consistent with updated hazard classifications.

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Copper 7440-50-8		Х	Х	
Nickel 7440-02-0		Х	Х	

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Copper 7440-50-8	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Aluminum foil 7429-90-5			
Nickel 7440-02-0	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical name	California Proposition 65			
Nickel - 7440-02-0	carcinogen, 10/1/1989 (metallic)			

U.S. State Right-to-Know Regulations

This product may contain substances regulated by state right-to-know regulations.

Chemical name	New Jersey	Massachusett	Pennsylvania	Rhode Island	Illinois
		S			
Lithium Cobalt Oxide (CoLiO2) 12190-79-3	X		Х	Х	Х
Graphite 7782-42-5	X	X	Х		
Phosphate(1-), hexafluoro-, lithium 21324-40-3	X				
Copper 7440-50-8	X	X	Х	Х	Х
Aluminum foil 7429-90-5	X	X	Х	Х	
Nickel 7440-02-0	X	X	Х	Х	Х



16. OTHER INFORMATION					
NFPA	Health hazards 1	Flammability 0	Instability 0	Physical and Chemical Properties -	
HMIS	Health hazards 0	Flammability 0	Physical hazards 0	Personal Protection X	
Prepared By	Product Stewardship 23 British American Blvd. Latham, NY 12110 1-800-572-6501				
Issuing Date	08-Feb-2019				
Revision Date	08-Feb-2019				
Revision Note	No information available				

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet