SAFETY DATA SHEET

Issuing Date 20-Dec-2021

Revision Date 20-Dec-2021

Revision Number 1

NGHS / English

(UL)

The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

1. IDENTIFICATION

Product identifier

Product Name Rechargeable Li-ion Battery L21B3PE0 - by BYD

Other means of identification

Product Code(s) 1674141

Recommended use of the chemical and restrictions on use

Recommended Use Lithium Ion Battery

Restrictions on use No information available

Details of the supplier of the safety data sheet

Supplier Identification Lenovo LNB laptops

Address Songtao Road 696

shanghai shanghai 201203 CN

Telephone Phone:18116118603

E-mail yuanbb1@lenovo.com

Emergency telephone number

Company Emergency Phone

Number

18116118603

2. HAZARDS IDENTIFICATION

Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Skin sensitization	Category 1
Carcinogenicity	Category 1B



Specific target organ toxicity (repeated exposure)

Category 1

This is a battery. In case of rupture: the above hazards exist.

Appearance Solid Physical state Solid

Odor No information available

GHS Label elements, including precautionary statements

Danger

Hazard statements

Causes skin irritation
Causes serious eye irritation
May cause an allergic skin reaction
May cause cancer

Causes damage to organs through prolonged or repeated exposure



Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Wear protective gloves/protective clothing/eye protection/face protection

Wash face, hands and any exposed skin thoroughly after handling

Contaminated work clothing must not be allowed out of the workplace

Do not breathe dust/fume/gas/mist/vapors/spray

Do not eat, drink or smoke when using this product

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

Specific treatment (see supplemental first aid instructions on this label)

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

Skin

IF ON SKIN: Wash with plenty of water and soap

Take off contaminated clothing and wash it before reuse

If skin irritation or rash occurs: Get medical advice/attention

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other information

Very toxic to aquatic life with long lasting effects.

Unknown acute toxicity 28.61 % of the mixture consists of ingredient(s) of unknown toxicity

1.34 % of the mixture consists of ingredient(s) of unknown acute oral toxicity



Page 2/13

28.61 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity

28.61 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)

28.61 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)

28.61 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance

Not applicable.

Mixture

Chemical name	CAS No	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
Lithium Cobalt Oxide (CoLiO2)	12190-79-3	45.5	-	-
Copper	7440-50-8	7.31	-	-
Aluminum	7429-90-5	3.9	-	-
Propylene carbonate	108-32-7	3.47	-	-
Phosphate(1-), hexafluoro-, lithium	21324-40-3	1.86	-	-
Ethylene carbonate	96-49-1	1.76	-	-
Propyl propionate	106-36-5	1.02	-	-
Ci 77266	1333-86-4	0.46	-	-
Nickel	7440-02-0	0.38	-	-

4. FIRST AID MEASURES

Description of first aid measures

Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get General advice

medical advice/attention. First aid is upon rupture of sealed battery.

Remove to fresh air. Get medical attention immediately if symptoms occur. Inhalation

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep

> eye wide open while rinsing. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists. Do not rub affected area.

May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a Skin contact

physician. Wash off immediately with soap and plenty of water for at least 15 minutes.

Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth Ingestion

to an unconscious person. Do NOT induce vomiting. Call a physician.

Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see section 8). Self-protection of the first aider

Most important symptoms and effects, both acute and delayed

Symptoms Itching. Rashes. Hives. Burning sensation.

Indication of any immediate medical attention and special treatment needed



Page 3 / 13

Note to physicians May cause sensitization in susceptible persons. Treat symptomatically.

5. FIRE-FIGHTING MEASURES

surrounding environment.

Large Fire CAUTION: Use of water spray when fighting fire may be inefficient.

Unsuitable extinguishing media Do not scatter spilled material with high pressure water streams.

Specific hazards arising from the

chemical

Product is or contains a sensitizer. May cause sensitization by skin contact.

Hazardous Combustion Products Carbon oxides.

Explosion Data

Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

Special protective equipment for

fire-fighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout

gear. Use personal protection equipment.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions In case of rupture: Avoid contact with skin, eyes or clothing. Ensure adequate ventilation.

Use personal protective equipment as required. Evacuate personnel to safe areas. Keep

people away from and upwind of spill/leak.

Other Information Refer to protective measures listed in Sections 7 and 8.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Pick up and transfer to properly labeled containers.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. In case of rupture:

Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this

product. Take off contaminated clothing and wash before reuse.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up.

Keep out of the reach of children.



8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Limits

The following ingredients are the only ingredients of the product above the cut-off level (or level that contributes to the hazard classification of the mixture) which have an exposure limit applicable in the region for which this safety data sheet is intended or other recommended limit. At this time, the other relevant constituents have no known exposure limits from the sources listed here.

Chemical name		ACGIH T	LV	03	SHA PEL		NIOSH IDLH
Lithium Cobalt Oxide (CoLiC 12190-79-3	2)	TWA: 0.02 mg/m ³			-		
Copper 7440-50-8		TWA: 0.2 mg/n	n ³ fume	TWA: 1 mg/ (vacated) T	1 mg/m³ fume /m³ dust and mist WA: 0.1 mg/m³ Cu , fume, mist	TWA:	I: 100 mg/m³ dust, fume and mist : 1 mg/m³ dust and mist VA: 0.1 mg/m³ fume
Aluminum		TWA: 1 mg/m ³ ı	respirable		ng/m³ total dust		A: 10 mg/m³ total dust
7429-90-5		particulate r		TWA: 5 m (vacated) TV (vacated)	ng/m³ respirable fraction VA: 15 mg/m³ total dust) TWA: 5 mg/m³		5 mg/m ³ respirable dust
Phosphate(1-), hexafluoro-		TWA: 2.5 mg	a/m³ ⊏		able fraction 2.5 mg/m ³ F		IDLH: 250 mg/m ³ F
lithium 21324-40-3	,	i VVA: 2.5 mį	g/m³ F		7.5 mg/m ³ F TWA: 2.5 mg/m ³		IDLH: 250 mg/m³ F
Ci 77266		TWA: 3 mg/m ³			: 3.5 mg/m ³		IDLH: 1750 mg/m ³
1333-86-4		particulate r	natter	(vacated)	TWA: 3.5 mg/m ³	in	TWA: 3.5 mg/m³ : 0.1 mg/m³ Carbon black presence of Polycyclic natic hydrocarbons PAH
Nickel 7440-02-0		TWA: 1.5 m	ng/m³		A: 1 mg/m³) TWA: 1 mg/m³		IDLH: 10 mg/m ³ TWA: 0.015 mg/m ³
Chemical name		Alberta	British C	Columbia	Ontario TWAE	V	Quebec
Lithium Cobalt Oxide (CoLiO2) 12190-79-3	TV	VA: 0.02 mg/m ³		D2 mg/m ³	TWA: 0.02 mg/		TWA: 0.02 mg/m ³
Copper 7440-50-8		WA: 0.2 mg/m ³ WA: 1 mg/m ³		mg/m³ 2 mg/m³	TWA: 0.2 mg/r TWA: 1 mg/m		TWA: 0.2 mg/m ³ TWA: 1 mg/m ³
Aluminum 7429-90-5		WA: 10 mg/m ³		0 mg/m ³	TWA: 1 mg/m		TWA: 10 mg/m ³
Phosphate(1-), hexafluoro-, lithium 21324-40-3	T	WA: 2.5 mg/m ³		5 mg/m³	TWA: 2.5 mg/r	n ³	TWA: 2.5 mg/m ³
Ci 77266 1333-86-4	T	WA: 3.5 mg/m ³	TWA: 3	3 mg/m³	TWA: 3 mg/m	3	TWA: 3 mg/m ³
Nickel 7440-02-0	T	WA: 1.5 mg/m ³	TWA: 0.0	05 mg/m³	TWA: 1 mg/m	3	TWA: 1.5 mg/m ³

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992). See section 15 for national exposure control parameters.

Appropriate engineering controls



Page 5/13

Engineering controls Showers

> Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Hand protection Wear suitable gloves. Impervious gloves.

Skin and body protection Wear suitable protective clothing. Long sleeved clothing.

Respiratory protection No protective equipment is needed under normal use conditions. If exposure limits are

exceeded or irritation is experienced, ventilation and evacuation may be required.

General hygiene considerations Do not eat, drink or smoke when using this product. Wash hands before breaks and

> immediately after handling the product. Wear suitable gloves and eye/face protection. Avoid contact with skin, eyes or clothing. Handle in accordance with good industrial hygiene and

safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Solid **Appearance** Solid

Odor No information available Color No information available **Odor Threshold** No information available

Remarks Method Property Values

No data available None known pН Melting / freezing point No data available None known Boiling point / boiling range No data available None known Flash Point No data available None known No data available **Evaporation Rate** None known Flammability (solid, gas) No data available None known Flammability Limit in Air None known

Upper flammability limit No data available Lower flammability limit No data available

No data available Vapor pressure None known Vapor density No data available None known Relative density No data available None known

Water Solubility Insoluble in water Solubility(ies) No data available

None known

Partition coefficient: n-octanol/water1

Autoignition temperature No data available None known **Decomposition temperature** No data available None known Kinematic viscosity No data available None known No data available Dynamic viscosity None known

Other Information

No information available **Explosive properties** No information available **Oxidizing properties Softening Point** No information available No information available **Molecular Weight** No information available **VOC Content (%) Liquid Density** No information available



Bulk Density

No information available
Particle Size

No information available
No information available
No information available

Particle Size Distribution No information available

10. STABILITY AND REACTIVITY

Reactivity No information available.

Chemical stability Stable under normal conditions.

Possibility of Hazardous Reactions None under normal processing.

Hazardous Polymerization Hazardous polymerization does not occur.

Conditions to avoid None known based on information supplied.

Incompatible materials Strong acids. Strong bases. Strong oxidizing agents.

Hazardous Decomposition Products Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information Product does not present an acute toxicity hazard based on known or supplied information.

In case of rupture:

Inhalation Specific test data for the substance or mixture is not available. May cause irritation of

respiratory tract. (based on components).

Eye contact Specific test data for the substance or mixture is not available. Irritating to eyes. (based on

components). Causes serious eye irritation.

Skin contact May cause sensitization by skin contact. Specific test data for the substance or mixture is

not available. Repeated or prolonged skin contact may cause allergic reactions with

susceptible persons. (based on components). Causes skin irritation.

Ingestion Specific test data for the substance or mixture is not available. Ingestion may cause

gastrointestinal irritation, nausea, vomiting and diarrhea. (based on components).

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Itching. Rashes. Hives. Redness. May cause redness and tearing of the eyes.

Numerical measures of toxicity

Acute toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 21,195.80 mg/kg
ATEmix (dermal) 11,397.00 mg/kg
ATEmix (inhalation-dust/mist) 105.00 mg/L
ATEmix (inhalation-vapor) 769.90 mg/L

Unknown acute toxicity 28.61 % of the mixture consists of ingredient(s) of unknown toxicity

1.34 % of the mixture consists of ingredient(s) of unknown acute oral toxicity



Page 7/13

28.61 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity

28.61 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)

28.61 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)

28.61 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

Product Information

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Lithium Cobalt Oxide (CoLiO2)	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rat)	> 5.05 mg/L (Rat) 4 h
Copper	-	-	> 5.11 mg/L (Rat) 4 h
Aluminum	-	-	> 0.888 mg/L (Rat) 4 h
Propylene carbonate	= 29000 mg/kg (Rat)	> 3000 mg/kg (Rabbit)	-
Ethylene carbonate	= 10 g/kg (Rat)	> 26420 mg/kg (Rabbit)	> 730 mg/m³ (Rat) 8 h
Propyl propionate	= 10331 mg/kg (Rat)	= 16 mL/kg (Rabbit)	-
Ci 77266	> 15400 mg/kg (Rat)	-	> 4.6 mg/m³ (Rat) 4 h
Nickel	> 9000 mg/kg (Rat)	-	> 10.2 mg/L (Rat) 1 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritationClassification based on data available for ingredients. Irritating to skin.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

Respiratory or skin sensitization May cause sensitization by skin contact.

Germ cell mutagenicity No information available.

Carcinogenicity Contains a known or suspected carcinogen. Classification based on data available for

ingredients. May cause cancer.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Lithium Cobalt Oxide	A3	Group 2B	Reasonably Anticipated	Х
(CoLiO2)				
12190-79-3				
Ci 77266	A3	Group 2B	-	X
1333-86-4				
Nickel	-	Group 2B	Reasonably Anticipated	X
7440-02-0				

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

NTP (National Toxicology Program)

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity No information available.

STOT - single exposure No information available.

STOT - repeated exposure Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard No information available.



12. ECOLOGICAL INFORMATION

Ecotoxicity

Very toxic to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Copper	96h EC50: 0.031 - 0.054 mg/L (Pseudokirchneriella subcapitata) 72h EC50: 0.0426 - 0.0535 mg/L (Pseudokirchneriella subcapitata)	96h LC50: 0.0068 - 0.0156 mg/L (Pimephales promelas) 96h LC50: < 0.3 mg/L (Pimephales promelas) 96h LC50: = 0.052 mg/L (Oncorhynchus mykiss) 96h LC50: = 0.112 mg/L (Poecilia reticulata) 96h LC50: = 0.2 mg/L (Pimephales promelas) 96h LC50: = 0.3 mg/L (Cyprinus carpio) 96h LC50: = 0.8 mg/L (Cyprinus carpio) 96h LC50: = 1.25 mg/L (Lepomis macrochirus)	No data available	48h EC50: = 0.03 mg/L (Daphnia magna)
Propylene carbonate	72h EC50: > 500 mg/L (Desmodesmus subspicatus)	(Cyprinus carpio)	EC50 > 10000 mg/L 17 h	48h EC50: > 500 mg/L (Daphnia magna)
Ethylene carbonate	No data available	96h LC50: > 100 mg/L (Oncorhynchus mykiss)	No data available	No data available
Nickel	96h EC50: 0.174 - 0.311 mg/L (Pseudokirchneriella subcapitata) 72h EC50: = 0.18 mg/L (Pseudokirchneriella subcapitata)	96h LC50: = 1.3 mg/L (Cyprinus carpio) 96h LC50: = 10.4 mg/L (Cyprinus carpio) 96h LC50: > 100 mg/L (Brachydanio rerio)	No data available	48h EC50: = 1 mg/L (Daphnia magna) 48h EC50: > 100 mg/L (Daphnia magna)

Persistence and Degradability

No information available.

Bioaccumulation

Component Information

Chemical name	Partition coefficient	
Propylene carbonate	0.48	

MobilityNo information available.Other adverse effectsNo information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste from residues/unused products

Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.



Contaminated packaging Do not reuse empty containers.

California Waste Codes 141

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical name	California Hazardous Waste
Lithium Cobalt Oxide (CoLiO2) 12190-79-3	Toxic
Aluminum 7429-90-5	Ignitable powder
Nickel 7440-02-0	Toxic powder Ignitable powder

14. TRANSPORT INFORMATION

Note:

The transportation of primary lithium cells and batteries is regulated by the International Civil Aviation Organization, International Air Transport Association, International Maritime Dangerous Goods Code and the US Department of Transportation. The batteries must meet the following criteria for shipment: 1. Air shipments must meet the requirements listed in Special Provision A45 of the International Air Transport Association Dangerous Goods Regulations. 2. Meet the requirements for the US Department of Transportation listed in 49 CFR 173.185. 3. The transport of primary lithium batteries is prohibited aboard passenger aircraft. Refer to the Federal Register December 15, 2004 (Hazardous Materials; Prohibited on the Transportation of Primary Lithium Batteries and Cells Aboard Passenger Aircraft; Final Rule)

Lithium batteries shipped as "Lithium batteries", "Lithium batteries packed with equipment", or "Lithium batteries contained in equipment" may not be classified as "Dangerous Goods" when shipped in accordance with "special provision A45 of IATA-DGR" or "special provision 188 of IMO-IMDG Code"

DOTNOT REGULATEDProper Shipping NameNON-REGULATED

Hazard Class N/A Emergency Response Guide 147

Number

TDG Not applicable

MEX Not applicable

ICAO Not applicable

IATA Not applicable
Proper Shipping Name NON REGULATED

Hazard Class N/A

IMDG/IMONot applicableHazard ClassN/A

EmS-No. F-A, S-I

RID Not applicable

ADR Not applicable



ADN Not applicable

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

International Inventories

TSCA

DSL/NDSL

Contact supplier for inventory compliance status.

KECL

Contact supplier for inventory compliance status.

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	CAS No	Weight-%	SARA 313 - Threshold Values %
Lithium Cobalt Oxide (CoLiO2) - 12190-79-3	12190-79-3	45.5	0.1
Copper - 7440-50-8	7440-50-8	7.31	1.0
Aluminum - 7429-90-5	7429-90-5	3.9	1.0
Nickel - 7440-02-0	7440-02-0	0.38	0.1

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications. Under the amended regulations at 40 CFR 370, EPCRA 311/312 Tier II reporting for the 2017 calendar year will need to be consistent with updated hazard classifications.

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Copper		X	X	



7440-50-8			
Nickel	Χ	Х	
7440-02-0			

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Copper 7440-50-8	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Nickel 7440-02-0	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical name	California Proposition 65
Ci 77266 - 1333-86-4	carcinogen, 2/21/2003 (airborne, unbound particles of respirable
	size)
Nickel - 7440-02-0	carcinogen, 10/1/1989 (metallic)

U.S. State Right-to-Know Regulations

This product may contain substances regulated by state right-to-know regulations.

Chemical name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Lithium Cobalt Oxide (CoLiO2) 12190-79-3	Х		X	X	X
Copper 7440-50-8	Х	X	Х	Х	Х
Aluminum 7429-90-5	Х	Х	Х	Х	
Phosphate(1-), hexafluoro-, lithium 21324-40-3	Х				
Ethylene carbonate 96-49-1		Х	Х		
Propyl propionate 106-36-5		Х	Х		
Ci 77266 1333-86-4	Х	Х	Х		Х
Nickel 7440-02-0	Х	Х	Х	Х	Х

NFPA	Health hazards 1	Flammability 0	Instability 0	Physical and Chemical Properties -
				i iopcitics

16. OTHER INFORMATION

<u>HMIS</u> Health hazards 1 Flammability 0 Physical hazards 0 Personal Protection X

Prepared By
Product Stewardship
23 British American Blvd.



טזי

Latham, NY 12110 1-800-572-6501

Issuing Date 20-Dec-2021

Revision Date 20-Dec-2021

Revision Note No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet



Revision Date 20-Dec-2021

SAFETY DATA SHEET

Issuing Date 20-Dec-2021

Revision Date 19-Dec-2021

Revision Number 1

NGHS / English



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

1. IDENTIFICATION

Product identifier

Product Name Rechargeable Li-ion Battery L21C3PE0 - by Celxpert

Other means of identification

Product Code(s) 1674125

Recommended use of the chemical and restrictions on use

Recommended Use Lithium Ion Battery

Restrictions on use No information available

Details of the supplier of the safety data sheet

Supplier Identification Lenovo LNB laptops

Address Songtao Road 696

shanghai shanghai 201203 CN

Telephone Phone:18116118603

E-mail yuanbb1@lenovo.com

Emergency telephone number

Company Emergency Phone

Number

18116118603

2. HAZARDS IDENTIFICATION

Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 1
Skin sensitization	Category 1
Carcinogenicity	Category 1B



Specific target organ toxicity (repeated exposure)

Category 1

This is a battery. In case of rupture: the above hazards exist.

Physical state Solid

Odor No information available

GHS Label elements, including precautionary statements

Danger

Hazard statements

Appearance Solid

Causes skin irritation
Causes serious eye damage
May cause an allergic skin reaction
May cause cancer

Causes damage to organs through prolonged or repeated exposure



Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Wear protective gloves/protective clothing/eye protection/face protection

Wash face, hands and any exposed skin thoroughly after handling

Contaminated work clothing must not be allowed out of the workplace

Do not breathe dust/fume/gas/mist/vapors/spray

Do not eat, drink or smoke when using this product

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

Specific treatment (see supplemental first aid instructions on this label)

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing Immediately call a POISON CENTER or doctor

Skin

IF ON SKIN: Wash with plenty of water and soap

Take off contaminated clothing and wash it before reuse

If skin irritation or rash occurs: Get medical advice/attention

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other information

Very toxic to aquatic life with long lasting effects.

Unknown acute toxicity 28.64 % of the mixture consists of ingredient(s) of unknown toxicity

6.56 % of the mixture consists of ingredient(s) of unknown acute oral toxicity



Page 2/12

28.64 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity

28.64 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)

28.64 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)

28.64 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance

Not applicable.

Mixture

Chemical name	CAS No	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
Lithium Cobalt Oxide (CoLiO2)	12190-79-3	42.28	-	-
Aluminum	7429-90-5	9.68	-	-
Copper	7440-50-8	8.6	-	-
Phosphate(1-), hexafluoro-, lithium	21324-40-3	3.13	-	-
Ethylene carbonate	96-49-1	3.09	-	-
Nickel	7440-02-0	0.45	-	-

4. FIRST AID MEASURES

Description of first aid measures

General advice Immediate medical attention is required. Show this safety data sheet to the doctor in

attendance. IF exposed or concerned: Get medical advice/attention. First aid is upon

rupture of sealed battery. This is a battery. In case of rupture:.

Inhalation Remove to fresh air. Get medical attention immediately if symptoms occur.

Eye contact Get immediate medical advice/attention. Rinse immediately with plenty of water, also under

the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do.

Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area.

Skin contact Wash off immediately with soap and plenty of water for at least 15 minutes. May cause an

allergic skin reaction. In the case of skin irritation or allergic reactions see a physician.

Ingestion Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth

to an unconscious person. Do NOT induce vomiting. Call a physician.

Self-protection of the first aider Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see section 8).

Most important symptoms and effects, both acute and delayed

Symptoms Burning sensation. Itching. Rashes. Hives.

Indication of any immediate medical attention and special treatment needed

Note to physicians May cause sensitization in susceptible persons. Treat symptomatically.



Page 3/12

5. FIRE-FIGHTING MEASURES

surrounding environment.

Large Fire CAUTION: Use of water spray when fighting fire may be inefficient.

Unsuitable extinguishing media Do not scatter spilled material with high pressure water streams.

Specific hazards arising from the

chemical

Product is or contains a sensitizer. May cause sensitization by skin contact.

Hazardous Combustion Products Carbon oxides.

Explosion Data

Sensitivity to Mechanical Impact None. **Sensitivity to Static Discharge** None.

Special protective equipment for

fire-fighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with skin, eyes or clothing. Use personal protective equipment as required.

Ensure adequate ventilation. Evacuate personnel to safe areas. Keep people away from

and upwind of spill/leak.

Other Information Refer to protective measures listed in Sections 7 and 8.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Pick up and transfer to properly labeled containers.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling In case of rupture. Handle in accordance with good industrial hygiene and safety practice.

Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Take off contaminated clothing and wash before reuse.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep out of the reach of children. Keep containers tightly closed in a dry, cool and

well-ventilated place. Store locked up.



8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Limits

The following ingredients are the only ingredients of the product above the cut-off level (or level that contributes to the hazard classification of the mixture) which have an exposure limit applicable in the region for which this safety data sheet is intended or other recommended limit. At this time, the other relevant constituents have no known exposure limits from the sources listed here.

Chemical name		ACGIH T	LV	03	SHA PEL	NIOS	SH IDLH
Lithium Cobalt Oxide (CoLid 12190-79-3	02)	TWA: 0.02 mg/m ³		-			
Aluminum		TWA: 1 mg/m ³ r	espirable	TWA: 15 mg/m ³ total dust			/m ³ total dust
7429-90-5		particulate n	natter	TWA: 5 m	ıg/m³ respirable	TWA: 5 mg/m ³	respirable dust
				I	fraction		
				(vacated) TV	VA: 15 mg/m ³ total		
					dust		
) TWA: 5 mg/m ³		
					able fraction		
Copper		TWA: 0.2 mg/n	n ³ fume		1 mg/m³ fume		g/m³ dust, fume
7440-50-8					/m³ dust and mist		d mist
				, ,	WA: 0.1 mg/m ³ Cu		3 dust and mist
Discoule at a (4) In a confliction		T\\\\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \		dust, fume, mist		TWA: 0.1 r	
Phosphate(1-), hexafluoro)-,	TWA: 2.5 mg	g/m³ F	TWA: 2.5 mg/m ³ F		IDLH: 2	50 mg/m³ F
lithium 21324-40-3				(vacated)	TWA: 2.5 mg/m ³		
Nickel		TWA: 1.5 m	ng/m3	T\\\/.	A: 1 mg/m ³	IDI II:	10 mg/m ³
7440-02-0		IVVA. 1.5 II	ig/iii°) TWA: 1 mg/m ³		015 mg/m ³
Chemical name		Alberta	British C		Ontario TWAE		Quebec
Lithium Cobalt Oxide	ΤV	VA: 0.02 mg/m ³		02 mg/m ³	TWA: 0.02 mg/i		A: 0.02 mg/m ³
(CoLiO2)	1 V	VA. 0.02 mg/m	1 VVA. 0.0	02 mg/m²	1 VVA. 0.02 mg/i	1111	4. 0.02 mg/m
12190-79-3							
Aluminum	Т	WA: 10 mg/m ³	TWA: 1	0 mg/m ³	TWA: 1 mg/m	3 T/V	/A: 10 mg/m ³
7429-90-5	•	vv, a 10 mg/m		o mg/m	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	'''	7 ti 10 mg/m
Copper	T۱	WA: 0.2 mg/m ³	TWA: 1	mg/m³	TWA: 0.2 mg/n	n³ TW	A: 0.2 mg/m ³
7440-50-8		WA: 1 mg/m ³		0.2 mg/m ³ TWA: 1 mg/m			VA: 1 mg/m ³
Phosphate(1-),		WA: 2.5 mg/m ³		5 mg/m³	TWA: 2.5 mg/n		A: 2.5 mg/m ³
hexafluoro-, lithium		-		J			·
21324-40-3							
Nickel	T۱	WA: 1.5 mg/m ³	TWA: 0.0	05 mg/m ³	TWA: 1 mg/m	³ TW	A: 1.5 mg/m ³
7440-02-0							

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992). See section 15 for national exposure control parameters.

Appropriate engineering controls

Engineering controls Showers

Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Tight sealing safety goggles.

Hand protection Wear suitable gloves. Impervious gloves.



Wear suitable protective clothing. Long sleeved clothing.

No protective equipment is needed under normal use conditions. If exposure limits are Respiratory protection

exceeded or irritation is experienced, ventilation and evacuation may be required.

Handle in accordance with good industrial hygiene and safety practice. Avoid contact with General hygiene considerations

skin, eyes or clothing. Wash hands before breaks and immediately after handling the product. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when

using this product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Solid **Appearance** Solid

Skin and body protection

Odor No information available Color No information available **Odor Threshold** No information available

Values Remarks Method Property

No data available None known Hq Melting / freezing point No data available None known Boiling point / boiling range No data available None known Flash Point No data available None known No data available **Evaporation Rate** None known Flammability (solid, gas) No data available None known Flammability Limit in Air None known

Upper flammability limit No data available Lower flammability limit No data available

No data available Vapor pressure None known No data available Vapor density None known No data available None known Relative density

Water Solubility Insoluble in water

No data available Solubility(ies) None known

Partition coefficient: n-octanol/water1

No data available None known **Autoignition temperature Decomposition temperature** No data available None known Kinematic viscosity No data available None known Dynamic viscosity No data available None known

Other Information

Explosive properties No information available No information available **Oxidizing properties Softening Point** No information available Molecular Weight No information available **VOC Content (%)** No information available **Liquid Density** No information available **Bulk Density** No information available **Particle Size** No information available **Particle Size Distribution** No information available

10. STABILITY AND REACTIVITY

Reactivity No information available.



Chemical stability Stable under normal conditions.

Possibility of Hazardous Reactions None under normal processing.

Hazardous Polymerization Hazardous polymerization does not occur.

Conditions to avoidNone known based on information supplied.

Incompatible materials Strong acids. Strong bases. Strong oxidizing agents.

Hazardous Decomposition Products Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information Product does not present an acute toxicity hazard based on known or supplied information.

In case of rupture:

Inhalation Specific test data for the substance or mixture is not available. May cause irritation of

respiratory tract. (based on components).

Eye contact Specific test data for the substance or mixture is not available. Causes serious eye

damage. (based on components). May cause burns. May cause irreversible damage to

eyes. Severely irritating to eyes.

Skin contact Specific test data for the substance or mixture is not available. May cause sensitization by

skin contact. Causes skin irritation. (based on components). Repeated or prolonged skin

contact may cause allergic reactions with susceptible persons.

Ingestion Specific test data for the substance or mixture is not available. Ingestion may cause

gastrointestinal irritation, nausea, vomiting and diarrhea. (based on components).

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Redness. Burning. May cause blindness. Itching. Rashes. Hives. May cause redness and

tearing of the eyes.

Numerical measures of toxicity

Acute toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 14,744.70 mg/kg **ATEmix (dermal)** 6,839.60 mg/kg

Unknown acute toxicity 28.64 % of the mixture consists of ingredient(s) of unknown toxicity

6.56 % of the mixture consists of ingredient(s) of unknown acute oral toxicity

28.64 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity

28.64 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas) 28.64 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)

28.64 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

Product Information

Component Information

Chemical name Oral LD50 Dermal LD50 Inhalation LC50



 Lithium Cobalt Oxide (CoLiO2)
 > 5000 mg/kg (Rat)
 > 2000 mg/kg (Rat)
 > 5.05 mg/L (Rat) 4 h

 Aluminum
 > 0.888 mg/L (Rat) 4 h

 Copper
 > 5.11 mg/L (Rat) 4 h

 Ethylene carbonate
 = 10 g/kg (Rat)
 > 26420 mg/kg (Rabbit)
 > 730 mg/m³ (Rat) 8 h

 Nickel
 > 9000 mg/kg (Rat)
 > 10.2 mg/L (Rat) 1 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritationClassification based on data available for ingredients. Irritating to skin.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes burns. Risk of serious

damage to eyes.

Respiratory or skin sensitization May cause sensitization by skin contact.

Germ cell mutagenicity No information available.

Carcinogenicity Contains a known or suspected carcinogen. Classification based on data available for

ingredients. May cause cancer.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Lithium Cobalt Oxide	A3	Group 2B	Reasonably Anticipated	X
(CoLiO2)				
12190-79-3				
Nickel	-	Group 2B	Reasonably Anticipated	X
7440-02-0				

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

NTP (National Toxicology Program)

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity No information available.

STOT - single exposure No information available.

STOT - repeated exposureCauses damage to organs through prolonged or repeated exposure.

Aspiration hazard No information available.

12. ECOLOGICAL INFORMATION

Ecotoxicity Very toxic to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to	Crustacea
			microorganisms	
Copper	96h EC50: 0.031 - 0.054	96h LC50: 0.0068 -	No data available	48h EC50: = 0.03 mg/L
	mg/L	0.0156 mg/L (Pimephales		(Daphnia magna)
	(Pseudokirchneriella	promelas) 96h LC50: <		



	subcapitata) 72h EC50:	0.3 mg/L (Pimephales		
	0.0426 - 0.0535 mg/L	promelas) 96h LC50: =		
	(Pseudokirchneriella	0.052 mg/L		
	subcapitata)	(Oncorhynchus mykiss)		
		96h LC50: = 0.112 mg/L		
		(Poecilia reticulata) 96h		
		LC50: = 0.2 mg/L		
		(Pimephales promelas)		
		96h LC50: = 0.3 mg/L		
		(Cyprinus carpio) 96h		
		LC50: = 0.8 mg/L		
		(Cyprinus carpio) 96h		
		LC50: = 1.25 mg/L		
		(Lepomis macrochirus)		
Ethylene carbonate	No data available	96h LC50: > 100 mg/L	No data available	No data available
		(Oncorhynchus mykiss)		
Nickel	96h EC50: 0.174 - 0.311	96h LC50: = 1.3 mg/L	No data available	48h EC50: = 1 mg/L
	mg/L	(Cyprinus carpio) 96h		(Daphnia magna) 48h
	(Pseudokirchneriella	LC50: = 10.4 mg/L		EC50: > 100 mg/L
	subcapitata) 72h EC50: =			(Daphnia magna)
	0.18 mg/L	LC50: > 100 mg/L] ' ' ' ' '
	(Pseudokirchneriella	(Brachydanio rerio)		
	` subcapitata)	,		

Persistence and Degradability

No information available.

Bioaccumulation

No information available.

MobilityNo information available.Other adverse effectsNo information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste from residues/unused

products

Dispose of in accordance with local regulations. Dispose of waste in accordance with

environmental legislation.

Contaminated packaging Do not reuse empty containers.

California Waste Codes 141

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical name	California Hazardous Waste
Lithium Cobalt Oxide (CoLiO2) 12190-79-3	Toxic
Aluminum 7429-90-5	Ignitable powder
Nickel 7440-02-0	Toxic powder Ignitable powder

14. TRANSPORT INFORMATION



Note: The transportation of primary lithium cells and batteries is regulated by the International

Civil Aviation Organization, International Air Transport Association, International Maritime Dangerous Goods Code and the US Department of Transportation. The batteries must meet the following criteria for shipment: 1. Air shipments must meet the requirements listed in Special Provision A45 of the International Air Transport Association Dangerous Goods Regulations. 2. Meet the requirements for the US Department of Transportation listed in 49 CFR 173.185. 3. The transport of primary lithium batteries is prohibited aboard passenger aircraft. Refer to the Federal Register December 15, 2004 (Hazardous Materials; Prohibited on the Transportation of Primary Lithium Batteries and Cells Aboard

Passenger Aircraft; Final Rule)

Lithium batteries shipped as "Lithium batteries", "Lithium batteries packed with equipment", or "Lithium batteries contained in equipment" may not be classified as "Dangerous Goods" when shipped in accordance with "special provision A45 of IATA-DGR" or "special provision

188 of IMO-IMDG Code"

DOTNOT REGULATEDProper Shipping NameNON-REGULATED

Hazard Class N/A Emergency Response Guide 147

Number

TDG Not applicable

MEX Not applicable

ICAO Not applicable

IATA Not applicable

Proper Shipping Name NON REGULATED

Hazard Class N/A

IMDG/IMO Not applicable

Hazard Class N/A EmS-No. F-A, S-I

RID Not applicable

ADR Not applicable

ADN Not applicable

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

International Inventories

TSCA Contact supplier for inventory compliance status.

DSL/NDSL Contact supplier for inventory compliance status.

EINECS/ELINCS Contact supplier for inventory compliance status.



ENCSContact supplier for inventory compliance status.KECLContact supplier for inventory compliance status.PICCSContact supplier for inventory compliance status.AICSContact supplier for inventory compliance status.

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	CAS No	Weight-%	SARA 313 - Threshold Values %
Lithium Cobalt Oxide (CoLiO2) - 12190-79-3	12190-79-3	42.28	0.1
Aluminum - 7429-90-5	7429-90-5	9.68	1.0
Copper - 7440-50-8	7440-50-8	8.6	1.0
Nickel - 7440-02-0	7440-02-0	0.45	0.1

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications. Under the amended regulations at 40 CFR 370, EPCRA 311/312 Tier II reporting for the 2017 calendar year will need to be consistent with updated hazard classifications.

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Copper		X	X	
7440-50-8				
Nickel		X	X	
7440-02-0				

<u>CERCLA</u>

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

	Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Γ	Copper	5000 lb		RQ 5000 lb final RQ
1	7440-50-8			RQ 2270 kg final RQ
ſ	Nickel	100 lb		RQ 100 lb final RQ
	7440-02-0			RQ 45.4 kg final RQ

US State Regulations

California Proposition 65



Page 11/12

This product contains the following Proposition 65 chemicals.

Chemical name	California Proposition 65
Nickel - 7440-02-0	carcinogen, 10/1/1989 (metallic)

U.S. State Right-to-Know Regulations

This product may contain substances regulated by state right-to-know regulations.

Chemical name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Lithium Cobalt Oxide (CoLiO2) 12190-79-3	X		X	X	Х
Aluminum 7429-90-5	Х	Х	Х	Х	
Copper 7440-50-8	Х	X	Х	Х	Х
Phosphate(1-), hexafluoro-, lithium 21324-40-3	Х				
Ethylene carbonate 96-49-1		Х	Х		
Nickel 7440-02-0	Х	X	Х	Х	Х

16. OTHER INFORMATION

NFPA Health hazards 1 Flammability 0 Instability 0 Physical and Chemical

Properties -

Health hazards 0 Flammability 0 Physical hazards 0 Personal Protection X

Prepared By Product Stewardship

23 British American Blvd. Latham, NY 12110 1-800-572-6501

Issuing Date 20-Dec-2021

Revision Date 19-Dec-2021

Revision Note No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet



SAFETY DATA SHEET

Issuing Date 20-Dec-2021

Revision Date 19-Dec-2021

Revision Number 1

NGHS / English

The

The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

1. IDENTIFICATION

Product identifier

Product Name Rechargeable Li-ion Battery L21L3PE0 - by LG

Other means of identification

Product Code(s) 1674127

Recommended use of the chemical and restrictions on use

Recommended Use Lithium Ion Battery

Restrictions on use No information available

Details of the supplier of the safety data sheet

Supplier Identification Lenovo LNB laptops

Address Songtao Road 696

shanghai shanghai 201203 CN

Telephone Phone:18116118603

E-mail yuanbb1@lenovo.com

Emergency telephone number

Company Emergency Phone

Number

18116118603

2. HAZARDS IDENTIFICATION

Classification

Skin sensitization	Category 1
Carcinogenicity	Category 1B
Specific target organ toxicity (repeated exposure)	Category 1



This is a battery. In case of rupture: the above hazards exist.

Appearance Solid Physical state Solid Odor No information available

GHS Label elements, including precautionary statements

Danger

Hazard statements

May cause an allergic skin reaction
May cause cancer
Causes damage to organs through prolonged or repeated exposure



Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood Wear protective gloves/protective clothing/eye protection/face protection Contaminated work clothing must not be allowed out of the workplace Do not breathe dust/fume/gas/mist/vapors/spray Wash face, hands and any exposed skin thoroughly after handling Do not eat, drink or smoke when using this product

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

Specific treatment (see supplemental first aid instructions on this label)

Skin

IF ON SKIN: Wash with plenty of water and soap

If skin irritation or rash occurs: Get medical advice/attention

Wash contaminated clothing before reuse

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other information

Causes mild skin irritation. Very toxic to aquatic life with long lasting effects.

Unknown acute toxicity 18 % of the mixture consists of ingredient(s) of unknown toxicity

- 0 % of the mixture consists of ingredient(s) of unknown acute oral toxicity 18 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity
- 18 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)
- 18 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)
- 18 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

3. COMPOSITION/INFORMATION ON INGREDIENTS



Page 2/12

Substance

Not applicable.

Mixture

Chemical name	CAS No	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
Nickel	7440-02-0	30	-	-
Lithium Cobalt Oxide (CoLiO2)	12190-79-3	30	-	-
Copper	7440-50-8	7	-	-
Aluminum	7429-90-5	3	-	-

4. FIRST AID MEASURES

Description of first aid measures

General advice Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get

medical advice/attention. First aid is upon rupture of sealed battery. This is a battery. In

case of rupture:.

Inhalation Remove to fresh air.

Eye contact Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids.

Consult a physician.

Skin contact Wash with soap and water. May cause an allergic skin reaction. In the case of skin irritation

or allergic reactions see a physician.

Ingestion Clean mouth with water and drink afterwards plenty of water.

Most important symptoms and effects, both acute and delayed

Symptoms Itching. Rashes. Hives.

Indication of any immediate medical attention and special treatment needed

Note to physicians May cause sensitization in susceptible persons. Treat symptomatically.

5. FIRE-FIGHTING MEASURES

surrounding environment.

Large Fire CAUTION: Use of water spray when fighting fire may be inefficient.

Unsuitable extinguishing media Do not scatter spilled material with high pressure water streams.

Specific hazards arising from the

chemical

Product is or contains a sensitizer. May cause sensitization by skin contact.

Hazardous Combustion Products Carbon oxides.



Explosion Data

Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

Special protective equipment for

fire-fighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout

gear. Use personal protection equipment.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal Personal precautions

protective equipment as required. Evacuate personnel to safe areas. Keep people away

from and upwind of spill/leak.

Other Information Refer to protective measures listed in Sections 7 and 8.

Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Methods for containment

Pick up and transfer to properly labeled containers. Methods for cleaning up

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling In case of rupture: Handle in accordance with good industrial hygiene and safety practice.

> Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this

product. Take off contaminated clothing and wash before reuse.

Conditions for safe storage, including any incompatibilities

Keep out of the reach of children. Keep containers tightly closed in a dry, cool and **Storage Conditions**

well-ventilated place. Store locked up.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Limits

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Nickel	TWA: 1.5 mg/m ³	TWA: 1 mg/m ³	IDLH: 10 mg/m ³
7440-02-0		(vacated) TWA: 1 mg/m ³	TWA: 0.015 mg/m ³
Lithium Cobalt Oxide (CoLiO2) 12190-79-3	TWA: 0.02 mg/m ³	-	
Copper 7440-50-8	TWA: 0.2 mg/m³ fume	TWA: 0.1 mg/m³ fume TWA: 1 mg/m³ dust and mist (vacated) TWA: 0.1 mg/m³ Cu	IDLH: 100 mg/m³ dust, fume and mist TWA: 1 mg/m³ dust and mist



dust, fume, mist TWA: 0.1 mg/m³ fume Aluminum TWA: 1 mg/m³ respirable TWA: 15 mg/m³ total dust TWA: 10 mg/m³ total dust TWA: 5 mg/m³ respirable TWA: 5 mg/m³ respirable dust 7429-90-5 particulate matter fraction (vacated) TWA: 15 mg/m3 total dust (vacated) TWA: 5 mg/m³ respirable fraction Chemical name Alberta British Columbia Ontario TWAEV Quebec Nickel TWA: 1.5 mg/m³ TWA: 1.5 mg/m³ TWA: 0.05 mg/m³ TWA: 1 mg/m³ 7440-02-0 Lithium Cobalt Oxide TWA: 0.02 mg/m³ TWA: 0.02 mg/m³ TWA: 0.02 mg/m³ TWA: 0.02 mg/m³ (CoLiO2) 12190-79-3 Copper TWA: 0.2 mg/m³ TWA: 1 mg/m³ TWA: 0.2 mg/m³ TWA: 0.2 mg/m³ 7440-50-8 TWA: 1 mg/m³ TWA: 0.2 mg/m³ TWA: 1 mg/m³ TWA: 1 mg/m³ TWA: 10 mg/m³ TWA: 10 mg/m³ Aluminum TWA: 1.0 mg/m³ TWA: 1 mg/m³ 7429-90-5

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992). See section 15 for national exposure control parameters.

Appropriate engineering controls

Engineering controls Showers

Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Hand protection Wear suitable gloves.

Skin and body protection Wear suitable protective clothing.

exceeded or irritation is experienced, ventilation and evacuation may be required.

General hygiene considerations Handle in accordance with good industrial hygiene and safety practice. Wash hands before

breaks and immediately after handling the product. Do not eat, drink or smoke when using

this product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Solid Appearance Solid

OdorNo information availableColorNo information availableOdor ThresholdNo information available

Property Values Remarks Method

pHNo data availableNone knownMelting / freezing pointNo data availableNone knownBoiling point / boiling rangeNo data availableNone knownFlash PointNo data availableNone known



None known

Evaporation RateNo data availableNone knownFlammability (solid, gas)No data availableNone knownFlammability Limit in AirNone known

Upper flammability limitNo data availableLower flammability limitNo data available

Vapor pressureNo data availableNone knownVapor densityNo data availableNone knownRelative densityNo data availableNone knownWater SolubilityInsoluble in water

Solubility(ies)

No data available

Partition coefficient: n-octanol/water1

Autoignition temperatureNo data availableNone knownDecomposition temperatureNo data availableNone knownKinematic viscosityNo data availableNone knownDynamic viscosityNo data availableNone known

Other Information

Explosive properties No information available **Oxidizing properties** No information available **Softening Point** No information available **Molecular Weight** No information available **VOC Content (%)** No information available **Liquid Density** No information available No information available **Bulk Density** No information available **Particle Size Particle Size Distribution** No information available

10. STABILITY AND REACTIVITY

Reactivity No information available.

Chemical stability Stable under normal conditions.

Possibility of Hazardous Reactions None under normal processing.

Hazardous Polymerization Hazardous polymerization does not occur.

Conditions to avoidNone known based on information supplied.

Incompatible materialsNone known based on information supplied.

Hazardous Decomposition Products Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information Product does not present an acute toxicity hazard based on known or supplied information.

In case of rupture:

Inhalation Specific test data for the substance or mixture is not available.

Eye contact Specific test data for the substance or mixture is not available.

Skin contact Specific test data for the substance or mixture is not available. May cause sensitization by



Page 6/12

skin contact. (based on components). Repeated or prolonged skin contact may cause

allergic reactions with susceptible persons.

Ingestion Specific test data for the substance or mixture is not available.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Itching. Rashes. Hives.

Numerical measures of toxicity

Acute toxicity

Unknown acute toxicity 18 % of the mixture consists of ingredient(s) of unknown toxicity

0 % of the mixture consists of ingredient(s) of unknown acute oral toxicity

18 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity

18 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)

18 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)

18 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

Product Information

Component Information

	Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
	Nickel	> 9000 mg/kg (Rat)	-	> 10.2 mg/L (Rat) 1 h
L	ithium Cobalt Oxide (CoLiO2)	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rat)	> 5.05 mg/L (Rat) 4 h
	Copper	-	-	> 5.11 mg/L (Rat) 4 h
Г	Aluminum	-	-	> 0.888 mg/L (Rat) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritationNo information available.

Serious eye damage/eye irritation No information available.

Respiratory or skin sensitization May cause sensitization by skin contact.

Germ cell mutagenicity No information available.

Carcinogenicity Contains a known or suspected carcinogen. Classification based on data available for

ingredients. May cause cancer.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Nickel	-	Group 2B	Reasonably Anticipated	Χ
7440-02-0				
Lithium Cobalt Oxide	A3	Group 2B	Reasonably Anticipated	X
(CoLiO2)			·	
12190-79-3				

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

NTP (National Toxicology Program)

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen



OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity No information available.

STOT - single exposure No information available.

STOT - repeated exposureCauses damage to organs through prolonged or repeated exposure.

Aspiration hazard No information available.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Very toxic to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to	Crustacea
			microorganisms	
Nickel	96h EC50: 0.174 - 0.311	96h LC50: = 1.3 mg/L	No data available	48h EC50: = 1 mg/L
	mg/L	(Cyprinus carpio) 96h		(Daphnia magna) 48h
	(Pseudokirchneriella	LC50: = 10.4 mg/L		EC50: > 100 mg/L
	subcapitata) 72h EC50: =	(Cyprinus carpio) 96h		(Daphnia magna)
	0.18 mg/L	LC50: > 100 mg/L		_
	(Pseudokirchneriella	(Brachydanio rerio)		
	subcapitata)			
Copper	96h EC50: 0.031 - 0.054	96h LC50: 0.0068 -	No data available	48h EC50: = 0.03 mg/L
	mg/L	0.0156 mg/L (Pimephales		(Daphnia magna)
	(Pseudokirchneriella	promelas) 96h LC50: <		_
	subcapitata) 72h EC50:	0.3 mg/L (Pimephales		
	0.0426 - 0.0535 mg/L	promelas) 96h LC50: =		
	(Pseudokirchneriella	0.052 mg/L		
	subcapitata)	(Oncorhynchus mykiss)		
		96h LC50: = 0.112 mg/L		
		(Poecilia reticulata) 96h		
		LC50: = 0.2 mg/L		
		(Pimephales promelas)		
		96h LC50: = 0.3 mg/L		
		(Cyprinus carpio) 96h		
		LC50: = 0.8 mg/L		
		(Cyprinus carpio) 96h		
		LC50: = 1.25 mg/L		
		(Lepomis macrochirus)		

Persistence and Degradability No information available.

Bioaccumulation No information available.

Mobility

No information available.

Other adverse effects

No information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste from residues/unused Dispose of in accordance with local regulations. Dispose of waste in accordance with



products environmental legislation.

Contaminated packaging Do not reuse empty containers.

California Waste Codes 141

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical name	California Hazardous Waste
Nickel	Toxic powder
7440-02-0	Ignitable powder
Lithium Cobalt Oxide (CoLiO2) 12190-79-3	Toxic
Aluminum 7429-90-5	Ignitable powder

14. TRANSPORT INFORMATION

Note:

The transportation of primary lithium cells and batteries is regulated by the International Civil Aviation Organization, International Air Transport Association, International Maritime Dangerous Goods Code and the US Department of Transportation. The batteries must meet the following criteria for shipment: 1. Air shipments must meet the requirements listed in Special Provision A45 of the International Air Transport Association Dangerous Goods Regulations. 2. Meet the requirements for the US Department of Transportation listed in 49 CFR 173.185. 3. The transport of primary lithium batteries is prohibited aboard passenger aircraft. Refer to the Federal Register December 15, 2004 (Hazardous Materials; Prohibited on the Transportation of Primary Lithium Batteries and Cells Aboard Passenger Aircraft; Final Rule)

Lithium batteries shipped as "Lithium batteries", "Lithium batteries packed with equipment", or "Lithium batteries contained in equipment" may not be classified as "Dangerous Goods" when shipped in accordance with "special provision A45 of IATA-DGR" or "special provision 188 of IMO-IMDG Code"

 DOT
 NOT REGULATED

 Proper Shipping Name
 NON-REGULATED

Hazard Class N/A Emergency Response Guide 147

Number

TDG Not applicable

MEX Not applicable

ICAO Not applicable

IATA Not applicable Proper Shipping Name NON REGULATED

Hazard Class N/A

IMDG/IMO Not applicable

Hazard Class N/A F-A, S-I

RID Not applicable

ADR Not applicable



ADN Not applicable

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

International Inventories

TSCA Contact supplier for inventory compliance status.

DSL/NDSL Contact supplier for inventory compliance status.

EINECS/ELINCS Contact supplier for inventory compliance status.

ENCS Contact supplier for inventory compliance status.

KECL Contact supplier for inventory compliance status.

PICCS Contact supplier for inventory compliance status.

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	CAS No	Weight-%	SARA 313 - Threshold Values %
Nickel - 7440-02-0	7440-02-0	30	0.1
Lithium Cobalt Oxide (CoLiO2) - 12190-79-3	12190-79-3	30	0.1
Copper - 7440-50-8	7440-50-8	7	1.0
Aluminum - 7429-90-5	7429-90-5	3	1.0

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications. Under the amended regulations at 40 CFR 370, EPCRA 311/312 Tier II reporting for the 2017 calendar year will need to be consistent with updated hazard classifications.

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable	CWA - Toxic Pollutants	CWA - Priority	CWA - Hazardous
	Quantities		Pollutants	Substances



Nickel 7440-02-0	Х	Х	
Copper 7440-50-8	Х	Х	

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

	Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
ı	Nickel	100 lb		RQ 100 lb final RQ
	7440-02-0			RQ 45.4 kg final RQ
ſ	Copper	5000 lb		RQ 5000 lb final RQ
	7440-50-8			RQ 2270 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical name	California Proposition 65	
Nickel - 7440-02-0	carcinogen, 10/1/1989 (metallic)	

U.S. State Right-to-Know Regulations

This product may contain substances regulated by state right-to-know regulations.

Chemical name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Nickel	X	X	X	X	X
7440-02-0					
Lithium Cobalt Oxide	X		X	X	X
(CoLiO2)					
12190-79-3					
Copper	X	X	X	X	X
7440-50-8					
Aluminum	X	X	X	X	
7429-90-5					

16. OTHER INFORMATION

NFPA Health hazards 1 Flammability 0 Instability 0 Physical and Chemical Properties -

HMIS Health hazards 0 Flammability 0 Physical hazards 0 Personal Protection X

Prepared By Product Stewardship

23 British American Blvd. Latham, NY 12110 1-800-572-6501

Issuing Date 20-Dec-2021

Revision Date 19-Dec-2021

Revision Note No information available

Disclaimer



The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet



SAFETY DATA SHEET

Issuing Date No data available

Revision Date 22-Dec-2021

Revision Number 1

NGHS / English

The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

1. IDENTIFICATION

Product identifier

Product Name Rechargeable Li-ion Battery L21M3PE0 - by Simplo

Other means of identification

Product Code(s) 1674668

Recommended use of the chemical and restrictions on use

Recommended Use Lithium Ion Battery

Restrictions on use No information available

Details of the supplier of the safety data sheet

Supplier Identification Lenovo LNB laptops

Address Songtao Road 696

shanghai shanghai 201203 CN

Telephone Phone:18116118603

E-mail yuanbb1@lenovo.com

Emergency telephone number

Company Emergency Phone

Number

18116118603

2. HAZARDS IDENTIFICATION

Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Skin sensitization	Category 1
Carcinogenicity	Category 1B



Specific target organ toxicity (repeated exposure)

Category 1

This is a battery. In case of rupture: the above hazards exist.

Appearance Solid Physical state Solid

Odor No information available

GHS Label elements, including precautionary statements

Danger

Hazard statements

Causes skin irritation
Causes serious eye irritation
May cause an allergic skin reaction
May cause cancer
Causes damage to organs through prolonged or repeated exposure



Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Wear protective gloves/protective clothing/eye protection/face protection

Wash face, hands and any exposed skin thoroughly after handling

Contaminated work clothing must not be allowed out of the workplace

Do not breathe dust/fume/gas/mist/vapors/spray

Do not eat, drink or smoke when using this product

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

Specific treatment (see supplemental first aid instructions on this label)

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

Skin

IF ON SKIN: Wash with plenty of water and soap

Take off contaminated clothing and wash it before reuse

If skin irritation or rash occurs: Get medical advice/attention

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other information

Very toxic to aquatic life with long lasting effects.

Unknown acute toxicity 31.9 % of the mixture consists of ingredient(s) of unknown toxicity

27.2 % of the mixture consists of ingredient(s) of unknown acute oral toxicity



Page 2/13

31.9 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity

31.9 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)

31.9 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)

31.9 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance

Not applicable.

<u>Mixture</u>

Chemical name	CAS No	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
Lithium Cobalt Oxide (CoLiO2)	12190-79-3	27	-	-
Graphite	7782-42-5	16	-	-
Copper	7440-50-8	14.2	-	-
Aluminum	7429-90-5	11	-	-
Propylene carbonate	108-32-7	5.42	-	-
Ethylene carbonate	96-49-1	5.42	-	-
Phosphate(1-), hexafluoro-, lithium	21324-40-3	2.43	-	-
Nylon-6	25038-54-4	2	-	-
Bisphenol A - Phosgene copolymer	25971-63-5	1.44	-	-
Nickel	7440-02-0	1.1	-	-
Bisphenol A - Epichlorohydrin polymer	25068-38-6	0.41	-	-

4. FIRST AID MEASURES

Description of first aid measures

General advice Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get

medical advice/attention. First aid is upon rupture of sealed battery. In case of rupture:

Inhalation Remove to fresh air. Get medical attention immediately if symptoms occur.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep

eye wide open while rinsing. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists. Do not rub affected area.

Skin contact May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a

physician. Wash off immediately with soap and plenty of water for at least 15 minutes.

Ingestion Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth

to an unconscious person. Do NOT induce vomiting. Call a physician.

Self-protection of the first aider Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see section 8).

Most important symptoms and effects, both acute and delayed



Page 3 / 13

Symptoms Itching. Rashes. Hives. Burning sensation.

Indication of any immediate medical attention and special treatment needed

Note to physicians May cause sensitization in susceptible persons. Treat symptomatically.

5. FIRE-FIGHTING MEASURES

surrounding environment.

Large Fire CAUTION: Use of water spray when fighting fire may be inefficient.

Unsuitable extinguishing media Do not scatter spilled material with high pressure water streams.

Specific hazards arising from the

chemical

Product is or contains a sensitizer. May cause sensitization by skin contact.

Hazardous Combustion Products Carbon oxides.

Explosion Data

Sensitivity to Mechanical Impact None. **Sensitivity to Static Discharge** None.

Special protective equipment for

fire-fighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout

gear. Use personal protection equipment.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal

protective equipment as required. Evacuate personnel to safe areas. Keep people away

from and upwind of spill/leak.

Other Information Refer to protective measures listed in Sections 7 and 8.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Pick up and transfer to properly labeled containers.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling In case of rupture: Handle in accordance with good industrial hygiene and safety practice.

Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this

product. Take off contaminated clothing and wash before reuse.

Conditions for safe storage, including any incompatibilities



Storage Conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Keep out of the reach of children.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Limits

Chemical name		ACGIH T	LV	0:	SHA PEL		NIOSH IDLH
Lithium Cobalt Oxide (Co 12190-79-3	LiO2)	TWA: 0.02 r	mg/m³		-		
Graphite 7782-42-5		TWA: 2 mg/m³ particulate matte except graphit	er all forms synthetic			IDLH: 1250 mg/m³ x: 2.5 mg/m³ respirable dust	
Copper 7440-50-8		TWA: 0.2 mg/r		TWA: 1 mg. (vacated) T dust	1 mg/m³ fume /m³ dust and mist WA: 0.1 mg/m³ Cu , fume, mist	TWA:	I: 100 mg/m³ dust, fume and mist 1 mg/m³ dust and mist VA: 0.1 mg/m³ fume
Aluminum 7429-90-5		TWA: 1 mg/m³ particulate r		TWA: 5 m (vacated) TV	ng/m³ total dust g/m³ respirable fraction VA: 15 mg/m³ total dust		A: 10 mg/m³ total dust 5 mg/m³ respirable dust
Dhaanhata(4) hayafiya		T\\\\\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	/2 F	respir) TWA: 5 mg/m ³ able fraction		IDLH: 250 mg/m ³ F
Phosphate(1-), hexafluc lithium 21324-40-3	oro-,	TWA: 2.5 mg	g/m³ F	TWA: 2.5 mg/m³ F (vacated) TWA: 2.5 mg/m³			IDLH: 250 mg/m³ F
Nickel 7440-02-0		TWA: 1.5 m	ng/m³		A: 1 mg/m³) TWA: 1 mg/m³		IDLH: 10 mg/m ³ TWA: 0.015 mg/m ³
Chemical name		Alberta	British C	Columbia	Ontario TWAE		Quebec
Lithium Cobalt Oxide (CoLiO2) 12190-79-3	TV	VA: 0.02 mg/m ³		02 mg/m ³	TWA: 0.02 mg/		TWA: 0.02 mg/m ³
Graphite 7782-42-5	٦	ΓWA: 2 mg/m³		2 mg/m³	TWA: 2 mg/m	3	TWA: 2 mg/m ³
Copper 7440-50-8	1	WA: 0.2 mg/m³ ГWA: 1 mg/m³	TWA: 0.	l mg/m³ .2 mg/m³	TWA: 0.2 mg/n TWA: 1 mg/m	3	TWA: 0.2 mg/m ³ TWA: 1 mg/m ³
Aluminum 7429-90-5		WA: 10 mg/m ³		.0 mg/m³	TWA: 1 mg/m		TWA: 10 mg/m ³
Phosphate(1-), hexafluoro-, lithium 21324-40-3		WA: 2.5 mg/m³		5 mg/m³	TWA: 2.5 mg/n		TWA: 2.5 mg/m ³
Nickel 7440-02-0	T	WA: 1.5 mg/m ³	TWA: 0.0	05 mg/m³	TWA: 1 mg/m	3	TWA: 1.5 mg/m ³



Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992). See section 15 for national exposure control parameters.

Appropriate engineering controls

Engineering controls Showers

Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Hand protection Wear suitable gloves. Impervious gloves.

Skin and body protectionWear suitable protective clothing. Long sleeved clothing.

Respiratory protection No protective equipment is needed under normal use conditions. If exposure limits are

exceeded or irritation is experienced, ventilation and evacuation may be required.

General hygiene considerations Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or

smoke when using this product. Wash hands before breaks and immediately after handling the product. Wear suitable gloves and eye/face protection. Avoid contact with skin, eyes or

clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Solid Appearance Solid

Odor No information available
Color No information available
Odor Threshold No information available

Property Values Remarks Method

На No data available None known Melting / freezing point No data available None known Boiling point / boiling range No data available None known **Flash Point** No data available None known No data available **Evaporation Rate** None known Flammability (solid, gas) No data available None known Flammability Limit in Air None known

Upper flammability limit No data available

Lower flammability limit

No data available

No data available

Vapor pressureNo data availableNone knownVapor densityNo data availableNone knownRelative densityNo data availableNone known

Water Solubility Insoluble in water

Solubility(ies) No data available None known

Partition coefficient: n-octanol/water1

Autoignition temperatureNo data availableNone knownDecomposition temperatureNo data availableNone knownKinematic viscosityNo data availableNone knownDynamic viscosityNo data availableNone known

Other Information



Explosive properties No information available No information available **Oxidizing properties Softening Point** No information available **Molecular Weight** No information available **VOC Content (%)** No information available No information available **Liquid Density Bulk Density** No information available **Particle Size** No information available **Particle Size Distribution** No information available

10. STABILITY AND REACTIVITY

Reactivity No information available.

Chemical stability Stable under normal conditions.

Possibility of Hazardous Reactions None under normal processing.

Hazardous Polymerization Hazardous polymerization does not occur.

Conditions to avoidNone known based on information supplied.

Incompatible materials Strong acids. Strong bases. Strong oxidizing agents.

Hazardous Decomposition Products Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information Product does not present an acute toxicity hazard based on known or supplied information.

In case of rupture:

Inhalation Specific test data for the substance or mixture is not available. May cause irritation of

respiratory tract.

Eye contact Specific test data for the substance or mixture is not available. Causes serious eye irritation.

(based on components). Irritating to eyes.

Skin contact Specific test data for the substance or mixture is not available. May cause sensitization by

skin contact. Causes skin irritation. (based on components). Repeated or prolonged skin

contact may cause allergic reactions with susceptible persons.

Ingestion Specific test data for the substance or mixture is not available. Ingestion may cause

gastrointestinal irritation, nausea, vomiting and diarrhea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Itching. Rashes. Hives. Redness. May cause redness and tearing of the eyes.

Numerical measures of toxicity

Acute toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 13,025.80 mg/kg



ATEmix (dermal) 8,407.40 mg/kg

Unknown acute toxicity 31.9 % of the mixture consists of ingredient(s) of unknown toxicity

27.2 % of the mixture consists of ingredient(s) of unknown acute oral toxicity

31.9 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity

31.9 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)

31.9 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)

31.9 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

Product Information

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Lithium Cobalt Oxide (CoLiO2)	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rat)	> 5.05 mg/L (Rat) 4 h
Graphite	-	-	> 2000 mg/m³ (Rat) 4 h
Copper	-	-	> 5.11 mg/L (Rat) 4 h
Aluminum	-	-	> 0.888 mg/L (Rat) 4 h
Propylene carbonate	= 29000 mg/kg (Rat)	> 3000 mg/kg (Rabbit)	-
Ethylene carbonate	= 10 g/kg (Rat)	> 26420 mg/kg (Rabbit)	> 730 mg/m ³ (Rat) 8 h
Nickel	> 9000 mg/kg (Rat)	-	> 10.2 mg/L (Rat) 1 h
Bisphenol A - Epichlorohydrin	= 11400 mg/kg (Rat)	-	-
polymer			

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritationClassification based on data available for ingredients. Irritating to skin.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

Respiratory or skin sensitization May cause sensitization by skin contact.

Germ cell mutagenicity No information available.

Carcinogenicity Contains a known or suspected carcinogen. Classification based on data available for

ingredients. May cause cancer.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Lithium Cobalt Oxide	A3	Group 2B	Reasonably Anticipated	Х
(CoLiO2)				
12190-79-3				
Nylon-6	-	Group 3	-	-
25038-54-4				
Nickel	-	Group 2B	Reasonably Anticipated	X
7440-02-0		-		

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

NTP (National Toxicology Program)

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity No information available.



Page 8 / 13

STOT - single exposure No information available.

STOT - repeated exposureCauses damage to organs through prolonged or repeated exposure.

Aspiration hazard No information available.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Very toxic to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Graphite	No data available	96h LC50: > 100 mg/L (Danio rerio)	No data available	No data available
Copper	96h EC50: 0.031 - 0.054 mg/L (Pseudokirchneriella subcapitata) 72h EC50: 0.0426 - 0.0535 mg/L (Pseudokirchneriella subcapitata)	96h LC50: 0.0068 - 0.0156 mg/L (Pimephales promelas) 96h LC50: < 0.3 mg/L (Pimephales promelas) 96h LC50: = 0.052 mg/L (Oncorhynchus mykiss) 96h LC50: = 0.112 mg/L (Poecilia reticulata) 96h LC50: = 0.2 mg/L (Pimephales promelas) 96h LC50: = 0.3 mg/L (Cyprinus carpio) 96h LC50: = 0.8 mg/L (Cyprinus carpio) 96h LC50: = 1.25 mg/L (Lepomis macrochirus)	No data available	48h EC50: = 0.03 mg/L (Daphnia magna)
Propylene carbonate	72h EC50: > 500 mg/L (Desmodesmus subspicatus)	96h LC50: > 1000 mg/L (Cyprinus carpio)	EC50 > 10000 mg/L 17 h	48h EC50: > 500 mg/L (Daphnia magna)
Ethylene carbonate	No data available	96h LC50: > 100 mg/L (Oncorhynchus mykiss)	No data available	No data available
Nickel	96h EC50: 0.174 - 0.311 mg/L (Pseudokirchneriella subcapitata) 72h EC50: = 0.18 mg/L (Pseudokirchneriella subcapitata)	96h LC50: = 1.3 mg/L (Cyprinus carpio) 96h LC50: = 10.4 mg/L (Cyprinus carpio) 96h LC50: > 100 mg/L (Brachydanio rerio)	No data available	48h EC50: = 1 mg/L (Daphnia magna) 48h EC50: > 100 mg/L (Daphnia magna)

Persistence and Degradability

No information available.

Bioaccumulation

Component Information

Chemical name	Partition coefficient
Propylene carbonate	0.48

Mobility No information available.



Other adverse effects No information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste from residues/unused

products

Dispose of in accordance with local regulations. Dispose of waste in accordance with

environmental legislation.

Contaminated packaging Do not reuse empty containers.

California Waste Codes 141

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical name	California Hazardous Waste
Lithium Cobalt Oxide (CoLiO2)	Toxic
12190-79-3	
Aluminum	Ignitable powder
7429-90-5	
Nickel	Toxic powder
7440-02-0	Ignitable powder

14. TRANSPORT INFORMATION

Note:

The transportation of primary lithium cells and batteries is regulated by the International Civil Aviation Organization, International Air Transport Association, International Maritime Dangerous Goods Code and the US Department of Transportation. The batteries must meet the following criteria for shipment: 1. Air shipments must meet the requirements listed in Special Provision A45 of the International Air Transport Association Dangerous Goods Regulations. 2. Meet the requirements for the US Department of Transportation listed in 49 CFR 173.185. 3. The transport of primary lithium batteries is prohibited aboard passenger aircraft. Refer to the Federal Register December 15, 2004 (Hazardous Materials; Prohibited on the Transportation of Primary Lithium Batteries and Cells Aboard Passenger Aircraft; Final Rule)

Lithium batteries shipped as "Lithium batteries", "Lithium batteries packed with equipment", or "Lithium batteries contained in equipment" may not be classified as "Dangerous Goods" when shipped in accordance with "special provision A45 of IATA-DGR" or "special provision

188 of IMO-IMDG Code"

DOT

Proper Shipping Name Hazard Class

Emergency Response Guide

Number

NOT REGULATED

NON-REGULATED N/A

147

TDG Not applicable

Not applicable **MEX**

ICAO Not applicable

IATA Not applicable

NON REGULATED **Proper Shipping Name**

Hazard Class N/A



IMDG/IMO Not applicable

Hazard Class N/A EmS-No. F-A, S-I

RID Not applicable

ADR Not applicable

ADN Not applicable

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

International Inventories

TSCA Contact supplier for inventory compliance status.

DSL/NDSL Contact supplier for inventory compliance status.

EINECS/ELINCS Contact supplier for inventory compliance status.

ENCS Contact supplier for inventory compliance status.

KECL Contact supplier for inventory compliance status.

PICCS Contact supplier for inventory compliance status.

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	CAS No	Weight-%	SARA 313 - Threshold Values %
Lithium Cobalt Oxide (CoLiO2) - 12190-79-3	12190-79-3	27	0.1
Copper - 7440-50-8	7440-50-8	14.2	1.0
Aluminum - 7429-90-5	7429-90-5	11	1.0
Nickel - 7440-02-0	7440-02-0	1.1	0.1

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications. Under the amended regulations at 40 CFR 370, EPCRA 311/312 Tier II reporting for the 2017 calendar year will



Revision Date 22-Dec-2021

need to be consistent with updated hazard classifications.

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Copper 7440-50-8		X	Х	
Nickel 7440-02-0		X	Х	

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Copper	5000 lb		RQ 5000 lb final RQ
7440-50-8			RQ 2270 kg final RQ
Nickel	100 lb		RQ 100 lb final RQ
7440-02-0			RQ 45.4 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical name	California Proposition 65
Nickel - 7440-02-0	carcinogen, 10/1/1989 (metallic)

U.S. State Right-to-Know Regulations

This product may contain substances regulated by state right-to-know regulations.

Chemical name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Lithium Cobalt Oxide (CoLiO2) 12190-79-3	Х		Х	X	Х
Graphite 7782-42-5	Х	Х	Х		
Copper 7440-50-8	Χ	X	Х	Х	Х
Aluminum 7429-90-5	Χ	X	Х	Х	
Ethylene carbonate 96-49-1		X	Х		
Phosphate(1-), hexafluoro-, lithium 21324-40-3	Х				
Nickel 7440-02-0	X	Х	Х	Х	Х

16. OTHER INFORMATION



NFPA Health hazards 1 Flammability 0 Instability 0 **Physical and Chemical**

Properties -Health hazards 0 Physical hazards 0 Personal Protection X HMIS Flammability 0

Prepared By Product Stewardship

23 British American Blvd. Latham, NY 12110 1-800-572-6501

Revision Date 22-Dec-2021

No information available **Revision Note**

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet



SAFETY DATA SHEET

Issuing Date No data available

Revision Date 22-Dec-2021

Revision Number 1

NGHS / English



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

1. IDENTIFICATION

Product identifier

Product Name Rechargeable Li-ion Battery L21M3PE1 - by Simplo

Other means of identification

Product Code(s) 1674676

Recommended use of the chemical and restrictions on use

Recommended Use Lithium Ion Battery

Restrictions on use No information available

Details of the supplier of the safety data sheet

Supplier Identification Lenovo LNB laptops

Address Songtao Road 696

shanghai shanghai 201203 CN

Telephone Phone:18116118603

E-mail yuanbb1@lenovo.com

Emergency telephone number

Company Emergency Phone

Number

18116118603

2. HAZARDS IDENTIFICATION

Classification

Acute toxicity - Oral	Category 3
Acute toxicity - Dermal	Category 4
Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Skin corrosion/irritation	Category 2



Serious eye damage/eye irritation	Category 1
Skin sensitization	Category 1
Carcinogenicity	Category 1B
Reproductive toxicity	Category 1B
Specific target organ toxicity (repeated exposure)	Category 1

This is a battery. In case of rupture: the above hazards exist.

Appearance Solid Physical state Solid Odor No information available

GHS Label elements, including precautionary statements

Danger

Hazard statements

Toxic if swallowed
Harmful in contact with skin
Harmful if inhaled
Causes skin irritation
Causes serious eye damage
May cause an allergic skin reaction
May cause cancer
May damage fertility or the unborn child

Causes damage to organs through prolonged or repeated exposure



Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Wear protective gloves/protective clothing/eye protection/face protection

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Use only outdoors or in a well-ventilated area

Contaminated work clothing must not be allowed out of the workplace

Do not breathe dust/fume/gas/mist/vapors/spray

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

Specific treatment (see supplemental first aid instructions on this label)

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing Immediately call a POISON CENTER or doctor

Skin

IF ON SKIN: Wash with plenty of water and soap

Call a POISON CENTER or doctor if you feel unwell

Take off contaminated clothing and wash it before reuse

If skin irritation or rash occurs: Get medical advice/attention

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing



Page 2/14

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor Rinse mouth

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other information

Very toxic to aquatic life with long lasting effects.

Unknown acute toxicity

27 % of the mixture consists of ingredient(s) of unknown toxicity

- 25.7 % of the mixture consists of ingredient(s) of unknown acute oral toxicity
- 27 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity
- 27 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)
- 27 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)
- 27 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance

Not applicable.

<u>Mixture</u>

Chemical name	CAS No	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
Lithium Cobalt Oxide (CoLiO2)	12190-79-3	40.7	-	-
Graphite	7782-42-5	23.2	-	-
Copper	7440-50-8	7.6	-	-
Aluminum	7429-90-5	5.2	-	-
1-Methyl-2-pyrrolidone	872-50-4	4.3	-	-
Ethanamine, 2-chloro-N,N-diethyl-, hydrochloride	869-24-9	3	-	-
Ethylene carbonate	96-49-1	2.5	-	-
Phosphate(1-), hexafluoro-, lithium	21324-40-3	1.5	-	-
Bisphenol A - Phosgene copolymer	25971-63-5	1.5	-	-
Aluminum oxide	1344-28-1	1.2	-	-
Propylene carbonate	108-32-7	1	-	-
Nickel	7440-02-0	0.42	-	-
Bisphenol A - Epichlorohydrin polymer	25068-38-6	0.4	-	-

4. FIRST AID MEASURES

Description of first aid measures



Page 3/14

Show this safety data sheet to the doctor in attendance. Immediate medical attention is **General advice**

required. IF exposed or concerned: Get medical advice/attention. First aid is upon rupture of

sealed battery. In case of rupture:

Inhalation Remove to fresh air. Get medical attention immediately if symptoms occur. If breathing has

stopped, give artificial respiration. Get medical attention immediately. If symptoms persist,

call a physician.

Eve contact Get immediate medical advice/attention. Rinse immediately with plenty of water, also under

the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do.

Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area.

Skin contact Wash off immediately with soap and plenty of water for at least 15 minutes. May cause an

allergic skin reaction. If symptoms persist, call a physician.

Do NOT induce vomiting. Clean mouth with water and drink afterwards plenty of water. Ingestion

Never give anything by mouth to an unconscious person. Get medical attention.

Self-protection of the first aider Ensure that medical personnel are aware of the material(s) involved, take precautions to

protect themselves and prevent spread of contamination. Avoid contact with skin, eyes or clothing. Avoid breathing dust/fume/gas/mist/vapors/spray. Use personal protective

equipment as required. See section 8 for more information.

Most important symptoms and effects, both acute and delayed

Burning sensation. Itching. Rashes. Hives. Coughing and/ or wheezing. Difficulty in **Symptoms**

breathing.

Indication of any immediate medical attention and special treatment needed

Note to physicians May cause sensitization in susceptible persons. Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media Use extinguishing measures that are appropriate to local circumstances and the

surrounding environment.

CAUTION: Use of water spray when fighting fire may be inefficient. Large Fire

Unsuitable extinguishing media Do not scatter spilled material with high pressure water streams.

Specific hazards arising from the

chemical

Product is or contains a sensitizer. May cause sensitization by skin contact.

Hazardous Combustion Products Carbon oxides.

Explosion Data

Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge

Special protective equipment for

fire-fighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout

gear. Use personal protection equipment.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures



Personal precautions Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal

protective equipment as required. Evacuate personnel to safe areas. Keep people away

from and upwind of spill/leak. Avoid generation of dust. Do not breathe dust.

Other Information Refer to protective measures listed in Sections 7 and 8.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Pick up and transfer to properly labeled containers.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling

In case of rupture: Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Do not eat, drink or smoke when using this product. In case of insufficient ventilation, wear suitable respiratory equipment. Take off contaminated clothing and wash before reuse. Remove contaminated clothing and shoes. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid generation of dust.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Keep out of the reach

of children. Store locked up.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Limits

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Lithium Cobalt Oxide (CoLiO2) 12190-79-3	TWA: 0.02 mg/m ³	-	
Graphite 7782-42-5	TWA: 2 mg/m³ respirable particulate matter all forms except graphite fibers	TWA: 15 mg/m³ total dust synthetic TWA: 5 mg/m³ respirable fraction synthetic (vacated) TWA: 2.5 mg/m³ respirable dust natural (vacated) TWA: 10 mg/m³ total dust synthetic (vacated) TWA: 5 mg/m³ respirable fraction synthetic TWA: 15 mppcf natural	IDLH: 1250 mg/m³ TWA: 2.5 mg/m³ respirable dust
Copper 7440-50-8	TWA: 0.2 mg/m³ fume	TWA: 0.1 mg/m³ fume TWA: 1 mg/m³ dust and mist (vacated) TWA: 0.1 mg/m³ Cu dust, fume, mist	IDLH: 100 mg/m³ dust, fume and mist TWA: 1 mg/m³ dust and mist TWA: 0.1 mg/m³ fume



	T TIAVA 4 / 0		T14/4 45			
Aluminum	TWA: 1 mg/m ³			mg/m³ total dust		A: 10 mg/m³ total dust
7429-90-5	particulate	matter		ng/m³ respirable	I WA:	5 mg/m³ respirable dust
				fraction		
			(vacated) IV	VA: 15 mg/m³ total		
				dust		
) TWA: 5 mg/m³		
				able fraction		
Phosphate(1-), hexafluo	ro-, TWA: 2.5 r	ng/m³ F		2.5 mg/m ³ F		IDLH: 250 mg/m ³ F
lithium			(vacated)	TWA: 2.5 mg/m ³		
21324-40-3						
Aluminum oxide	TWA: 1 mg/m ³			mg/m³ total dust		
1344-28-1	particulate	matter		ng/m³ respirable		
				fraction		
			(vacated) TV	VA: 10 mg/m ³ total		
				dust		
) TWA: 5 mg/m³		
				able fraction		
Nickel	TWA: 1.5	mg/m³		A: 1 mg/m³		IDLH: 10 mg/m ³
7440-02-0			(vacated) TWA: 1 mg/m ³		TWA: 0.015 mg/m ³
Chemical name	Alberta	British (Columbia	Ontario TWAE	V	Quebec
Lithium Cobalt Oxide	TWA: 0.02 mg/m ³	TWA: 0.	02 mg/m³	TWA: 0.02 mg/	m³	TWA: 0.02 mg/m ³
(CoLiO2)						
12190-79-3						
Graphite	TWA: 2 mg/m ³	TWA: 2	2 mg/m³	TWA: 2 mg/m	3	TIMA . O
7782-42-5				1	ĭ	TWA: 2 mg/m ³
Copper				1		TVVA: 2 mg/m ³
7440-50-8	TWA: 0.2 mg/m ³	TWA:	1 mg/m ³	TWA: 0.2 mg/r		TWA: 2 mg/m ³ TWA: 0.2 mg/m ³
	TWA: 0.2 mg/m ³ TWA: 1 mg/m ³		1 mg/m³ .2 mg/m³		n ³	·
Aluminum		TWA: 0		TWA: 0.2 mg/r	n ³ 3	TWA: 0.2 mg/m ³
Aluminum 7429-90-5	TWA: 1 mg/m ³	TWA: 0	.2 mg/m³	TWA: 0.2 mg/r TWA: 1 mg/m	n ³ 3	TWA: 0.2 mg/m³ TWA: 1 mg/m³
7429-90-5	TWA: 1 mg/m ³	TWA: 0	.2 mg/m³	TWA: 0.2 mg/r TWA: 1 mg/m	n ³ 3	TWA: 0.2 mg/m³ TWA: 1 mg/m³
	TWA: 1 mg/m ³	TWA: 0	.2 mg/m³	TWA: 0.2 mg/r TWA: 1 mg/m TWA: 1 mg/m	n ³ 3	TWA: 0.2 mg/m³ TWA: 1 mg/m³
7429-90-5 1-Methyl-2-pyrrolidone 872-50-4	TWA: 1 mg/m ³ TWA: 10 mg/m ³	TWA: 0 TWA: 1	.2 mg/m ³ .0 mg/m ³	TWA: 0.2 mg/r TWA: 1 mg/m TWA: 1 mg/m	n ³ 3 3	TWA: 0.2 mg/m³ TWA: 1 mg/m³ TWA: 10 mg/m³
7429-90-5 1-Methyl-2-pyrrolidone 872-50-4 Phosphate(1-),	TWA: 1 mg/m ³	TWA: 0 TWA: 1	.2 mg/m³	TWA: 0.2 mg/r TWA: 1 mg/m TWA: 1 mg/m	n ³ 3 3	TWA: 0.2 mg/m³ TWA: 1 mg/m³
7429-90-5 1-Methyl-2-pyrrolidone 872-50-4	TWA: 1 mg/m ³ TWA: 10 mg/m ³	TWA: 0 TWA: 1	.2 mg/m ³ .0 mg/m ³	TWA: 0.2 mg/r TWA: 1 mg/m TWA: 1 mg/m	n ³ 3 3	TWA: 0.2 mg/m³ TWA: 1 mg/m³ TWA: 10 mg/m³
7429-90-5 1-Methyl-2-pyrrolidone 872-50-4 Phosphate(1-), hexafluoro-, lithium 21324-40-3	TWA: 1 mg/m³ TWA: 10 mg/m³ TWA: 2.5 mg/m³	TWA: 0 TWA: 1	.2 mg/m ³ .0 mg/m ³	TWA: 0.2 mg/rr TWA: 1 mg/m TWA: 1 mg/m TWA: 400 mg/r	n ³ 3 3 m ³	TWA: 0.2 mg/m³ TWA: 1 mg/m³ TWA: 10 mg/m³ TWA: 2.5 mg/m³
7429-90-5 1-Methyl-2-pyrrolidone 872-50-4 Phosphate(1-), hexafluoro-, lithium	TWA: 1 mg/m ³ TWA: 10 mg/m ³	TWA: 0 TWA: 1	.2 mg/m ³ .0 mg/m ³	TWA: 0.2 mg/r TWA: 1 mg/m TWA: 1 mg/m	n ³ 3 3 m ³	TWA: 0.2 mg/m³ TWA: 1 mg/m³ TWA: 10 mg/m³
7429-90-5 1-Methyl-2-pyrrolidone 872-50-4 Phosphate(1-), hexafluoro-, lithium 21324-40-3 Aluminum oxide	TWA: 1 mg/m³ TWA: 10 mg/m³ TWA: 2.5 mg/m³	TWA: 0 TWA: 1 TWA: 2	.2 mg/m ³ .0 mg/m ³	TWA: 0.2 mg/rr TWA: 1 mg/m TWA: 1 mg/m TWA: 400 mg/r	n ³ 3 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7	TWA: 0.2 mg/m³ TWA: 1 mg/m³ TWA: 10 mg/m³ TWA: 2.5 mg/m³

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992). See section 15 for national exposure control parameters.

Appropriate engineering controls

Engineering controls

Eyewash stations Ventilation systems.

Showers

Individual protection measures, such as personal protective equipment

Eye/face protection Tight sealing safety goggles.

Hand protection Wear suitable gloves. Impervious gloves.

Skin and body protection Wear suitable protective clothing. Long sleeved clothing.

Respiratory protection No protective equipment is needed under normal use conditions. If exposure limits are

exceeded or irritation is experienced, ventilation and evacuation may be required.



General hygiene considerations

Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product. Avoid breathing dust/fume/gas/mist/vapors/spray.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Solid Appearance Solid

OdorNo information availableColorNo information availableOdor ThresholdNo information available

Property Values Remarks Method

рΗ No data available None known No data available None known Melting / freezing point Boiling point / boiling range No data available None known **Flash Point** No data available None known **Evaporation Rate** No data available None known Flammability (solid, gas) No data available None known Flammability Limit in Air None known

Upper flammability limitNo data availableLower flammability limitNo data available

Vapor pressureNo data availableNone knownVapor densityNo data availableNone knownRelative densityNo data availableNone known

Water Solubility Insoluble in water

Solubility(ies) No data available None known

Partition coefficient: n-octanol/water1

Autoignition temperatureNo data availableNone knownDecomposition temperatureNo data availableNone knownKinematic viscosityNo data availableNone knownDynamic viscosityNo data availableNone known

Other Information

Explosive properties No information available Oxidizing properties No information available **Softening Point** No information available **Molecular Weight** No information available No information available **VOC Content (%) Liquid Density** No information available **Bulk Density** No information available **Particle Size** No information available **Particle Size Distribution** No information available

10. STABILITY AND REACTIVITY

Reactivity No information available.

Chemical stability Stable under normal conditions.

Possibility of Hazardous Reactions None under normal processing.

Hazardous Polymerization Hazardous polymerization does not occur.



Conditions to avoid Excessive heat.

Incompatible materials Strong acids. Strong bases. Strong oxidizing agents.

Hazardous Decomposition Products Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information Product does not present an acute toxicity hazard based on known or supplied information.

In case of rupture:

Inhalation Specific test data for the substance or mixture is not available. May cause irritation of

respiratory tract. Harmful by inhalation. (based on components).

Eye contact Specific test data for the substance or mixture is not available. Causes serious eye

damage. (based on components). May cause burns. Severely irritating to eyes. May cause

irreversible damage to eyes.

Skin contact Specific test data for the substance or mixture is not available. May cause sensitization by

skin contact. Causes skin irritation. (based on components). Repeated or prolonged skin

contact may cause allergic reactions with susceptible persons.

Ingestion Specific test data for the substance or mixture is not available. Toxic if swallowed. (based

on components). Ingestion may cause gastrointestinal irritation, nausea, vomiting and

diarrhea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Redness. Burning. May cause blindness. Itching. Rashes. Hives. May cause redness and

tearing of the eyes. Coughing and/ or wheezing.

Numerical measures of toxicity

Acute toxicity

The following values are calculated based on chapter 3.1 of the GHS document

 ATEmix (oral)
 123.20 mg/kg

 ATEmix (dermal)
 1,114.10 mg/kg

 ATEmix (inhalation-dust/mist)
 1.2191 mg/L

Unknown acute toxicity 27 % of the mixture consists of ingredient(s) of unknown toxicity

25.7 % of the mixture consists of ingredient(s) of unknown acute oral toxicity

27 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity

27 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)

27 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)

27 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

Product Information

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Lithium Cobalt Oxide (CoLiO2)	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rat)	> 5.05 mg/L (Rat) 4 h
Graphite	-	-	> 2000 mg/m³ (Rat) 4 h
Copper	-	-	> 5.11 mg/L (Rat) 4 h



Aluminum	-	-	> 0.888 mg/L (Rat) 4 h
1-Methyl-2-pyrrolidone	= 3914 mg/kg (Rat)	= 8 g/kg(Rabbit)	> 5.1 mg/L (Rat) 4 h
Ethanamine,	-	-	= 103 mg/m ³ (Rat) 4 h
2-chloro-N,N-diethyl-,			
hydrochloride			
Ethylene carbonate	= 10 g/kg (Rat)	> 26420 mg/kg (Rabbit)	> 730 mg/m³ (Rat) 8 h
Aluminum oxide	> 5000 mg/kg (Rat)	-	-
Propylene carbonate	= 29000 mg/kg (Rat)	> 3000 mg/kg (Rabbit)	-
Nickel	> 9000 mg/kg (Rat)	-	> 10.2 mg/L (Rat) 1 h
Bisphenol A - Epichlorohydrin	= 11400 mg/kg (Rat)	-	-
polymer			

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritationClassification based on data available for ingredients. Irritating to skin.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes burns. Risk of serious

damage to eyes.

Respiratory or skin sensitization May cause sensitization by skin contact.

Germ cell mutagenicity No information available.

Carcinogenicity Contains a known or suspected carcinogen. Classification based on data available for

ingredients. May cause cancer.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Lithium Cobalt Oxide	A3	Group 2B	Reasonably Anticipated	X
(CoLiO2)		-		
12190-79-3				
Nickel	-	Group 2B	Reasonably Anticipated	X
7440-02-0		-		

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

NTP (National Toxicology Program)

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity Contains a known or suspected reproductive toxin. Classification based on data available

for ingredients. May damage fertility or the unborn child.

STOT - single exposure No information available.

STOT - repeated exposureCauses damage to organs through prolonged or repeated exposure.

Aspiration hazard No information available.

12. ECOLOGICAL INFORMATION



Page 9/14

Ecotoxicity

Very toxic to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Graphite	No data available	96h LC50: > 100 mg/L (Danio rerio)	No data available	No data available
Copper	(Pseudokirchneriella subcapitata) 72h EC50: 0.0426 - 0.0535 mg/L (Pseudokirchneriella subcapitata)	96h LC50: 0.0068 - 0.0156 mg/L (Pimephales promelas) 96h LC50: < 0.3 mg/L (Pimephales promelas) 96h LC50: = 0.052 mg/L (Oncorhynchus mykiss) 96h LC50: = 0.112 mg/L (Poecilia reticulata) 96h LC50: = 0.2 mg/L (Pimephales promelas) 96h LC50: = 0.3 mg/L (Cyprinus carpio) 96h LC50: = 0.8 mg/L (Cyprinus carpio) 96h LC50: = 1.25 mg/L (Lepomis macrochirus)		48h EC50: = 0.03 mg/L (Daphnia magna)
1-Methyl-2-pyrrolidone	72h EC50: > 500 mg/L (Desmodesmus subspicatus)	96h LC50: = 1072 mg/L (Pimephales promelas) 96h LC50: = 1400 mg/L (Poecilia reticulata) 96h LC50: = 832 mg/L (Lepomis macrochirus)	No data available	48h EC50: = 4897 mg/L (Daphnia magna)
Ethanamine, 2-chloro-N,N-diethyl-, hydrochloride	No data available	96h LC50: = 150 mg/L (Oncorhynchus mykiss)	No data available	No data available
Ethylene carbonate	No data available	96h LC50: > 100 mg/L (Oncorhynchus mykiss)	No data available	No data available
Propylene carbonate	72h EC50: > 500 mg/L (Desmodesmus subspicatus)	96h LC50: > 1000 mg/L (Cyprinus carpio)	EC50 > 10000 mg/L 17 h	48h EC50: > 500 mg/L (Daphnia magna)
Nickel	96h EC50: 0.174 - 0.311 mg/L (Pseudokirchneriella subcapitata) 72h EC50: = 0.18 mg/L (Pseudokirchneriella subcapitata)	96h LC50: = 1.3 mg/L (Cyprinus carpio) 96h LC50: = 10.4 mg/L (Cyprinus carpio) 96h LC50: > 100 mg/L (Brachydanio rerio)	No data available	48h EC50: = 1 mg/L (Daphnia magna) 48h EC50: > 100 mg/L (Daphnia magna)

Persistence and Degradability

No information available.

Bioaccumulation

Component Information

Chemical name	Partition coefficient
1-Methyl-2-pyrrolidone	-0.46
Propylene carbonate	0.48

Mobility No information available.

Other adverse effects No information available.



13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste from residues/unused

products

Dispose of in accordance with local regulations. Dispose of waste in accordance with

Revision Date 22-Dec-2021

environmental legislation.

Contaminated packaging Do not reuse empty containers.

141 California Waste Codes

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical name	California Hazardous Waste
Lithium Cobalt Oxide (CoLiO2)	Toxic
12190-79-3	
Aluminum	Ignitable powder
7429-90-5	·
Nickel	Toxic powder
7440-02-0	Ignitable powder

14. TRANSPORT INFORMATION

Note:

The transportation of primary lithium cells and batteries is regulated by the International Civil Aviation Organization, International Air Transport Association, International Maritime Dangerous Goods Code and the US Department of Transportation. The batteries must meet the following criteria for shipment: 1. Air shipments must meet the requirements listed in Special Provision A45 of the International Air Transport Association Dangerous Goods Regulations. 2. Meet the requirements for the US Department of Transportation listed in 49 CFR 173.185. 3. The transport of primary lithium batteries is prohibited aboard passenger aircraft. Refer to the Federal Register December 15, 2004 (Hazardous Materials; Prohibited on the Transportation of Primary Lithium Batteries and Cells Aboard Passenger Aircraft; Final Rule)

Lithium batteries shipped as "Lithium batteries", "Lithium batteries packed with equipment", or "Lithium batteries contained in equipment" may not be classified as "Dangerous Goods" when shipped in accordance with "special provision A45 of IATA-DGR" or "special provision 188 of IMO-IMDG Code"

DOT

Proper Shipping Name Hazard Class

Emergency Response Guide

Number

NOT REGULATED

NON-REGULATED

N/A 147

TDG Not applicable

MEX Not applicable

ICAO Not applicable

Not applicable **Proper Shipping Name** NON REGULATED

Hazard Class N/A

IMDG/IMO Not applicable

Hazard Class N/A EmS-No. F-A, S-I

RID Not applicable

ADR Not applicable

Not applicable **ADN**

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

International Inventories

Contact supplier for inventory compliance status. **TSCA** Contact supplier for inventory compliance status. **DSL/NDSL** Contact supplier for inventory compliance status. **EINECS/ELINCS** Contact supplier for inventory compliance status. **ENCS KECL** Contact supplier for inventory compliance status. **PICCS** Contact supplier for inventory compliance status. Contact supplier for inventory compliance status. **AICS**

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	CAS No	Weight-%	SARA 313 - Threshold Values %
Lithium Cobalt Oxide (CoLiO2) - 12190-79-3	12190-79-3	40.7	0.1
Copper - 7440-50-8	7440-50-8	7.6	1.0
Aluminum - 7429-90-5	7429-90-5	5.2	1.0
1-Methyl-2-pyrrolidone - 872-50-4	872-50-4	4.3	1.0
Aluminum oxide - 1344-28-1	1344-28-1	1.2	1.0
Nickel - 7440-02-0	7440-02-0	0.42	0.1

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate



classifications. Under the amended regulations at 40 CFR 370, EPCRA 311/312 Tier II reporting for the 2017 calendar year will need to be consistent with updated hazard classifications.

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Copper 7440-50-8		X	Х	
Nickel 7440-02-0		Х	Х	

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Copper 7440-50-8	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Nickel 7440-02-0	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical name	California Proposition 65		
1-Methyl-2-pyrrolidone - 872-50-4	Developmental		
Nickel - 7440-02-0	carcinogen, 10/1/1989 (metallic)		

U.S. State Right-to-Know Regulations

This product may contain substances regulated by state right-to-know regulations.

Chemical name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Lithium Cobalt Oxide (CoLiO2) 12190-79-3	X		Х	X	Х
Graphite 7782-42-5	Χ	X	Х		
Copper 7440-50-8	Χ	X	Х	X	Х
Aluminum 7429-90-5	Χ	X	Х	Х	
1-Methyl-2-pyrrolidone 872-50-4	Х	Х	Х	Х	
Ethylene carbonate 96-49-1		Х	Х		
Phosphate(1-), hexafluoro-, lithium 21324-40-3	Х				
Aluminum oxide 1344-28-1	Х	Х	Х	Х	
Nickel	Χ	X	Х	X	Х



7440-02-0

16. OTHER INFORMATION

NFPA Health hazards 1 Flammability 0 Instability 0 Physical and Chemical

Properties -

Health hazards 0 Flammability 0 Physical hazards 0 Personal Protection X

Prepared By Product Stewardship

23 British American Blvd. Latham, NY 12110 1-800-572-6501

Revision Date 22-Dec-2021

Revision Note No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet

