Safety Data Sheet (SDS)

The content and format of this SDS is accordant with 29 CFR 1910.1200 (OSHA standard)

1. Identification

Product details:
Product name: <u>Refrigerator</u>
Recommended use of the chemical and restrictions on use: Refrigerating machines. Restrictions on use: Do NOT use it in an application which may contaminate food or do harm to human health.
Manufacturer/Supplier: NINGBO LAMO ELECTRIC APPLIANCE CO., LTD.
Address: RONGYU VILLAGE, XINPU TOWN, CIXI CITY, ZHEJIANG PROVINCE, CHINA.
Tel.: (+86) 574 56776255
Fax: (+86) 574 56776255
Email: trade16@lamo-china.com
Distributor: Curtis International Ltd.
Address: 7045 Beckett Drive, Unit 15, Mississauga,Ontario, Canada L5S 2A3
Further information obtainable from: NINGBO LAMO ELECTRIC APPLIANCE CO., LTD.
Information in case of emergency: (+86) 574 56776255

2. Hazards identification

GHS classification:	
Physical hazards:	Flammable gases - Category 1
	Gases under pressure - Liquefied gas
Health hazards:	Not classified
Environmental hazards:	Not classified

Signal Word: Danger

Pictograms:



Hazard Statements:

H220: Extremely flammable gas.

H280: Contains gas under pressure; may explode if heated.

Precautionary Statements:

P210: Keep away from heat/sparks/open flames/hot surfaces. -No smoking.

Response Precautionary Statements:

P377: Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

P381: Eliminate all ignition sources if safe to do so.

Storage precautionary statements:

P403: Store in well-ventilated place.

P410 + P403: Protect from sunlight. Store in a well-ventilated place.

Disposal precautionary statements:

No special requirements.

3. Composition/information on ingredients

Product description: substance ($\sqrt{}$); preparation/mixture ()

Ingredient (s)	CAS No.	EC No.	% by weight
Isobutane	75-28-5	200-857-2	100

4. First aid measures

Persons using this product should consult a physician or other medical professional if an accident involving this product results in injury. Specific first-aid measures are as follows:

Inhalation: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin Contact: Wash with plenty water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.

Eyes Contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Ingestion: Unlikely route of exposure. As this product is a gas, refer to the section "Inhalation". Do not induce vomiting without medical advice. Obtain immediate medical attention.

Acute effect and delayed effect: Acute effect: Not found. Delayed effect: Not found.

Personal protective equipment: Wear protective gloves/protective clothing/eye protection/face protection when necessary.

Indication of immediate medical attention and treatment needed, if necessary: Treat according to symptoms and exposure dose.

5. Fire-fighting measures

Extinguishing Media: Dry powder, water spray, alcohol-resistant foam and CO2.

Unsuitable Extinguishing Media: Discharging cylinder shape water from fire hose may lead to spread fire to the surroundings.

Special hazards arising from the chemical: Extremely flammable gas. Contains gas under pressure; may explode if heated. Exercise caution when fighting any chemical fire. Vapors are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapors. In case of fire, decomposition products may include the following materials: carbon dioxide and monoxide.

Fire Fighting Method:

For initial fire, use dry powder, carbon dioxide, etc.

For large fire, it is effective to use fire foam, etc. to shut off air supply.

Deny unnecessary entry to the place around the fire.

Remove containers from fire area if it can be done without risk.

Cool surrounding facilities, etc. with water spray.

Extinguish fire from upwind, and the fire extinguishing method should be appropriate to the situation in the surroundings.

Special actions for fire-fighters: Firefighters must wear self-contained breathing apparatus and full protective equipment.

Check whether the protective equipment is in good condition before use.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Use proper personal protective equipment as indicated in Section 8.

Environmental precautions: Keep cleaning run-offs out of municipal sewers and open bodies of water. Comply with local and national laws and regulations.

Methods and material for containment and cleaning up:

Stop the source of the release, if safe to do so. Consider the use of water spray to disperse vapors. Isolate the area until gas has dispersed. Ventilate and gas test area before entering. Contact competent authorities after a spill.

7. Handling and storage

Precautions for safe handling:

The substance must be handled in accordance with good industrial hygiene and safety procedures.

Refer to supplier's / manufacturer's handling instructions.

Handle and open container with care. Caution when opening, pressurized container.

Protect from sunlight and do not expose to temperatures exceeding 50° C (122 °F).

Do not spray on a naked flame or any incandescent material.

Do not use in area without adequate ventilation.

Protect containers from physical damage; do not drag, roll, slide or drop.

Do not pierce or burn, even after use.

Leave valve protection caps in place until the container is ready for use.

Close container valve after each use and when empty, even if still connected to equipment.

Do not remove or deface labels provided by the supplier for the identification of the container contents.

Keep away from heat/sparks/open flames/hot surfaces. -No smoking.

Conditions for safe storage, including any incompatibilities: Keep containers tightly closed in a dry, cool and well-ventilated place, away from any ignition or heat sources. Store in original container. Container valves or caps should be in place.

Incompatible substances or mixtures: Avoid storage with oxidizing products, acids and, in general, with chemicals. Avoid storage with tools or equipment that may cause sparks.

Packing material: No relevant information.

8. Exposure controls/personal protection

Occupational Exposure Limits:

Ingredients	OSHA PEL-TWA	ACGIH TLV-TWA
Isobutane (CAS: 75-28-5)		1000 ppm

Engineering Controls:

Use this product only in closed systems fully or with local exhaust ventilation.

Install washer eyes and safety showers near to the handling and storage area.

Shows the location of these facilities, with a clear and prominent warning board.

Personal Protective Equipment (For workers): Protection of Hands: Wear protective gloves.



Protection of Eyes: Safety glasses with side-shields or face shield recommended to wear.



Respiratory Protection: In gas leak case, to wear compressed air breathing apparatus is recommended.



Protection of Body: Wear anti-static and flame-retardant safety-clothing.



General protective and hygienic measures:

Wash hands before breaks and at the end of work.

9. Physical and chemical properties

General Information				
Form	Liquefied gas			
Color	Colorless			
Odor	Odorless			
Odor threshold	No data available			
рН	No data available			
Melting point/freezing point	-159.0℃			
Initial boiling point and boiling range	-12.0°C			
Flash point	-82.8°C			
Evaporation rate	No data available			
Flammability (solid, gas, etc.)	Extremely flammable gas.			
	Contains gas under pressure; may explode if heated.			
Upper/lower flammability or explosive limits	No data available			
Vapor pressure	No data available			
Vapor density	No data available			

No data available
Slightly soluble in water
No data available
-

10. Stability and reactivity

Reactivity and Chemical stability: Stable under normal handling and storage conditions.

Possibility of hazardous reactions: May react violently with oxidants. Can form explosive mixture with air.

Conditions to Avoid: Contains gas under pressure, may explode if heated. Protect from sunlight and do not expose to temperatures exceeding 50 °C. Keep away from heat, sparks, open flame or other sources of ignition. Do not smoke. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material.

Incompatible materials: Avoid storage with oxidizing products, acids and, in general, with chemicals. Avoid storage with tools or equipment that may cause sparks.

Hazardous decomposition products: In case of fire, decomposition products may include the following materials: carbon dioxide and monoxide.

11. Toxicological information

Product Toxicity Data:

Ingredient (s)	CAS No.	LD 50/LC 50 (Median lethal dose)	
Isobutane 75-28-5		Acute toxicity (inhalation) LC50: 520,400 ppm/120min (mouse	
		Data source: ECHA	
Classification of the whole product:		Not classified	
Skin corrosion/irritation		No classification for this product.	
Serious eye damage/eye irritation		No classification for this product.	
Respiratory sensitizer		No classification for this product.	
Skin sensitizer		No classification for this product.	
Germ cell mutagenicity		No classification for this product.	
Carcinogenicity		No classification for this product.	
Reproductive Toxicity Specific target organ toxicity, single exposure:		No classification for this product.	
		No classification for this product.	
Specific target organ toxicity, repe	ated exposure:	No classification for this product.	
Aspiration hazard		No classification for this product.	

12. Ecological information

Ecotoxicity: Isobutane (CAS: 75-28-5): 96h-LC₅₀: 49.9 mg/L, fish (ECHA) 48h-LC₅₀: 27.14 mg/L, aquatic invertebrates (Daphnia sp.) (ECHA) Classification of the whole product: Not classified **Persistence and degradability:** No data available. **Bioaccumulative potential:** No data available. **Mobility in Soil:** No data available **Other adverse effects:** No relevant information.

13. Disposal considerations

Waste treatment methods:

It is recommended to use physical and chemical treatment methods for waste disposal.

Any disposal practice must be in compliance with country, local, state, and federal laws and regulations.

Generally this product will not contaminate the packaging, so the packaging can be disposed of as non-hazardous waste.

14. Transport Information

DOT/Air-Transportation- IATA/ICAO/Sea-Transportation-IMO/IMDG: UN proper shipping name: <u>Refrigerating machines</u> Transport hazard class(es): 2.1 UN number: 3358 Packing Group: Not applicable Packing Group Symbol:



Marine Pollutant (Yes/No): No EMS NO.: F-D S-U Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code): Not applicable.

Special precautions:

Check whether the package is completed or sealed before transporting; make sure no damage of packages and prevent goods from falling down during transporting; the transport vehicle should be equipped with facilities for fire-fighting and accidental release handling; do NOT transport this product together with incompatible substances; stay away from fire and areas of high temperature during stopovers.

15. Regulatory information

United States:

Section 355 (extremely hazardous substances): Not listed.

SARA 313:

Chemical Name	CAS No.	Weight-%	SARA 313 – Threshold Values %
Not applicable	Not applicable	Not applicable	Not applicable

Clean Water Act:

Chemical Name	CWA - Reportable	CWA - Hazardous	CWA - Priority	CWA - Toxic
	Quantities	Substances	Pollutants	Pollutants
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
Toxic Substances Control Act (TSCA):				
Ingred	ient (s)	CAS No.	TSCA Inventory	
Isobutane		75-28-5	Listed	
Carcinogenicity catego	wigge Not applicable	·		-

Canada Domestic Substances List (DSL):

Ingredient (s)	CAS No.	DSL
Isobutane	75-28-5	Listed

Canada Non-domestic Substance List (NDSL): Not listed.

Candidate List of Substances of very high concern (SVHC) according to ECHA: Not listed.

REACH Regulation Annex XVII Regulation List: Not listed.

REACH Regulation Annex XIV Authorization List: Not listed.

Germany – WGK: Not classified.

(EC) 1272/2008 Annex VI Table 3.1:

Ingredient(s)	EC No. 1272/2008 Classification		
	CLASS. CODE	HAZARD CODE	
Isobutane (CAS: 75-28-5)	Flam. Gas 1	H220	
	Press. Gas		

Chemical Safety Assessment: A Chemical Safety Assessment has not been carried out.

16. Other information

DISCLAIMER:

All the information of this SDS is true and effective, and only for reference. Our company will not control the way how people use it, neither will we be responsible for any consequence. The users shall decide how to properly use the product or adopt certain production way for some special purpose. The above-mentioned precautionary measures are helpful to avoid damage to the property or life safety during the operation or use of this product.

References:

GHS Annex II GHS SDS Instruction ANSI Z400.1/Z129.1-2010 OSHA Hazard Communication Standard (HCS) 2012

Full description of some acronyms:

CAS-Chemical Abstracts Service EINECS-European Inventory of Existing Commercial Chemical Substances IMO-International Maritime Organization IMDG-International Maritime Dangerous Goods IATA-International Air Transport Association ICAO-International Civil Aviation Organization ICAO-International Civil Aviation Organization StSA-Toxic Substances Control Act OSHA-Occupational Safety and Health Administration ACGIH- American Conference of Governmental Industrial Hygienists ECHA- European Chemicals Agency NITE-CHRIP- Japan National Institute of Technology and Evaluation-Chemical Risk Information Platform

The Issuing date: March 23, 2022 SDS Version: 1.0