SAFETY DATA SHEET

Issuing Date 26-Dec-2023

Revision Date 21-Dec-2023

Revision Number 1

NGHS / English

(U_L)

The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

1. IDENTIFICATION

Product identifier

Product Name Rechargeable Li-ion Battery L22M3PG1 by Simplo

Other means of identification

Product Code(s) 1776252

Recommended use of the chemical and restrictions on use

Recommended Use Lithium Ion Battery

Restrictions on use No information available

Details of the supplier of the safety data sheet

Supplier Identification Lenovo LNB laptops

Address Songtao Road 696

shanghai shanghai 201203 CN

Telephone Phone:18116118603

E-mail yuanbb1@lenovo.com

Emergency telephone number

Company Emergency Phone

Number

18116118603

2. HAZARDS IDENTIFICATION

Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Skin sensitization	Category 1
Carcinogenicity	Category 1B



Specific target organ toxicity (repeated exposure)

Category 1

This is a battery. In case of rupture: the above hazards exist.

Appearance Black Physical state Solid **Odor** Odorless

GHS Label elements, including precautionary statements

Danger

Hazard statements

Causes skin irritation Causes serious eye irritation May cause an allergic skin reaction May cause cancer

Causes damage to organs through prolonged or repeated exposure



Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood Wear protective gloves/protective clothing/eye protection/face protection

Wash face, hands and any exposed skin thoroughly after handling

Contaminated work clothing must not be allowed out of the workplace

Do not breathe dust/fume/gas/mist/vapors/spray

Do not eat, drink or smoke when using this product

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

Specific treatment (see supplemental first aid instructions on this label)

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

Skin

IF ON SKIN: Wash with plenty of water and soap

Take off contaminated clothing and wash it before reuse

If skin irritation or rash occurs: Get medical advice/attention

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other information

Very toxic to aquatic life with long lasting effects.

Unknown acute toxicity 30.87 % of the mixture consists of ingredient(s) of unknown toxicity

27.75 % of the mixture consists of ingredient(s) of unknown acute oral toxicity



Page 2/13

30.87 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity

30.87 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)

30.87 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)

30.87 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance

Not applicable.

Mixture

Chemical name	CAS No	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
Lithium Cobalt Oxide (CoLiO2)	12190-79-3	43.72	-	-
Graphite	7782-42-5	23.27	-	-
Copper	7440-50-8	10.19	-	-
Aluminum	7429-90-5	4.95	-	-
Propylene carbonate	108-32-7	2.24	-	-
Ethylene carbonate	96-49-1	2.24	-	-
Phosphate(1-), hexafluoro-, lithium	21324-40-3	1.28	-	-
Nickel	7440-02-0	0.38	-	-
1,3-Propane sultone	1120-71-4	0.32	-	-

4. FIRST AID MEASURES

Description of first aid measures

General advice Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get

medical advice/attention. First aid is upon rupture of sealed battery. In case of rupture:

Inhalation Remove to fresh air. Get medical attention immediately if symptoms occur.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep

eye wide open while rinsing. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists. Do not rub affected area.

Skin contactMay cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a

physician. Wash off immediately with soap and plenty of water for at least 15 minutes.

Ingestion Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth

to an unconscious person. Do NOT induce vomiting. Call a physician.

Self-protection of the first aider Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see section 8).

Most important symptoms and effects, both acute and delayed

Symptoms Itching. Rashes. Hives. Burning sensation.

Indication of any immediate medical attention and special treatment needed



Page 3 / 13

- Rechargeable Li-ion Battery L22M3PG1 by Revision Date 21-Dec-2023

Note to physicians May cause sensitization in susceptible persons. Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media Use extinguishing measures that are appropriate to local circumstances and the

surrounding environment.

Large Fire CAUTION: Use of water spray when fighting fire may be inefficient.

Unsuitable extinguishing media Do not scatter spilled material with high pressure water streams.

Specific hazards arising from the

chemical

Product is or contains a sensitizer. May cause sensitization by skin contact.

Hazardous Combustion Products Carbon oxides.

Explosion Data

Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

Special protective equipment for

fire-fighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal

protective equipment as required. Evacuate personnel to safe areas. Keep people away

from and upwind of spill/leak.

Other Information Refer to protective measures listed in Sections 7 and 8.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Pick up and transfer to properly labeled containers.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling In case of rupture: Handle in accordance with good industrial hygiene and safety practice.

Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this

product. Take off contaminated clothing and wash before reuse.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up.

Keep out of the reach of children.



Page 4/13

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Limits

Chemical name		ACGIH T	LV	0	SHA PEL		NIOSH IDLH
Lithium Cobalt Oxide (CoLi	O2)	TWA: 0.02 mg/m ³			-		
12190-79-3		T14/A 0 / 2 : 11		T) A / A - 4 - 5	/ 2 / / 1 / /		IDI I 1050 / 0
Graphite		TWA: 2 mg/m³ respirable particulate matter all forms			mg/m³ total dust		IDLH: 1250 mg/m ³
7782-42-5		except graphi			synthetic ng/m³ respirable	I IVVA	: 2.5 mg/m³ respirable dust
		except graprii	ie libers		on synthetic		uust
					pcf respirable dust		
					natural		
					TWA: 2.5 mg/m ³		
					le dust natural		
					VA: 10 mg/m³ total		
					t synthetic		
				(vacated) TWA: 5 mg/m ³		
					fraction synthetic		
					5 mppcf natural		
Copper		TWA: 0.2 mg/r	n³ fume		1 mg/m ³ fume	IDLH:	: 100 mg/m³ dust, fume
7440-50-8				TWA: 1 mg	/m³ dust and mist		and mist
					WA: 0.1 mg/m ³ Cu		1 mg/m ³ dust and mist
		T14/4 4 / 0			, fume, mist		/A: 0.1 mg/m³ fume
Aluminum		TWA: 1 mg/m ³		TWA: 15 mg/m³ total dust TWA: 5 mg/m³ respirable			A: 10 mg/m³ total dust
7429-90-5		particulate r	natter		ig/m³ respirable fraction	II WA: 5	5 mg/m³ respirable dust
				1	VA: 15 mg/m ³ total		
				(vacated) i v	dust		
				(vacated) TWA: 5 mg/m ³		
					rable fraction		
Phosphate(1-), hexafluoro	D-,	TWA: 2.5 mg	g/m³ F		2.5 mg/m ³ F		IDLH: 250 mg/m ³ F
lithium				(vacated)	TWA: 2.5 mg/m ³		
21324-40-3							
Nickel		TWA: 1.5 m	ng/m³		A: 1 mg/m ³		IDLH: 10 mg/m ³
7440-02-0) TWA: 1 mg/m ³		TWA: 0.015 mg/m ³
Chemical name		Alberta		Columbia	Ontario TWAE		Quebec
Lithium Cobalt Oxide	TV	VA: 0.02 mg/m ³	TWA: 0.0	02 mg/m ³	TWA: 0.02 mg/	m³	TWA: 0.02 mg/m ³
(CoLiO2)							
12190-79-3		T\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	T\\\\\ \. C) a. / 3	T\\\\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	3	TMA . O
Graphite 7782-42-5		ΓWA: 2 mg/m³	I VVA: 2	2 mg/m ³	TWA: 2 mg/m	·	TWA: 2 mg/m ³
Copper	т,	WA: 0.2 mg/m ³	Τ\Λ/Λ · 1	l mg/m³	TWA: 0.2 mg/r	n3	TWA: 0.2 mg/m ³
7440-50-8				.2 mg/m³	TWA: 0.2 mg/m		TWA: 0.2 mg/m ³
Aluminum		WA: 10 mg/m ³		.0 mg/m³	TWA: 1 mg/m		TWA: 10 mg/m ³
7429-90-5	•	····	'''''		1 ****	'	. **/ 1. 10 mg/m
Phosphate(1-),	T	WA: 2.5 mg/m ³	TWA: 2	.5 mg/m ³	TWA: 2.5 mg/r	n ³	TWA: 2.5 mg/m ³
hexafluoro-, lithium	•	· -·· -·· -·· -··					
21324-40-3							
Nickel	T'	WA: 1.5 mg/m ³	TWA: 0.0	05 mg/m ³	TWA: 1 mg/m	3	TWA: 1.5 mg/m ³
7440-02-0]	
1,3-Propane sultone			TV	VA:	TWA:		TWA:
1120-71-4							



Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992). See section 15 for national exposure control parameters.

Appropriate engineering controls

Engineering controls Showers

> Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Wear suitable gloves. Impervious gloves. Hand protection

Wear suitable protective clothing. Long sleeved clothing. Skin and body protection

Respiratory protection No protective equipment is needed under normal use conditions. If exposure limits are

exceeded or irritation is experienced, ventilation and evacuation may be required.

Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or **General hygiene considerations**

smoke when using this product. Wash hands before breaks and immediately after handling the product. Wear suitable gloves and eye/face protection. Avoid contact with skin, eyes or

clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Solid **Appearance** Black Odor Odorless

Color No information available **Odor Threshold** No information available

Remarks Method Property Values

pН No data available None known Melting / freezing point No data available None known No data available Boiling point / boiling range None known **Flash Point** No data available None known No data available **Evaporation Rate** None known Flammability (solid, gas) No data available None known

Flammability Limit in Air

Upper flammability limit No data available Lower flammability limit No data available

Vapor pressure No data available None known Vapor density None known No data available Relative density No data available None known

Insoluble in water Water Solubility

Solubility(ies) No data available None known

Partition coefficient: n-octanol/water1

Autoignition temperature No data available None known **Decomposition temperature** No data available None known Kinematic viscosity No data available None known **Dynamic viscosity** No data available None known

Other Information



Page 6/13

Explosive properties No information available No information available **Oxidizing properties Softening Point** No information available **Molecular Weight** No information available **VOC Content (%)** No information available No information available **Liquid Density Bulk Density** No information available **Particle Size** No information available **Particle Size Distribution** No information available

10. STABILITY AND REACTIVITY

Reactivity No information available.

Stable under normal conditions. Chemical stability

Possibility of Hazardous Reactions None under normal processing.

Hazardous Polymerization Hazardous polymerization does not occur.

Conditions to avoid None known based on information supplied.

Strong acids. Strong bases. Strong oxidizing agents. Incompatible materials

Hazardous Decomposition Products Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information Product does not present an acute toxicity hazard based on known or supplied information.

In case of rupture:

Inhalation Specific test data for the substance or mixture is not available. May cause irritation of

respiratory tract.

Specific test data for the substance or mixture is not available. Causes serious eye irritation. Eye contact

(based on components). Irritating to eyes.

Specific test data for the substance or mixture is not available. May cause sensitization by Skin contact

skin contact. Causes skin irritation. (based on components). Repeated or prolonged skin

contact may cause allergic reactions with susceptible persons.

Ingestion Specific test data for the substance or mixture is not available. Ingestion may cause

gastrointestinal irritation, nausea, vomiting and diarrhea.

Symptoms related to the physical, chemical and toxicological characteristics

Itching. Rashes. Hives. Redness. May cause redness and tearing of the eyes. **Symptoms**

Numerical measures of toxicity

Acute toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 23,817.00 mg/kg



ATEmix (dermal) 16,202.30 mg/kg

30.87 % of the mixture consists of ingredient(s) of unknown toxicity Unknown acute toxicity

27.75 % of the mixture consists of ingredient(s) of unknown acute oral toxicity

30.87 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity

30.87 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)

30.87 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)

30.87 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

Product Information

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Lithium Cobalt Oxide (CoLiO2)	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rat)	> 5.05 mg/L (Rat) 4 h
Graphite	-	-	> 2000 mg/m³ (Rat) 4 h
Copper	-	-	> 5.11 mg/L (Rat) 4 h
Aluminum	-	-	> 0.888 mg/L (Rat) 4 h
Propylene carbonate	= 29000 mg/kg (Rat)	> 3000 mg/kg (Rabbit)	-
Ethylene carbonate	= 10 g/kg (Rat)	> 26420 mg/kg (Rabbit)	> 730 mg/m³ (Rat) 8 h
Nickel	> 9000 mg/kg (Rat)	-	> 10.2 mg/L (Rat) 1 h
1,3-Propane sultone	= 157 mg/kg (Rat)	-	-

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Classification based on data available for ingredients. Irritating to skin. Skin corrosion/irritation

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

Respiratory or skin sensitization May cause sensitization by skin contact.

Germ cell mutagenicity No information available.

Contains a known or suspected carcinogen. Classification based on data available for Carcinogenicity

ingredients. May cause cancer.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Lithium Cobalt Oxide	A3	Group 2B	Reasonably Anticipated	X
(CoLiO2)			·	
12190-79-3				
Nickel	-	Group 2B	Reasonably Anticipated	X
7440-02-0			·	
1,3-Propane sultone	A3	Group 2A	Reasonably Anticipated	X
1120-71-4		•		

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2A - Probably Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

NTP (National Toxicology Program)

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity No information available.



Page 8 / 13

STOT - single exposure No information available.

STOT - repeated exposure Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard No information available.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Very toxic to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Graphite	No data available	96h LC50: > 100 mg/L (Danio rerio)	No data available	No data available
Copper	96h EC50: 0.031 - 0.054 mg/L (Pseudokirchneriella subcapitata) 72h EC50: 0.0426 - 0.0535 mg/L (Pseudokirchneriella subcapitata)	96h LC50: 0.0068 - 0.0156 mg/L (Pimephales promelas) 96h LC50: < 0.3 mg/L (Pimephales promelas) 96h LC50: = 0.052 mg/L (Oncorhynchus mykiss) 96h LC50: = 0.112 mg/L (Poecilia reticulata) 96h LC50: = 0.2 mg/L (Pimephales promelas) 96h LC50: = 0.3 mg/L (Cyprinus carpio) 96h LC50: = 0.8 mg/L (Cyprinus carpio) 96h LC50: = 1.25 mg/L (Lepomis macrochirus)	No data available	48h EC50: = 0.03 mg/L (Daphnia magna)
Propylene carbonate	72h EC50: > 500 mg/L (Desmodesmus subspicatus)	96h LC50: > 1000 mg/L (Cyprinus carpio)	EC50 > 10000 mg/L 17 h	48h EC50: > 500 mg/L (Daphnia magna)
Ethylene carbonate	No data available	96h LC50: > 100 mg/L (Oncorhynchus mykiss)	No data available	No data available
Nickel	96h EC50: 0.174 - 0.311 mg/L (Pseudokirchneriella subcapitata) 72h EC50: = 0.18 mg/L (Pseudokirchneriella subcapitata)	96h LC50: = 1.3 mg/L (Cyprinus carpio) 96h LC50: = 10.4 mg/L (Cyprinus carpio) 96h LC50: > 100 mg/L (Brachydanio rerio)	No data available	48h EC50: = 1 mg/L (Daphnia magna) 48h EC50: > 100 mg/L (Daphnia magna)

Persistence and Degradability

No information available.

Bioaccumulation

Component Information

Chemical name	Partition coefficient	
Propylene carbonate	0.48	
Ethylene carbonate	0.11	

Mobility No information available.



Simplo

Other adverse effects No information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste from residues/unused

products

Dispose of in accordance with local regulations. Dispose of waste in accordance with

Revision Date 21-Dec-2023

environmental legislation.

Contaminated packaging Do not reuse empty containers.

California Waste Codes 141

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical name	California Hazardous Waste
Lithium Cobalt Oxide (CoLiO2)	Toxic
12190-79-3	
Aluminum	Ignitable powder
7429-90-5	
Nickel	Toxic powder
7440-02-0	Ignitable powder

14. TRANSPORT INFORMATION

Note:

The transportation of primary lithium cells and batteries is regulated by the International Civil Aviation Organization, International Air Transport Association, International Maritime Dangerous Goods Code and the US Department of Transportation. The batteries must meet the following criteria for shipment: 1. Air shipments must meet the requirements listed in Special Provision A45 of the International Air Transport Association Dangerous Goods Regulations. 2. Meet the requirements for the US Department of Transportation listed in 49 CFR 173.185. 3. The transport of primary lithium batteries is prohibited aboard passenger aircraft. Refer to the Federal Register December 15, 2004 (Hazardous Materials; Prohibited on the Transportation of Primary Lithium Batteries and Cells Aboard Passenger Aircraft: Final Rule)

Lithium batteries shipped as "Lithium batteries", "Lithium batteries packed with equipment", or "Lithium batteries contained in equipment" may not be classified as "Dangerous Goods" when shipped in accordance with "special provision A45 of IATA-DGR" or "special provision 188 of IMO-IMDG Code"

100 01 11010-11010-000

DOTNOT REGULATEDProper Shipping NameNON-REGULATED

Hazard Class N/A Emergency Response Guide 147

Number

TDG

MEX Not applicable

ICAO Not applicable

<u>IATA</u>

UN-No. UN3480

Proper Shipping Name LITHIUM ION BATTERIES



Simplo

Hazard Class 9 ERG Code 12FZ

Description UN3480, LITHIUM ION BATTERIES, 9

IMDG/IMO Not applicable

Proper Shipping Name NON-REGULATED PER SP 188

Hazard Class N/A EmS-No. F-A, S-I

Marine Pollutant This product contains a chemical which is listed as a marine pollutant according to

IMDG/IMO

RID Not applicable

ADR Not applicable

ADN Not applicable

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

International Inventories

TSCA

DSL/NDSL

Contact supplier for inventory compliance status.

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	CAS No	Weight-%	SARA 313 - Threshold Values %
Lithium Cobalt Oxide (CoLiO2) - 12190-79-3	12190-79-3	43.72	0.1
Copper - 7440-50-8	7440-50-8	10.19	1.0
Aluminum - 7429-90-5	7429-90-5	4.95	1.0



Revision Date 21-Dec-2023

Nickel - 7440-02-0 7440-02-0 0.38 0.1
1,3-Propane sultone - 1120-71-4 1120-71-4 0.32 0.1

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications. Under the amended regulations at 40 CFR 370, EPCRA 311/312 Tier II reporting for the 2017 calendar year will need to be consistent with updated hazard classifications.

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Copper 7440-50-8		Х	Х	
Nickel 7440-02-0		Х	Х	

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Copper	5000 lb		RQ 5000 lb final RQ
7440-50-8			RQ 2270 kg final RQ
Nickel	100 lb		RQ 100 lb final RQ
7440-02-0			RQ 45.4 kg final RQ
1,3-Propane sultone	10 lb		RQ 10 lb final RQ
1120-71-4			RQ 4.54 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical name	California Proposition 65
Nickel - 7440-02-0	carcinogen, 10/1/1989 (metallic)
1,3-Propane sultone - 1120-71-4	carcinogen, 1/1/1988

U.S. State Right-to-Know Regulations

This product may contain substances regulated by state right-to-know regulations.

Chemical name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Lithium Cobalt Oxide (CoLiO2) 12190-79-3	X		X	X	X
Graphite 7782-42-5	X	X	X		
Copper 7440-50-8	X	X	X	X	X
Aluminum 7429-90-5	X	X	X	X	
Ethylene carbonate 96-49-1		X	X		
Phosphate(1-),	Х				



hexafluoro-, lithium 21324-40-3					
Nickel 7440-02-0	Х	Х	X	Х	X
1,3-Propane sultone 1120-71-4	X	X	X	Х	X

16. OTHER INFORMATION

Health hazards 1 Instability 0 **Physical and Chemical** NFPA Flammability 0

Properties -Health hazards 0 Flammability 0 Physical hazards 0 Personal Protection X HMIS

Prepared By Product Stewardship

23 British American Blvd. Latham, NY 12110 1-800-572-6501

Issuing Date 26-Dec-2023

21-Dec-2023 **Revision Date**

Revision Note No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet

