

 Address: Lianding Testing Building, No.18 Center Road of Yayuan Industrial Zone, Nancheng District, Dongguan, Guangdong, China.

 Tel:
 86-769-3893 3228
 Email: utl@gdutl.com



Report No.: PNS21095848 02001

Name of goods	Li-ion Battery				
Type/Model	LIP603862				
Ratings	7.4V, 1700mAh, 12.58Wh				
Commissioned by	SHENZHEN MOTOMA POWER CO., LTD.				
Commissioner address	NO. 321, 3/F, BUILDING A, 5TH. ZONE HONGHUALING INDUSTRIAL ZONE, TAOYUAN ROAD, NANSHAN, SHENZHEN, CHINA SHENZHEN MOTOMA POWER CO., LTD.				
Factory's name					
Factory address	NO. 321, 3/F, BUILDING A, 5TH. ZONE HONGHUALING INDUSTRIAL ZONE, TAOYUAN ROAD, NANSHAN, SHENZHEN, CHINA				
Inspection according to	OSHA GHS 《A Guide to The Globally Harmonized System of Classification and Labelling of Chemicals》 IATA DGR 《Dangerous Goods Regulations》 IMO IMDG CODE 《INTERNATIONAL MARITIME Dangerous Goods CODE》				
Receiving date: 2	022-05-26 Issue date: 2022-06-07				



Address: Lianding Testing Building, No.18 Center Road of Yayuan Industrial Zone, Nancheng District, Dongguan, Guangdong, China.Tel:86-769-3893 3228Email:utl@gdutl.comhttp://www.gdutl.com



Page 2 of 14

# 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product Identifier

Product name: Li-ion Battery

Model: LIP603862 7.4V, 1700mAh, 12.58Wh

#### Other means of identification

Synonyms:

#### Recommended use of the chemical and restrictions on use

Recommended Use:

Uses advised against:

a) Do not dismantle, open or shred secondary cells or batteries.

b) Do not expose cells or batteries to heat or fire. Avoid storage in direct sunlight.

c) Do not short-circuit a cell or battery. Do not store cells or batteries haphazardly in a box or drawer.

where they may short-circuit each other or be short-circuited by other metal objects.

d) Do not remove a cell or battery from its original packaging until required for use.

e) Do not subject cells or batteries to mechanical shock.

f) In the event of a call leaking, do not allow the liquid to come in contact with the skin or eyes. If contact has

been made, wash the affected ares with copious amounts of water and seek medical advice.

g) Do not use any charger other than that specifically provided for use with the equipment.

h) Observe the plus(+) and minus(-) marks on the cell, battery and equipment and ensure correct use.

i) Do not use any cell or battery which is not designed for use with the equipment.

j) Do not mix cells of different manufacturer, capacity, size or type within a device.

k) Battery usage by children should be supervised.

I) Seek medical advice immediately if a cell or a battery has been swallowed.

m) Always purchase the battery recommended by the device manufacturer for the equipment.

n) Keep cells and batteries clean and dry.

o) Wipe the cell or battery terminals with a clean dry cloth if they become dirty.

p) Secondary cells and batteries need to be charged before use. Always use the correct charger and refer to the manufacturer's instructions or equipment manual for proper charging instructions.

q) Do not leave a battery on prolonged charge when not in use.

r) After extended periods of storage, it may be necessary to charge and discharge the cells or batteries several times to obtain maximum performance.

s) Retain the original product literature for future reference.

t) Use only the cell or battery in the application for which it was intended.

u) When possible, remove the battery from the equipment when not in use.

v) Dispose of properly.

#### Details of the Manufacturer of the safety data sheet:

Name: SHENZHEN MOTOMA POWER CO., LTD.

Address: NO. 321, 3/F, BUILDING A, 5TH. ZONE HONGHUALING INDUSTRIAL ZONE, TAOYUAN ROAD, NANSHAN, SHENZHEN, CHINA

Telephone number of the supplier: +86-755-83736206

Fax: N/A

E-mail address: P8@motoma.com

#### Emergency telephone number

Company Emergency Phone Number: +86-13825851151

Postcode: 523000



Page 3 of 14

## 2. HAZARDS IDENTIFICATION

#### **Classification**

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200). This product is an article which is a sealed battery and as such does not require an MSDS per the OSHA hazard communication standard unless ruptured. The hazards indicated are for a ruptured battery.

#### Classification of the substance or mixture

Classification according to GHS

#### ACUTE TOXICITY-ORAL

Hazard category: 4

Signal world: Warning

Hazard statement: Harmful if swallowed



 $\langle \mathbf{D} \rangle$ 

Prevention: Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Response: Call a Poison center or doctor/physician if you feel unwel Storage:

Disposal: Dispose of contents/container in accordance with local/national regulations

#### ACUTE TOXICITY-DERMAL

Hazard category: 4

Signal world: Warning.

Hazard statement: Harmful in contact with skin



Prevention: Wear protective gloves/protective clothing

Response: Call a Poison center or doctor/physician if you feel unwel

Storage:

Disposal: Dispose of contents/container in accordance with local/national regulations

#### SKIN CORROSION/IRRITATION

Hazard category: 2 Signal world: Warning.

Hazard statement: Causes skin irritation.

Pictogram:



Prevention: Wash thoroughly after handing. Wear protective gloves. Response: Take off contaminated clothing and wash it before reuse. Storage:

Disposal:













Page 5 of 14

#### SENSITIZATION-SKIN

Hazard category: 1A

Signal world: Warning

Hazard statement: May cause an allergic skin reaction.

Pictogram:

Prevention: Avoid breathing dust/fume/gas/mist/vapors/spray. Wear protective gloves.

Response: If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Storage:

Disposal: Dispose of contents/container in accordance with local/national regulations.

#### **EXPLOSIVES (CONTINUED)**

Hazard category: Division 1.4

Signal world: Warning

Hazard statement: Fire or project hazard.

Pictogram:

Prevention: Keep away from heat/sparks/open flames/hot surfaces.-No smoking.

Response: In case of fire: evacuate area. Explosion risk in case of fire. Do NOT fight fire reaches explosives.

Storage: Store in accordance with local/regional/national/international regulations.

Disposal: Dispose of contents/container in accordance with local/national regulations.

#### FLAMMABLE SOLIDS

Hazard category: 2 Signal world: Warning

Hazard statement: Flammable solid.

Pictogram:



Prevention: Keep away from heat/sparks/open flames/hot surfaces.-No smoking.

Response: In case of fire: Use to extinguish.

Storage:

Disposal:













# **3. COMPOSITION/INFORMATION ON INGREDIENTS**

#### **Chemical characterization: Mixtures**

#### **Description:**

Product: Consisting of the following components

			_
Chemical Formula	Weight(%)	CAS Number	
LiNi <sub>x</sub> Co <sub>y</sub> Mn <sub>1-x-y</sub> O <sub>2</sub>	32.15	182442-95-1	
Li <sub>2</sub> MnO <sub>4</sub>	8.03	12057-17-9	
(CH <sub>2</sub> -CF <sub>2</sub> )n	0.62	24937-79-9	
AI	9.03	7429-90-5	
C <sub>24</sub> X <sub>12</sub>	19.77	7782-42-5	
(C <sub>8</sub> H <sub>8</sub> C₄H <sub>6</sub> )x	0.52	9003-55-8	
C <sub>8</sub> H <sub>15</sub> NaO <sub>8</sub>	0.21	9000-11-7	
Cu	9.2	7440-50-8	
Ni	1.08	7440-02-0	
LiPF <sub>6</sub>	15.56	21324-40-3	
(C <sub>2</sub> H <sub>4</sub> )n	2.03	9002-88-4	
C <sub>2</sub> CIF <sub>3</sub>	0.8	24937-16-4	
(C <sub>3</sub> H <sub>6</sub> )n	1	9003-07-0	
	LiNi <sub>x</sub> Co <sub>y</sub> Mn <sub>1-x-y</sub> O <sub>2</sub> Li <sub>2</sub> MnO <sub>4</sub> (CH <sub>2</sub> -CF <sub>2</sub> )n Al C <sub>24</sub> X <sub>12</sub> (C <sub>8</sub> H <sub>8</sub> C <sub>4</sub> H <sub>6</sub> )x C <sub>8</sub> H <sub>15</sub> NaO <sub>8</sub> Cu Ni LiPF <sub>6</sub> (C <sub>2</sub> H <sub>4</sub> )n C <sub>2</sub> ClF <sub>3</sub>	LiNixCoyMn1-x-yO2         32.15           Li2MnO4         8.03           (CH2-CF2)n         0.62           Al         9.03           C24X12         19.77           (C8H8C4H6)x         0.52           C8H15NaO8         0.21           Cu         9.2           Ni         1.08           LiPF6         15.56           (C2H4)n         2.03           C2CIF3         0.8	LiNi <sub>x</sub> Co <sub>y</sub> Mn <sub>1-x-y</sub> O <sub>2</sub> 32.15         182442-95-1           Li <sub>2</sub> MnO <sub>4</sub> 8.03         12057-17-9           (CH <sub>2</sub> -CF <sub>2</sub> )n         0.62         24937-79-9           Al         9.03         7429-90-5           C <sub>24</sub> X <sub>12</sub> 19.77         7782-42-5           (C <sub>8</sub> H <sub>8</sub> C <sub>4</sub> H <sub>6</sub> )x         0.52         9003-55-8           C <sub>8</sub> H <sub>15</sub> NaO <sub>8</sub> 0.21         9000-11-7           Cu         9.2         7440-50-8           Ni         1.08         7440-02-0           LiPF <sub>6</sub> 15.56         21324-40-3           (C <sub>2</sub> H <sub>4</sub> )n         2.03         9002-88-4           C <sub>2</sub> CIF <sub>3</sub> 0.8         24937-16-4

Note: CAS number is Chemical Abstract Service Registry Number. N/A=Not apply.

Address: Lianding Testing Building, No.18 Center Road of Yayuan Industrial Zone, Nancheng District, Dongguan, Guangdong, China.Tel:86-769-3893 3228Email:utl@gdutl.comhttp://www.gdutl.com



# 4. FIRST-AID MEASURES

#### First aid measures

Eye Contact Rinse thoroughly with plenty of water, also under the eyelids. If symptoms persist, call a physician.

Skin Contact Remove contaminated clothing and shoes. Wash skin with soap and water. In the case of skin irritation or allergic reactions see a physician.

Inhalation Move to fresh air. If symptoms persist, call a physician.

Ingestion Do NOT induce vomiting. Drink plenty of water. If symptoms persist, call a physician.

Most important symptoms and effects, both acute and delayed

Swallowing Do not induce vomiting. Get medical attention.

Most Important Symptoms/Effects No information available.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Test symptomatically

### **5. FIRE-FIGHTING MEASURES**

#### Suitable Extinguishing Media

CO2, dry chemical powder, water spray.

Unsuitable Extinguishing Media: No information available.

#### Specific Hazards Arising from the Chemical

Formation of toxic gases is possible during heating or case of fire.

In case of fire, the following can be released:

Carbon monoxide (Co)

Carbon dioxide

Other irritating and toxic gases.

#### Hazardous Combustion Products

Carbon oxides.

**Explosion Date** 

Sensitivity to Mechanical Impact No

Sensitivity to Static Discharge No

#### Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. For example: Wear self-contained respiratory protective device.

Wear suitable protective clothing and eye/face protection.

#### Special hazards arising from the substance or mixture:

Battery may burst and release hazardus decomposition products when exposed to a fire situation. Lithium ion batteries contain flammable electrolyte that may vent, ignite and produce sparks when subjected to high temperature (>150°C), When damaged or abused (e.g. mechanical damage or electrical overcharging); may burn rapidly with flare-burning effect; may ignite other batteries in clothes proximity.







<



# 6. ACCIDENTAL RELEASE MEASURES

#### Personal precautions, protective equipment and emergency procedures

Personal Precautions Avoid contact with eyes.

Refer to section 8 for personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition.

Evacuate personnel to safe areas.

#### **Environmental Precautions**

Environmental Precautions Refer to protective measures listed in Sections 7 and 8. Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13.

#### Methods and material for containment and cleaning up

Methods for ContainmentPrevent further leakage or spillage if safe to do so.Methods for Cleaning upUse personal protective equipment. Dam up. Cover liquid spill with sand,earth or other Non combustible absorbent material. Pick up and transfer to properly labelled containers.Clean contaminated surface thoroughly.

# 7. HANDLING AND STORAGE

#### Precautions for safe handling

Handing Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes and clothing. Wear personal protective equipment.

Wash thoroughly after handling. Use this material with adequate ventilation.

The Product is not explosive.

#### Conditions for safe storage, including any incompatibilities

If the Lithium-ion Battery is subject to storage for such a long term as more than 3 months, it is recommended to recharge the Lithium-ion Battery Periodically.

3 months: -20°C~ +45°C, 45 to 85% RH

And recommended at -20°C~ +25°C for long period storage.

The capacity recovery rate in the delivery state (50% capacity of fully charged) after storage is assumed to be 80% or more.

The voltage for a long time storage shall be 2.8-4.2V range.

Do not storage Lithium-ion Battery haphazardly in a box or drawer where they may short-circuit each other or be short-circuited by other metal objects.

Keep out of reach of children.

Do not expose Lithium-ion Polymer Battery to heat or fire. Avoid storage in direct sunlight.

Do not store together with oxidizing and acidic materials.

Keep ignition sources away- Do not smoke.

Store in cool, dry and well-ventilated place.

Incompatible Products None known.



# 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

#### Control parameters

Ingredients with limit values that require monitoring at the workplace:12190-79-3Lithium Cobalt Oxide

TLV(USA)	0.02mg/m³
MAK(Germany)	0.1mg/m³

**Other Exposure Guidelines** Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

#### Appropriate engineering controls

Engineering Measures Showers

Eyewash stations

Ventilation systems

Use adequate general or local exhaust ventilation to keep airborne concentrations below the permissible Exposure limits. Ensure or adequate ventilation.

#### Individual protection measures, such as personal protective equipment

Eye/Face Protection:



Tightly sealed goggles

#### **Body protection:**

Protective work clothing.

Skin protection:



**Protective gloves** 

#### Material of gloves:

The selection of the suitable gloves does not noly depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is preparation of several substances, the resistance of the glove material can not to be calculated in advance and has therefore to be checked prior to the application.

#### Penetration time of glove material:

The exact break trough time has to be found out by manufacturer of the Protective gloves and has to be observed.

**Respiratory Protection** No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

Hygiene Measures Handle in accordance with good Industrial hygiene and safety practice.











Page 9 of 14

 Address: Lianding Testing Building, No.18 Center Road of Yayuan Industrial Zone, Nancheng District, Dongguan, Guangdong, China.

 Tel:
 86-769-3893 3228

 Email:
 utl@gdutl.com

 http:
 //www.gdutl.com



# 9. PHYSICAL AND CHEMICAL PROPERTIES

			_	
	Form: Quadrate shape			
Physician	Colour: Blue			
State	Odour: Odourless			
	Odor Threshold: No information avaliable			
Change in	condition:			
pH, with in	dication of the concentration	Not determined.	5	
Melting Po	int/freezing point	Not determined.		
Initial boilin	g point and Boiling range:	Not determined.		
Flash Poin	t	Not determined.		
Evaporatio	n rate	Not determined.		
Flammabili	ty (solid, gas)	Not determined.		
Upper/lowe	er flammability or explosive limits	Not determined.		
Vapor Pres	ssure:	Not determined.		
Vapor Den	sity:	Not determined.		
relative de	nsity:	Not determined.	D	
Solubility ir	n Water:	Not determined.		
Solubility ir	o other solvents	Not determined.		
n-octanol/v	vater partition coefficient	Not determined.		
Auto-ignitic	on temperature	Product is not self-igniting.		
Decompos	ition temperature	Not determined.		
Odout thre	shold	Not determined.		
Evaporatio	n rate	Not determined.		
Viscosity		Not determined.		
Other Infor	mation	No further relevant information available.	5.	

# **10. STABILITY AND REACTIVITY**

**<u>Reactivity</u>**: Stable under recommended storage and handling conditions (see section 7, Handling and storage)

<u>Chemical stability:</u> Stable Under normal conditions of use, storage and transport.


Thermal decomposition/conditions to be avoided: No decomposition if used according to specifications. <u>Possibility of Hazardous Reactions:</u> None under normal processing.

Hazardous Polymerization: Hazardous polymerization does not occur.

Conditions to avoid: Strong heating, fire, Incompatible materials.

Incompatible materials: Strong oxidizing agents. Strong acids. Base metals.

Hazardous Decomposition Products: Carbon oxides, Other irritating and toxic gases.





# 11. TOXICOLOGICAL INFORMATION

#### Acute toxiciy: No data available.

LD/LC50 values relevant for classification:

Not available.

Skin corrosion/irritation: No irritant effect.

Serious eye damage/irritation: Cause serious eye irritation.

Respiratory or skin sensitization: No sensitizing effects known.

Specific target organ system toxicity: No information available.

CMR effects (carcinogenity, mutagenicity and toxicity for reproduction: No information available.

# **12. ECOLOGICAL INFORMATION**

#### Toxicity:

Acquatic toxicity:

No further relevant information available.

Persistence and degradability: No further relevant information available.

Bioaccumulation potential: No further relevant information available.

Mobility in soil: No further relevant information available.

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

Other adverse effects: No information available.

# **13. DISPOSAL CONSIDERATIONS**

#### Waste treatment methods

Recommendation: Must not be disposed together with household garbage.

Do not allow product to reach sewage system

#### Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.





Page 11 of 14

### **14. TRANSPORT INFORMATION**

#### Land transport

ADR/RID class: Not regulated.

UN-Number: UN3480 or UN3481

#### Maritime transport

IMDG Class: Class 9.

UN Number: UN3480 or UN3481

Marine pollutant: No

#### Air transport

ICAO/IATA Class: Class 9

UN/ID Number: UN3480 or UN3481.

Environmental hazards: Not applicable.

Special precautions for user: Not applicable.

Transport/Additional information: Not restricted goods according to the above specifications.

The Li-ion Battery bad been tested according to the requirements of the UN manual of tests and Criteria, Part III, subsection 38.3;

The Li-ion Battery according to Section II/Section IB of PACKING INSTRUCTION 965, or Section II of

PACKING INSTRUCTION 966~967 of the Dangerous Goods regulations 62nd Edition may be transported.

The packaging shall be adequate to avoid mechanical damage during transport, handling and stacking. The materials and pack design shall be chosen so as to prevent the development of unintentional electrical conduction, corrosion of the terminals and ingress of moisture.

Meets requirements of DOT Special Provision 188 to be transported as non-dangerous goods

Meets the requirements of 49CFR173.185 to be transported as non-dangerous goods for road, rail, air, and vessel (Effective August 6, 2014 per HM224F)

The package must be handled with care and that a flammability hazard exists if the package is damaged;

## **15. REGULATORY INFORMATION**

Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation:

Authorisations: No information available.

Restrictions on use: No information available.

#### Regulatory information





CAS NO.	EU (EINECS)	US (TSCA)	Japan (ENCS)	Canada (DSL/ NDSL)	Australia (AICS)	Korea (ECL)	China (IECSC)
182442-95-1	Listed	Not listed	Not listed	NDSL	Not listed	Not listed	Not listed
7782-42-5	Listed	Listed	Listed	DSL	Listed	Listed	Listed
7439-89-6	Listed	Listed	Listed	DSL	Listed	Listed	Listed
7440-50-8	Not listed	Listed	Not listed	DSL	Listed	Listed	Listed
96-49-1	Not listed	Listed	Not listed	DSL	Listed	Listed	Listed
623-53-0	Listed	Listed	Listed	DSL	Listed	Listed	Listed
21324-40-3	Listed	Listed	Listed	DSL	Listed	Listed	Listed
114435-02-8	Listed	Listed	Listed	DSL	Listed	Listed	Listed
14283-07-9	Not listed	Listed	Not listed	DSL	Listed	Listed	Listed
7440-02-0	Not listed	Listed	Not listed	DSL	Listed	Listed	Listed
1333-86-4	Listed	Listed	Listed	DSL	Listed	Listed	Listed
872-50-4	Listed	Listed	Listed	DSL	Listed	Listed	Listed
7440-47-3	Listed	Listed	Listed	DSL	Listed	Listed	Listed
554-13-2	Listed	Listed	Listed	DSL	Listed	Listed	Listed

Chemical safety assessment A Chemical Safety Assessment has not been carried out

# **16. OTHER INFORMATION**

This information is based on out present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

N

#### **Relevant Phrases:**

R20/22: Harmful by inhalation and if swallowed.

R36: Irritating to eyes.

H302: Harmful if swallowed.

H332: Harmful if inhaled.


Address: Lianding Testing Building, No.18 Center Road of Yayuan Industrial Zone, Nancheng District, Dongguan, Guangdong, China.Tel:86-769-3893 3228Email: utl@gdutl.comhttp://www.gdutl.com



Page 13 of 14

ß

Report No.: PNS21095848 02001



# Important

1. Nobody is allowed to photocopy or partly photocopy this test report without written permission of UTL.

- 2. The test report is invalid without the signatures of Approver, Reviewer and Tester.
- 3. The test report is invalid if altered.
- 4. Objections to the test report must be submitted to UTL within 15 days.
- 5. Throughout this report a point is used as the decimal separator.
- 6. The test report is valid for the tested samples only.
- 7. The test report does not grant applicant the use of UTL name, trademark or label.

8. UTL's liability under no circumstance will exceed the testing fee received from applicant for test conducted hereof this testing report.

9. The test data and results do not have social proof function.



 Address: Lianding Testing Building, No.18 Center Road of Yayuan Industrial Zone, Nancheng District, Dongguan, Guangdong, China.

 Tel:
 86-769-3893 3228

 Email:
 utl@gdutl.com

 http://www.gdutl.com

