

SAFETY DATA SHEET

Issuing Date 19-May-2021

Revision Date 03-Feb-2021

Revision Number 1

NGHS / English



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is ©2014 UL LLC. All rights reserved.

1. IDENTIFICATION

Product identifier

Product Name Evolution Water Base RAL Acrylic 520cc

Other means of identification

Product Code(s) 1622721

Recommended use of the chemical and restrictions on use

Recommended Use Topcoat (Paint or Paint-Related) - Aerosol

Restrictions on use No information available

Details of the supplier of the safety data sheet

Supplier Identification M&P Export Managment Corporation

Address 140 Central Avenue
Farmingdale
NJ
07727
US

Telephone Phone:732-223-0160

E-mail mzdzinski@mpexport.com

Emergency telephone number

Company Emergency Phone Number 800-535-5053

2. HAZARDS IDENTIFICATION

Classification

Serious eye damage/eye irritation	Category 2A
Specific target organ toxicity (single exposure)	Category 1
Specific target organ toxicity (repeated exposure)	Category 2



Flammable aerosols	Category 2
Gases under pressure	Liquefied Gas

Appearance Multiple Colors**Physical state** Liquid spray Aerosol**Odor** Mild**GHS Label elements, including precautionary statements****Danger****Hazard statements**

Causes serious eye irritation

Causes damage to organs

May cause damage to organs through prolonged or repeated exposure

Flammable Aerosol

Contains gas under pressure; may explode if heated

**Precautionary Statements - Prevention**

Wash face, hands and any exposed skin thoroughly after handling

Wear eye protection/ face protection

Do not breathe dust/fume/gas/mist/vapors/spray

Do not eat, drink or smoke when using this product

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

Do not spray on an open flame or other ignition source

Pressurized container: Do not pierce or burn, even after use

Precautionary Statements - Response

IF exposed: Call a POISON CENTER or doctor

Specific treatment (see supplemental first aid instructions on this label)

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

Precautionary Statements - Storage

Store locked up

Protect from sunlight. Store in a well-ventilated place

Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other information

May be harmful if swallowed. Causes mild skin irritation.

Unknown acute toxicity

70.9 % of the mixture consists of ingredient(s) of unknown toxicity

53.75 % of the mixture consists of ingredient(s) of unknown acute oral toxicity

57.5 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity

70.9 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)

70.9 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)
 67.15 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance

Not applicable.

Mixture

Chemical name	CAS No	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
Supplier Trade Secret	-	50 - 60%	-	-
Propan-2-ol	67-63-0	13.4	-	-
Supplier Trade Secret	-	0 - 10%	-	-
Supplier Trade Secret	-	0 - 10%	-	-
2-Butoxyethanol	111-76-2	3.725	-	-
Supplier Trade Secret	-	0 - 10%	-	-

4. FIRST AID MEASURES

Description of first aid measures

General advice

Show this safety data sheet to the doctor in attendance.

Inhalation

Remove to fresh air. IF exposed or concerned: Get medical advice/attention.

Eye contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and persists. If symptoms persist, call a physician.

Skin contact

In case of contact with liquefied gas, thaw frosted parts with lukewarm water. Wash off immediately with plenty of water for at least 15 minutes. If symptoms persist, call a physician.

Ingestion

Do NOT induce vomiting. Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Call a physician.

Self-protection of the first aider

Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Wear personal protective clothing (see section 8). Avoid contact with skin, eyes or clothing.

Most important symptoms and effects, both acute and delayed

Symptoms

Burning sensation.

Indication of any immediate medical attention and special treatment needed

Note to physicians

Treat symptomatically.

5. FIRE-FIGHTING MEASURES



Suitable Extinguishing Media	Dry chemical. Carbon dioxide (CO ₂). Water spray.
Large Fire	CAUTION: Use of water spray when fighting fire may be inefficient.
Unsuitable extinguishing media	DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED.
Specific hazards arising from the chemical	Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Cylinders may rupture under extreme heat. Damaged cylinders should be handled only by specialists. Containers may explode when heated. Ruptured cylinders may rocket.
Hazardous Combustion Products	Carbon oxides. Carbon monoxide. Carbon dioxide (CO ₂). Formaldehyde.
Explosion Data	
Sensitivity to Mechanical Impact	Yes.
Sensitivity to Static Discharge	Yes.
Special protective equipment for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions	Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Take precautionary measures against static discharges. Contents under pressure. Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.
Other Information	Ventilate the area. Refer to protective measures listed in Sections 7 and 8.
<u>Methods and material for containment and cleaning up</u>	
Methods for containment	Stop leak if you can do it without risk. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Flood with water to complete polymerization and scrape off floor.
Methods for cleaning up	Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling	Use personal protection equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use spark-proof tools and explosion-proof equipment. Handle product only in closed system or provide appropriate exhaust ventilation. Keep in an area equipped with sprinklers. Do not puncture or incinerate cans. Contents under pressure. In case of rupture. Avoid breathing vapors or mists. Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers. Handle in
--------------------------------	---

accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from sunlight. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Limits

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Propan-2-ol 67-63-0	STEL: 400 ppm TWA: 200 ppm	TWA: 400 ppm TWA: 980 mg/m ³ (vacated) TWA: 400 ppm (vacated) TWA: 980 mg/m ³ (vacated) STEL: 500 ppm (vacated) STEL: 1225 mg/m ³	IDLH: 2000 ppm TWA: 400 ppm TWA: 980 mg/m ³ STEL: 500 ppm STEL: 1225 mg/m ³
Supplier Trade Secret	TWA: 10 mg/m ³	TWA: 15 mg/m ³ total dust (vacated) TWA: 10 mg/m ³ total dust	IDLH: 5000 mg/m ³
Supplier Trade Secret	TWA: 3 mg/m ³ inhalable particulate matter	TWA: 3.5 mg/m ³ (vacated) TWA: 3.5 mg/m ³	IDLH: 1750 mg/m ³ TWA: 3.5 mg/m ³ TWA: 0.1 mg/m ³ Carbon black in presence of Polycyclic aromatic hydrocarbons PAH
2-Butoxyethanol 111-76-2	TWA: 20 ppm	TWA: 50 ppm TWA: 240 mg/m ³ (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m ³ (vacated) S*	IDLH: 700 ppm TWA: 5 ppm TWA: 24 mg/m ³

Chemical name	Alberta	British Columbia	Ontario TWAEV	Quebec
Supplier Trade Secret		TWA: 1000 ppm		
Propan-2-ol 67-63-0	TWA: 200 ppm TWA: 492 mg/m ³ STEL: 400 ppm STEL: 984 mg/m ³	TWA: 200 ppm STEL: 400 ppm	TWA: 200 ppm STEL: 400 ppm	TWA: 400 ppm TWA: 985 mg/m ³ STEL: 500 ppm STEL: 1230 mg/m ³
Supplier Trade Secret	TWA: 10 mg/m ³	TWA: 10 mg/m ³ TWA: 3 mg/m ³	TWA: 10 mg/m ³	TWA: 10 mg/m ³
Supplier Trade Secret	TWA: 3.5 mg/m ³	TWA: 3 mg/m ³	TWA: 3 mg/m ³	TWA: 3 mg/m ³
2-Butoxyethanol 111-76-2	TWA: 20 ppm TWA: 97 mg/m ³	TWA: 20 ppm	TWA: 20 ppm	TWA: 20 ppm

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992). See section 15 for national exposure control parameters.

Appropriate engineering controls



Engineering controls Showers
 Eyewash stations
 Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Tight sealing safety goggles.

Hand protection Impervious gloves. Wear suitable gloves.

Skin and body protection Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron.
 Antistatic boots.

Respiratory protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

General hygiene considerations Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Liquid spray; Aerosol
Appearance Multiple Colors
Odor Mild
Color No information available
Odor Threshold No data available

<u>Property</u>	<u>Values</u>	<u>Remarks Method</u>
pH	UNKNOWN	
Melting / freezing point	No data available	None known
Boiling point / boiling range	No data available	None known
Flash Point	No data available	None known
Evaporation Rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		None known
Upper flammability limit	No data available	
Lower flammability limit	No data available	
Vapor pressure	No data available	None known
Vapor density	No data available	None known
Relative density	1	
Water Solubility	Completely soluble	
Solubility(ies)	No data available	None known
Partition coefficient: n-octanol/water	No data available	
Autoignition temperature	No data available	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known

Other Information

Explosive properties No information available
Oxidizing properties No information available
Softening Point No information available
Molecular Weight No information available

VOC Content (%)	No information available
Liquid Density	No information available
Bulk Density	No information available
Particle Size	No information available
Particle Size Distribution	No information available

10. STABILITY AND REACTIVITY

Reactivity	No information available.
Chemical stability	Stable under normal conditions.
Possibility of Hazardous Reactions	None under normal processing.
Hazardous Polymerization	Hazardous polymerization does not occur.
Conditions to avoid	Heat, flames and sparks. Excessive heat.
Incompatible materials	None known based on information supplied.
Hazardous Decomposition Products	Carbon oxides. Formaldehyde. Carbon monoxide. Carbon dioxide (CO ₂).

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation	Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract.
Eye contact	Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components). May cause redness, itching, and pain.
Skin contact	Specific test data for the substance or mixture is not available. May cause irritation. Prolonged contact may cause redness and irritation.
Ingestion	Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. May be harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms	May cause redness and tearing of the eyes.
----------	--

Numerical measures of toxicity

Acute toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral)	3,064.70 mg/kg
ATEmix (dermal)	6,355.00 mg/kg
ATEmix (inhalation-gas)	35,154.40 ppm
ATEmix (inhalation-dust/mist)	10.20 mg/L
ATEmix (inhalation-vapor)	85.90 mg/L

Unknown acute toxicity	70.9 % of the mixture consists of ingredient(s) of unknown toxicity
------------------------	---



53.75 % of the mixture consists of ingredient(s) of unknown acute oral toxicity
 57.5 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity
 70.9 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)
 70.9 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)
 67.15 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Supplier Trade Secret	-	-	= 164000 ppm (Rat) 4 h
Propan-2-ol	= 1870 mg/kg (Rat)	= 4059 mg/kg (Rabbit)	> 10000 ppm (Rat) 6 h
Supplier Trade Secret	> 10000 mg/kg (Rat)	-	= 5.09 mg/L (Rat) 4 h
Supplier Trade Secret	> 15400 mg/kg (Rat)	-	> 4.6 mg/m ³ (Rat) 4 h
2-Butoxyethanol	= 470 mg/kg (Rat)	= 435 mg/kg (Rabbit)	= 450 ppm (Rat) 4 h = 486 ppm (Rat) 4 h
Supplier Trade Secret	= 3200 mg/kg (Rat)	> 15200 mg/kg (Rat)	> 3.55 mg/L (Rat) 6 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	May cause skin irritation.
Serious eye damage/eye irritation	Classification based on data available for ingredients. Causes serious eye irritation.
Respiratory or skin sensitization	No information available.
Germ cell mutagenicity	No information available.
Carcinogenicity	No information available.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Propan-2-ol 67-63-0	-	Group 3	-	X
Supplier Trade Secret	-	Group 2B	-	X
Supplier Trade Secret	A3	Group 2B	-	X
2-Butoxyethanol 111-76-2	A3	Group 3	-	-

Legend**ACGIH (American Conference of Governmental Industrial Hygienists)**

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity	No information available.
STOT - single exposure	Based on the classification criteria of the Globally Harmonized System as adopted in the country or region with which this safety data sheet complies, this product has been determined to cause systemic target organ toxicity from acute exposure. (STOT SE). Causes damage to organs.
STOT - repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	No information available.

12. ECOLOGICAL INFORMATION

Ecotoxicity The environmental impact of this product has not been fully investigated.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Supplier Trade Secret	No data available	96h LC50: > 4.1 g/L (Poecilia reticulata)	No data available	No data available
Propan-2-ol	72h EC50: > 1000 mg/L (Desmodesmus subspicatus) 96h EC50: > 1000 mg/L (Desmodesmus subspicatus)	96h LC50: = 11130 mg/L (Pimephales promelas) 96h LC50: = 9640 mg/L (Pimephales promelas) 96h LC50: > 1400000 µg/L (Lepomis macrochirus)	No data available	48h EC50: = 13299 mg/L (Daphnia magna)
2-Butoxyethanol	No data available	96h LC50: = 1490 mg/L (Lepomis macrochirus) 96h LC50: = 2950 mg/L (Lepomis macrochirus)	No data available	48h EC50: > 1000 mg/L (Daphnia magna)
Supplier Trade Secret	72h EC50: = 18.4 mg/L (Pseudokirchneriella subcapitata)	96h LC50: = 30 mg/L (Pimephales promelas)	No data available	No data available

Persistence and Degradability No information available.

Bioaccumulation

Component Information

Chemical name	Partition coefficient
Supplier Trade Secret	-0.18
Propan-2-ol	0.05
2-Butoxyethanol	0.81
Supplier Trade Secret	3.47

Mobility No information available.

Other adverse effects No information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste from residues/unused products Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Do not reuse empty containers.

US EPA Waste Number D001

California Waste Codes 331

This product contains one or more substances that are listed with the State of California as a hazardous waste.



Chemical name	California Hazardous Waste
Propan-2-ol 67-63-0	Toxic Ignitable

14. TRANSPORT INFORMATION

DOT

UN-No. UN1950
Proper Shipping Name AEROSOLS
Hazard Class 2.1
Description UN1950, AEROSOLS, 2.1, LTD QTY
Emergency Response Guide Number 126

TDG

UN-No. UN1950
Proper Shipping Name AEROSOLS
Hazard Class 2.1
Description UN1950, AEROSOLS, 2.1, LTD QTY

MEX

UN-No. UN1950
Proper Shipping Name AEROSOLS
Hazard Class 2.1
Description UN1950, AEROSOLS, 2.1

ICAO

UN-No. UN1950
Proper Shipping Name AEROSOLS
Hazard Class 2.1
Description UN1950, AEROSOLS, 2.1, LTD QTY

IATA

UN-No. UN1950
Proper Shipping Name AEROSOLS, FLAMMABLE
Hazard Class 2.1
ERG Code 10L
Description UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD QTY

IMDG/IMO

UN-No. UN1950
Proper Shipping Name AEROSOLS
Hazard Class 2.1
EmS-No. F-D, S-U
Description UN1950, AEROSOLS, 2.1, LTD QTY

RID

UN-No. UN1950
Proper Shipping Name AEROSOLS
Hazard Class 2.1
Classification code 5F
Description UN1950, AEROSOLS, 2.1
ADR/RID-Labels 2.1

ADR

UN-No. UN1950
Proper Shipping Name AEROSOLS
Hazard Class 2.1



Classification code 5F
 Tunnel restriction code (D)
 Description UN1950, AEROSOLS, 2.1, (D)

ADN

UN-No. UN1950
 Proper Shipping Name AEROSOLS
 Hazard Class 2.1
 Classification code 5F
 Special Provisions 190, 327, 344, 625
 Description UN1950, AEROSOLS, 2.1
 Hazard Labels 2.1
 Limited Quantity 1 L
 Ventilation VE01, VE04

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

International Inventories

TSCA Contact supplier for inventory compliance status.
 DSL/NDSL Contact supplier for inventory compliance status.
 EINECS/ELINCS Contact supplier for inventory compliance status.
 ENCS Contact supplier for inventory compliance status.
 KECL Contact supplier for inventory compliance status.
 PICCS Contact supplier for inventory compliance status.
 AICS Contact supplier for inventory compliance status.

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
 DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
 EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
 ENCS - Japan Existing and New Chemical Substances
 KECL - Korean Existing and Evaluated Chemical Substances
 PICCS - Philippines Inventory of Chemicals and Chemical Substances
 AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	CAS No	Weight-%	SARA 313 - Threshold Values %
Propan-2-ol - 67-63-0	67-63-0	13.4	1.0
2-Butoxyethanol - 111-76-2	111-76-2	3.725	1.0

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications. Under the amended regulations at 40 CFR 370, EPCRA 311/312 Tier II reporting for the 2017 calendar year will



need to be consistent with updated hazard classifications.

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

US State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals.

Chemical name	California Proposition 65
Supplier Trade Secret -	carcinogen, 2/21/2003 (airborne, unbound particles of respirable size)
Supplier Trade Secret -	Carcinogen

U.S. State Right-to-Know Regulations

This product may contain substances regulated by state right-to-know regulations.

Chemical name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Supplier Trade Secret	X	X	X		
Propan-2-ol 67-63-0	X	X	X	X	
Supplier Trade Secret	X	X	X		
Supplier Trade Secret	X	X	X		X
2-Butoxyethanol 111-76-2	X	X	X	X	X

16. OTHER INFORMATION

NFPA	Health hazards 3	Flammability 3	Instability 0	Physical and Chemical Properties -
HMIS	Health hazards 3 *	Flammability 3	Physical hazards 0	Personal Protection X
	Chronic Hazard Star Legend	* = Chronic Health Hazard		

Prepared By Product Stewardship
23 British American Blvd.
Latham, NY 12110
1-800-572-6501

Issuing Date 19-May-2021

Revision Date 03-Feb-2021

Revision Note No information available

Disclaimer



The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet

