according to Hazard Communication Standard; 29 CFR 1910.1200



GLADE PLUG IN SCENTED OIL FIRST FROST

Version 1.0 Print Date 04/15/2024

Revision Date 08/01/2023 SDS Number 350000044315 GEN SOF Number 78980

1. PRODUCT AND COMPANY IDENTIFICATION

Product information

Product name : GLADE PLUG IN SCENTED OIL FIRST FROST

Recommended use : Air Freshener

Restrictions on use : Use only as directed on label

Manufacturer, importer,

supplier

: S.C. Johnson & Son, Inc.

Racine WI 53403-2236

1525 Howe Street

Telephone : +1-800-558-5252

Emergency telephone

number

: 24 Hour Medical Emergency Phone: (866)231-5406 24 Hour Transport Emergency Phone: (800)424-9300

2. HAZARDS IDENTIFICATION

Classification of the substance or mixture

Globally Harmonized System (GHS) Classification

Hazard classification	Hazard category	Hazards identification
Flammable liquids	Category 4	Combustible liquid.
Eye irritation	Category 2B	Causes eye irritation.

Labelling

Signal word

Warning

Hazard statements

Combustible liquid. Causes eye irritation.

Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

according to Hazard Communication Standard; 29 CFR 1910.1200



GLADE PLUG IN SCENTED OIL FIRST FROST

Version 1.0 Print Date 04/15/2024

Revision Date 08/01/2023 SDS Number 350000044315 GEN SOF Number 78980

In case of fire: Use alcohol-resistant foam, carbon dioxide or dry sand to extinguish.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/ attention.

Store in a well-ventilated place. Keep cool.

Dispose of contents/ container to an approved incineration plant.

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Wear protective gloves.

Wash hands thoroughly after handling.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS-No.	Weight percent
Fragrance - Trade Secret	Mixture	60.00 - 100.00

The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

For additional information on product ingredients, see www.whatsinsidescjohnson.com.

4. FIRST AID MEASURES

Description of first aid measures

Eye contact : IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/ attention.

Skin contact : Wash off with plenty of water. Take off contaminated clothing

and wash before reuse. If skin irritation or rash occurs: Get

medical advice/ attention.

Inhalation : No special requirements.

Ingestion : No special requirements

Most important symptoms and effects, both acute and delayed

Eyes : May irritate eyes.

according to Hazard Communication Standard; 29 CFR 1910.1200



GLADE PLUG IN SCENTED OIL FIRST FROST

Version 1.0 Print Date 04/15/2024

Revision Date 08/01/2023 SDS Number 350000044315

GEN_SOF Number 78980

Skin effect : May cause allergic skin reaction.

Causes skin irritation.

No adverse effects expected when used as directed.

Inhalation : May cause allergic respiratory reaction.

Ingestion : May cause irritation to mouth, throat and stomach.

May cause abdominal discomfort.

No adverse effects expected when used as directed.

Indication of any immediate medical attention and special treatment needed

See Description of first aid measures unless otherwise stated.

5. FIREFIGHTING MEASURES

Suitable extinguishing

media

: Use water spray, alcohol-resistant foam, dry chemical or

carbon dioxide.

Specific hazards during

firefighting

: Flammable liquid. Vapors are heavier than air and may travel to a source of ignition and flash back. Liquid run-off to sewers may create fire/explosion hazard. Do not use a solid water

stream as it may scatter and spread fire. Container may melt

and leak in heat of fire.

Further information : Cool and use caution when approaching or handling fire-

exposed containers. For large quantities of flammable liquids, consider containment to prevent the spread of fire. Wear full protective clothing and positive pressure self-contained breathing apparatus. In case of fire and/or explosion do not

breathe fumes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Remove all sources of ignition.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Wear personal protective equipment.

according to Hazard Communication Standard; 29 CFR 1910.1200



GLADE PLUG IN SCENTED OIL FIRST FROST

Version 1.0 Print Date 04/15/2024

Revision Date 08/01/2023 SDS Number 350000044315 GEN SOF Number 78980

Wash thoroughly after handling.

Environmental precautions

: Outside of normal use, avoid release to the environment.

Methods and materials for containment and

cleaning up

: Use only non-sparking equipment.

Dike large spills.

Clean residue from spill site.

7. HANDLING AND STORAGE

Handling

Precautions for safe

handling

: Avoid contact with skin, eyes and clothing. For personal protection see section 8.

Use only as directed.

KEEP OUT OF REACH OF CHILDREN AND PETS.

Contaminated work clothing should not be allowed out of the

workplace.

Avoid breathing vapours, mist or gas. Wash thoroughly after handling.

Advice on protection against fire and explosion : Keep away from sources of ignition - No smoking.

Storage

Requirements for storage

areas and containers

Keep container closed when not in use. Store in a well-ventilated place. Keep cool.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

ACGIH or OSHA exposure limits have not been established for this product or reportable ingredients unless noted in the table above.

Personal protective equipment

Respiratory protection Substantial amounts of mist/vapors can be controlled with

local exhaust ventilation or respiratory protection.

Hand protection : Wear suitable gloves.

according to Hazard Communication Standard; 29 CFR 1910.1200



GLADE PLUG IN SCENTED OIL FIRST FROST

Version 1.0 Print Date 04/15/2024

Revision Date 08/01/2023 SDS Number 350000044315 GEN SOF Number 78980

Eye protection : Safety glasses with side-shields

Skin and body protection : No special requirements.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form : liquid

Color : colourless to light yellow

Odour : Woody

Fruity

Odour Threshold : Test not applicable for this product type

pH : Mixture is not soluble in water

Melting point/freezing point : <-20°C

Initial boiling point and

boiling range

: 70 - 140 C

Flash point : 80.6 C

177.08 °F

Method: ASTM D 93

Evaporation rate : Test not applicable for this product type

Flammability (solid, gas) : Sustains combustion

Upper/lower flammability or

explosive limits

: Not determined as it does not affect the liquid flammability

classification. Flash point is used for classification of

flammable liquids.

according to Hazard Communication Standard; 29 CFR 1910.1200



GLADE PLUG IN SCENTED OIL FIRST FROST

Version 1.0 Print Date 04/15/2024

Revision Date 08/01/2023 SDS Number 350000044315 GEN SOF Number 78980

Vapour pressure : 0.18091 mmHg

at 20 °C

Vapour density : >1

Relative density : 0.9654 g/cm3 at 25 °Cestimated

Solubility(ies) : immiscible

Partition coefficient: n-

octanol/water

: Not required as the product is a mixture.

: not auto-flammable Auto-ignition temperature

Decomposition temperature: Not measured as mixture is not self-reactive

Viscosity, dynamic : < 5 cps

at 20 °C

Viscosity, kinematic : Test not applicable for this product type

Oxidizing properties : Test not applicable for this product type

Volatile Organic : 84 % - additional exemptions may apply

Compounds *as defined by US Federal and State Consumer Product Total VOC (wt. %)*

Regulations

Other information : None identified

according to Hazard Communication Standard; 29 CFR 1910.1200



GLADE PLUG IN SCENTED OIL FIRST FROST

Version 1.0 Print Date 04/15/2024

Revision Date 08/01/2023 SDS Number 350000044315 GEN_SOF Number 78980

10. STABILITY AND REACTIVITY

Reactivity: No dangerous reaction known under conditions of normal use.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous

reactions

: Stable under recommended storage conditions.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition

products

: Stable under recommended storage conditions.

11. TOXICOLOGICAL INFORMATION

Acute dermal toxicity : LD50 > 5000 mg/kg

GHS Properties	Classification	Routes of entry
Acute toxicity	No classification proposed	Oral
Acute toxicity	No classification proposed	Dermal
Acute toxicity	No classification proposed	Inhalation - Dust and Mist
Acute toxicity	No classification proposed	Inhalation - Vapour
Acute toxicity	No classification proposed	Inhalation - Gas
Skin irritation	No classification proposed	-

according to Hazard Communication Standard; 29 CFR 1910.1200



GLADE PLUG IN SCENTED OIL FIRST FROST

Version 1.0 Print Date 04/15/2024

Revision Date 08/01/2023 SDS Number 350000044315 GEN_SOF Number 78980

Eye irritation	Category 2B	-
Skin sensitisation	No classification proposed	-
Respiratory sensitisation	No classification proposed	-
Germ cell mutagenicity	No classification proposed	-
Carcinogenicity	No classification proposed	-
Reproductive toxicity	No classification proposed	-
Specific target organ toxicity - single exposure	No classification proposed	-
Specific target organ toxicity - repeated exposure	No classification proposed	-
Aspiration hazard	No classification proposed	-

Aggravated Medical

: None known.

Condition

12. ECOLOGICAL INFORMATION

Product : The product itself has not been tested.

Toxicity

The ingredients in this formula have been reviewed and no adverse impact to the environment is expected when used according to label directions.

Toxicity to fish

Components	End point	Species	Value	Exposure time
Fragrance - Trade Secret	No data available			

Toxicity to aquatic invertebrates

according to Hazard Communication Standard; 29 CFR 1910.1200



GLADE PLUG IN SCENTED OIL FIRST FROST

Version 1.0 Print Date 04/15/2024

Revision Date 08/01/2023 SDS Number 350000044315

GEN_SOF Number 78980

Components	End point	Species	Value	Exposure time
Fragrance - Trade Secret	No data available			

Toxicity to aquatic plants

Components	End point	Species	Value	Exposure time
Fragrance - Trade Secret	No data available			

Persistence and degradability

Component	Biodegradation	Exposure time	Summary
Fragrance - Trade Secret	No data available		

Bioaccumulative potential

Component	Bioconcentration factor (BCF)	Partition Coefficient n- Octanol/water (log)
Fragrance - Trade Secret	No data available	No data available

Mobility

Component	End point	Value
Fragrance - Trade Secret	No data available	

PBT and vPvB assessment

Component	Results
Fragrance - Trade Secret	Not fulfilling PBT and vPvB criteria

Other adverse effects : None known.

according to Hazard Communication Standard; 29 CFR 1910.1200



GLADE PLUG IN SCENTED OIL FIRST FROST

Version 1.0 Print Date 04/15/2024

Revision Date 08/01/2023 SDS Number 350000044315 GEN SOF Number 78980

13. DISPOSAL CONSIDERATIONS

Consumer may discard empty container in trash, or recycle where facilities exist.

14. TRANSPORT INFORMATION

Please refer to the Bill of Lading/receiving documents for up-to-date shipping information.

Land transport

Not classified as dangerous in the meaning of transport regulations.

Sea transport

Not classified as dangerous in the meaning of transport regulations.

Air transport

Not classified as dangerous in the meaning of transport regulations.

15. REGULATORY INFORMATION

Notification status : All ingredients of this product are listed or are excluded from

listing on the U.S. Toxic Substances Control Act (TSCA)

Chemical Substance Inventory.

California Prop. 65 : This product is not subject to the reporting requirements under

California's Proposition 65.

according to Hazard Communication Standard; 29 CFR 1910.1200



GLADE PLUG IN SCENTED OIL FIRST FROST

Version 1.0 Print Date 04/15/2024

Revision Date 08/01/2023 SDS Number 350000044315 GEN SOF Number 78980

16. OTHER INFORMATION

ЦN	AIC.	Rati	-
нΝ	MIS.	Katı	nas

HIVIIS Natilitys		
Health	2	
Flammability	2	
Reactivity	0	

NFPA Ratings

NEPA Kaungs		
Health	2	
Fire	2	
Reactivity	0	
Special	-	

This information is being provided in accordance with the Occupational Safety and Health Administration (OSHA) regulation (29 CFR 1910.1200). The information supplied is designed for workplaces where product use and frequency of exposure exceeds that established for the labeled consumer use.

Further information

This document has been prepared using data from sources considered to be technically reliable. It does not constitute a warranty, expressed or implied, as to the accuracy of the information contained herein. Actual conditions of use are beyond the seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.

Prepared by	SC Johnson Global Safety Assessment &
	Regulatory Affairs (GSARA)