

# Safety Data Sheets (SDSs)

DONG GUAN SHI RUIFENG ENERGY TECHNOLOGY CO., LTD. Client

Room 201. Building 1. No.13, Dalingbian Road, Shahu. Tangxia Town, Dongguan

Add. of Client City, Guangdong Province, China

Li-ion Battery Description

RF18650 Model /Type

DONG GUAN SHI RUIFENG ENERGY TECHNOLOGY CO., LTD. Manufacturer

Add. of Room 201. Building 1. No.13, Dalingbian Road, Shahu. Tangxia Town, Dongguan

City, Guangdong Province, China Manufacturer

Nominal Voltage 7.4V, 2000mAh,14.8Wh

2023-01-01 Date of Receipt

Laboratory GUANGDONG UTL CO., LTD.

Lianding Testing Building, No.18 Center Road of Yayuan Industrial Address

Zone, Nancheng District, Dongguan, Guangdong, China.

Approved

Signatory

Maggie.Gao

Inspected by

Ailis.Ma

Moggie Goo Ailis Ma Lahn Peng

Censored by

Lahm Peng

Report No.: ZKS200900547

Page 1 of 11



# 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

#### **Product Identifier**

Product name: Li-ion Battery

Model: RF18650

#### Other means of identification

Synonyms:noneRecommended use of the chemical and

#### restrictions on use

Recommended Use: Used in portabl electronic equipments;

Uses advidsed against:

- a) Do not dismantle, open or shred secondary cells or batteries.
- b) Keep batteries out of the reach of children

Battery usage by children should be supervised. Especially keep small batteries out of reach of small children.

- c) Seek medical advice immediately if a cell or a battery has been swallowed.
- d) Do not expose cells or batteries to heat or fire. Avoid storage in direct sunlight.
- e) Do not short-circuit a cell or a battery. Do not store cells or batteries haphazardly in a box or drawer where they may short-circuit each other or be short-circuited by other metal objects.
- f) Do not remove a cell or battery from its original packaging until required for use.
- g) Do not subject cells or batteries to mechanical shock.
- h) In the event of a cell leaking, do not allow the liquid to come in contact with the skin or eyes. If contact has been made, wash the affected area with copious amounts of water and seek medical advice.
- i) Do not use any charger other than that specifically provided for use with the equipment.
- j) Observe the plus (+) and minus (-) marks on the cell, battery and equipment and ensure correct use.
- k) Do not use any cell or battery which is not designed for use with the equipment.
- 1) Do not mix cells of different manufacture, capacity, size or type within a device.
- m) Always purchase the battery recommended by the device manufacturer for the equipment.
- n) Keep cells and batteries clean and dry.
- o) Wipe the cell or battery terminals with a clean dry cloth if they become dirty.
- p) Secondary cells and batteries need to be charged before use. Always use the correct charger and refer to the manufacturer's instructions or equipment manual for proper charging instructions.
- q) Do not leave a battery on prolonged charge when not in use.
- r) After extended periods of storage, it may be necessary to charge and discharge the cells or batteries several times to obtain maximum performance.
- s) Retain the original product literature for future reference.
- t) Use the cell or battery only in the application for which it was intended.
- u) When possible, remove the battery from the equipment when not in use.
- v) Dispose of properly.

#### Details of the supplier of the safety data sheet:

Supplier Name: DONG GUAN SHI RUIFENG ENERGY TECHNOLOGY CO., LTD.

Address: Room 201. Building 1. No.13, Dalingbian Road, Shahu. Tangxia Town, Dongguan City, Guangdong

Province, China

Telephone number of the supplier: +86-15986625256

Fax: N/A

Report No.: ZKS200900547



Postcode: 321400 E-mail address: N/A

**Emergency telephone number** 

Company Emergency Phone Number: +86-769-87285025

# 2. HAZARDS IDENTIFICATION

#### Classification

Acute toxicity - Dermal	Category 3
Serious eye damage/eye irritation	Category 2A
Carcinogenicity	Category 2
Specific target organ toxicity (repeated exposure)	Category 1

## GHS Label elements, including precautionary statements

#### Danger

#### **Hazard statements**

Toxic in contact with skin

Causes serious eye irritation

Suspected of causing cancer

Causes damage to organs through prolonged or repeated exposure



## **Precautionary statements-Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Wear protective gloves/protective clothing/eye protection/face protection

Wash face, hands and any exposed skin thoroughly after handling

Do not breathe dust/fume/gas/mist/vapors/spray

Do not eat, drink or smoke when using this product

## **Precautionary Statements - Response**

If exposed or concerned: Get medical advice/attention Specific treatment (see supplemental first aid instructions on this label)

Report No.: ZKS200900547



#### Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

#### Skin

IF ON SKIN: Wash with plenty of water and soap
Call a POISON CENTER or doctor if you feel unwell

Take off immediately all contaminated clothing and wash it before reuse

## **Precautionary Statements - Storage**

Store locked up

## **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

#### Other information

harmful if swallowed. Very toxic to aquatic life with long lasting effects.

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

**Chemical characterixation: Mixtures** 

**Description:** 

Product: Consisting of the following components.

Common Chemical Name	Chemical Formula	Concentration (%)	CAS Number	
Lithium Cobalt Oxide	LiCoO <sub>2</sub>	40	12190-79-3	
Graphite	C <sub>24</sub> X <sub>12</sub>	19	7782-42-5	
Polyvinylidene Fluoride (PVDF)	C₂H₂F₂	0.8	24937-79-9	
Aluminium	Al	5.8	7429-90-5	
Styrene Butadiene Rubber (SBR)	C <sub>36</sub> H <sub>42</sub> X <sub>2</sub>	1.2	61789-96-6	
Carboxymethylcellulose	C <sub>6</sub> H <sub>12</sub> O <sub>6</sub>	0.3	9000-11-7	
Copper	Cu	10.6	7440-50-8	
Nickel	Ni	0.4	7440-02-0	
Lithium Hexafluorophosphate	LiPF <sub>6</sub>	21.9	21324-40-3	

Note: CAS number is Chemical Abstract Service Registry Number.

N/A=Not apply.

Report No.: ZKS200900547



## 4. FIRST-AID MEASURES

#### First aid measures

Eye Contact Rinse thoroughly with plenty of water, also under the eyelids. If symptoms persist, call a physician.

Skin Contact Remove contaminated clothing and shoes. Wash skin with soap and water. In the case of skin irritation or allergic reactions see a physician.

Inhalation Move to fresh air. If symptoms persist, call a physician.

Ingestion Do NOT induce vomiting. Drink plenty of water. If symptoms persist, call a physician.

Most important symptoms and effects, both acute and delayed

Swallowing Do not induce vomiting. Get medical attention.

**Most Important Symptoms/Effects** No information available.

# Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically

# 5. FIRE-FIGHTING MEASURES

#### Suitable Extinguishing Media

CO<sub>2</sub>, dry chemical powder, water spray.

Unsuitable Extinguishing Media:No information available.

#### **Specific Hazards Arising from the Chemical**

Formation of toxic gases is possible during heating or in case of fire.

In case of fire, the following can be released:

Carbon monoxide(CO)

Carbon dioxide

Other irritating and toxic gases.

## **Hazardous Combustion Products**

Carbon oxides.

**Explosion Data** 

Sensitivity to Mechanical Impact No

Sensitivity to Static Discharge No

#### **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. For example: Wear self-contained respiratory protective device. Wear suitable protective clothing and eye/face protection.

# **Special hazards arising from the substance or mixture:**

Battery may burst and release hazardus decomposition products when exposed to a fire situation. Lithium ion batteries contain flammable electrolyte that may vent, ignite and produce sparks when subjected to high temperature(>150°C), When damaged or abused(e.g. mechanical damage or electrical overcharging); may burn rapidly with flare-burning effect; may ignite other batteries in clothes proximity.

# 6. ACCIDENTAL RELEASE MEASURES

Report No.: ZKS200900547 Page 5 of 11



#### Personal precautions, protective equipment and emergency procedures

Personal Precautions Avoid contact with eyes.

Refer to section 8 for personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition.

Evacuate personnel to safe areas.

#### **Environmental precautions**

Environmental Precautions Refer to protective measures listed in Sections 7 and 8.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

#### Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Cleaning up Use personal protective equipment. Dam up. Cover liquid spill with sand, earth or other Non combustible absorbent material. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly.

# 7. HANDLING AND STORAGE

#### Precautions for safe handling

Handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes and clothing. Wear personal protective equipment.

Wash thoroughly after handling. Use this material with adequate ventilation.

The product is not explosive.

#### Conditions for safe storage, including any incompatibilities

If the Lithium-ion Battery is subject to storage for such a long term as more than 3 months, it is recommended to recharge the Li-ion Polymer Battery periodically.

3 months: -10°C~+40°C, 45 to 85%RH

And recommended at 0°C~+35°C for long period storage.

The capacity recovery rate in the delivery state (50% capacity of fully charged) after storage is assumed to be 80% or more.

The voltage for a long time storage shall be 3.7V~4.2V range.

Do not storage Lithium-ion Battery haphazardly in a box or drawer where they may short-circuit each other or be short-circuited by other metal objects.

Keep out of reach of children.

Do not expose Li-ion Polymer Battery to heat or fire. Avoid storage in direct sunlight.

Do not store together with oxidizing and acidic materials.

Keep ignition sources away- Do not smoke.

Store in cool, dry and well-ventilated place.

**Incompatible Products** None known.

# 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

# **Control parameters**

Ingredients with limit values that require monitoring at the workplace:

12190-79-3 Lithium Manganese Nickel And Cobalt

Report No.: ZKS200900547



TLV (USA)	$0.02 \text{mg/m}^3$
MAK (Germany)	$0.1 \text{mg/m}^3$

**Other Exposure Guidelines** Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962(11th Cir., 1992).

#### Appropriate engineering controls

**Engineering Measures** Showers

Eyewash stations

Ventilation systems

Use adequate general or local exhaust ventilation to keep airborne concentrations below the permissible exposure limits. Ensure adequate ventilation.

#### Individual protection measures, such as personal protective equipment

## **Eye/Face Protection:**



Tightly sealed goggles

#### **Body protection:**

Protective work clothing.

#### **Skin protection:**



## **Protective gloves**

#### Material of gloves:

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### Penetration time of glove material:

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

**Respiratory Protection** No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical	Form: Cylindrical
State	Color: Pink

Report No.: ZKS200900547



	Odour: Odourless						
	Odor Threshold: No information available						
Change in co	hange in condition:  Not determined.						
pH, with ind	ication of the concentration	Not determined.					
Melting poir	nt/freezing point	Not determined.					
Initial boilin	g point and Boiling range:	Not determined.					
Flash Point		Not determined.					
Evaporation	rate	Not determined.					
Flammabilit	y (solid, gas)	Not determined.					
Upper/lower	flammability or explosive limits	Not determined.					
Vapor Pressure:		Not determined.					
Vapor Density:		Not determined.					
relative dens	sity:	Not determined.					
Solubility in	Water:	Not determined.					
Solubility in	other solvents	Not determined.					
n-octanol/wa	ater partition coefficient	Not determined.					
Auto-ignitio	n temperature	Product is not self-igniting.					
Decompositi	ion temperature	Not determined.					
Odout threshold		Not determined.					
Evaporation rate		Not determined.					
Viscosity		Not determined.					
Other Inforn	nation	No further relevant information available.					

# 10. STABILITY AND REACTIVITY

**Reactivity:** Stable under recommended storage and handling conditions (see section 7, Handling and storage).

Chemical stability: Stable under normal conditions of use, storage and transport.

Thermal decomposition/conditions to be avoided: No decomposition if used according to specifications.

Possibility of Hazardous Reactions: None under normal processing.

Hazardous Polymerization: Hazardous polymerization does not occur.

**Conditions to avoid:** Strong heating, fire, Incompatible materials.

Incompatible materials: Strong oxidizing agents. Strong acids. Base metals.

Hazardous Decomposition Products: Carbon oxides, Other irritating and toxic gases.

# 11. TOXICOLOGICAL INFORMATION

Report No.: ZKS200900547 Page 8 of 11



Acute toxiciy: No data available.

LD/LC50 values relevant for classification:

Not available.

Skin corrosion/irritation: No irritant effect.

Serious eye damage/irritation: Cause serious eye irritation.

Respiratory or skin sensitization: No sensitizing effects known.

Specific target organ system toxicity: No information available.

CMR effects(carcinogenity, mutagenicity and toxicity for reproduction): No information available.

# 12. Ecological Information

## **Toxicity:**

Acquatic toxicity:

No further relevant information available.

Persistence and degradability: No further relevant information available.

**Bioaccumulative potential:** No further relevant information available.

Mobility in soil: No further relevant information available.

Results of PBT and vPvB assessment

PBT: Not applicable. vPvB: Not applicable.

Other adverse effects: No information available.

# 13. DISPOSAL CONSIDERATIONS

#### Waste treatment methods

Recommendation: Must not be disposed together with household garbage.

Do not allow product to reach sewage system

## **Uncleaned packaging:**

Recommendation: Disposal must be made according to official regulations.

## 14. TRANSPORT INFORMATION

This report applies to by sea, by air and by land;

The Polymer Li-ion Rechargeable Battery must be of a design type proved to meet the testing requirements of the Manual of test and criteria, Part III, subsection 38.3;

The Polymer Li-ion Rechargeable Battery according to Section II of PACKING INSTRUCTION 965-967 of the 2019 IATA Dangerous Goods regulations 60<sup>th</sup> Edition may be transported. and applicable U.S. DOT regulations for the safe transport of Lithium-ion Battery.

Polymer Li-ion Rechargeable Battery was protected so as to prevent short circuits. This includes protection against contact with conductive materials within the same packaging that could lead to short circuit;

Report No.: ZKS200900547



Cell and batteries offered for transport must be packed in inner packaging's that completely enclose the cell or battery; to provide protection from damage or compression to the batteries, the inner packaging's must be placed in a strong rigid outer packaging;

The packaging shall be adequate to avoid mechanical damage during transport, handling and stacking. The materials and pack design shall be chosen so as to prevent the development of unintentional electrical conduction, corrosion of the terminals and ingress of moisture.

The package must be handled with care and that a flammability hazard exists if the package is damaged;

With regard to transport, the following regulations are cited and considered:

- The International Civil Aviation Organization (ICAO) Technical Instructions.
- The International Air transport Association (IATA) Dangerous Goods Regulations.

UN number of lithium battery: UN3480;

UN Proper shipping name/Description (technical name): Lithium ion batteries;

- The International Maritime Dangerous Goods Code 2018 Edition (Amdt.39-18)

For lithium-ion batteries by sea, provided that packaging is strong and prevent the products from short-circuit. UN number of lithium battery: UN3481;

UN Proper shipping name/Description (technical name): Lithium ion batteries

Special Provision: International maritime dangerous goods code (IMDG) 188, 230, 310, 348, 957;

- The US Hazardous Materials Regulation (HMR) pursuant to a final rule issued by RSPA
- The Office of Hazardous Materials Safety within the US Department of Transportations' (DOT) Research and Special Programs Administration (RSPA)

## 15. REGULATORY INFORMATION

# Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation:

**Authorisations:** No information available. **Restrictions on use:** No information available.

Regulatory information

CAS No.	EU	US	Japan	Canada	Austrlia	Korea	China
	(EINECS	(TSCA)	(ENCS)	(DSL/	(AICS)	(ECL)	(IECSC)
	)			NDSL)			
12190-79-3	Listed	Not listed	Not listed	NDSL	Not listed	Not listed	Not listed
7429-90-5	Listed	Listed	Listed	DSL	Listed	Listed	Listed
24937-79-9	Listed	Listed	Listed	DSL	Listed	Listed	Listed
7782-42-5	Not listed	Listed	Not listed	DSL	Listed	Listed	Listed
7440-50-8	Not listed	Listed	Not listed	DSL	Listed	Listed	Listed
9003-55-8	Listed	Not listed	Not listed	NDSL	Not listed	Not listed	Not listed
21324-40-3	Listed	Not listed	Not listed	NDSL	Not listed	Not listed	Not listed
96-49-1	Listed	Not listed	Not listed	NDSL	Not listed	Not listed	Not listed
616-38-6	Listed	Not listed	Not listed	NDSL	Not listed	Not listed	Not listed
623-53-0	Listed	Not listed	Not listed	NDSL	Not listed	Not listed	Not listed

Report No.: ZKS200900547





440-02-0 Listed Not li	ted Not listed NDS	L Not listed	Not listed	Not listed
------------------------	--------------------	--------------	------------	------------

<u>Chemical safety assessment</u> A Chemical Safety Assessment has not been carried out.

# 16. OTHER INFORMATION

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Report No.: ZKS200900547