

# MATERIAL SAFETY DATA SHEET

According to the European directive 2001/58/CE Issue Date:01/23/2013

Doc. No.: 01232013-01A

## 1. Product & Company Identification

<b>Product Description:</b>	Li-Ion Polymer Rechargeable Battery	<b>Model Name:</b>	
<b>UN No:</b>	3480	<b>Capacity:</b>	0.55Ah
<b>Watt hour:</b>	2.04Wh		

## 2. Composition /Information on Ingredients:

**Important note: The battery should not be opened or burned. Exposure to the ingredients contained within or their combustion products could be harmful.**

MATERIAL OR INGREDIENT	PEL (OSHA)	TLV (ACGIH)	%/wt.
Graphite (CAS# 7782-42-5)			
Lithium Cobalt Oxide (CAS# 12190-79-3)			
Hexafluoropropylene-vinylidene fluoride Copolymer (CAS#9011-17-0)	None established	None established	
Lithium Hexafluorophosphate (CAS# 21324-40-3)	None established	None established	
MATERIAL OR INGREDIENT	PEL (OSHA)	TLV (ACGIH)	%/wt.
Acetylene Black (CAS# 1333-86-4)			
Diethyl Carbonate (CAS# 105-58-8)	None established	None established	
Dimethyl Carbonate (CAS# 616-38-6)	None established	None established	
Ethyl Methyl Carbonate (CAS# 623-53-0)	None established	None established	
Propylene Carbonate (CAS# 108-32-7)	None established	None established	
Ethylene Carbonate (CAS# 96-49-1)	None established	None established	

# MATERIAL SAFETY DATA SHEET

According the European directive 2001/58/CE Issue Date:01/23/2013

Doc. No.: 01232013-01A

---

## 3. Hazardous Identification

**Chemical Nature:** White color solid

CAS-No/EINECS NO.:N/A

INCI CTFA-Description: Lithium ion polymer rechargeable battery series

**Ingestion:** No effect under routine handling and use.

**Inhalation:** No effect under routine handling and use.

**Skin contact:** No effect under routine handling and use.

**Eye contact:** No effect under routine handling and use.

**Skin absorption:** No effect under routine handling and use.

**Reported as carcinogen:** Not applicable

## 4. First Aid Measures

Under normal conditions of use, the battery is hermetically sealed.

**Ingestion:** Swallowing a battery can be harmful. Contents of an open battery can cause serious chemical burns of mouth, esophagus, and gastrointestinal tract. If battery or open battery is ingested, do not induce vomiting or give food or drink. Seek medical attention immediately.

**Inhalation:** Contents of an open battery can cause respiratory irritation. Inhalation of vapors may cause irritation of the upper respiratory tract and lungs. Provide fresh air and seek medical attention.

**Skin Absorption:** Ethylene carbonate, diethyl carbonate and dimethyl carbonate may be absorbed through the skin causing localized inflammation.

**Skin Contact:** Contents of an open battery can cause skin irritation and/or chemical burns. Remove contaminated clothing and wash skin with soap and water. If a chemical burn occurs or if irritation persists, seek medical attention.

**Eye Contact:** Contents of an open battery can cause severe irritation and chemical burns. Immediately flush eyes thoroughly with water for at least 15 minutes, lifting upper and lower lids, until no evidence of the chemical remains. Seek medical attention. Note: Acetylene black and cobalt compounds are listed as possible carcinogens by the International Agency for Research on Cancer (IARC).

## 5. Fire Fighting Measures

If fire or explosion occurs when batteries are on charge, shut off power to charger. In case of fire where lithium ion batteries are present, flood the area with water. If any batteries are burning, water may not extinguish them, but will cool the adjacent

# MATERIAL SAFETY DATA SHEET

According to the European directive 2001/58/CE Issue Date:01/23/2013

Doc. No.: 01232013-01A

---

batteries and control the spread of fire. CO<sub>2</sub>, dry chemical, and foam extinguishers are preferred for small fires, but also may not extinguish burning lithium ion batteries.

Burning batteries will burn themselves out. Virtually all fires involving lithium ion batteries can be controlled with water. When water is used, however, hydrogen gas may be evolved which can form an explosive mixture with air. LITH-X (powdered graphite) or copper powder fire extinguishers, sand, dry ground dolomite or soda ash may also be used. These materials act as smothering agents.

Fire fighters should wear self-contained breathing apparatus. Burning lithium ion batteries can produce toxic fumes including HF, oxides of carbon, aluminum, lithium, copper, and cobalt. Volatile phosphorus pent fluoride may form at a temperature above 230° Fahrenheit.

## 6. Accidental Release Measures

**On hand:** Place material into suitable containers and call local fire/police department.

**In water:** If possible. Remove from water and call local fire/police department.

## 7. Handling & Storage

**Handling:** Do not expose the battery to excessive physical shock or vibration. Short-circuiting should be avoided; however, accidental short-circuiting for a few seconds will not seriously affect the battery. Prolonged short circuits will cause the battery to rapidly lose energy, could generate enough heat to burn skin. Sources of short circuits include jumbled batteries in bulk containers, coins, metal jewelry, metal covered tables, or metal belts used for assembly of batteries in devices. To minimize risk of short-circuiting, the protective case supplied with the battery should be used to cover the terminals when transporting or storing the battery. Do not disassemble or deform the battery. Should an individual cell within a battery become ruptured, do not allow contact with water.

**Storage:** The lithium ion battery should be between 25% and 75% of full charge when stored for a long period of time. Stored in a cool, dry, and well ventilated area. Elevated temperatures can result in loss of battery performance, leakage, or rust. Do not expose the battery to open flames.

## 8. Exposure Control/Personal Protection

# MATERIAL SAFETY DATA SHEET

According the European directive 2001/58/CE Issue Date:01/23/2013

Doc. No.: 01232013-01A

---

**Engineering Control:** Keep away from heat and open flame. Stored in a cool dry place.

## Personal Protection:

**Respiratory Protection:** Not necessary under normal conditions.

**Eye/Face Protection:** Not necessary under normal conditions. Wear safety glasses with side shields if handling an open or leaking battery.

**Gloves:** Not necessary under normal conditions. Use neoprene or natural rubber gloves if handling an open or leaking battery.

**Foot Protection:** Steel toed shoes recommended for large container handling.

## 9. Physical/Chemical Properties

Physical state	Solid	Solubility in water:	Not Applicable
Color	White	Vapor pressure	Not Applicable
Odor	No	Explosion limit	Not Applicable
Flash point	Not Applicable	Auto flammability	Not Applicable
Solubility in ethanol soluble	Not Applicable	Melting Point	Not Applicable
Boiling Point	Not Applicable	Freezing Point	Not Applicable

## 10. Stability & Reactivity

**Stability:** Good stability at standard temperature.

**Reactivity:** None

Avoid contact with water and acids. Hazardous decomposition products: If Al package foil of battery is damaged, the battery should avoid to contact strong oxidizer, acids and high temperature, and the electrolyte will be formed HF.

## 11. Toxicological information

This product does not elicit toxicological properties during routine handling and use.

## 12. Ecological information

# MATERIAL SAFETY DATA SHEET

According the European directive 2001/58/CE Issue Date:01/23/2013

Doc. No.: 01232013-01A

If the battery is scrapped, it should be selected and disposed by professional company.

## 13. Disposal considerations

Do not dispose of battery into environment or sewerage. It should be recycled and disposed basing on your local legislation and regulations.

## 14. Transport Information

The battery models listed is considered to be “rechargeable batteries” and meet the requirements of transportation by the U.S. Department of Transportation International Civil Aviation Administration (ICAO) and the most recent edition of the International Air Transportation Association (IATA) regulations.

Shipment contains no item listed under IATA DGR Special Provision A154 and meets all requirements under UN Manual of Tests and Criteria Part III, subsection 38.3.

No	ITEMS	RESULT	REMARKS
1	Altitude simulation	Pass	Test 1 to 5 must be conducted in sequence on the same cell or battery
2	Thermal test	Pass	
3	Vibration	Pass	
4	Shock	Pass	
5	External short circuit	Pass	
6	Impact	Pass	
7	Overcharge	Pass	Only battery do need this test item
8	Forced Discharge	Pass	

The product is not classified as dangerous Goods according to the current edition of IATA Dangerous Goods Regulations. And not regulated by IATA DGR. This product fully conforms to IATA Shipping PI 967, section. Do not damage or mishandle this

# MATERIAL SAFETY DATA SHEET

According to the European directive 2001/58/CE Issue Date:01/23/2013

Doc. No.: 01232013-01A

---

package. If package is damaged, batteries must be quarantined, inspected, and repacked. For emergency information, call: +86-769-88989338.

For more information on IATA regulations, please refer to the most recent IATA regulations, Packing Instructions 965-967. Lithium ion cells and batteries offered for transportation are NOT subject to additional requirements of the UN Regulations if:

- ✓ for cells, the watt-hour rating is not more than 20Wh
- ✓ for batteries, Watt-hour rating is not more than 100Wh (for batteries, the Watt-hour rating must be marked on the outside of the battery case except those manufactured before 1 January 2009 which may be transported without this marking until 31 December 2010). Cells and batteries must be packed in accordance with the IATA packing Instructions 965-967

## 15. Regulatory Information

See ACGIH exposure limits information as noted in Section 3.

**US:** This MSDS meets/exceeds OSHA requirements.

**International:** This MSDS conforms to European Union (UN), the International Standards Organization (ISO) and the International Labor Organization (ILO) and as documented in ANSI (American National Standards Institute) Standard Z400.1-1993.

## 16. Charging and labeling

**Charging:** This battery is made to be charged many times. Use an Energizer approved battery charger. Never use a modified or damaged battery charger. A backup charge termination based on time is recommended to prevent overcharging. The charging temperature should be between 0° C and 45° C (32° F and 113° F). The battery pack will be normally warm during charging.

**Charging Voltages and Currents:** Charging voltages are prevented from exceeding the specified limits by an internal battery protection circuit. Never use a battery that shows signs of a damaged protection circuit or broken case. (Such damage to the protection circuit may be indicated by voltages at the battery terminals outside of their specified ranges.) Adhere to all specified charging and discharging voltages and currents. Do not use battery if its voltage drops below the specified minimum voltage.

**Labeling:** If the label or package warnings are not visible, it is important to provide a package and/or device label stating:

**WARNING: CHARGE ONLY WITH SPECIFIED CHARGERS ACCORDING TO DEVICE MANUFACTURER'S INSTRUCTIONS. DO NOT OPEN BATTERY,**

# MATERIAL SAFETY DATA SHEET

According the European directive 2001/58/CE Issue Date:01/23/2013

Doc. No.: 01232013-01A

---

**DISPOSE OF IN FIRE, OR SHORT CIRCUIT - MAY IGNITE, EXPLODE, LEAK,  
OR GET HOT CAUSING PERSONAL INJURY.**

**Disposal:** Dispose in accordance with all applicable federal, state and local regulations.

## 17. Other information

The information contained herein is furnished without warranty of any kind. Users should consider this data only as a supplement to other information gathered by them and must make independent determinations of the suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers.