Revision Number 3

Revision Date 29-Mar-2016



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Name AHB572535PJT

Other means of identification

Issuing Date 29-Mar-2016

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use LITHIUM ION BATTERIES

Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Name SYNergy ScienTech Corp.

Supplier Address 7F, No9, Park Avenue II,

Science-based Industrial Park

HsinChu N/A 30075 TW

Supplier Phone Number Phone:886-3-5643700

Fax:886-3-5646767

Supplier Email stellah0917@gmail.com

Emergency telephone number

Company Emergency Phone

886-911254622

Number

2. HAZARDS IDENTIFICATION

Classification

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200). This product is an article which is a sealed battery and as such does not require an MSDS per the OSHA hazard communication



Page 1/14

standard unless ruptured. The hazards indicated are for a ruptured battery.

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Skin sensitization	Category 1
Carcinogenicity	Category 1A
Specific target organ toxicity (repeated exposure)	Category 1

GHS Label elements, including precautionary statements

Emergency Overview

Signal word Danger

Hazard Statements

Causes skin irritation
Causes serious eye irritation
May cause an allergic skin reaction
May cause cancer

Causes damage to organs through prolonged or repeated exposure





This product is an article which contains a chemical substance. Safety information is given for exposure to the article as sold. Intended use of the product should not result in exposure to the chemical substance. This is a battery. In case of rupture: the above hazards exist.

Appearance No information available Physical state Solid Odor No information available

Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Contaminated work clothing should not be allowed out of the workplace

Wear protective gloves

Do not breathe dust/fume/gas/mist/vapors/spray

Do not eat, drink or smoke when using this product

Wear eye/face protection

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

Specific treatment (see supplemental first aid instructions on this label)

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

Skin

IF ON SKIN: Wash with plenty of soap and water



Take off contaminated clothing and wash before reuse If skin irritation or rash occurs: Get medical advice/attention

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Unknown Toxicity

24.6 % of the mixture consists of ingredient(s) of unknown toxicity

Other information

May be harmful in contact with skin Very toxic to aquatic life with long lasting effects Repeated or prolonged skin contact may cause allergic reactions with susceptible persons

Interactions with Other Chemicals

No information available.

3. COMPOSITION/INFORMATION ON INGREDIENTS

.

Chemical name	CAS No	Weight-%	Trade Secret
Lithium Cobalt Oxide (LiCoO ₂)	12190-79-3	15 - 40	*
Carbon black	1333-86-4	10 - 30	*
Aluminum	7429-90-5	10 - 30	*
Copper	7440-50-8	5 - 10	*
Phosphate(1-), hexafluoro-, lithium	21324-40-3	1 - 5	*
Nickel	7440-02-0	0.1 - 1	*
Propylene imine	75-55-8	0.1 - 1	*

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

First aid measures

General Advice First aid is upon rupture of sealed battery.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep

eye wide open while rinsing. Remove contact lenses, if present and easy to do. Continue rinsing. Do not rub affected area. Get medical attention if irritation develops and persists.

Skin contact Wash off immediately with soap and plenty of water for at least 15 minutes. May cause an

allergic skin reaction. In the case of skin irritation or allergic reactions see a physician.

Inhalation Remove to fresh air. Get medical attention immediately if symptoms occur.



Page 3/14

Ingestion Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an

unconscious person. Do NOT induce vomiting. Call a physician.

Self-protection of the first aider Avoid contact with skin, eyes or clothing. Use personal protective equipment as required.

Wear personal protective clothing (see section 8).

Most important symptoms and effects, both acute and delayed

Most Important Symptoms and

Burning sensation. Itching. Rashes. Hives. Coughing and/ or wheezing.

Effects

Indication of any immediate medical attention and special treatment needed

Notes to Physician May cause sensitization in susceptible persons. Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media

CAUTION: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

Product is or contains a sensitizer. May cause sensitization by skin contact.

Uniform Fire Code Sensitizer: Solid

Explosion Data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

U

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal

protective equipment as required. Evacuate personnel to safe areas.

Other Information Refer to protective measures listed in Sections 7 and 8.

Environmental precautions

Environmental precautions Prevent further leakage or spillage if safe to do so.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Pick up and transfer to properly labeled containers.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling In case of rupture: Handle in accordance with good industrial hygiene and safety practice.

Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this

product. Take off contaminated clothing and wash before reuse.

Conditions for safe storage, including any incompatibilities

Storage Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up.

Keep out of the reach of children.

Incompatible Products Strong acids. Strong oxidizing agents. Strong bases.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Lithium Cobalt Oxide (LiCoO ₂) 12190-79-3	TWA: 0.02 mg/m ³	-	
Carbon black 1333-86-4	TWA: 3 mg/m ³ inhalable fraction	TWA: 3.5 mg/m ³ (vacated) TWA: 3.5 mg/m ³	IDLH: 1750 mg/m³ TWA: 3.5 mg/m³ TWA: 0.1 mg/m³ Carbon black in presence of Polycyclic aromatic hydrocarbons PAH
Aluminum 7429-90-5	TWA: 1 mg/m ³ respirable fraction	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust



		fraction	
		(vacated) TWA: 15 mg/m ³ total	
		dust	
		(vacated) TWA: 5 mg/m ³	
		respirable fraction (vacated)	
		TWA: 5 mg/m ³ Al Aluminum	
Copper	TWA: 0.2 mg/m ³ fume TWA: 1	TWA: 0.1 mg/m ³ fume	IDLH: 100 mg/m ³ dust, fume
7440-50-8	mg/m ³ Cu dust and mist	TWA: 1 mg/m ³ dust and mist	and mist
	_	(vacated) TWA: 0.1 mg/m ³ Cu	TWA: 1 mg/m ³ dust and mist
		dust, fume, mist	TWA: 0.1 mg/m ³ fume
Phosphate(1-), hexafluoro-, lithium	TWA: 2.5 mg/m ³ F	TWA: 2.5 mg/m ³ F	
21324-40-3		TWA: 2.5 mg/m ³ dust	
		(vacated) TWA: 2.5 mg/m ³	
Nickel	TWA: 1.5 mg/m ³	TWA: 1 mg/m ³	IDLH: 10 mg/m ³
7440-02-0		(vacated) TWA: 1 mg/m ³	TWA: 0.015 mg/m ³
Propylene imine	STEL: 0.4 ppm	TWA: 2 ppm	IDLH: 100 ppm
75-55-8	TWA: 0.2 ppm	TWA: 5 mg/m ³	TWA: 2 ppm
	S*	(vacated) TWA: 2 ppm	TWA: 5 mg/m ³
		(vacated) TWA: 5 mg/m ³	
		(vacated) S*	
		S*	

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits NIOSH IDLH Immediately Dangerous to Life or Health

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d

962 (11th Cir., 1992)

Appropriate engineering controls

Engineering Measures Showers

Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin and body protectionWear protective gloves and protective clothing. Long sleeved clothing. Impervious gloves.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice. Avoid contact with

skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling

the product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Physical state Solid

AppearanceNo information availableOdorNo information availableColorNo information availableOdor ThresholdNo information available

<u>Property</u> <u>Values</u> <u>Remarks Method</u>



Hq No data available None known Melting / freezing point No data available None known Boiling point / boiling range No data available None known **Flash Point** No data available None known **Evaporation Rate** No data available None known Flammability (solid, gas) No data available None known

Flammability Limit in Air

Upper flammability limit

Lower flammability limit

No data available
No data available

Vapor pressure No data available None known Vapor density No data available None known **Specific Gravity** No data available None known Water Solubility No data available None known Solubility in other solvents No data available None known Partition coefficient: n-octanol/water No data available None known **Autoignition temperature** No data available None known **Decomposition temperature** No data available None known Kinematic viscosity No data available None known **Dynamic viscosity** No data available None known

Explosive properties

Oxidizing properties

No data available
No data available
No data available

Other Information

Softening Point
VOC Content (%)
Particle Size
No data available
No data available
No data available

Particle Size Distribution

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

None known based on information supplied.

Incompatible materials

Strong acids. Strong oxidizing agents. Strong bases.

Hazardous Decomposition Products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information Product does not present an acute toxicity hazard based on known or supplied information.

In case of rupture:.

Inhalation Specific test data for the substance or mixture is not available. May cause irritation of

respiratory tract.



Eye contact Specific test data for the substance or mixture is not available. Causes serious eye

irritation. (based on components). May cause redness, itching, and pain.

Skin contact Specific test data for the substance or mixture is not available. Causes skin irritation.

(based on components). Prolonged contact may cause redness and irritation.

Ingestion Specific test data for the substance or mixture is not available. Ingestion may cause

irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea,

vomiting and diarrhea.

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Carbon black 1333-86-4	> 15400 mg/kg (Rat)	> 3 g/kg (Rabbit)	-
Nickel 7440-02-0	> 9000 mg/kg (Rat)	-	-
Propylene imine 75-55-8	= 19 mg/kg (Rat)	-	•

Information on toxicological effects

Symptoms Erythema (skin redness). May cause redness and tearing of the eyes. Itching. Rashes.

Hives.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization May cause sensitization by skin contact.

Mutagenic Effects No information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Lithium Cobalt Oxide (LiCoO ₂) 12190-79-3	A3	Group 2B		Х
Carbon black 1333-86-4	A3	Group 2B		Х
Nickel 7440-02-0		Group 1 Group 2B	Reasonably Anticipated	X
Propylene imine 75-55-8	A3	Group 2B	Reasonably Anticipated	Х

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

NTP (National Toxicology Program)

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity No information available.

STOT - single exposure No information available.

STOT - repeated exposure Causes damage to organs through prolonged or repeated exposure. Based on

classification criteria from the 2012 OSHA Hazard Communication Standard (29 CFR



1910.1200), this product has been determined to cause systemic target organ toxicity from

chronic or repeated exposure. (STOT RE).

Chronic Toxicity Contains a known or suspected carcinogen. Avoid repeated exposure. Prolonged exposure

may cause chronic effects. May cause adverse liver effects.

Target Organ Effects Respiratory system. Eyes. Skin. Gastrointestinal tract (GI). Kidney. Liver. Lymphatic

System. Lungs.

Aspiration Hazard No information available.

Numerical measures of toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)
7,646.00 mg/kg
ATEmix (dermal)
2,893.00 mg/kg (ATE)
ATEmix (inhalation-gas)
75,407.54 ppm (4 hr)
ATEmix (inhalation-dust/mist)
37.78 mg/l
ATEmix (inhalation-vapor)
377.75 ATEmix



Page 9/14

12. ECOLOGICAL INFORMATION

Ecotoxicity

Very toxic to aquatic life with long lasting effects.

Chemical name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Carbon black 1333-86-4				24h EC50: > 5600 mg/L
Copper 7440-50-8	96h EC50: 0.031 - 0.054 mg/L (Pseudokirchneriella subcapitata) 72h EC50: 0.0426 - 0.0535 mg/L (Pseudokirchneriella subcapitata)	96h LC50: 0.0068 - 0.0156 mg/L (Pimephales promelas) 96h LC50: = 1.25 mg/L (Lepomis macrochirus) 96h LC50: = 0.052 mg/L (Oncorhynchus mykiss) 96h LC50: = 0.2 mg/L (Pimephales promelas) 96h LC50: < 0.3 mg/L (Pimephales promelas) 96h LC50: = 0.112 mg/L (Poecilia reticulata) 96h LC50: = 0.3 mg/L (Cyprinus carpio) 96h LC50: = 0.8 mg/L (Cyprinus carpio)		48h EC50: = 0.03 mg/L
Nickel 7440-02-0	72h EC50: = 0.18 mg/L (Pseudokirchneriella subcapitata) 96h EC50: 0.174 - 0.311 mg/L (Pseudokirchneriella subcapitata)	96h LC50: > 100 mg/L (Brachydanio rerio) 96h LC50: = 1.3 mg/L (Cyprinus carpio) 96h LC50: = 10.4 mg/L (Cyprinus carpio)		48h EC50: > 100 mg/L 48h EC50: = 1 mg/L

Persistence and Degradability

No information available.

Bioaccumulation

No information available

Other adverse effects

No information available.



Page 10/14

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal methods

This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.

Contaminated Packaging

Dispose of contents/containers in accordance with local regulations.

Chemical name	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
Propylene imine 75-55-8		P067		

California Hazardous Waste Codes 141

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical name	California Hazardous Waste
Lithium Cobalt Oxide (LiCoO ₂) 12190-79-3	Toxic
Aluminum 7429-90-5	Ignitable powder
Copper 7440-50-8	Toxic
Nickel 7440-02-0	Toxic powder Ignitable powder

14. TRANSPORT INFORMATION

Note:

The transportation of primary lithium cells and batteries is regulated by the International Civil Aviation Organization, International Air Transport Association, International Maritime Dangerous Goods Code and the US Department of Transportation. The batteries must meet the following criteria for shipment: 1. Air shipments must meet the requirements listed in Special Provision A45 of the International Air Transport Association Dangerous Goods Regulations. 2. Meet the requirements for the US Department of Transportation listed in 49 CFR 173.185. 3. The transport of primary lithium batteries is prohibited aboard passenger aircraft. Refer to the Federal Register December 15, 2004 (Hazardous Materials; Prohibited on the Transportation of Primary Lithium Batteries and Cells Aboard Passenger Aircraft; Final Rule)

Lithium batteries shipped as "Lithium batteries", "Lithium batteries packed with equipment", or "Lithium batteries contained in equipment" may not be classified as "Dangerous Goods" when shipped in accordance with "special provision A45 of IATA-DGR" or "special provision 188 of IMO-IMDG Code"

DOTNOT REGULATEDProper Shipping NameNON-REGULATED

Hazard Class N/A Emergency Response Guide 147

Number

Not regulated



TDG

MEX Not regulated

ICAO Not regulated

IATA Not regulated
Proper Shipping Name NON REGULATED

Hazard Class N/A

IMDG/IMO Not regulated

Hazard Class N/A EmS-No. F-A, S-I

RID Not regulated

ADR Not regulated

ADN Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA Complies

DSL All components are listed either on the DSL or NDSL.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	CAS No	Weight-%	SARA 313 - Threshold Values %
Lithium Cobalt Oxide (LiCoO ₂) - 12190-79-3	12190-79-3	15 - 40	0.1
Aluminum - 7429-90-5	7429-90-5	10 - 30	1.0
Copper - 7440-50-8	7440-50-8	5 - 10	1.0
Nickel - 7440-02-0	7440-02-0	0.1 - 1	0.1
Propylene imine - 75-55-8	75-55-8	0.1 - 1	0.1

SARA 311/312 Hazard Categories

Acute Health Hazard	No
Chronic Health Hazard	No
Fire Hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Copper		X	X	
7440-50-8				



Revision Date 29-Mar-2016 1319829 - AHB572535PJT

Nickel	X	X	
7440-02-0			

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Copper 7440-50-8	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Nickel 7440-02-0	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
Propylene imine 75-55-8	1 lb	1 lb	RQ 1 lb final RQ RQ 0.454 kg final RQ

US State Regulations

<u>California Proposition 65</u>
This product contains the following Proposition 65 chemicals.

Chemical name	California Proposition 65
Carbon black - 1333-86-4	Carcinogen
Nickel - 7440-02-0	Carcinogen
Propylene imine - 75-55-8	Carcinogen

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Lithium Cobalt Oxide (LiCoO2) 12190-79-3	Х		Х	Х	Χ
Carbon black 1333-86-4	Х	Х	Х		Χ
Aluminum 7429-90-5	X	X	Х	Х	
Copper 7440-50-8	Х	Х	Х	X	Χ
Ethylene carbonate 96-49-1		Х	Х		
Diethyl carbonate 105-58-8	Х	Х	Х		
Nickel 7440-02-0	Х	Х	Х	Х	Х
Propylene imine 75-55-8	Х	Х	Х	Х	Х

International Regulations

Mexico

National occupational exposure limits

Component	Carcinogen Status	Exposure Limits
Carbon black		Mexico: TWA 3.5 mg/m ³
1333-86-4 (10 - 30)		Mexico: STEL 7 mg/m ³
Aluminum		Mexico: TWA= 10 mg/m ³
7429-90-5 (10 - 30)		
Copper		Mexico: TWA= 1 mg/m ³
7440-50-8 (5 - 10)		Mexico: TWA= 0.2 mg/m ³
		Mexico: STEL= 2 mg/m ³
Nickel		Mexico: TWA 1 mg/m ³
7440-02-0 (0.1 - 1)		
Propylene imine	A3	Mexico: TWA 2 ppm
75-55-8 (0.1 - 1)		Mexico: TWA 5 mg/m ³

A3 - Confirmed Animal Carcinogen



Mexico - Occupational Exposure Limits - Carcinogens

Canada

WHMIS Hazard Class

Non-controlled

16. OTHER INFORMATION

NFPA Health Hazards 1 Flammability 0 Instability 0 Physical and

Chemical Hazards - HMIS Health Hazards 0 Flammability 0 Physical Hazard 0 Personal Protection

Χ

Prepared By Product Stewardship

23 British American Blvd. Latham, NY 12110

1-800-572-6501 29-Mar-2016

Issuing Date29-Mar-2016Revision Date29-Mar-2016

Revision Note No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet

(U)

Page 14/14