

SAFETY DATA SHEET

Issue Date: 06/25/2015

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name	:	Brighton Professional™ Heavy Duty Carpet Spot Remover		
Material number	:	BPR173A19-A		
Manufacturer or supplier's o	deta	ails		
Company	:	Staples Contract & Commercial, Inc.		
Address	:	500 Staples Drive		
Telephone	:	Framingham, MA 01702 USA 1-888-322-0912		
Emergency	:	1-888-322-0912 (24-HRS, 7 DAYS A WEEK)		

Note: Products labeled as a consumer product in accordance with the United States Consumer Product Safety Commission regulations: The warnings presented below in this Safety Data Sheet (SDS) comply with the 2012 OSHA Hazard Communication Standard (GHS - Globally Harmonized System of Classification and Labeling). The requirements for the labeling and warnings of consumer products may differ from those required for GHS based hazard communication.

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Emergency Overview			
Appearance	Aerosol containing a liquefied gas		
Colour	clear		
Odour	characteristic		
GHS Classification			
Flammable aerosols Gases under pressure Eye irritation	: Category 2 : Liquefied gas : Category 2A		
GHS Label element			
Hazard pictograms			
Signal word	: Warning		
Hazard statements	 H223 Flammable aerosol. H280 Contains gas under pressure; may explode if heated. H319 Causes serious eye irritation. 		
Precautionary statements	: Prevention: P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.		
	1 / 12		

Version 1.0	Revision Date 06/25/2015
Potential Health Effects	 P211 Do not spray on an open flame or other ignition source. P251 Pressurized container: Do not pierce or burn, even after use. P264 Wash skin thoroughly after handling. P280 Wear eye protection/ face protection. Response: P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337 + P313 If eye irritation persists: Get medical advice/ attention. Storage: P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.
Carcinogenicity:	
IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
ACGIH	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.
OSHA	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical Name	CAS-No.	Concentration [%]
butane	106-97-8	>= 5 - < 10
propan-2-ol	67-63-0	>= 5 - < 10
2-(2-butoxyethoxy)ethanol	112-34-5	>= 5 - < 10
acetone	67-64-1	>= 1 - < 5
D-Glucopyranose, oligomers, decyl octyl glycosides	68515-73-1	>= 1 - < 5
1-phenoxypropan-2-ol	770-35-4	>= 1 - < 5
propane	74-98-6	>= 1 - < 5
D-Glucopyranose, oligomeric, C10-16-alkyl glycosides	110615-47-9	>= 1 - < 5

SECTION 4. FIRST AID MEASURES

General advice

: Move out of dangerous area.

Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.

Version 1.0	Revision Date 06/25/2015		
If inhaled	: Remove person to fresh air. If signs/symptoms continue, get medical attention. If unconscious place in recovery position and seek medical		
In case of skin contact	 advice. In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash contaminated clothing before re-use. 		
In case of eye contact	 Call a physician if irritation develops or persists. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses. If eye irritation persists, consult a specialist. 		
If swallowed	: DO NOT induce vomiting unless directed to do so by a physician or poison control center. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.		

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical Water spray jet		
Unsuitable extinguishing media	:	High volume water jet		
Specific hazards during firefighting	:	Do not allow run-off from fire fighting to enter drains or water courses.		
Hazardous combustion products	:	Carbon dioxide (CO2) Carbon monoxide Nitrogen oxides (NOx) Smoke		
Specific extinguishing methods	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.		
Further information	:	For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.		
Special protective equipment for firefighters	:	Wear self-contained breathing apparatus for firefighting if necessary.		

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions,	: Use personal protective equipment.
protective equipment and	Ensure adequate ventilation.

Version 1.0	Revision Date 06/25/2015
emergency procedures	Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Environmental precautions	 Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	 Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Sweep up or vacuum up spillage and collect in suitable container for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling	 Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Always replace cap after use. Dispose of rinse water in accordance with local and national regulations. Do not breathe vapours or spray mist.
Conditions for safe storage	 BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. No smoking. Observe label precautions. Keep in a dry, cool and well-ventilated place. Electrical installations / working materials must comply with the technological safety standards.
Materials to avoid	: Strong oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
butane	106-97-8	TWA	800 ppm 1,900 mg/m3	NIOSH REL
		TWA	800 ppm 1,900 mg/m3	OSHA P0
propan-2-ol	67-63-0	TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH

Revision Date 06/25/2015

		TWA	400 ppm 980 mg/m3	NIOSH REL
		ST	500 ppm 1,225 mg/m3	NIOSH REL
		TWA	400 ppm 980 mg/m3	OSHA Z-1
		TWA	400 ppm 980 mg/m3	OSHA P0
		STEL	500 ppm 1,225 mg/m3	OSHA P0
acetone	67-64-1	TWA	500 ppm	ACGIH
		STEL	750 ppm	ACGIH
		TWA	250 ppm 590 mg/m3	NIOSH REL
		TWA	1,000 ppm 2,400 mg/m3	OSHA Z-1
		TWA	750 ppm 1,800 mg/m3	OSHA P0
		STEL	1,000 ppm 2,400 mg/m3	OSHA P0
propane	74-98-6	TWA	1,000 ppm	ACGIH
· ·		TWA	1,000 ppm 1,800 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,800 mg/m3	OSHA Z-1
		TWA	1,000 ppm 1,800 mg/m3	OSHA P0

Biological occupational exposure limits

Component	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
PROPAN-2-OL	67-63-0	Acetone	Urine	End of shift at end of workwee k	40 mg/l	ACGIH BEI
2-PROPANONE	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	50 mg/l	ACGIH BEI

Personal protective equipment

Respiratory protection	:	Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
Hand protection Remarks	:	The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Eye protection	:	Ensure that eyewash stations and safety showers are close to the workstation location. Safety glasses

Version 1.0	Revision Date 06/25/2015
Skin and body protection	: impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Hygiene measures	 When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	Aerosol containing a liquefied gas
Colour	:	clear
Odour	:	characteristic
Odour Threshold	:	no data available
рН	:	no data available
Melting point/freezing point	:	no data available
Boiling point	:	no data available
Flash point	:	not applicable
Evaporation rate	:	1
Flammability (solid, gas)	:	The product is not flammable.
Upper explosion limit	:	no data available
Lower explosion limit	:	no data available
Vapour pressure	:	4,136 hPa (21 °C)
Relative vapour density	:	no data available
Density	:	0.985 g/cm3
Solubility(ies)		
Water solubility	:	soluble
Partition coefficient: n- octanol/water	:	no data available
Auto-ignition temperature	:	not determined
Thermal decomposition	:	no data available
Viscosity		
Viscosity, kinematic	:	no data available
Heat of combustion	:	10.46 kJ/g

Version 1.0

Revision Date 06/25/2015

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed.
reactions	Vapours may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks. Extremes of temperature and direct sunlight.
Incompatible materials	: Strong oxidizing agents
Hazardous decomposition products	: Carbon dioxide (CO2) Carbon monoxide Nitrogen oxides (NOx)

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Product:	
Acute oral toxicity	: Acute toxicity estimate : > 5,000 mg/kg Method: Calculation method
Acute dermal toxicity	: Acute toxicity estimate : > 5,000 mg/kg Method: Calculation method
Components:	
butane: Acute inhalation toxicity	: LC50 mouse: 1,237 mg/l Exposure time: 2 h
	LC50 rat: 1,355 mg/l
propan-2-ol: Acute oral toxicity	: LD50 Oral rat: 4,396 mg/kg Method: Calculation method
acetone: Acute oral toxicity	: LD50 rat: 5,800 mg/kg
Acute inhalation toxicity	: LC50 rat: 132 mg/l Exposure time: 3 h
	LC50 rat: 50.1 mg/l
Acute dermal toxicity	: LD50 guinea pig: > 7,426 mg/kg
Acute inhalation toxicity	: LC50 rat: 132 mg/l Exposure time: 3 h LC50 rat: 50.1 mg/l

Version 1.0

Revision Date 06/25/2015

LD50 rabbit: > 7,426 mg/kg

propane:

Acute inhalation toxicity	: LC50 mouse: 1,237 mg/l
-	Exposure time: 2 h

LC50 rat: 658 mg/l Exposure time: 4 h

LC50 rat: 1,355 mg/l

Skin corrosion/irritation

Product:

Remarks: May cause skin irritation and/or dermatitis.

Serious eye damage/eye irritation

Product:

Remarks: Eye irritation

Respiratory or skin sensitisation

no data available

Germ cell mutagenicity

no data available

Carcinogenicity

no data available

Reproductive toxicity

no data available

butane: propan-2-ol: 2-(2-butoxyethoxy)ethanol: acetone: D-Glucopyranose, oligomers, decyl octyl glycosides: 1-phenoxypropan-2-ol: propane: D-Glucopyranose, oligomeric, C10-16-alkyl glycosides:

STOT - single exposure

no data available

STOT - repeated exposure

no data available

Aspiration toxicity

no data available

Further information

Version 1.0

Revision Date 06/25/2015

Product:

Remarks: no data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

no data available Persistence and degradability no data available **Bioaccumulative potential** Product: Partition coefficient: n-: Remarks: no data available octanol/water Components: butane : : Pow: 2.89 Partition coefficient: noctanol/water 2-(2-butoxyethoxy)ethanol : Partition coefficient: n-: Pow: 1 octanol/water D-Glucopyranose, oligomeric, C10-16-alkyl glycosides : : Pow: 0.07 Partition coefficient: noctanol/water Mobility in soil no data available Other adverse effects no data available Product: Regulation 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances Remarks This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B). Additional ecological : no data available information

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	: Do not dispose of waste into sewer.
	Do not contaminate ponds, waterways or ditches with

Version 1.0	Revision Date 06/25/2015
	chemical or used container. Dispose of in accordance with local regulations.
Contaminated packaging	 Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA): ORM-D, LIMITED QUANTITY

Transportation Regulation: IMDG (Vessel): UN1950, AEROSOLS, 2.1, - Limited quantity

Transportation Regulation: IATA (Cargo Air): UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: IATA (Passenger Air): UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: TDG (Canada): UN1950, AEROSOLS, 2.1, - Limited quantity

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
sodium nitrite	7632-00-0	100	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards	:	Fire Hazard Acute Health Hazard Sudden Release of Pressure Hazard
SARA 302	:	SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

ersion 1.0	Revision Date 06/25/2015
SARA 313	: SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.
California Prop 65	WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.
methanol	67-56-1

TSCA DSL	On TSCA Inventory This product contains one or several components that are not on the Canadian DSL nor NDSL.
AICS	Not in compliance with the inventory
NZIOC	Not in compliance with the inventory
PICCS	Not in compliance with the inventory
IECSC	Not in compliance with the inventory

Inventory Acronym and Validity Area Legend:

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIOC (New Zealand), PICCS (Philippines), TSCA (USA)

WHMIS Classification(s):


Class A - Compressed Gas Class D2B - Skin/Eye Irritant

WHMIS Hazard Symbols:



SECTION 16. OTHER INFORMATION

Further information



HI

HEALTH	3
FLAMMABILITY	3
PHYSICAL HAZARD	2

0 = not significant, 1 =Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic

Version 1.0

Revision Date 04/24/2015

Print Date 06/23/2015

OSHA GHS Label Info	ormation:
Hazard pictograms	
Signal word	: Warning:
Hazard statements	: Flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation.
Precautionary statements	:
	Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition
	sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wash skin thoroughly after handling. Wear eye protection/ face protection. Response: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/ attention. Storage: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Prepared By: Regulatory Specialist, Staples Brand Group, (508) 253-5000

Always follow label directions carefully when using this or any other chemical product. If information about this product is required, please contact Staples at 1-888-322-0912 or visit our website at www.staplesadvantage.com. Keep Safety Data Sheets filed and organized in an area accessible to workers according to all applicable regulations.

All information contained in this SDS is provided to the best of Staples Contract & Commercial Inc's knowledge. No warranty is made with respect to this information expressed or implied, including warranties of merchantability or fitness for a particular purpose. Users are responsible for verifying the information under their own operating conditions to determine whether the products listed in the SDS are suitable for their intended use. Users are responsible for compliance with all laws and regulations as may be required by their receipt of the information and use of the products provided with this SDS.