

SAFETY DATA SHEET

Issue Date: 06/25/2015

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Emergency	:	1-888-322-0912 (24-HRS, 7 DAYS A WEEK)
Telephone	:	Framingham, MA 01702 USA 1-888-322-0912
Address	:	500 Staples Drive
Company	:	Staples Contract & Commercial, Inc.
Manufacturer or supplier's o	leta	ails
Material number	:	BPR239A10-A
Material name	:	Brighton Professional™ Summer Breeze Dry Air Freshener

Note: Products labeled as a consumer product in accordance with the United States Consumer Product Safety Commission regulations: The warnings presented below in this Safety Data Sheet (SDS) comply with the 2012 OSHA Hazard Communication Standard (GHS - Globally Harmonized System of Classification and Labeling). The requirements for the labeling and warnings of consumer products may differ from those required for GHS based hazard communication.

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	Aerosol containing a liquefied gas
Colour	clear
Odour	characteristic

GHS Classification

Flammable aerosols Gases under pressure Eye irritation Skin sensitisation Specific target organ toxicity - single exposure	Category 1 Liquefied gas Category 2A Category 1 Category 3 (Central nervous system)	
GHS Label element		
Hazard pictograms		
Signal word	Danger	
Hazard statements	H222 Extremely flammable aerosol. H280 Contains gas under pressure; may explode if H317 May cause an allergic skin reaction.	heated.

sion 1.0	Revision Date 06/25/2015
	H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.
Precautionary statements	 Prevention: P210 Keep away from heat, hot surfaces, sparks, open flame and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source P251 Pressurized container: Do not pierce or burn, even afte use. P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. P264 Wash skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P272 Contaminated work clothing should not be allowed out the workplace. P280 Wear eye protection/ face protection. P280 Wear eye protection/ face protection. P280 Wear eye protection face protection. P280 Wear eye protection face protection. P302 + P352 IF ON SKIN: Wash with plenty of soap and wat P304 + P340 + P312 IF INHALED: Remove victim to fresh a and keep at rest in a position comfortable for breathing. Call POISON CENTER or doctor/ physician if you feel unwell. P305 + P351 + P338 IF IN EYES: Rinse cautiously with wate for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention. P363 Wash contaminated clothing before reuse. Storage: P405 Store locked up. P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. P403 Store in a well-ventilated place. Disposal: P501 Dispose of contents/container in accordance with local regulation.
Potential Health Effects	
Carcinogenicity:	
IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
ACGIH	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.
OSHA	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.
NTP	No component of this product present at levels greater than or

Version 1.0

Revision Date 06/25/2015

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical Name	CAS-No.	Concentration [%]
acetone	67-64-1	>= 70 - < 90
propane	74-98-6	>= 10 - < 20
butane	106-97-8	>= 5 - < 10
benzyl salicylate	118-58-1	>= 0.1 - < 1

SECTION 4. FIRST AID MEASURES

General advice :	Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.
If inhaled :	Move to fresh air. Consult a physician after significant exposure. If unconscious place in recovery position and seek medical advice.
In case of skin contact :	In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash contaminated clothing before reuse. Call a physician if irritation develops or persists.
In case of eye contact :	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed :	DO NOT induce vomiting unless directed to do so by a physician or poison control center. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical Water spray jet
Unsuitable extinguishing media	: High volume water jet
Hazardous combustion products	: Carbon dioxide (CO2) Carbon monoxide Smoke
Specific extinguishing	: Use extinguishing measures that are appropriate to local

Version 1.0	Revision Date 06/25/2015	
methods	circumstances and the surrounding environment.	
Further information	: For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.	
Special protective equipment for firefighters	: Wear self-contained breathing apparatus for firefighting if necessary.	

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	:	Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Environmental precautions	:	Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Sweep up or vacuum up spillage and collect in suitable container for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling	 Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Container may be opened only under exhaust ventilation hood. Always replace cap after use. Dispose of rinse water in accordance with local and national regulations. Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
	Do not breathe vapours or spray mist.
Conditions for safe storage	 BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. No smoking. Observe label precautions.

Version 1.0	Revision Date 06/25/2015
	Keep in a dry, cool and well-ventilated place. Electrical installations / working materials must comply with the technological safety standards.
Materials to avoid	: Oxidizing agents Store and keep away from bases and alkalies.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
acetone	67-64-1	TWA	500 ppm	ACGIH
		STEL	750 ppm	ACGIH
		TWA	250 ppm 590 mg/m3	NIOSH REL
		TWA	1,000 ppm 2,400 mg/m3	OSHA Z-1
		TWA	750 ppm 1,800 mg/m3	OSHA P0
		STEL	1,000 ppm 2,400 mg/m3	OSHA P0
propane	74-98-6	TWA	1,000 ppm	ACGIH
		TWA	1,000 ppm 1,800 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,800 mg/m3	OSHA Z-1
		TWA	1,000 ppm 1,800 mg/m3	OSHA P0
butane	106-97-8	TWA	800 ppm 1,900 mg/m3	NIOSH REL
		TWA	800 ppm 1,900 mg/m3	OSHA P0

Components with workplace control parameters

Biological occupational exposure limits

Component	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
2-PROPANONE	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	50 mg/l	ACGIH BEI

Personal protective equipment

Respiratory protection

: Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Version 1.0	Revision Date 06/25/2015
Hand protection Remarks	: The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Eye protection	: Ensure that eyewash stations and safety showers are close to the workstation location. Safety glasses
Skin and body protection	: impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Hygiene measures	: When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	Aerosol containing a liquefied gas
Colour	:	clear
Odour	:	characteristic
Odour Threshold	:	no data available
рН	:	no data available
Melting point/freezing point	:	no data available
Boiling point	:	no data available
Flash point	:	not applicable
Evaporation rate	:	no data available
Flammability (solid, gas)	:	Extremely flammable aerosol.
Upper explosion limit	:	no data available
Lower explosion limit	:	no data available
Vapour pressure	:	4,826 hPa
Relative vapour density	:	no data available
Density	:	< 1 g/cm3
Solubility(ies)		
Water solubility	:	soluble
Partition coefficient: n- octanol/water	:	no data available
Auto-ignition temperature	:	not determined
Thermal decomposition	:	no data available
Viscosity		
Viscosity, kinematic	:	no data available

Version 1.0

Revision Date 06/25/2015

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Vapours may form explosive mixture with air. No decomposition if stored and applied as directed.
Conditions to avoid	: Heat, flames and sparks. Extremes of temperature and direct sunlight.
Incompatible materials	: Oxidizing agents Amines Bases
Hazardous decomposition products	: Carbon monoxide Carbon dioxide (CO2)

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Product:	
Acute oral toxicity	: Acute toxicity estimate : > 5,000 mg/kg Method: Calculation method
Components:	
acetone:	
Acute oral toxicity	: LD50 rat: 5,800 mg/kg
Acute inhalation toxicity	: LC50 rat: 132 mg/l
	Exposure time: 3 h
	1 CE0 rot: E0 1 mg/
	LC50 rat: 50.1 mg/l
Acute dermal toxicity	: LD50 guinea pig: > 7,426 mg/kg
Addie definal toxicity	guillou pig. > 1, 120 mg/kg
	LD50 rabbit: > 7,426 mg/kg
	, , , , ,
propane:	
Acute inhalation toxicity	: LC50 mouse: 1,237 mg/l
	Exposure time: 2 h
	LC50 rat: 658 mg/l Exposure time: 4 h

(DFR239A10-A)			
Version 1.0	Revision Date 06/25/2015		
	LC50 rat: 1,355 mg/l		
butane: Acute inhalation toxicity	: LC50 mouse: 1,237 mg/l Exposure time: 2 h		
	LC50 rat: 1,355 mg/l		
benzyl salicylate: Acute oral toxicity	: LD50 Oral rat: 2,227 mg/kg		
Skin corrosion/irritation			
Product:			
Remarks: May cause skin irritati	on and/or dermatitis.		
Serious eye damage/eye irritation			
Product:			
Remarks: Eye irritation			
Respiratory or skin sensitisation			
Product:			
Remarks: Causes sensitisation.			
Germ cell mutagenicity			
no data available			
Carcinogenicity			
no data available			
Reproductive toxicity			
no data available			
acetone: propane: butane: benzyl salicylate:			
STOT - single exposure			
no data available			
STOT - repeated exposure			
no data available			
Aspiration toxicity			
no data available			
Further information			

Version 1.0

Revision Date 06/25/2015

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

no data available

Persistence and degradability

no data available Bioaccumulative potential

Product:

Partition coefficient: n- octanol/water <u>Components:</u> butane :	: Remarks: no data available
Partition coefficient: n- octanol/water	: Pow: 2.89
Mobility in soil	
no data available	
Other adverse effects	
no data available Product:	
Regulation	40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
Remarks	This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).
Additional ecological information	: no data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues	 Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of in accordance with local regulations.
---------------------	--

Version 1.0	Revision Date 06/25/2015
Contaminated packaging :	Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA): ORM-D, LIMITED QUANTITY

Transportation Regulation: IMDG (Vessel): UN1950, AEROSOLS, 2.1, - Limited quantity

Transportation Regulation: IATA (Cargo Air): UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: IATA (Passenger Air): UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: TDG (Canada): UN1950, AEROSOLS, 2.1, - Limited quantity

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
acetone	67-64-1	5000	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards	: Fire Hazard Sudden Release of Pressure Hazard Acute Health Hazard
SARA 302	: SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.
SARA 313	: SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Version 1.0	Revision Date 04/27/2015	Print Date 06/22/2015

Califor	roduct does not contain any chemicals known to State of nia to cause cancer, birth defects, or any other luctive harm.
---------	--

The components of this product are reported in the following inventories:

TSCA	On TSCA Inventory
DSL	This product contains one or several components that are not on the
	Canadian DSL nor NDSL.
AICS	Not in compliance with the inventory
NZIoC	Not in compliance with the inventory
PICCS	Not in compliance with the inventory
IECSC	Not in compliance with the inventory

Inventory Acronym and Validity Area Legend:

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIOC (New Zealand), PICCS (Philippines), TSCA (USA)

WHMIS Classification(s):


Class A - Compressed Gas Class B5 - Flammable Aerosol Class D2B - Skin/Eye Irritant

WHMIS Hazard Symbols:



SECTION 16. OTHER INFORMATION

Further information



HMIS III:

HEALTH	3
FLAMMABILITY	4
PHYSICAL HAZARD	2

0 = not significant, 1 = Slight, 2 = Moderate, 3 = High

4 = Extreme, * = Chronic

Version 1.0

Revision Date 04/27/2015

Print Date 06/22/2015

OSHA GHS Label Information:

Hazard pictograms	
Signal word	: Danger:
Hazard statements	 Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May cause an allergic skin reaction. Causes serious eye irritation. May cause drowsiness or dizziness.
Precautionary statements	:
	 Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear eye protection/ face protection. Wear protective gloves. Response: IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention. Wash contaminated clothing before reuse. Storage: Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a well-ventilated place. Disposal: Dispose of contents/container in accordance with local regulation.

Prepared By: Regulatory Specialist, Staples Brand Group, (508) 253-5000

Always follow label directions carefully when using this or any other chemical product. If information about this product is required, please contact Staples at 1-888-322-0912 or visit our website at www.staplesadvantage.com. Keep Safety Data Sheets filed and organized in an area accessible to workers according to all applicable regulations.

All information contained in this SDS is provided to the best of Staples Contract & Commercial Inc's knowledge. No warranty is made with respect to this information expressed or implied, including warranties of merchantability or fitness for a particular purpose. Users are responsible for verifying the information under their own operating conditions to determine whether the products listed in the SDS are suitable for their intended use. Users are responsible for compliance with all laws and regulations as may be required by their receipt of the information and use of the products provided with this SDS.