

Premium, durable floor finish for use with or without ultra-high-speed burnishing.

Coastwide Professional™ 83 Wax and Floor Stripper is a highly concentrated, low-odor, ammonia-free, rapid-response stripper that dissolves multiple coats of finish without the strong and unpleasant odor associated with conventional strippers. Coastwide Professional 83 rinses quickly without leaving residual alkali to interfere with finish application.

Features

- Dilutes at 1:20 for heavy-buildup conditions
- Formulated to be used in cold water
- Powerful formula removes the heaviest buildups
- Rapid penetration and liquefaction of finish
- Low foam characteristics
- Can also be used as a mop-on and mop-off stripper
- Leaves minimal alkali residues and does not interfere with sealer or finish application
- Express Mix™ package configuration meets Green Seal™ 40 performance standards, since it is in a closed loop system and eliminates contact with the concentrated product

**Products****83 Wax and Floor Stripper
Express Mix™**

3.25 liter, 2 units/case

Yields 18 ready-to-use gallons

Item no. 24323032



Order online at coastwideprofessional.com or through your ordering site.

Usage information

1. Mix product with cold water and test in small area to verify compatibility with floor surface before applying generally.
2. Dilute this product as directed. Stronger dilutions do not improve performance.
3. Do not use on wood floors or painted surfaces.
4. Test before attempting to strip linoleum, rubber or asphalt tile. Wax removers can cause damage to these types of surfaces. Always test before proceeding.
5. Immediately wipe away all splashes from baseboards, walls, fixtures or painted surfaces.

Stripping procedure

1. Dust mop or sweep the floor to remove debris.
2. Dispense or mix according to dilution chart.
3. Apply liberally to floor surface. Be sure to keep the floor surface wet with the stripper solution for 5 to 10 minutes, depending upon finish buildups.
4. Agitate using a mop or with floor machine or auto scrubber fitted with an appropriate stripping pad.
5. Pick up the stripping solution and residue using a wet vacuum or auto scrubber. Reapply stripping solution and agitate if needed.
6. Thoroughly rinse floor with cold water to remove leftover residues from stripping.
7. Allow floor to dry and apply floor sealer and/or finish.

Wear protective gloves/protective clothing/eye protection/face protection when handling concentrated product. Wash face, hands and any exposed skin thoroughly after handling. Read and understand SDS and label directions before use. Always follow good industrial hygiene practices when using chemicals. Improper use or improper dilution could result in damage to cleaning surfaces or to personal health. Dispose of product and container in accordance with all applicable federal, state, regional and local regulations.

Attributes

Physical form:	Pale-yellow liquid
Odor:	Pleasant
pH concentrated:	20% minimum
pH diluted:	(1:20): 10.0–12.0
Dilution ratio:	1:20
Foam level:	Low
Concentrated:	Reduces package waste
Shelf life:	2 years minimum in unopened container

These specifications were correct at the time of printing but are subject to change without notice.

Certifications



This product meets Green Seal™ Standard GS-40 based on effective performance and protective limits on VOCs and human & environmental toxicity. Learn more at GreenSeal.org.



All plastic containers used in packaging products display the Society of Plastics Industries' 3-side triangular arrow to make recycling easier. The majority of our containers are readily recyclable and classified as 2-HDPE (High-Density Polyethylene) and some contain 25% post-consumer recycled plastic.