

Premium, durable floor finish for use with or without ultra-high-speed burnishing.

Coastwide Professional™ Diamond is a blend of extremely hard, new-generation acrylic terpolymers, thermoplastics, resins and plasticizers designed to provide exceptional durability, gloss and reflection. Diamond Floor Finish and Sealer achieves levels of hardness and clarity never before available in conventional floor finishes. It builds gloss quickly and responds with unmatched brilliance to burnishing by 1,000- to 3,000-rpm machines. Burnishing is not required to maintain its high gloss and superior appearance level. One floor finish that is clear, hard, durable, slip resistant and designed to be used with or without burnishing.

Features

- Extremely durable, high-gloss, long-lasting floor finish
- Works on most resilient surfaces with most maintenance methods
- Universally compatible formula
- Meets industry guidelines for slip resistance
- Coverage: 2,500–3,000 square feet per gallon
- Excellent leveling and adhesion properties
- Resists black heel marks and scuffing



Products



Diamond Floor Finish
2.5 gallons, 2 units/case
Item no. 24381048

Order online at coastwideprofessional.com or through your ordering site.

Application procedures

1. Strip floors using Coastwide Professional 82 or 83 to remove buildup of old finishes, sealers or waxes.
2. Thoroughly rinse with cold water and let floor dry.
3. Apply thin to medium even coats of Coastwide Professional Floor Finish and Sealer 80 with an appropriate finish mop or applicator.
4. Allow each coat to dry before applying next coat. 30-minute drying time recommended under normal conditions.
5. Apply a maximum of 4–6 coats in a 24-hour period.

Maintenance procedures

1. Frequently dust mop or sweep to remove abrasive and gritty soils.
2. Use Coastwide Professional 64, 65 or pH Neutral floor cleaners to damp mop or auto scrub. Promptly damp mop spills to prevent slips and falls.
3. Buff or burnish if desired with high-speed equipment and the appropriate ultra-high-speed burnishing or buffing pads.

Attributes

Physical form:	Opaque, white liquid
Odor:	Characteristic
Non-volatile solids:	20% minimum
pH as is:	8.5–9.5
Film color:	Clear and colorless
Coverage:	2,500–3,000 square feet per gallon (min.)
Slip resistance:	Meets ASTM D2047
Shelf life:	2 years minimum in unopened container

These specifications were correct at the time of printing but are subject to change without notice.

Certifications



All plastic containers used in packaging products display the Society of Plastics Industries' 3-side triangular arrow to make recycling easier. The majority of our containers are readily recyclable and classified as 2-HDPE (High-Density Polyethylene) and some contain 25% post-consumer recycled plastic.