

**High-gloss finish when high durability and low maintenance are desired.**

Coastwide Professional™ Optimum provides maximum gloss and durability to extend the life and improve the appearance of floors. Superior scratch-, scuff- and heel mark-resistance is a result of a blend of tough, hard and flexible polymers. It is internally plasticized to give excellent burnish response. This fast-drying formulation builds gloss quickly and responds with unmatched brilliance to burnishing by 1,000- to 3,000-rpm machines. Burnishing is not required to maintain its high gloss and outstanding appearance. The unique copolymerization system in Coastwide Professional Optimum allows it to be used with or without a sealer. Use Coastwide Professional Optimum on almost any type of flooring except unsealed wood, cork or conductive flooring.

**Features**

- Versatile, durable floor finish
- Use with or without burnishing
- Resists black heel marks and scuffing
- Works on most resilient surfaces with most maintenance methods
- Universally compatible formula
- Use with or without a sealer
- Meets industry guidelines for slip resistance
- Coverage: 2,500–3,000 square feet per gallon
- Excellent leveling and adhesion properties

**Products**

**Optimum Floor Finish**  
2.5 gallons, 2 units/case  
Item no. 24381055

**Order online at [coastwideprofessional.com](http://coastwideprofessional.com) or through your ordering site.**

### Application procedures

1. Strip floors using Coastwide Professional 82 or 83 to remove buildup of old finishes, sealers or waxes.
2. Thoroughly rinse with cold water and let floor dry.
3. Apply thin to medium even coats of Coastwide Professional Optimum with an appropriate finish mop or applicator.
4. Allow each coat to dry before applying next coat. 30-minute drying time recommended under normal conditions.
5. Apply a maximum of 4–6 coats in a 24-hour period.

### Maintenance procedures

1. Frequently dust mop or sweep to remove abrasive and gritty soils.
2. Use Coastwide Professional 64, 65, or pH Neutral floor cleaners to damp mop or auto scrub. Promptly damp mop spills to prevent slips and falls.
3. Buff or burnish if desired with high-speed equipment and the appropriate ultra-high-speed burnishing or buffing pads.

### Attributes

<b>Physical form:</b>	Opaque, white liquid
<b>Odor:</b>	Characteristic
<b>Non-volatile solids:</b>	19% minimum
<b>pH as is:</b>	8.5–9.5
<b>Film color:</b>	Clear and colorless
<b>Coverage:</b>	2,500–3,000 square feet per gallon (min.)
<b>Slip resistance:</b>	Meets ASTM D2047
<b>Shelf life:</b>	2 years minimum in unopened container

These specifications were correct at the time of printing but are subject to change without notice.

### Certifications



All plastic containers used in packaging products display the Society of Plastics Industries' 3-side triangular arrow to make recycling easier. The majority of our containers are readily recyclable and classified as 2-HDPE (High-Density Polyethylene) and some contain 25% post-consumer recycled plastic.