

Metal-free combination floor finish and sealer formulated for high performance.

Coastwide Professional™ 80 Floor Finish and Sealer is designed with eco-preferable* metal-free polymer technology for sealing and finishing all types of resilient flooring. It does not contain zinc or other metals that can harm the environment or interfere with industrial wastewater treatment processes. This finish has exceptional gloss, durability, soil resistance, detergent resistance, recoatability and removability, and meets industry's slip-resistant standards. Coastwide Professional 80 is a combination sealer and finish that dries to a smooth, hard, clear and colorless coating in about 20–30 minutes under normal conditions. This ultra-low-odor finish is versatile and can be maintained using traditional maintenance procedures, including scrub/recoat or high-speed burnishing.

Features

- High durability, outstanding gloss retention and superior detergent resistance
- Formulated with self cross-linking no-metal technology
- Eco preferable* and free from alkyl phenol ethoxylate (APE), formaldehyde, phthalate and metals
- Outstanding performance reduces the labor costs associated with burnishing, recoating and stripping
- Ultra-low-odor characteristics make it ideal for floor care in schools, hospitals and patient care facilities
- Seals and finishes in one easy step
- Rapid leveling and film formation
- Balances outstanding sealer adhesion with unsurpassed finish durability
- Use with or without burnishing
- Exhibits outstanding black heel mark and scuff mark resistance
- Meets industry guidelines for slip resistance
- Excellent soil resistance reduces deep scrubbing and stripping
- Outstanding clarity and brightness
- One gallon covers 2,500–3,000 square feet
- Universally compatible with most sealers and finishes
- Meets Green Seal™ GS-40 performance requirements

*Compared to conventional cleaning products.

**Products**

80 Floor Finish and Sealer
2.5 gallons, 2 units/case
Item no. 24381059

Order online at coastwideprofessional.com or through your ordering site.

Application procedures

1. Strip floors using Coastwide Professional 82 or 83 to remove buildup of old finishes, sealers or waxes.
2. Thoroughly rinse with cold water and let floor dry.
3. Apply thin to medium even coats of Coastwide Professional 80 with an appropriate finish mop or applicator.
4. Allow each coat to dry before applying next coat. 30-minute drying time recommended under normal conditions.
5. Apply a maximum of 4–6 coats in a 24-hour period.

Maintenance procedures

1. Frequently dust mop or sweep to remove abrasive and gritty soils.
2. Use Coastwide Professional 64 or 65 to damp mop or auto scrub. Promptly damp mop spills to prevent slips and falls.
3. Buff or burnish if desired with high-speed equipment and the appropriate ultra-high-speed burnishing or buffing pads.

Attributes

Physical form:	Opaque, white liquid
Odor:	Characteristic
Non-volatile solids:	20% minimum
pH as is:	7.5–8.5
Film color:	Clear and colorless
Coverage:	2,500–3,000 square feet per gallon (min.)
Slip resistance:	Meets ASTM D2047
Shelf life:	2 years minimum in unopened container

These specifications were correct at the time of printing but are subject to change without notice.

Certifications



This product meets Green Seal™ Standard GS-40 based on effective performance and protective limits on VOCs and human & environmental toxicity. Learn more at GreenSeal.org.



All plastic containers used in packaging products display the Society of Plastics Industries' 3-side triangular arrow to make recycling easier. The majority of our containers are readily recyclable and classified as 2-HDPE (High-Density Polyethylene) and some contain 25% post-consumer recycled plastic.