

Duragloss™

Floor Finish 17% NV Solids

Economical finish for low-maintenance programs.

Item #	Description	Size	Units Per Case
BPR520001-B	Duragloss™ Floor Finish	Gallon	4
BPR520005-B	Duragloss™ Floor Finish	5-Gallon Pail	1



Features

- High gloss, tough and durable
- Use with or without burnishing
- Low mop drag and outstanding leveling
- Universally compatible formula
- Use with or without a sealer
- Fast drying, curing and recoating
- Meets industry guidelines for slip resistance
- Coverage: 2,500–3,000 sq. ft./gallon



Duragloss™

Floor Finish 17% NV Solids

Duragloss™ is a unique fast-drying metal interlock floor finish that provides exceptionally good appearance and wear characteristics. It levels easily and dries quickly to a durable film and provides outstanding resistance to black heel marks, scuffing, maintenance cleaning and heavy traffic. Duragloss is a blend of extremely hard, new-generation acrylic terpolymers, thermoplastics, resins and plasticizers designed to provide exceptional durability, gloss and reflection. Duragloss achieves high levels of hardness and clarity. It builds gloss quickly and responds with unmatched brilliance to burnishing by 1,000- to 3,000-rpm machines. Burnishing is not required to maintain its high gloss.

Physical Data

Physical form: Opaque, white liquid
Odor: Fruity
Non-volatile solids: 20% minimum
pH (as is): 8.0 - 9.0
Film color: Colorless
Freeze/thaw stability: Excellent
Shelf life: 2 years minimum in unopened container

Performance Data

Dilution ratio: Ready to use
Drying time: 15–20 minutes
Recoat time: 20–30 minutes
Specular gloss (60°): 80° minimum
Slip resistance: Meets ASTM D-2047
Water resistance: Excellent
Detergent resistance: Excellent
Leveling: Excellent
Removability: Easy to remove
Normal coverage: 2,500–3,000 square feet per gallon