# **91** Optimum<sup>™</sup> Floor Finish & Sealer

### High-gloss finish when high durability and low maintenance are desired.

Coastwide Professional 91 Optimum Floor Finish & Sealer is an economical finish, providing maximum gloss and durability. It is formulated with durable polymers to extend the life and appearance of floors. See side panel for directions for use.

#### **Features**

- · Versatile, durable floor finish
- Use with or without burnishing
- Resists black heel marks and scuffing
- Works on most resilient surfaces with most maintenance methods
- Universally compatible formula
- Use with or without a sealer
- Meets industry guidelines for slip resistance
- Coverage: 2,500-3,000 square feet per gallon
- Excellent leveling and adhesion properties

#### **Directions**



Strip floors with Coastwide 82 / 83 or top scrub with Coastwide 64.



Ensure floor is clean and dry before application.

With clean Rayon mop / microfiber flat mop apply 4–6 coats over 24 hours (30 minutes between coats). Only use in a well-ventilated area.

4-6 x



Line mop bucket with trash bag to avoid contamination.

#### Maintenance Procedures:

Frequently dust mop, clean daily with Coastwide 64 or 50, buff/burnish as needed.

## Use On:



VCI/LVI



Concrete floors



Terrazzo



Other resilient flooring



## **Attributes**

Physical form:	Opaque, white liquid
Odor:	Characteristic
Non-volatile solids:	19% minimum
pH as is:	8.5-9.5
Film color:	Clear and colorless
Coverage:	2,500-3,000 square feet per gallon (min.)
Slip resistance:	Meets ASTM D2047
Shelf life:	2 years minimum in unopened container

These specifications were correct at the time of printing but are subject to change without notice.

## 1 Gallon CW091RU01-A



1 gallon, 4 units/case

## 5 Gallon CW091RU05-A



5 gallons/each