

Durathane™

Floor Finish 24% NV Solids

A high-solids finish fortified with urethane for improved adhesion and durability.



Item #	Description	Size	Units Per Case
BPR523005-B	Durathane™ Floor Finish	5-Gallon Pail	1

Features

- Outlasts conventional acrylic finishes
- Superior response to burnishing
- Rapid leveling
- Higher solids require less coats
- Effective coating for synthetic and rubberized flooring
- Coverage 2,500–3,000 square feet per gallon
- Meets industry guidelines for slip resistance



Durathane™

Floor Finish 24% NV Solids

A blend of tough urethane polymers and acrylic polymers designed to provide high-gloss levels, excellent wear characteristics, superior slip resistance and ease of application. For best results, it can be maintained with high-speed burnishers generating 1,000- to 3,000-rpms.

Physical Data

Physical form: Opaque, white liquid
Odor: Fruity
pH (as is): 8.0 -9.0
Non-volatile solids: 25% minimum
Film color: Clear and colorless
Freeze/thaw stability: Excellent
Odor index: Low
Shelf life: 2 years minimum in unopened container

Performance Data

Dilution ratio: Ready to use
Drying time: 20-40 minutes
Recoat time: 30-45 minutes
Specular gloss (60°): 70° minimum
Burnish response: Outstanding
Slip resistance: Meets ASTM D-2047
Water resistance: Excellent
Detergent resistance: Excellent
Adhesion: Excellent, without cracking, powdering or peeling
Removability: Easy to remove
Normal coverage: 2,500-3,000 square feet per gallon (min.)