

80

FLOOR FINISH AND SEALER



Sustainable Earth
By Staples™

Metal-free combination floor finish and sealer formulated for high performance

PRODUCT DESCRIPTION

Sustainable Earth by Staples™ Floor Finish and Sealer (SEB80) is designed with the newest in eco-preferable* metal-free polymer technology for sealing and finishing all types of resilient flooring. It does not contain zinc or other metals that can harm the environment or interfere with industrial wastewater treatment processes. This state-of-the-art finish has exceptional gloss, durability, soil resistance, detergent resistance, recoatability and removability, and meets industry's slip-resistant standards. Sustainable Earth by Staples™ Floor Finish and Sealer is a combination seal and finish that dries to a smooth, hard, clear and colorless coating in about 20-30 minutes under normal conditions. This ultra-low-odor finish is versatile and can be maintained using traditional maintenance procedures, including scrub/recoat or high-speed burnishing.

FEATURES

- High durability, outstanding gloss retention and superior detergent resistance
- Formulated with new self-crosslinking no-metal technology
- Eco preferable and free from alkyl phenol ethoxylate (APE), formaldehyde, phthalate and metals
- Outstanding performance reduces the labor costs associated with burnishing, recoating and stripping
- Ultra-low-odor characteristics make SEB80 ideal for floor care in schools, hospitals and patient care facilities
- Seals and finishes in one easy step
- Rapid leveling and film formation
- Balances outstanding sealer adhesion with unsurpassed finish durability
- Use with or without burnishing
- Exhibits outstanding black heel mark and scuff mark resistance
- Excellent soil resistance reduces deep scrubbing and stripping
- Outstanding clarity and brightness
- One gallon covers 2,500 square feet
- Universally compatible with most sealers and finishes
- Meets Green Seal™ GS-40 Performance Requirements



Performance Data

Drying time	20-30 min.
Recoat time	30-40 min.
Specular gloss (60°)	85% minimum
Slip resistance	Static coefficient of friction of >0.5 as measured by ASTM D2047-04 and UL Method 410
Water resistance	Excellent
Detergent resistance	Excellent, as measured by ASTM D3207-92, using SEB64 floor cleaner diluted at 1 ounce per gallon of water
Adhesion	Excellent, without cracking, powdering or peeling
Soil resistance	Performs equal to nationally recognized floor finish as measured by ASTM D3206-08 Standard Test Method for Soil Resistance of Floor Polishes

*Compared to conventional cleaning products.

80 Floor Finish and Sealer

Available exclusively from:

STAPLES Advantage



About Sustainable Earth by Staples™

Our exclusive eco-preferable* line offers great ways to get the products your business needs and to lessen the impact on the environment. Every Sustainable Earth by Staples™ product meets our brand's highest environmental standards.

Plus, like all Staples® brand products, the quality is guaranteed. It's a real win-win for you — and the environment.

*Compared to conventional cleaning products.

PACKAGE SIZES

Item #	Description	Size	Units Per Case
SEB800001-D	SEB80 Floor Finish and Sealer	Gallon	4
SEB800005-D	SEB80 Floor Finish and Sealer	Pail	1-5 GL PA

Physical Data

Physical Form: Milky white liquid

Odor: Low

pH (as is): 7.8-8.8

Non-Volatile Solids: Minimum 20.0%

Total Solids: Over 25%

Film Color: Colorless

Shelf Life: 2 years in unopened container

Freeze/Thaw Stability: Do not freeze

Dilution Ratio: Ready-to-use

Usage Information

1. Strip floors to remove buildup of old finishes, sealers or waxes.
2. Thoroughly rinse with cold water and let floor dry.
3. Apply thin to medium even coats of SEB80 with an appropriate finish mop or applicator.
4. Allow each coat to dry before applying next coat — 30 mins. drying time recommended under normal conditions.
5. Apply a maximum of 4-6 coats in a 24-hour period.

Always follow good industrial hygiene practices when using chemicals. Improper use or improper dilution could result in damage to cleaning surfaces or to personal health. Please follow label directions. Dispose of product and container in accordance with applicable federal, state and local regulations.

Certification Definitions



This product meets Green Seal™ Standard GS-40 based on effective performance and protective limits on VOCs and human & Environmental toxicity. Green Seal.org



All plastic containers used in packaging products display the Society of Plastics Industries' 3-side triangular arrow to make recycling easier. The majority of our containers are readily recyclable and classified as 2-HDPE (high-Density Polyethylene) and some contain 25% post-consumer recycled plastic.

Order online at:
StaplesAdvantage.com,
CoastwideLabs.com
or your favorite ordering system